MIL-C-14383D(WV)

30 December 1974

SUPERSEDING
MIL-R-14383C(WC)
16 June 1971
w/AMENDMENT 1
25 April 1973

MILITARY SPECIFICATION

CANNONS, 106MM RECOILLESS RIFLE: M206 AND M206A1

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers two types of 106MM recoilless cannons.

1.2 Classification. Recoilless cannons shall be of the following types

Type I - Cannon, 106MM Recoilless Rifle: M206
Type II - Cannon, 106MM Recoilless Rifle: M206A1

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of the specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-C-13931 - Cannons, General Specification for
MIL-P-14232 - Parts, Equipment and Tools for Ordnance Materiel, Packaging of
MIL-C-45607 - Inspection Equipment Acquisition, Maintenance and Disposition of

STANDARDS

Military

MIL-STD-109 Quality Assurance Terms and Definitions
MIL-STD-129 Marking for Shipment and Storage

FSC 1015

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:08Z
Check the source to verify that this is the currentversion before use.

requirements. All responsibility for compliance. All items must meet all

DRAWINGS

U. S. Army Armament Command

P8772341 - Gage, Location
F8772432 - Gage, Electric Load Indicator
D8772635 - Go Thread Ring

PUBLICATIONS

U. S. Army Armament Command

EPL 11578013 - Engineering Parts List, Cannon, 106MM Recoilless Rifle: M206A1
EPL 11578014 - Engineering Parts List, Cannon, 106MM Recoilless Rifle: M206
Master LSQAP 11578013 - Master Index of Supplementary Quality Assurance Provisions, Cannon, 106MM Recoilless Rifle: M206A1
Master LSQAP 11578014 - Master Index of Supplementary Quality Assurance Provisions, Cannon, 106MM Recoilless Rifle: M206
DL 11578013 - Index of Inspection Equipment Lists, Cannon, 106MM Recoilless Rifle: M206A1
DL 11578014 - Index of Inspection Equipment Lists, Cannon, 106MM Recoilless Rifle: M206
PDS P11578013 - Packaging Data Sheet, Cannon, 106MM: M206A1
PDS P11578014 - Packaging Data Sheet, Cannon, 106MM: M206

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 First article. When specified in the contract, the contractor shall submit a first article. Unless otherwise specified (see 6.2.1), the first article shall be included in the first article package (see 5.1).

3.2 General requirements. Cannons and parts thereof shall conform to the drawings and specifications listed in Engineering Parts List EPL 11578014 for Type I and EPL 11578013 for Type II and the requirements of this specification and MIL-C-13931.

3.3 Mechanical requirements.

3.3.1 Torque at cable operating lever. The torque required on the cable operating lever to fire the cannon shall not exceed 24 pound-inches.

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:08Z
Check the source to verify that this is the currentversion before use.

3.3.2 Lanyard pull. The force required to actuate the trigger by axial pull on the lanyard shall not exceed 35 pounds.

3.3.3 Headspace. The requirements for headspace shall be .354 - .365 inch inclusive.

3.4 Operation. Operation shall be in accordance with the applicable requirements of MIL-C-13931 and the following:

3.4.1 Cartridge case detent. The cartridge case detent, on insertion of a round, shall depress and return without erratic movement or binding.

3.4.2 Breechblock operating lever. The breechblock operating lever, when depressed and rotated through its range of travel, shall open the breech for ejection of the empty cartridge case. The cam in the base of the lever shall operate to permit rotation of the lever when the lever is depressed and to engage the slots in the hinge block to prevent rotation when the lever is not depressed.

3.4.3 Breech operation and firing control, type II cannons. Type II cannons shall be fitted to the electrical and hydraulic systems which fire the weapon and control the operation of the breech. The tubes of type II cannons shall be fitted with a round-indicator device which shall indicate the presence of a round of ammunition in the chamber. The alignment and protrusion of the round-sensing core shall be as specified on the applicable drawing.

3.5 Performance.

3.5.1 High pressure resistance. The cannons shall be capable of withstanding chamber pressures of 12400 $\pm$ 400 pounds per square inch when tested as specified in 4.5.5.

3.5.2 Functioning. There shall be no impairment in the functioning of the cannon components during and after the testing specified in 4.5.5.1.

3.5.3 Bore. Enlargement of the bore diameters across lands resulting from testing shall not exceed 0.004 inch from actual diameters. There shall be no indication of abnormal wear, damage or deformation of the bore surface.

3.5.4 Material soundness. The cannon shall meet the requirements specified herein without evidence of cracks and fractures and shall comply with soundness requirements specified on the applicable drawings.

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:08Z
Check the source to verify that this is the currentversion before use.

4. Quality Assurance Provisions.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Quality Assurance terms and definitions. Quality assurance terms and definitions used in this specification are in accordance with MIL-STD-109.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First Article inspection (see 4.4)
b. Quality conformance inspection (see 4.5)

4.4 First Article inspection. A first article shall be submitted for inspection in accordance with contract requirements. The first article shall be representative of the production process to be used during quantity production. The first article shall be subjected to the inspections, examinations, and tests specified herein and such other inspections, examinations, and tests as are necessary to determine compliance with the requirements of the contract.

4.5 Quality Conformance inspection.

4.5.1 Inspection Provisions. Cannon shall be inspected for conformance to requirements of the provisions in this specification, and MIL-C-13931, and SQAPs listed in Master LSQAP 11578014 for Cannon, M206 and Master LSQAP 11578013 for Cannon, M206A1, and SQAP-Appendix-WVT.

4.5.1.1 Final Examination. Final examination of each cannon shall be completed after testing and prior to preservation and packaging to determine compliance with this specification, and MIL-C-13931, and as specified in the contract (see 6.2).

4.5.1.2 Inspection Approval Stamp. The application of the inspection approval stamp shall be as specified in MIL-C-13931.

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:08Z
Check the source to verify that this is the currentversion before use.

4.5.2 Inspection Equipment. Data lists containing drawing numbers of Government-designed inspection equipment used in the inspection of parts, subassemblies, and assemblies are listed in DL11578014 for cannon, M206 and DL11578013 for cannon, M206A1.

4.5.2.1 Acquisition, Maintenance and Disposition. Unless otherwise specified, responsibility for acquisition, maintenance and disposition of acceptance inspection and test equipment prescribed on the Lists of Inspection Equipment DL11578013 and DL11578014, and for all other inspection equipment required to perform inspection prescribed by applicable specifications, shall be in accordance with MIL-I-45607.

4.5.2.2 Accuracy of standard measuring equipment. When commercial and modified-commercial inspection and test equipment is used, it shall be capable of repetitive measurements to an accuracy of 10 percent of the total tolerance of the characteristic being inspected.

4.5.3 Examinations.

4.5.3.1 Headspace. Headspace shall be checked on each cannon with Gage D8772635 or an approved equivalent to determine compliance with headspace requirements specified in 3.3.3.

4.5.3.2 Round-Sensing Device. (Applicable to Cannon, M206A1 only.) The alignment and protrusion of the round-sensing device core with the rifling land of the barrel shall be inspected on each cannon with Gage F8772341 or an approved equivalent to determine compliance with the requirements specified on the applicable drawing.

4.5.3.3 Workmanship. Workmanship shall be examined visually in accordance with MIL-C-13931.

4.5.4 Tests.

4.5.4.1 Trigger Load. Each assembled cannon shall be subjected to the following tests or comparable tests acceptable to the Government representative to determine compliance with 3.3.

4.5.4.1.1 Torque on Cable Operating Lever. With the cannon removed from the mount, the trigger shall be actuated by means of a torque wrench with a suitable adapter applied to the slot in the cable operating lever. Force to actuate the trigger shall be applied gradually until the sear is released and the maximum torque indicated shall be recorded. For acceptance, none of three successive trials shall exceed the torque specified in 3.3.1. The accuracy of the torque wrench shall be such that the deviation of scale reading from the true torque does not exceed 5 percent of the true torque.

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:08Z
Check the source to verify that this is the currentversion before use.

4.5.4.1.2 Lanyard Pull. Force shall be applied to the lanyard rod through a spring scale linked to the lanyard rod by a yoke (or C-link) in such a manner that the pull is parallel to the axis of the rifle bore. Force shall be applied gradually until the sear is released. The maximum pull indicated shall then be recorded. For acceptance, none of three successive trials shall exceed the pull specified in 3.3.2. The accuracy of the spring scale shall be such that the deviation of the scale reading from the true force does not exceed 2 percent of the true force.

4.5.4.2 Cartridge Case Detent. The cartridge case detent of each assembled cannon shall be tested for proper functioning by insertion of an inert round into the chamber of the cannon and noting the operation of the detent. For acceptance, none of three successive trials shall fail to meet the functioning requirements of 3.4.1.

4.5.4.3 Breech Mechanism Operation. With an inert round inserted in the chamber, each cannon shall be functioned a minimum of two complete cycles to determine smoothness of operation of the breechblock operating lever and capability of functioning as specified in 3.4.2. Any cannon failing to comply with the requirements in either of the two operational cycles shall be cause for rejection.

4.5.4.4 Round Indicator. (Applicable to Cannon, M206A1 only.) Each assembled round indicator shall be tested functionally using Gage F8772432 or an approved equivalent. This device approximates the condition of the vehicle system. The brightness of the "empty" comparison light is first adjusted to that of the indicator light when the barrel is empty, then the "loaded" comparison light is matched in brightness to the indicator light when an inert round or plug gage is inserted. The conformance of the indicator on subsequent barrels shall be determined by one pass of an inert round or a plug gage of a diameter equal to the minimum round size. If the indicator light fails to diminish to the intensity of the "loaded" comparison light, the indicator assembly shall be replaced and tested according to this paragraph for conformance with 3.4.3.

4.5.5 Performance. Cannon shall be subject to acceptance testing by a Government testing activity to assure compliance with 3.5. Acceptance testing shall be in accordance with procedures specified by the Quality Assurance element of the procuring activity.

4.5.5.1 Functioning. Functioning tests shall be conducted in accordance with MIL-C-13931 and as specified herein. A minimum of two complete cycles of operation shall be performed on each cannon. Any evidence of binding, interference, or erratic operation shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:08Z
Check the source to verify that this is the currentversion before use.

4.5.5.2 Bore Enlargement and Condition. After testing, the bore diameters across lands of each cannon shall be measured with an air gage, a star gage, or other approved equivalent gage. Enlargement exceeding the limit specified in 3.5.3 shall be cause for rejection. Also, after testing, the bore of each cannon shall be visually examined to determine the condition of the bore surface. Any indication of abnormal wear, damage, or deformation of the bore surface shall be cause for rejection.

4.5.5.3 Material Soundness. After testing, the breechblock, bushing, and the external surfaces of the barrel assembly of each cannon shall be magnetic-particle tested in accordance with applicable drawings and specifications. The interior surfaces of the barrel assembly of each cannon shall be visually examined by means of a borescope. All other components and subassemblies of each cannon shall be visually examined. Cannon not conforming to the requirements of 3.5.4 shall be rejected.

4.5.5.4 Records. Cannon that pass the firing tests shall be furnished with applicable data on DA Form 2408-4 by the Proving Ground. Cannon accepted on a proof sampling basis shall be furnished with applicable data on DA Form 2408-4 by the contractor and approved by the Government representative. The responsibility of the contractor for cannons which fail the firing tests shall be as specified in the contract. (see 6.1.1)

4.5.6 Inspection of Preparation for Delivery.

4.5.6.1 Packaging inspection. Unless otherwise specified, inspection to determine compliance with cleaning, preservation, packaging, packing, and marking requirements of the applicable packaging data sheets for the level designated in the contract shall be as specified in MIL-P-14232.

5. PREPARATION FOR DELIVERY

5.1 First article package. On each contract, a first article package shall be provided in accordance with 3.1. The first article package for the cannon shall be unit packaged for the level of protection specified in the contract and packed level C. Unit packaging and packing shall be in accordance with MIL-P-14232 and Packaging Data Sheets P11578013 for Cannon, 106mm Recoilless Rifle, M206A1, or P11578014 for Cannon, 106mm Recoilless Rifle: M206. Marking shall be in accordance with MIL-STD-129.

5.2 Unit packaging, packing and marking of cannon. The cannon shall be unit packaged and packed in accordance with the requirements of MIL-P-14232 and the applicable packaging data sheets (see 5.1), for the level of protection specified in the contract (see 6.2.1). Marking shall be in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:08Z
Check the source to verify that this is the currentversion before use.

5.3 Unit packaging, packing and marking of repair parts. Repair parts shall be unit packaged and packed in accordance with the requirements of MIL-P-14232 and the applicable packaging data sheets (see 5.1), for the level of protection specified in the contract (see 6.2.1). Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.

6.1.1 Type I. The M206 cannon is intended for use with Mount M79 or with Mount M92 and Tripod M27 as a ground or vehicle-mounted weapon.

6.1.2 Type II. The M206A1 cannon is intended for use as the six primary weapons on the 106mm Self-propelled Multiple Rifle M50. The two outboard cannons are readily demountable for use on Mount M79 or Mount M92 and Tripod M27.

6.1.3 Difference between types. The M206A1 differs from the M206 in that it has a round indicator for remote indication that the cannon is loaded and has provision for the attachment of a hydraulic breech actuator.

6.2 Ordering data. Procurement documents should specify the following:

6.2.1 Procurement requirements.

a. Title, number and date of the specification.

b. Requirements for submission of and shipping instructions for first article (see 3.1 and 4.4) and first article package. (See 3.1 and 5.1.)

(1) The contract should designate the examinations and tests to be performed by the contractor and the examinations and tests to be performed by the Government.

(2) The contract should specify the sample size (i.e., the number of units) of the first article.

(3) The contract should designate the inspection and test data that is required to be furnished the Government when the contractor is required to perform either or both examinations and tests.

(4) The contract should designate at whose expense a retest may be performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.

(5) The contract should specify that the acceptable first article shall be delivered in accordance with the terms of the contract, or

(6) Any additional or extended examinations and tests beyond the scope of this specification should be specified and identified as a separate item of the contract.

c. Block of serial numbers for cannons and vents.

d. List of inspection equipment, responsibility for acquisition, maintenance, and disposition thereof, if other than as specified (see 4.5.2).

e. Availability of inspection equipment from the Government.

f. Extent of supplier's responsibility for Government-furnished and for supplier-required final inspection equipment.

g. Applicable acceptance test procedures and frequency of testing (see 4.5.5).

h. The levels of preservation, packaging, and packing required (see 5).

i. Packaging instructions for repair parts (see 5.3).

6.2.2 Contract data requirements. Monthly reports of the results of final examination and performance testing shall be as specified for delivery on DD Form 1423 in the contract.

6.3 When warranted, the contract should specify the application of MIL-Q-9858 or MIL-I-45208, as appropriate, on the Management Control Systems Summary List DD Form 1660.

6.4 Unless otherwise specified, the contract should specify the application of MIL-I-45607 and MIL-C-45662 on the Management Control Systems Summary List, DD Form 1660.

6.5 Definitions.

6.5.1 Vent Index. The vent index referred to on a drawing is defined as the sum of the individual products obtained by multiplying the chordal length of each throat by its radial width.

6.5.2 Frequency of testing. Frequency of testing is defined as the proportion of the lot to be tested after initial 100 percent testing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.

6.6 International standardization agreement. The Cannon M206 is the subject of international standardization agreement ABCA-ARMY-STD-46. When amendment, revision or cancellation of this specification is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

6.7 Change in model designation. The M40 model designation of Revision B of this specification applies at present to the complete 106mm Recoilless Rifle Weapon System. The M206 and M206A1 designations as used herein apply to the 106mm Recoilless Cannons.

Custodians:

Army-WV

Preparing activity:

Army-WV

Project No. 1015-A259

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.