INCH-POUND
MIL-C-14384D(AR)
7 April 1989

SUPERSEDING
MIL-C-14384C(AR)
2 July 1985

MILITARY SPECIFICATION

CANNON, 105MM HOWITZER: M2A2

This specification is approved for use by the Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification supports the acquisition of the Cannon, 105MM Howitzer: M2A2 consisting of the tube and the breech mechanism. This specification includes the minimum essential Engineering and Packaging Requirements and the necessary Quality Assurance Provisions to determine that these requirements have been met.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

Military

MIL-C-13931 - Cannon, General Specification for

MIL-P-14232 - Parts, Tools and Equipment for Army Material, Packaging of

MIL-I-45607 - Inspection Equipment Acquistion, Maintenance, and Disposition of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Armament Research, Development and Engineering Center, US Army Armament, Munitions and Chemical Command, ATTN: SMCAR-CCB-SAS, Watervliet, N.Y. 12189-4050 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1015

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-129 - Marking for Shipment and Storage

MIL-STD-1189 - Standard Symbology for Marking Unit Packs, Outer Containers, and Selected Documents

MIL-STD-1235 - Single and Multi-Level Continuous Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-2073-1 - DOD Materiel Procedures for Development and Application of Packaging

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099).

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document, to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.7)

U.S. Army Armament Research, Development and Engineering Center (ARDEC)

EPL7827208 - Engineering Parts Lists for Cannon, 105MM Howitzer: M2A2

LSPI7827208 - List of Special Packaging Instructions, Cannon, 105MM Howitzer: M2A2

P7827208 - Special Packaging Instructions Cannon, 105MM Howitzer: M2A2

PUBLICATIONS

QAP-APPENDIX-WVA - General Quality Assurance Provisions

Master LQAP 7827208 - Master Index of Quality Assurance Provisions for Cannon, 105MM Howitzer: M2A2

DL7827208 - Index of Inspection Equipment Lists for Cannon, 105MM Howitzer: M2A2

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the Procuring Contracting Officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

American Society for Testing and Materials (ASTM)

ASTM D 3951 - Commercial Packaging, Practice for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General requirements. Cannon and component parts shall be in accordance with the applicable drawings (EPL7827208), the requirements of this specification, the applicable paragraphs of the General Cannon Specification - MIL-C-13931 as incorporated in this document, and all referenced documents. Any conflicts are to be resolved by means of the order of precedence (see 2.3).

3.2 First article. The contractor shall submit a first article unless it is specifically waived in the contract (see 4.3 and 6.2). No first article requirements shall be waived without review and approval by the Procuring Contracting Officer (see 6.4).

3.3 Functional characteristics. Each cannon assembly shall perform the firing and pressure sustaining function of the 105MM: M2A2 Howitzer. All moving parts shall function smoothly without interference, erratic movement or malfunction.

3.3.1 Breech mechanism. When the operating lever is unlatched and rotated rearward (clockwise), it shall cam the breechblock horizontally to the right (facing the breech) and thereby open the breech. After the insertion of a round in the chamber, the breechblock shall be cammed back into the breech ring by rotating the operating lever forward (counterclockwise). During this closing movement, the beveled (front) face of the breechblock shall contact the base of the cartridge case and force it to seat in the chamber. When the breech is fully closed, the operating lever shall be locked in closed position by the catch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.

During the closing of the breech, the extractor path in the bottom of the breechblock shall cam and rotate the extractor until its lip is positioned in front of the rim of the cartridge case. Then, the opening of the breech shall cam the extractor lip sharply rearward, thereby extracting and ejecting the case from the chamber.

3.3.2 Firing mechanism group. The firing mechanism consists of the Firing Lock M13 which is operated by movement of the trigger-shaft. For firing, the trigger-shaft-lever-arm is rotated clockwise (by pulling the lanyard outward). This action shall rotate the trigger-fork forward to force the sleeve forward and compress the firing-spring. The moving sleeve shall trip the sear which shall release the firing-pin-holder and allow the compressed firing-spring to expand and drive the firing-pin forward to strike the primer. The firing-spring shall then force the sleeve and firing pin holder rearward, which in turn shall rotate the trigger fork clockwise. The sleeve engages the sear and thereby completes the firing cycle.

3.3.3 Firing pin protrusion. When fired, the protrusion of the firing pin from the front of the breechblock shall be not less than 0.164 inch nor more than 0.296 inch.

3.3.4 Headspace. Headspace, the distance from the front face of the closed and locked breechblock and the rear face of the tube, shall be not less than 0.189 inch nor more than 0.209 inch.

3.4 Performance.

3.4.1 High pressure resistance. The cannon and repair tubes shall be capable of withstanding a chamber pressure of 44,100 plus or minus 1,600 pounds per square inch when tested as specified in 4.4.6.1.

3.4.2 Material soundness. After testing, all parts shall be free of cracks and fractures and shall comply with any soundness requirements specified on the applicable drawings (see 3.1).

3.4.3 Bore enlargement. If proof firing is used to evaluate high pressure resistance, bore diameters (measured across the lands) after proof firing no more than 10 rounds shall not exceed the before firing diameters by more than the amounts specified in TABLE I.

TABLE I. Bore enlargement.

Distance forward of commencement of rifling	0.1 inch	1 inch	1 cal. to muzzle
Amount (in inches)	0.003	0.003	0.002

NOTE: Interpolate to determine the amount between given distance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in this specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection. Unless otherwise specified in the contract, (see 6.2), First Article cannon and specified parts thereof shall be inspected by the contractor and submitted to the Government for approval. Inspection shall be in accordance with applicable Quality Assurance Provisions (QAPs) and QAP-APPENDIX-WVA. QAPs are listed in Master LQAP 7827208. First Article sample sizes shall be as specified in applicable item QAPs, or the contract, as applicable. First Article cannon and parts thereof shall be representative of the production processes to be used during quantity production.

4.3.1 First Article - Initial Production Test (FA-IPT). When specified in the contract, (see 6.2.1), First Article cannon shall be subjected to Initial Production Testing by the Government or any agency specified by the Government and may be conducted at a Government facility to assure compliance with the requirements of this specification and any additional requirements listed in the contract. Initial Production Testing procedures and the sample size of first article cannon shall be as specified in the contract. First article cannon and parts thereof shall be representative of the production processes to be used during quantity production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Quality conformance inspection is listed in TABLE II.

TABLE II. Quality conformance inspection.

Category	Requirement Paragraph	Inspection Paragraph
Examinations		
Firing pin protrusion	3.3.3	4.4.4.1
Headspace	3.3.4	4.4.4.2
Material soundness	3.4.2	4.4.4.3
Packaging	5.	4.4.4.4
Functional inspection	3.3	4.4.5
Breech mechanism	3.3.1	4.4.5.1
Extractors	3.3.1	4.4.5.2
Firing mechanism group	3.3.2	4.4.5.3
Tests		
Proof acceptance	3.4	4.4.6.1
Proof firing		4.4.6.1.1
Proof pressure simulation		4.4.6.1.2

4.4.1 Inspection provisions. Cannon and parts thereof shall be inspected for conformance to requirements of this specification, MIL-C-13931, QAPs listed in Master LQAP 7827208, and QAP-APPENDIX-WVA.

4.4.2 Inspection approval stamp. The application of the inspection approval stamp shall be as specified in MIL-C-13931.

4.4.3 Inspection equipment. Data lists containing equipment used in the inspection of parts, subassemblies, and assemblies are listed in DL 7827208.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.

4.4.3.1 Acquisition, maintenance and disposition. Unless otherwise specified (see 6.2), responsibility for acquisition, maintenance, and disposition of acceptance inspection and test equipment referenced in the List of Inspection Equipment DL 7827208, and for all other inspection equipment required to perform inspection prescribed by applicable specifications, shall be in accordance with MIL-I-45607.

4.4.3.2 Accuracy of standard measuring equipment. When commercial and modified commercial inspection and test equipment is used, it shall be capable of repetitive measurements to an accuracy of 10 percent of the total tolerance of the characteristic being inspected.

4.4.4 Examinations.

4.4.4.1 Firing pin protrusion. Firing pin protrusion of the breech mechanism of each cannon shall be measured using gage 5256336 or approved equivalent to determine compliance with 3.3.3.

4.4.4.2 Headspace. Headspace, as defined in 3.3.4, shall be measured on each cannon using gages 8775727 and 8775728 or approved equivalent gages to determine compliance with 3.3.4.

4.4.4.3 Material soundness. All surfaces of the tube, breech ring, and the breechblock shall be examined by magnetic particle inspection in accordance with applicable drawings and specifications. Acceptance criteria shall be as stated on the applicable drawings. The bore surfaces of the tube shall be examined by means of a borescope. There shall be no evidence of cracks or fractures.

4.4.4.4 Packaging inspection. Packaging inspection for the level designated in the contract shall be performed in accordance with the applicable packaging data sheets and MIL-P-14232 or Special Packaging Instruction and MIL-STD-2073-1. Packaging failing to comply with the packaging requirements of Section 5 and the contract shall be cause for rejection.

4.4.5 Functional inspection. Functioning tests shall be conducted in accordance with MIL-C-13931 and as specified herein. A minimum of two complete cycles of operation shall be performed on each cannon.

4.4.5.1 Breech mechanism. Each breech mechanism shall be operated manually to determine smoothness of operation in compliance with 3.3.1. Action of the operating lever shall be observed to assure that the lever is locked when in the closed position. Any evidence of interference, erratic movement, or malfunction of any component shall be cause for rejection.

4.4.5.2 Extractors. With the cannon in a horizontal position, extraction and ejection shall be tested with an empty service cartridge case to determine compliance with 3.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.

4.4.5.3 Firing mechanism group. When assembled in a breechblock or breech mechanism, each firing mechanism shall be operated manually to determine smoothness of operation in compliance with 3.3.2. Any evidence of interference, erratic movement, or malfunction of any component shall be cause for rejection.

4.4.6 Tests.

4.4.6.1 Proof acceptance. Cannon shall be proof accepted through proof firing, proof pressure simulation tests, or both. Cannon and repair tubes to be proof fired shall be fired using the test method of 4.4.6.1.1. Failure to comply with the requirements of 3.4.1, 3.4.2, and 3.4.3 shall be cause for rejection. Cannon breech mechanisms to be simulation proof tested shall be proof tested using the test method of 4.4.6.1.2. Failure to comply with the requirements of 3.4.1 and 3.4.2 shall be cause for rejection. Proof firing performed on a sampling basis shall be conducted as follows:

a. Using plan CSP-1 of MIL-STD-1235, the Procuring Contracting Officer at Watervliet Arsenal shall designate the appropriate initial quantity (i), sample frequency (f), and AQL in the contract (see 6.2).

b. The first "i" quantity of cannon or tubes produced in a particular buy shall be proof fired. When the "i" quantity has been satisfied, sampling shall be put into effect using the "f" sampling frequency. If a cannon is rejected, the "f" sampling frequency shall be discontinued, and the "i" quantity reinstated. All cannon not proof fired shall have the breech mechanisms simulation proof tested in the Product Assurance weapon test facility at Watervliet Arsenal.

c. Successive production buys shall not require "i" quantities. However, if the time lag between two successive buys exceeds one year, or if a new cannon or tube contractor is utilized, a new "i" quantity shall be proof fired.

d. Proof fired cannon and replacement tubes, and simulation proof tested breech mechanisms shall be furnished with applicable data on DA Form 2408-4 (Weapon Record Data) as specified by Procuring Contracting Officer at Watervliet Arsenal.

e. When specified in the contract (see 6.2), the weapon simulation test facility shall be qualified as follows: a sample of two breech mechanisms of cannon to be sent to the proving ground for proof firing shall be subjected initially to simulation proof testing at the weapon simulation test facility.

4.4.6.1.1 Proof firing. Proof firing shall be conducted at a Government test site. The procedure shall be as follows:

a. Each cannon or repair tube shall be proof fired once within the proof pressure range specified in 3.4.1.

b. A facility mount may be used if necessary.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.

c. Chamber pressure shall be measured and recorded.

d. After proof firing:

(1) The bore of each tube shall be examined for bore enlargement using an air gage or other approved gage. Enlargements exceeding the limits specified in TABLE I shall be cause for rejection (see 3.4.3).

(2) Each tube shall be borescoped and magnetic particle inspected (see 4.4.4.3).

(3) Each breech mechanism, including the extractors, shall be examined for looseness or interference of fit and other defects of workmanship and function (see 4.4.5.1 and 4.4.5.2).

(4) Each firing mechanism group shall be examined for looseness or interference of fit and other defects of workmanship and function (see 4.4.5.3).

(5) Each breech mechanism shall be disassembled and examined for soundness of material. All components shall be examined to assure freedom from cracks and fractures. Each breech ring and breechblock shall be magnetic particle inspected (see 4.4.4.3).

(6) All breech mechanism components, including the breech ring and breechblock, shall be cleaned. Before shipment it shall function in accordance with 4.4.5.

e. Cannon found to be defective at the proving ground shall be reported to the Product Assurance Directorate, Watervliet Arsenal, Watervliet, NY 12189-4050 and Benet Laboratories, Watervliet, NY 12189-4050 within one working day. The test agency shall forward a Test Incident Report (TIR), incident to the deficiency, within three working days.

4.4.6.1.2 Proof pressure simulation. All cannon not proof fired at a proving ground shall have the breech mechanism proof tested in accordance with the following procedure:

a. Each breech mechanism shall be tested by means of suitable hydraulic pressure testing equipment at a pressure within the proof pressure range specified in 3.4.1.

b. Cycle time to achieve test pressure and release shall not exceed three minutes. Test pressure shall be immediately released upon its attainment. Dwell time at test pressure shall not exceed three seconds.

(1) When difficulty is encountered in attaining test pressure, the number of attempts in which 10 percent or less of the test pressure is attained shall not be counted. The number of attempts in which over 10 percent of the test pressure is attained shall not exceed five.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.

(2) If the cause of difficulty is not identified and corrected within five pressure cycles, the breech mechanism shall be subjected to proof firing as part of a cannon (see 4.4.6.1.1). A notification of this condition shall be submitted with the breech mechanism to the proving ground.

c. The peak pressure shall be recorded for each test and attached to inspection records identifiable with the specific breech mechanism undergoing test.

d. After the pressure test, each breech mechanism shall be examined for looseness or interference of fit and other defects of workmanship and function (see 4.4.5.1).

e. Each breech mechanism shall be disassembled and examined for soundness of material. All components shall be visually examined to assure freedom from cracks and fractures. Each breech ring and breechblock shall be magnetic particle inspected (see 4.4.4.3).

f. All breech mechanism components, including the breech ring and breechblock, shall be cleaned. Before shipment it shall function in accordance with 4.4.5.

5. PACKAGING

5.1 Cannon - Levels A, B and C. Cleaning, drying, preservation, unit packaging and packing of cannon shall be in accordance with the requirements of Special Packaging Instruction (SPI) P7827208 and MIL-STD-2073-1 for the level of protection specified in the contract (see 6.2).

5.2 Repair parts - Level A, B, and C. Cleaning, drying, preservation, unit packaging and packing of repair parts, shall be in accordance with the applicable repair part SPI and MIL-STD-2073-1 or the applicable repair part Packaging Data Sheet (PDS) and MIL-P-14232, for the level of protection specified in the contract (see 6.2). When Level C requirements are not shown on the PDS/SPI, Level C packaging shall be in accordance with MIL-STD-1190.

5.2.1 Level X - Industrial packaging. Cleaning, drying, preservation, unit packaging and packing of repair parts shall be in accordance with ASTM D3951 when industrial packaging is specified in the contract (see 6.2).

5.2.1.1 Quantity in Unit Package (QUP). When Level C packaging in accordance with MIL-STD-1190 or industrial packaging of repair parts is specified in the contract, the QUP shall be the same as specified in the contract (see 6.2).

5.3 Marking of packages.

5.3.1 Levels A, B and C. Marking of the unit package, intermediate packages, and exterior shipping containers shall be in accordance with MIL-STD-129. When specified (see 6.2), bar code marking shall be in accordance with MIL-STD-129 and MIL-STD-1189.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.

5.3.2 Level X - industrial. Marking of the unit package, intermediate packages, and exterior shipping containers shall be in accordance with ASTM D3951. When specified (see 6.2), bar code marking shall be in accordance with MIL-STD-129 and MIL-STD-1189.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory).

6.1 Intended use. The cannon specified herein is intended for use with the 105MM M101 and M101A1 Howitzer systems.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of the specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1 and 2.2).

c. Requirements for and the number of cannon, components thereof, or both to be submitted for first article by the contractor (see 3.2).

d. The examinations and tests to be performed by the contractor and the examinations and tests to be performed by the Government.

e. All inspection and test data that is required.

f. At whose expense a retest may be performed.

g. Any additional or extended examinations and tests beyond the scope of this specification.

h. Serial numbers for the cannon and repair tube assemblies.

i. Inspection equipment, responsibility for acquisition, maintenance, and disposition thereof, if other than as specified (see 4.4.3).

j. Availability of inspection equipment from the Government.

k. Extent of contractor responsibility for Government furnished and for contractor-required final inspection equipment.

l. Applicable acceptance test procedures.

m. When a proof firing sampling plan is authorized, the proof firing sampling plan parameters: initial consecutive quantity (i), sampling frequency (f), and AQL (see 4.4.6.1).

n. Under what conditions simulated firing may be performed, the test equipment available, and the procedures to be followed.

o. The levels of preservation, packaging, and packing required for cannon assemblies (see 5.1) and repair parts (see 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.

p. When applicable, bar code marking requirements (see 5.3).

q. When warranted, the application of MIL-Q-9858 or MIL-I-45208, as appropriate.

r. Unless otherwise specified, the application of MIL-I-45607 and MIL-STD-45662.

6.3 Consideration of Data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DID's) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DID's are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference Paragraph	DID Number	DID Title	Suggested Tailoring
4.3	DI-T-4902	First Article Inspection Report	

The above DID's were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are cited on the DD Form 1423.

6.4 First article. When first article inspection is required, the Procuring Contracting Officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first production item, a sample selected from the first __ production items, a standard production item from the contractor's current inventory (see 3.2), and the number of items to be tested as specified in 4.3. The Procuring Contracting Officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.5 Waivers and deviations. The Procuring Contracting Officer shall coordinate all requests for waiver or deviation to this specification with Benet Laboratories and the Product Assurance Directorate at Watervliet Arsenal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.

6.6 Subject term (key word) listing.

Cannon, 105MM: M2A2

Howitzer, Light, Towed: 105MM, M101

Howitzer, Light, Towed: 105MM, M101A1

6.7 Drawings. Drawings listed in Section 2 of this specification under the heading "U.S. Army Armament Research, Development and Engineering Center" (ARDEC) may also include drawings prepared by, and identified as Watervliet Arsenal, Ordnance Corps, Weapons Command, or U.S. Army Armament Research and Development Command, U.S. Army Armament, Munitions and Chemical Command, etc. Technical data originally prepared by these activities are now under the cognizance of ARDEC.

6.8 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.9 International standardization agreement. Certain provisions of this specification are the subject of international standardization agreement QSTAG-150. When amendment, revision, or cancellation of this specification is proposed which will modify the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization offices to change the agreement or make other appropriate accommodations.

Custodian:

Army-AR

Preparing activity:

Army-AR

(Project 1015-A321)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-14384D (AR)	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:08Z
Check the source to verify that this is the current version before use.