MIL-D-14360F
17 July 1970
SUPERSEDING
MIL-D-0014360E(MU)
26 May 1969
MIL-D-14360B
14 May 1963

MILITARY SPECIFICATION

DOCUMENT DESTROYER,

EMERGENCY, INCENDIARY, M3

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of document destroyer.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-378 - Plastic Film (Polyethylene Thin Gage).
MMM-A-250 - Adhesive, Water Resistant (For Sealing Fiberboard Boxes).
PPP-B-636 - Box, Fiberboard.
PPP-T-60 - Tape, Pressure-Sensitive Adhesive, Waterproof for Packaging.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1168 - Lot Numbering of Ammunition.

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:05Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

DL4-11-12 - Document Destroyer, Emergency, Incendiary, M3.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL4-11-12 or on the subsidiary drawings shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the document destroyer shall conform to the specifications and drawings listed on Drawing DL4-11-12 and subsidiary drawings.

3.2 Assembly. The document destroyer shall be assembled in accordance with Drawing D4-11-12 (see 6.3).

3.3 Igniter charge. The igniter charge, Drawing B143-8-1, shall ignite readily when tested as specified in 4.4.4.

3.4 Preproduction. Prior to the start of regular production, a pre-production sample of document destroyers shall be produced in accordance with this specification for examination and test (see 4.3).

3.5 Workmanship. The document destroyer shall be free from contamination (foreign matter, oil or grease) and damage such as broken or leaking containers or deformation of metal parts which could affect its intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:05Z
Check the source to verify that this is the current version before use.

otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections.

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of four document destroyers shall be manufactured using the same methods, materials, equipment and processes as will be used during regular production.

4.3.2 Inspection procedure.

4.3.2.1 For examination. The sample document destroyers shall be examined in accordance with the classification of defects (4.4.3.3). The AQL's do not apply.

4.3.2.2 For destructive test. A 4-ounce specimen shall be taken from each igniter charge in the preproduction sample and tested in accordance with 4.4.4.

4.3.3 Acceptance/rejection criteria. The preproduction sample shall comply with the examinations and test specified in 4.3.2 to be acceptable. The acceptance number is zero. The supplier shall obtain written approval from the contracting officer prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting.

(a) Document destroyers. Each lot of document destroyers shall be identified and controlled in accordance with MIL-STD-1168. Contained in any one interfix number of document destroyers, no more than

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:05Z
Check the source to verify that this is the current version before use.

one interfix number from one manufacturer of the following component is permitted.

a. Igniter charge.

(b) Igniter charge. Each lot of igniter charges shall be identified and controlled in accordance with MIL-STD-1168. Contained in any one interfix number of igniter charges, no more than one interfix number from one manufacturer of the following components is permitted.

a. One batch of mix (see 6.4).

4.4.2 Sampling.

4.4.2.1 For examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.2.2 For destructive test. A 4-ounce specimen shall be taken from each batch of igniter charge.

4.4.3 Inspection procedure.

4.4.3.1 For examination. The sample document destroyers shall be examined in accordance with the classification of defects and MIL-STD-105.

4.4.3.2 For destructive test. The sample specimen of igniter charges shall be tested in accordance with 4.4.4. The acceptance number is zero.

4.4.3.3 Classification of defects.

(a) Preparation for delivery (section 5).

Categories	Defects
Critical:	None defined
Major:	AQL 4.0 percent defective
101	Package methods incorrect
102	Container incorrect
103	Quantity per container incorrect
104	Container closure incorrect
105	Container damaged (broken or punctured)
106	Marking missing or illegible
107	Igniter package missing (6.2)
108	Protective finish missing or incorrect
109	Workmanship (3.5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:05Z
Check the source to verify that this is the current version before use.

4.4.4 Igniter charge test. The igniter charge specimen, when interleaved with a crumpled 5 inch by 5 inch scrap of paper, shall ignite readily when a match is applied to the paper.

5. PREPARATION FOR DELIVERY

5.1 Packaging, level A.

5.1.1 Screen and retaining wire. The screen shall be folded once along the centerline through the square openings and again twice transversely to make a configuration approximately 8 by 12 inches. The retaining wire shall be coiled with plain and looped ends positioned in a manner to avoid sharp bends. The screen and wire shall be packaged in a fiberboard box conforming to style OPF, type CF, class weather-resistant, grade W5c of PPP-B-636. Box dimensions shall be 10-1/4 by 12-3/4 by 1-1/2 inches. Closure of the box shall be in accordance with the appendix to the box specification using tape conforming to PPP-T-60 in accordance with Drawing D4-11-12.

5.1.2 Oxidizing agent. A minimum of 19 pounds of sodium nitrate (Drawing B143-13-3) shall be packaged in a self opening sack of 2-ply, 60 pounds basis weight wet strength kraft paper. When fully opened, the sack shall measure 6 inches by 3-1/2 by 24 inches deep. The paper sack will be fitted with a 3-mil-thick polyethylene liner, 26-3/4 inches long and conforming to type 1, grade B of L-P-378. The liner shall be closed by heat sealing. The sack shall be sealed with water-resistant adhesive conforming to MMM-A-250. The sack shall be folded twice into approximately 2-inch-wide folds, the last of which shall be sealed with the above adhesive.

5.1.3 Igniter charge. A minimum of four pounds of igniter charge (Drawing B143-8-1) shall be packaged in four 1-pound cans conforming to Drawing C4-11-33.

5.2 Packing, level A. The components, packaged as specified in 5.1, shall be packed in a metal drum conforming to Drawing D4-11-20. Arrangement of the items in the drum and closure of the drum shall be in accordance with Drawing D4-11-12.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages shall be marked in accordance with MIL-STD-129. The metal drum (5.2) shall be marked as specified on Drawing D4-11-12.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:05Z
Check the source to verify that this is the current version before use.

5.4 Palletization. When specified in the contract or order (see 6.2), the document destroyer packed as specified in 5.2, shall be palletized in accordance with Drawing D4-11-26.

6. NOTES

6.1 Intended use. This item is intended for destroying documents in an emergency.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Whether igniters are required.
(c) Preproduction.

(1) Time allowed for suppliers submission of samples for Government test and evaluation after award of contract.
(2) Destination of samples when testing is performed by the Government.
(3) Packing and shipping instructions when applicable.
(4) Time required for the Government to notify the supplier whether to proceed with production.

(d) Whether palletization is required.

6.3 Caution. Suppliers are advised to take all necessary precautions to protect personnel while filling and assembling destroyers and while testing, due to the incendiary nature of item.

6.4 Batch. A batch is defined as that quantity of material which has been manufactured by some unit chemical process and subjected to some physical mixing operation intended to make the final product substantially uniform.

Custodians:

Army - MU
Navy - OS
Air Force - 70

Review activities:

Navy - OS
Air Force - 70

Preparing activity:

Army - MU(EA)

Project No. 1375-1007

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:05Z
Check the source to verify that this is the current version before use.