MIL-R-14364F

18 March 1985

SUPERSEDING
MIL-R-14364E(ME)
15 January 1976

# MILITARY SPECIFICATION

# ROLLER, RUBBERIZED, PNEUMATIC:

# BRIDGE ERECTION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 This specification covers a pneumatic, bridge erection roller.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research and Development Center, ATTN: STRBE-DS, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 5420

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:06Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

| | |
|---|---|
| QQ-S-781 | - Strapping, Steel and Seals. |
| PPP-B-601 | - Boxes, Wood, Cleated-Plywood. |
| PPP-B-636 | - Boxes, Shipping, Fiberboard. |

MILITARY

| | |
|---|---|
| MIL-A-5540 | - Adhesive, Polychloroprene. |
| MIL-C-14505 | - Cloth, Nylon, Polychloroprene/Coated (For Pneumatic Floating Equipment). |

STANDARDS

MILITARY

| | |
|---|---|
| MIL-STD-105 | - Sampling Procedure and Tables for Inspection by Attributes. |
| MIL-STD-129 | - Marking for Shipment and Storage. |

2.1.1 Government drawings. The following Government drawings form a part of this specification to the extent specified herein.

DRAWINGS

ME

| | |
|---|---|
| TA13215E9750 | - Roller, Rubberized, Pneumatic: Bridge Erection. |

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:06Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 751 - Testing Coated Fabrics.
ASTM D 3951 - Standard Practice for Commercial Packaging.

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The roller shall be in accordance with Top Assembly TA13215E9750, and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the roller. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or the designated representative.

3.2 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.3 Material. Material shall be as specified herein and on the applicable drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3.1 Material deterioration and control. The roller shall be fabricated from compatible materials, inherently corrosion and deterioration resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable storage and operating environment to which the item may be exposed.

3.3.1.1 Identification of materials and finishes. The contractor shall identify the specific material, finish or treatment for use with components and sub-components and shall make information available, upon request, to the contracting officer or designated representative.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:06Z
Check the source to verify that this is the current version before use.

3.3.2 Gum sheeting and strips. Gum sheeting shall be fabricated from coating compound specified in MIL-C-14505; thickness shall be .025 inch minimum .035 inch maximum. Gum strips shall be cut from the sheeting, width as specified on the drawings; and shall be used to cover all seaming tape and other fabric edges. When joining two sections of gum stripping, the ends shall overlap not less than 1/2 inch.

3.3.3 Coated cloth. The uncured coated cloth used in fabrication of the roller shall conform to MIL-C-14505, class as specified on the drawings.

3.3.4 Seaming and hinge tapes. Tapes used as seam overlaps and as hinge tape shall be cut from coated fabric specified in 3.3.2, class and width as specified on the drawings. When joining two sections of the tape, the ends shall overlap not less than 1 inch.

3.3.5 Adhesive. The adhesive required in the fabrication of the roller shall conform to MIL-A-5540, class 1, color black.

3.3.6 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the roller may be newly fabricated from recovered materials to the maximum extent practicable, provided the roller produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the roller.

3.4 Seams. Cemented seams shall develop the full strength of the coated cloth. Seam overlap for both air chamber and bulkhead fabrics, unless specified otherwise on the drawings, shall be not less than 1-1/2 inches. When tested as specified in 4.5.2.1, the cured seams shall show no slippage greater than 0.1 inch.

3.5 Fabrication. The roller shall be fabricated from uncured coated cloth specified in 3.3.3. All surfaces to be cemented shall be thoroughly cleaned before applying adhesive. Not more than two longitudinal seams shall be allowed in the roller. The end caps of the roller shall be fabricated of either the baseball or gore-type pattern; and the bulkhead shall be fabricated of either the baseball or two-piece (half sphere) type construction. All exposed fabric edges shall be covered with gum strip specified in 3.3.2. The roller, less the handle ropes, shall be vulcanized as a complete unit in a steam-pressure-type autoclave. Swashing of the inner walls of the inflatable compartments with latex or any other sealing compound shall not be permitted either before or after vulcanization. Cemented surfaces shall be adhering with any necessary repairs to be in accordance with 3.11.



Source: https://assist.dla.mil -- Downloaded: 20261O-18T03:06Z
Check the source to verify that this is the current version before use.

3.6 Air retention.

3.6.1 Roller inflation. With both compartments inflated to a pressure of 4 pounds per square inch (psi), the roller shall retain a pressure of not less than 3 psi, after a period of 24 hours. With one compartment inflated to a pressure of 4 psi, the bulkhead shall retain a pressure of not less than 3-1/2 psi, after a period of 4 hours. At the completion of each of these inflation test periods, the roller shall show no evidence of permanent distortion or slippage of seams.

3.6.2 After foldings. When tested as specified in 4.5.2.3.3, repeated folding and inflation of the roller shall not cause damage to the roller; and shall retain a pressure of not less than 2.5 psi, after a period of 24 hours.

3.7 Valve/patch assemblies. When tested as specified in 4.5.2.2.1, the valve/patch assemblies shall show no evidence of separation of the valve core or base from the roller, or permanent deformation of any part of the valve/patch assembly.

3.8 Handle patches. The D-ring handle patches shall withstand a 500 pound pull, applied to the D-ring handle, without any evidence of failure of component parts or separation of the patches from the roller.

3.9 Dimensions. Dimensions subject to variation with air pressure shall be taken with the roller inflated to a pressure of 2 psi.

3.10 Markings. Identification and instructional markings shall be as specified on the drawings, and shall be legible.

3.11 Repair. The first article roller shall not contain any repair patches. Production rollers may be patched with patches prepared from coated cloth conforming to MIL-C-14505, class 7, applied with adhesive specified in 3.3.5, and vulcanized (cured) with the local application of heat and pressure. The edge of any repair patch shall extend not less than 3 inches beyond the extremity of the defect. Gum strips as specified in 3.3.2 shall be used on the periphery of all repair patches. Covering or overlapping of patches shall not be permitted. Not more than 10 percent of the roller shall be patched. Any applied patch shall not adversely affect the strength or serviceability of the roller; and all patched rollers shall conform to the requirements of this specification. Any injury or damage that exposes the base fabric (nylon) of the roller's air chamber cloth shall be repaired with patch material as specified above. Exposed base fabric of nonair-retaining ponton cloth shall be repaired with gum sheeting, cemented, and cured by applying local heat and pressure. Any nonadhering surfaces of cemented material shall be repaired by recementing and curing by applying local heat and pressure; except that in cases of minor edge looseness (maximum distance of 1/4 inch from edge) of nonair-retention material, repair may be made by recementing with an appropriate air curing cement with subsequent rolling or stitching.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:06Z
Check the source to verify that this is the current version before use.

3.12 Workmanship. The finished roller complete with all specified bonded and attached components, shall be free from folds, wrinkles, puckers, defective or missing components, or any other defects.

3.12.1 Cemented surfaces. Surfaces to be cemented shall be thoroughly wiped clean with a cleaning solvent before applying adhesive. The surfaces shall be free from grease, grit and dirt, oil, excess material used in fabrication, and any other foreign materials that could harmfully affect the application of adhesive and the bonding of the cemented surfaces.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications, standards, and drawings, as applicable.

4.1.2 Parts and components. Parts and components detailed on the drawings shall be inspected in accordance with the quality assurance provisions (QAP) shown on the drawings. The drawings specify the characteristics requiring QAP inspection, the sampling plan, and the basis for acceptance and rejection (see 6.4 and 6.5).

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The roller shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.



Source: https://assist.dla.mil -- Downloaded: 202610-18T03:06Z
Check the source to verify that this is the currenversion before use.

4.3.2 Tests. The roller shall be tested as specified in 4.5.2. Samples for the lap seam strength tests shall be fabricated identically to seams in the first article roller from coated cloth representative of the roller and shall be vulcanized identically with the roller represented. Failure of any test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling.

4.4.1.1 For examination. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.1.2 For tests.

4.4.1.2.1 Lap seams. Samples for lap seam tests shall be fabricated identically to seams in the roller, from coated cloth representative of the rollers, and vulcanized simultaneously with, and identically to, the rollers represented. Width of the overlap in the seam shall not exceed the minimum overlap used in any seam in the roller. The sample shall contain not less than 13 inches of linear seam and shall contain 3 inches of coated cloth extending on each side of the seam overlap. One sample shall be furnished for each 40 rollers or fraction thereof submitted for acceptance at one time.

4.4.1.2.2 Production rollers. One sample roller shall be selected at random from each lot of 40 rollers or fraction thereof submitted for acceptance at one time.

4.4.2 Examination. Samples selected in accordance with 4.4.1.1 shall be examined for the major and minor defects specified in 4.5.1. AQL shall be 2.5 percent defective for major defects, and 4.0 percent defective for minor defects.

4.4.3 Tests.

4.4.3.1 Individual. Each roller shall be tested as specified in 4.5.2.3.1 and 4.5.2.3.2. Rollers failing to pass either test shall be rejected. Rejected rollers may be repaired and resubmitted for test and acceptance. Repairs shall conform to the requirements specified in 3.11. Failure of a test of a repaired roller shall be cause for rejection.

4.4.3.2 Samples.

4.4.3.2.1 Lap seam. Samples selected and fabricated in accordance with 4.4.1.2.1 shall be tested as specified in 4.5.2.1. Failure of any test specimen prepared from the samples shall be cause for rejection of the lot of rollers represented by the samples.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:06Z
Check the source to verify that this is the current version before use.

4.4.3.2.2 Production rollers. Rollers selected in accordance with 4.4.1.2.2 shall be tested as specified in 4.5.2.2 and 4.5.2.3.3. Failure of any test shall be cause for rejection of the lot of rollers represented by the tested sample roller.

4.5 Inspection procedure.

4.5.1 Examination. The completed roller shall be examined as specified herein for the following defects:

Major

101. Roller is not in accordance with the drawings as specified.
102. Any part (or component) not in accordance with the QAP requirements as shown on the drawings.
103. Materials not as specified.
104. Materials are not resistant to corrosion and deterioration or treated to be resistant to corrosion and deterioration for the applicable and operating environments.
105. Contractor does not have documentation available for identification of material, material finishes or treatment.
106. Gum sheeting and strips not as specified.
107. Coated cloth not as specified.
108. Seaming and hinge tapes not as specified.
109. Adhesive not as specified.
110. Used, rebuilt or remanufactured components, pieces or parts incorporated in the roller.
111. Fabrication not as specified.
112. More than two longitudinal seams.
113. Gum strip overlap less than 1/2 inch.
114. Seam width (overlap) less than 1-1/2 inch.
115. Swashing of inner walls of air compartments with liquid sealing compound.
116. Repair patches not as specified or overlapping.
117. Nonadhering cemented surfaces.
118. Fittings/hardware not as specified.
119. Hardware finish incorrect.
120. Workmanship not as specified.
121. Cemented surfaces not as specified.

Minor

201. Any dimensions other than those identified on the QAP requirements shown on the drawings not as specified.
202. Identification and instruction markings incorrect, illegible, or missing.
203. Color of materials not as specified.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:06Z
Check the source to verify that this is the current version before use.

4.5.2 Tests.

4.5.2.1 Lap seam strength. Prepare six specimens by cutting the seam sample into 2 inch widths. Test three specimens to failure in accordance with ASTM D 751, modified grab method. Ruptures of any specimen at the seam before rupture of the coated cloth shall constitute failure of this test. If the specimens pass the above test, test the remaining three specimens as follows: The test specimens shall be 1.0 inch, plus or minus 0.020 inch wide, (parallel to the seam) and coated fabric shall extend a minimum of 3 inches (perpendicular to the seam) on each side of the seam. One index mark shall be scribed on each side of the seam to facilitate observation and measurement of slippage. Subject each specimen to a tensile load (dead weight) of 80 pounds (40 pounds per inch width) at a temperature of 200° F, for a period of 24 hours and examine the seams for slippage. Nonconformance to 3.4 shall constitute failure of this test.

4.5.2.2 Pull resistance.

4.5.2.2.1 Valve/patch assemblies. Apply a pulling force of 200 pounds to one valve/patch assembly of the roller. Apply the pulling force to either the valve core (with the valve cap assembly removed) or to the valve cap (with the valve cap assembly installed), in a direction perpendicular to the plane of the valve base. Hold the pulling force for not less than 10 seconds. Nonconformance to 3.7 shall constitute failure of this test.

4.5.2.2.2 Handle patches. Apply a pulling force of 500 pounds to one D-ring handle of the roller. Apply the pull perpendicular to the plane of the patch for the D-ring handle. Position the roller so that the test load will not cause distortion. Hold the load for not less than 10 seconds and examine the attachment for defects. Nonconformance to 3.8 shall constitute failure of this test.

4.5.2.3 Air retention.

4.5.2.3.1 Roller compartments. Inflate both compartments of the roller with air to a pressure of approximately 4 psi. After not less than 1 hour, adjust the pressure in both compartments as closely as possible to 4 psi. After this adjustment, seal the valve caps in such a manner that the roller cannot be inflated without breaking the seal. After 24 hours, take a final pressure reading of each compartment. Adjust the final pressure reading to compensate for any temperature and barometric pressure change during the test period. This adjustment shall be calculated on the basis of a change in pressure of 0.3 psi per 10° F change in temperature, and 0.49 psi per 1 inch (mercury) change in barometric pressure. Nonconformance to 3.6.1 shall constitute failure of this test.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:06Z
Check the source to verify that this is the current version before use.

4.5.2.3.2 Bulkhead. Inflate one compartment of the roller with air to a pressure of approximately 4 psi. After not less than 1 hour, adjust the pressure as closely as possible to 4 psi, and seal the valve as specified in 4.5.2.3.1. After 4 hours take a final pressure reading of the inflated compartment. Adjust the final reading to compensate for temperature and barometric pressure changes as specified in 4.5.2.3.1. Nonconformance to 3.6.1 shall constitute failure of this test.

4.5.2.3.3 Folding and air retest. Deflate both compartments of the roller; fold both ends toward the center and then fold one-half of the roller on top of the other folded half; unfold the roller and inflate both compartments to 4 psi. Repeat this cycle 25 times. After completion of these 25 cycles, inflate, both air compartments of the roller to 4 psi and test for air retention, for 24 hours, as specified in 4.5.2.3.1. Nonconformance to 3.6.2 shall constitute failure of this test.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Inspection stages. Inspection shall be in two stages as follows:

a. The first stage shall include inspection of materials, methods, and interior marking inside the shipping container.

b. The second stage shall include inspection of materials and marking after closing of the shipping container.

4.6.1.2 Unit of product. For the purpose of inspection a unit of product for the first stage of inspection shall be a complete pack with the box top off. For the second stage of inspection, a unit of product shall be a completed pack ready for shipment.

4.6.1.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.4 Examination. Samples selected in accordance with 4.6.1.3 shall be examined for the following defects. AQL shall be 2.5 percent defective.

| | |
|---|---|
| 122. | Materials not as specified for level A. |
| 123. | Powdered soapstone or talc not applied to the roller before folding for level A or commercial. |
| 124. | Box not closed and sealed as specified for level A. |
| 125. | Boxes not as specified for level A or B. |
| 126. | Preservation and packing not in accordance with the referenced document as specified for commercial. |
| 127. | Marking missing, illegible, incorrect, or incomplete for level A, B, or commercial. |



Source: https://assist.dla.mil -- Downloaded: 20260-18T03:06Z
Check the source to verify that this is the current version before use.

5. PACKING

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

5.1.1 Level A. Each deflated roller shall be dusted with powered soapstone or talc and compactly folded, then placed in a close fitting box conforming to PPP-B-636, W5c, style optional. The box shall be closed and sealed as specified for method V in the appendix to the box specification.

5.1.2 Commercial. Each roller shall be preserved in accordance with ASTM D 3951 and in addition shall be dusted with powdered soapstone or talc to prevent adhesion to itself.

5.2 Packing. Packing shall be level A, B, or commercial as specified (see 6.2).

5.2.1 Level A. Rollers, preserved as specified in 5.1, shall be packed together in a close-fitting box conforming to PPP-B-601, overseas type, style optional. The boxes shall be closed and strapped in accordance with the appendix to the box specification. Strapping shall conform to QQ-S-781, class 1, type I or IV, size as applicable. Unless otherwise specified (see 6.2) strapping shall be finish B. When specified (see 6.2) strapping shall be finish A.

5.2.2 Level B. Rollers, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except the boxes shall be domestic type and strapping shall be finish A.

5.2.3 Commercial. Rollers, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking.

5.3.1 Military. Marking for military levels of protection (level A or B) shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Commercial marking shall be in accordance with ASTM D 3951.

6. NOTES

6.1 Intended use. The pneumatic roller is intended for use in launching of floating supports for various military floating bridges.



Source: https://assist.dla.mil -- Downloaded: 202640-18T03:06Z
Check the source to verify that this is the currentversion before use.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this specification.

b. When a first article is required for inspection and approval, and the number of units required (see 3.2).

c. Degree of preservation and degree of packing required (see 5.1 and 5.2).

d. When other than finish B strapping is required (see 5.2.1).

6.3 First article. When a first article inspection is required the item shall be examined and tested and should be a first produced roller. The contracting officer should include specific instructions in the acquisition documents regarding arrangements for examinations and approval of the document's first article.

6.4 Quality assurance provisions (QAP). The contracting officer should require the contractor to maintain records of all QAP inspections. A suggested paragraph is as follows:

> "The contractor shall maintain complete records of all examinations and tests performed to varify the requirements of classified QAP characteristics. The records shall include as a minimum, lot size, sample size, drawing requirement, actual measurement, number and type of deficiencies found, quantity approved, quantity rejected, corrective action taken when applicable."

6.5 Definition.

6.5.1 Quality assurance provisions (QAP). A QAP is a contractual requirement that supplements section 4 of the specification. AQP indicates the minimum requirements which must be inspected on the product drawings to verify the design objectives of the product and assure interchangeability of repair parts.

Custodians:
Army - ME
Navy - MC

Preparing activity:
Army - ME

Project 5420-0154



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:06Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-R-14364F | Roller, Rubberized, Pneumatic: Bridge Erection |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR |
| | ☐ USER |
| b. ADDRESS *(Street, City, State, ZIP Code)* | ☐ MANUFACTURER |
| | ☐ OTHER *(Specify)*: _____ |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:06Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE ARMY
USA Belvoir R&D Center
STRBE-DS
Fort Belvoir, VA 22060-5606

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

**BUSINESS REPLY MAIL**
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
USA Belvoir R&D Center
STRBE-DS
Fort Belvoir, VA 22060-5606

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:06Z
Check the source to verify that this is the current version before use.