INCH POUND

MIL-T-14358C
INT. AMENDMENT 1(CR)
12 December 1991

MILITARY SPECIFICATION

TELEPHONE SET TA-312( )/PT

This interim amendment is approved for use within the Communications-Electronics Command, Department of the Army, with MIL-T-14358C, dated 7 Sept 89.

PAGE 2

2.1.2, line 8: Delete "DL-SM-B-283350" and substitute "DL-A3057865."

PAGE 3

3.2, line 2: Delete "specification and Drawing and Data List DL-SM-B-283350" and substitute " specification, Drawing A3057865, and Data List DL-A3057865."

PAGE 4

3.8.1.2, first line: Delete "500 Volts" and substitute "500 Volts dc."

3.8.2.6, line 3: Add "This requirement is for reference only."

3.8.2.7, first line: Delete "500 volts" and substitute "500 volts dc."

PAGE 5

3.12.5.1: Delete in its entirety. Substitute "The equipment shall meet the requirements of para 3.8.2.9 following testing specified in para 4.14."

PAGE 13

4.9.2, line 2: Delete "500 volts" and substitute "500 volts dc."

4.9.3, line 3: Add "Electrification time shall be for at least one (1) minute."

PAGE 14

4.10.3, line 2: Delete "500 volts" and substitute "500 volts dc."
line 3: Delete "10 seconds" and substitute "30 seconds."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:05Z
Check the source to verify that this is the current version before use.

4.10.4, line 3: Add "Electrification time shall be for at least one (1) minute."

4.10.5.3, line 2: Delete "4.10.3.2" and substitute "4.10.5.2."

PAGE 15

4.10.5.5: Delete in its entirety. Substitute "A loud and clear two-way conversation shall be established between two sets which are connected together with the following switch settings and external connections:

Test No.	Condition(s)	TA-312( )/PT #1	TA-312( )/PT #2
1	Batteries:	internal (only)	internal (only)
	INT-EXT switch:	INT	INT
	Mode selector switch:	LB	LB
	Test:	Two-way conversation	Two-way conversation
2	Batteries:	Remove internal batteries and connect a 3 volt dc power source to the BAT terminals	Same as Unit #1
	INT-EXT switch:	EXT (connect an external handset to the U-79/U receptacle)	Same as Unit #1
	Mode selector switch:	CBS	CBS
	Test:	Two-way conversation	Two-way conversation

4.11.1, line 2: Delete "Method 502" and substitute "Method 502.1."

4.11.2, line 2: Delete "Method 501" and substitute "Method 501.1."


4.12, first line: Delete "Method 507" and substitute "Method 507.1."
line 3: Add "The insulation resistance specified during humidity cycling shall be 1 megohm minimum."

4.13, first line: Delete "Method 500" and substitute "Method 500.1."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:05Z
Check the source to verify that this is the current version before use.


4.14: Delete in its entirety and substitute the following:
"(a) Clamp the TA-312( )/PT to the vibration table in each of the following positions:

Position 1.



Vibration Axis

Position 2.



Vibration Axis

(b) In each of the above positions, vibrate the equipment for a total of 1-1/2 hours as follows: At a non-resonant frequency with an acceleration of 2.5 G's for a 1/2 hour in each of the following frequency ranges: 20-30 Hz; 40-50 Hz.

(c) At the conclusion of the three hour test, the unit shall meet the requirements of paragraph 3.8.2.9.

4.15, line 2: Delete "Method 514.1" and substitute "Method 514.2."

4.16, line 2: Delete "Method 516.1" and substitute "Method 516.2."

PAGE 16

4.18, line 2: Delete "Method 508" and substitute "Method 508.1."

4.19, line 2: Delete "Method 509" and substitute "Method 509.1."

4.20, first line: Delete "Method 510" and substitute "Method 510.1."

Preparing Activity:
Army - CR

Project No. 5805-A361

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:05Z
Check the source to verify that this is the current version before use.