MIL-T-14382W
2 March 1988
SUPERSEDING
MIL-T-14382V
22 March 1985

MILITARY SPECIFICATION

TRUCKS, AMBULANCE: DIESEL, OR GASOLINE ENGINE DRIVEN, 10,000 POUNDS GVW, 4X4, 4-LITTER (COMMERCIAL, FIELD TYPE)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers diesel or gasoline engine driven, four-wheel, four-wheel drive, field type ambulance trucks having a gross vehicle weight (GVW) rating of not less than 10,000 pounds. Vehicles procured under this specification are commercial items which shall be warranted by the manufacturer as specified in acquisition documents.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS), and supplement thereto, cited in the solicitation.

SPECIFICATIONS
FEDERAL

W-B-131	- Battery, Storage: Vehicular, Ignition, Lighting and Starting.
ZZ-T-381	- Tires, Pneumatic, Vehicular (Highway).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC-2310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-514	- Plates, Identification, Instruction and Markings, Blank.
MIL-B-46176	- Brake Fluid, Silicone, Automotive All Weather, Operational and Preservative.

STANDARDS

FEDERAL

FED-STD-297	- Rustproofing of Commercial (Nontactical) Vehicles.
FED-STD-595	- Colors.

MILITARY

MIL-STD-1223	- Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking and Data Plate Standards.
MS3112	- Connectors, Receptacle, Electric.
MS3116	- Connectors, Plug, Electric.
MSS1317	- Light, Warning, Vehicular, Rotating, D.C.
MSS1335	- Pintle Assembly, Towing.

DRAWINGS

MILITARY

11658584	- Strap Assembly

2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

(Application for copies of DoT publications should reference the Code of Federal Regulations, 49 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.
Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

(Application for copies of EPA publications should reference the Code of Federal Regulations, 40 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the non-Government document which is current on the date of the solicitation.

SAE, INC.

SAE Standards and Recommended Practices

J537	- Storage Batteries.
J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
J560	- Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
J706	- Rating of Winches.
J1349	- Engine Power Test Code -Spark Ignition and Diesel.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.

Yearbook.

(Application for copies of Tire and Rim Association publications should be addressed to The Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.11, the vehicle, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items, which meet or exceed the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

All chassis items shall be as represented in the chassis manufacturer's technical data, and special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be available to the engineering offices of the procuring activity prior to delivery of the item. The chassis model furnished shall be not older than the chassis manufacturer's current model on the date of invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

3.1.1.1 Painting and marking. Treatment, painting, marking and data plates shall be in accordance with MIL-STD-1223. The exterior color and identification markings shall be in accordance with the requirements of MIL-STD-1223 for the military service identified by the procuring activity (see 6.2). When specified (see 6.2), concealed markings shall be furnished. Unless otherwise specified (see 6.2), ambulance markings for all vehicle colors shall be furnished as follows:

(a) On the front, where space permits, the word "AMBULANCE" shall be displayed in mirror image, in letters three inches high, centered above the windshield. A three-inch high red cross on a four-inch square white field shall be located both to the left and to the right and in line with the word "AMBULANCE" above the windshield
(b) On the rear, a six-inch high red cross on an eight-inch square white field shall be centered on each rear door panel, approximately eight to ten inches below the window, depending on the vehicle configuration
(c) On the sides, a 36-inch red cross on a 48-inch square white field shall be centered between the front door and the rear corner
(d) On the top, a 36-inch red cross on a 48-inch square white field shall be applied
(e) The color of the markings for the crosses shall be gloss red matching color chip No. 11136 of FED-STD-595. The color of each white field shall be gloss white matching color chip No. 17886 of FED-STD-595. The color of the word "AMBULANCE" shall be in contrast to the vehicle's exterior color and shall be either gloss white matching the color of the white field, or the manufacturer's standard gloss black.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.1.1.2 No smoking signs. Signs reading "NO SMOKING IN MEDICAL VEHICLES" shall be prominently displayed, one in the driver's and one in the patients' compartment. The signs shall be not less than 3-1/2 inches high and 5 inches wide. The letters shall be red on a contrasting background.

3.1.1.3 Identification and instruction plates. All operating controls for equipment in the patient's compartment and for ambulance equipment shall be provided with identification plates and, as appropriate, with caution, warning and instruction plates. Plates shall conform to composition A (class 1 or 2) or composition C of MIL-P-514.

3.1.1.4 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297. When specified (see 6.2), tropical rustproofing in accordance with FED-STD-297 shall be furnished.

3.1.1.5 Towing devices. Not less than two hooks, loops, or pins for towing the vehicle shall be furnished on the front of the vehicle.

3.1.1.6 Wood treatment. Wood shall be treated in accordance with MIL-STD-1223.

3.1.1.7. Brushguard. The vehicle shall be equipped with a radiator and headlamp brushguard.

3.1.1.8 Drive hubs. Unless interaxle compensating devices between front and rear axles are furnished, manual or automatic drive hubs, for disengaging the front wheels from the power train, shall be provided.

3.1.1.9 Trailer towing package. When specified (see 6.2), a trailer towing package consisting of a pintle, safety chain attachment devices, a lighting receptacle, and associated reinforcements and wiring shall be installed on the rear of the vehicle. The pintle shall be of the fixed type conforming to MS51335-2 and shall be installed on the chassis frame with reinforcements to transfer a vertical tongue load of not less than 1,800 pounds and a horizontal drawbar load of not less than 18,000 pounds directly to the chassis rails. The rearmost portion of the pintle shall be forward but not more than four inches forward of the rearmost part of the vehicle. Two trailer safety chain attachment devices, one adjacent to each side of the pintle, shall be provided. Each attachment device shall provide an ultimate strength at least equal to the GVW of the truck furnished. The attachment devices shall be capable of accommodating a standard grab hook (2-3/16 inches wide, 47/64 inch thick, and 31/64-inch throat width) for a 3/8-inch chain. The lighting receptacle, conforming to SAE J560, with its conductors connected and color coded as specified therein, shall be mounted in a readily accessible location near the pintle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.1.1.10 Winch. When specified (see 6.2), a winch assembly to be used for assist the truck in negotiating difficult terrain shall be provided on the front of the vehicle. The winch shall conform to SAE J706. The winch shall have forward and reverse drum drive and a drum clutch to permit free-spooling of the cable. The winch may be mechanically or hydraulically driven and may be powered from either the transmission or the transfer case power takeoff. The winch shall be wound with not less than 150 feet of wire rope and shall be furnished with an end chain and hook. The winch single line pull rating on the bare drum and nominal breaking strength of the wire rope, chain and hook shall be not less than the chassis manufacturer's GVW rating. The wire rope shall be of improved plow steel, six-strand, 37-wire, hemp core, preformed, regular lay hoisting rope, with cable loop formed at the end. A four-way roller guide shall be furnished. The bumper shall be mounted forward of the winch. The open area on either side of the winch shall be covered by a plate.

3.1.1.11 Silicone brake fluid. When specified (see 6.2), and if available as the manufacturer's standard or optional brake fluid, brake fluid conforming to MIL-B-46l76 shall be provided in the hydraulic brake system. A tag shall be placed near the master cylinder stating: "CAUTION: USE SILICONE BRAKE FLUID ONLY, MIL-B-46176.

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

3.2.2 Air pollution control. The vehicle shall comply with EPA Regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, vehicles destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

3.2.3 Sound level. The interior sound level shall conform to Federal Motor Carrier Safety Regulation 393.94. The vehicle exterior sound level shall conform to EPA Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

3.2.4 Curb weight. The curb weight shall include the weight of the chassis, integral cab and body, with all attachments, accessories, equipment, and a full complement of fuel, lubricants and coolant.

Source: https://assist.dla.mil -- Downloaded: 2026l0-18T03:07Z
Check the source to verify that this is the current version before use.

3.2.5 Gross vehicle weight. The gross vehicle weight (GVW) shall consist of the curb weight, the driver and the assistant driver weights (175 pounds each), and a payload, evenly distributed over the load area, to provide not less than 10,000 pounds GVW. In addition, the actual GVW of the vehicle furnished shall exceed the 10,000 pounds GVW when required to provide a payload of not less than 1,600 pounds.

3.2.6 Dimensions. The wheelbase shall be not less than 135 inches. The vehicle height shall be not more than 105 inches, exclusive of the warning light(s). The overall width of the vehicle, exclusive of mirrors, lights and reflectors, shall be not more than 84 inches. The patients' compartment floor shall be not more than 39 inches from the ground when the vehicle is without payload and is in a level position.

3.2.7 Standard frame and driveline. The chassis frame and driveline shall be the chassis manufacturer's standard and shall not be spliced to extend the wheelbase.

3.2.8 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

3.3 Performance.

3.3.1 Speeds and gradeability. High and low speed requirements shall be met with the vehicle loaded to specified GVW and with the front wheel drive disengaged.

3.3.1.1 High speed performance. The vehicle, loaded to rated GVW shall be capable of maintaining a high speed of not less than 60 mph on smooth, level, hard-surfaced roads.

3.3.1.2 Low speed gradeability. The vehicle, loaded to rated GVW, shall be capable of ascending continuous grades of not less than 35 percent in low speed range.

3.3.1.3 Low speed. Low speed for vehicles with manual transmissions shall be calculated with the engine operating at not less than 35 percent of recommended governed speed and shall provide a vehicle speed of not more than 4 mph.

3.3.2 Service brakes. The service brakes shall control and hold the vehicle, when loaded to its required GVW, on a 35 percent grade. Under all conditions of loading, the service brakes shall stop the vehicle, from a speed of 20 mph, in not more than 30 feet from the point at which

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

movement of the brake pedal begins. Deceleration and stopping distance shall be demonstrated on dry, hard, approximately level road surface free from loose material.

3.3.2.1 Parking brakes. A hand or foot actuated parking brake shall be furnished in addition to the service brakes. When a foot actuated parking brake is furnished, a hand lever shall be furnished to release the parking brake. The vehicle parking brake shall be capable of holding the vehicle, loaded to required GVW, on a 35 percent slope.

3.4 Chassis components.

3.4.1 Engine. The engine furnished for the specified vehicle shall be the chassis manufacturer's standard or optional engine for the commercial model truck which meets or exceeds the requirements of this specification.

3.4.1.1 Diesel engine. Unless otherwise specified (see 3.4.1.2), the vehicle shall be equipped with a liquid cooled, compression ignition, two-stroke or four-stroke cycle diesel engine, with not less than eight cylinders. Engine net torque capacity shall be not less than 240 pound-feet. Engine net torque capacity and net horsepower used in performance prediction calculations shall be determined in accordance with SAE J1349.

3.4.1.2 Gasoline engine. When specified (see 6.2), the vehicle shall be equipped with a liquid cooled, internal combustion, four-stroke cycle gasoline engine with not less than eight cylinders. The engine furnished shall produce the required vehicle performance when operated on unleaded fuel with a research octane rating of 91, at an engine speed of not more than the manufacturer's recommended operating speed. The engine shall be capable of warranted operation on unleaded fuel, when used in accordance with the operator's manual. The rated net torque output of the engine shall be not less than 230 pound-feet. Engine net torque ratings and net horsepower used in performance prediction calculations shall be determined in accordance with SAE J1349. Unless otherwise specified or required by foreign laws, vehicles for overseas use shall be capable of accepting and operating on leaded gasoline.

3.4.1.3 Oil filter. A full flow type oil filter shall be furnished.

3.4.1.4 Cooling system. The cooling system shall maintain the engine coolant at a temperature below the boiling point with the vehicle loaded to rated GVW and operated at an altitude of 10,000 feet above sea level or in an ambient air temperature of not less than 125 degrees Fahrenheit (F°). The coolant system shall include a surge tank or a coolant recovery

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

reservoir of not less than two quart capacity. A high coolant temperature red indicator warning light shall be provided on the instrument panel.

3.4.1.5 Coolant temperature control. Thermostatic control of engine coolant temperature shall be provided. On diesel engine driven vehicles, the control shall include partial thermostatic control of coolant flow through the radiator and thermostatically controlled radiator shutters, or complete thermostatic control of all coolant flow through the radiator.

3.4.1.6 Fan clutch. A fan clutch shall be provided. The fan clutch shall reduce the fan speed automatically when the fan is not required for engine cooling.

3.4.1.7 Power plant heaters and fuel warmers. When specified (see 6.2), a coolant heater, an engine oil heater, and a fuel warmer (diesel engine driven vehicles only) shall be provided. Unless otherwise specified (see 6.2), a battery heater shall be provided when power plant heaters are specified. Heaters shall operate on 110-volt alternating current (ac), and shall be wired through a junction block to a single, three-pronged (male), weatherproof slave receptacle for receiving external power and grounding the vehicle. A three-wire connecting cable, 25 feet long, and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. The connecting cable shall include a matching female connector at the vehicle end and a standard, weatherproof, three-pronged (two power plus one ground) male connector at the other end. Electrical apparatus shall conform to Federal Motor Carrier Safety Regulation 393.77(c)(7). Electrical insulation of connecting cable shall withstand normal operating stresses in low ambient air temperatures (down to minus 60°F) without cracking or loss of dielectric capacity. All heater lead wires shall be installed without interfering with vehicle component operation and without loose excess wire. Provisions for stowage of the cable shall be provided in the vehicle cab. Heaters shall be furnished as follows:

(a) Coolant heaters, 1500-watt minimum rating, shall be installed in the engine block or in the lower coolant inlet hose. Engine thermostat with an operating range of 170°F to 195°F shall be installed
(b) Immersion type engine oil heater, 300-watt minimum rating, with 170°F to 195°F thermostat, shall be installed in oil pan through any convenient opening
(c) Battery heater shall have a capacity adequate to maintain the battery electrolyte at a temperature of not less than l0°F during vehicle exposure in ambient air temperatures as low as minus 60°F, and shall embody a thermostat to limit the temperature of the electrolyte to not more than 80°F

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

(d) A fuel warmer or preheater shall be provided on diesel engine driven vehicles to prevent clogging of fuel filters due to wax crystallization in the fuel. The fuel warmer shall use engine coolant to transfer sufficient heat to the diesel fuel to heat it from an inlet temperature of minus 40°F to an outlet temperature of plus 9°F, with a flow rate not less than the maximum fuel demand of the engine fuel system. A coolant shutoff valve shall be provided for the coolant inlet side of the fuel warmer unit.

3.4.1.8 Fuel fired engine preheater. When specified (see 6.2), for diesel engine driven vehicles, a diesel fuel fired engine coolant heater shall be furnished to preheat the engine. The heater shall include a timer, a thermostat and a circulating pump and shall be connected directly across the engine coolant inlet and outlet. The heater shall be capable of starting and operating at minus 60°F and shall heat the engine to plus 40°F from minus 60°F in not more than 1 hour. The system shall be equipped with a light, visible to the driver, to indicate that the preheater is operating.

3.4.2 Electrical system. The electrical system shall be in accordance with Federal Motor Carrier Safety Regulations 393.27 through 393.31 and 393.33.

3.4.2.1 Starting system (diesel engine). For diesel engine driven vehicles, a 12 or 24-volt direct current (dc starting system, with a 12-volc dc lighting system, shall be furnished. Unless otherwise specified (see 6.2), a minimum 90-ampere alternator shall be furnished which provides a dc output capacity, at normal engine idle speed, adequate to support all electrical loads operating simultaneously, except the winch. Engine starting equipment shall include au ether starting system or a glow plug. If an ether system is furnished in lieu of a glow plug, it shall be of the measured shot type. The measured shot type ether system shall be key operated or manually operated from the driver's compartment, and shall be inoperative with the engine warm. Complete provisions for a replaceable reservoir of not less than 12 fluid ounces shall be furnished. A reservoir need not be furnished.

3.4.2.2 Ignition system (gasoline engine). For gasoline engine driven vehicles, a 12-volt dc system shall be furnished. Unless otherwise specified (see 6.2), an alternator of not less than 60 amperes rated capacity shall be furnished which provides a dc output capacity, at normal engine idle speed, adequate to support all electrical loads operating simultaneously, except the winch.

3.4.2.3 Battery. The battery furnished shall be of 12-volt potential. The total reserve capacity ratings and the total cold cranking ratings at 0°F, both measured in accordance with

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

SAE J537, shall be not less than specified in table I. The batteries shall be of the maintenance-free type having the maintenance-free characteristics listed in W-B-131.

Table I. Batteries.

Engine Type	Reserve Capacity (minutes)	Cold Cranking (amperes)
Gasoline	100	450
Diesel	320	1,200

3.4.2.4 Lighting. All vehicle lights, reflectors and wiring shall conform to Federal Motor Carrier Safety Regulations 393.12, 393.19, 393.20 and 393.22 through 393.26(d). When available as the manufacturer's standard or optional feature, the brake lights shall override the four way emergency flashers. When specified (see 6.2), left-dip headlights (as used on right-hand drive vehicles) shall be furnished, and shall be adjusted prior to shipment for driving on the left side of the road.

3.4.2.4.1 Turn signals. Turn signal operating unit shall be of the self cancelling type with a visible and audible type flash indicator.

3.4.2.5 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Any body equipment emitting electromagnetic radiation shall be suppressed to the same level as the vehicle chassis.

3.4.3 Fuel system. The fuel system shall conform to Federal Motor Carrier Safety Regulations 393.65 and 393.67, except compliance with 393.67(c), subparagraphs (1), (4)(ii), (7)(ii), (8), (9), (11); 393.67(d) and 393.67(f) is not required. The total capacity of the fuel tank(s) shall be not less than 35 gallons. When more than one tank is furnished on gasoline engine driven vehicles, a selector valve connecting either tank to the engine fuel intake shall be provided, and means shall be provided to monitor the fuel level of either tank from a single gage. When more than one tank is furnished on diesel engine driven vehicles, means shall be provided to assure an equalized fuel level in both tanks or a selector valve and fuel monitor gage as described above shall be furnished.

3.4.3.1 Air cleaner. An air cleaner shall be furnished.

3.4.4 Exhaust system. The exhaust system shall conform to Federal Motor Carrier Safety Regulation 393.83. The exhaust tailpipe shall extend to the rear of the body or to the side behind

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

the rear wheels, and shall be so located as to minimize the possibility of exhaust fumes entering the body.

3.4.5 Transmission. Unless an automatic transmission is specified (see 3.4.5.3), a manually shifted transmission shall be provided. The input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine. The transmission shall have not less than four forward speeds and one reverse speed. The transmission shall provide for the maximum ease of shifting with synchronized shift for at least the two highest forward speeds.

3.4.5.1 Transfer case. A two-speed transfer case shall be furnished. The transfer case shall provide for driver selection of either two-wheel or four-wheel drive.

3.4.5.2 Clutch. The clutch for the manual transmission shall be the largest capacity clutch offered for the type of vehicle and size of engine furnished, with the clutch torque capacity exceeding the maximum delivered engine torque.

3.4.5.3 Automatic transmission. When specified (see 6.2), the vehicle shall be provided with an automatic transmission. The input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine. The transmission shall have not less than three forward gear ratios and one reverse gear ratio.

3.4.6 Driveline components. The driveline components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

3.4.7 Frame. The chassis frame shall be the manufacturer's standard for the vehicle furnished.

3.4.8 Suspension. The vehicle shall be equipped with a suspension system, with components having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the vehicle loaded to the required GVW. When suspension is rated at the spring pads, unsprung weight shall be deducted.

3.4.8.1 Shock absorbers. The vehicle shall be provided with heavy duty, hydraulic, double-acting shock absorbers on the front and rear axles. The heavy duty shock absorbers shall have a diameter larger than the manufacturer's standard shock absorbers for the model vehicle furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.4.8.2 Heavy duty suspension. When specified (see 6.2), heavy duty springs shall be furnished. The heavy duty springs shall have a rated capacity equal to the load imposed, plus at least 10 percent, with the vehicle loaded to specified GVW.

3.4.9 Axles. The front and rear axle ratings shall be at least equal to the load imposed on each axle, measured at the ground, with the vehicle loaded to required GVW. In addition, the front axle rating shall be not less than 4,000 pounds. A single reduction rear axle shall be furnished.

3.4.9.1 Positive traction differential. When specified (see 6.2), a rear axle with positive traction, limited slip, or automatic locking differential shall be furnished.

3.4.10 Wheels, rims, tires and tubes. The vehicle shall be equipped with single front and dual rear wheels. Except as specified herein, rims and tire ratings shall conform to Tire and Rim Association recommendations for the type and size of tires furnished. Rims and disc wheel sizes shall be the same for all wheels. Tire size and load range (ply rating) shall be the same for all tires. When specified (see 6.2), disc type wheels shall be furnished.

3.4.10.1 Tires. Unless otherwise specified (see 6.2), tires shall be tube type with nondirectional mud and snow tread. Tires shall have a rated capacity at least equal to the load imposed on each wheel, measured at the ground, with the vehicle loaded to required GVW. A tire load range rating of not less than a D (8-ply) shall be furnished. The tires shall conform to Tire and Rim Association recommendations, or to ZZ-T-381 with a size designation system the same as the Tire and Rim Association.

3.4.10.2 Inner tubes. The inner tubes shall be of the proper size for the tires furnished. When mounted on other than drop center rims tire flaps shall be furnished.

3.4.10.3 Carrier for spare tire assembly. Unless otherwise specified (see 6.2), a carrier for a spare wheel or rim and tire assembly shall be installed in a cabinet in the patients' compartment or under the rear of the vehicle body. Threaded fasteners, when used to secure the spare wheel or rim or the spare tire assembly in the carrier, shall be constructed of or plated with corrosion-resistant material. The carrier design shall permit removal or installation of the spare wheel or rim or spare tire assembly using only the tools specified in 3.4.15. When the carrier is located under the vehicle, instructions and a means shall be furnished to assist the vehicle operator in lowering the spare tire assembly to the ground.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.4.10.4 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be furnished. When a spare tire assembly is specified, a spare wheel or rim shall be furnished.

3.4.10.4.1 Spare tire assembly. Unless otherwise specified (see 6.2), an inflated spare tire mounted on the spare wheel or rim shall be furnished. The spare tire shall be of the same size, tread design and load range (ply rating) as the tires in use on the vehicle.

3.4.11 Brakes. Brakes shall conform to Federal Motor Carrier Safety Regulations 393.40 through 393.42 (except 393.40(b)(1)(i)), 393.45 through 393.49, and 393.51. When available as the manufacturer's standard or as an option, brake linings shall be of nonasbestos material. The vehicle shall be equipped with power assisted, hydraulically actuated, four wheel service brakes.

3.4.11.1 Split hydraulic brake system. The power-hydraulic brake system shall be so arranged as to provide separate systems for at least two wheels and so designed and constructed that rupture or leakage type failure of any single pressure component of the service brake system, except structural failures of the brake master cylinder body, effectiveness indicator body, or other housing common to the divided system, will not result in complete loss of function of the vehicle brakes when force on the brake pedal is continued. "Pressure component" means any internal component of the brake master cylinder or master control unit, wheel brake cylinder, brake line, brake hose, or equivalent, except power assist components.

3.4.11.2 Indicator lights. The split hydraulic brake system shall be equipped with an electrically operated red light mounted on the instrument panel to indicate system effectiveness. The light shall have an area of not less than 0.196 square inch. It shall illuminate before or upon application of the brakes when an actuating-pressure component of the system has sustained a loss of pressure. The indicator light system shall include a means for testing by the vehicle operator to assure that the light bulb is operable.

3.4.12 Steering. Power steering shall be furnished.

3.4.13 Windshield wipers and washers. The vehicle shall be equipped with dual windshield wipers and windshield washers. Windshield wipers shall be of the multispeed type and operated by electric motor(s).

3.4.14 Bumpers. Front and rear bumpers and rear end protection shall be provided. Rear end protection shall conform to Federal Motor Carrier Safety Regulation 393.86. The rear bumper shall conform to 3.5.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.4.15 Tools. Unless otherwise specified (see 6.2), the vehicle shall be furnished with tools required for exchanging a mounted tire assembly with the spare assembly, and shall include at least a hydraulic jack, jack handle and wheel nut wrench. The jack shall be of such closed height as to permit its location under axle or other satisfactory lift point, at any wheel with a tire flat. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of the wheel and tire assembly.

3.4.16 Controls and operating mechanisms. All controls and operating mechanisms shall be located for left-hand drive. The controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of the operator to and from the driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. The instruments shall be panel mounted.

3.4.17 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

(a) Inside rearview mirror
(b) Key-operated ignition switch
(c) Ammeter or charging indicator
(d) Fuel gage
(e) Oil-pressure gage or indicator
(f) Engine temperature gage or indicator
(g) Speedometer with recording odometer
(h) Dual sunvisors
(1) Front door mounted armrest on driver's side
(j) Hooded dash light, located to illuminate accessory controls
(k) A positive locking hand throttle, when manual transmission and winch are furnished
(l) Tachometer (for diesel engine driven vehicles).

3.4.18 Outside rearview mirrors. An outside rearview mirror shall be provided on each side of the vehicle. The mirrors shall be of the Junior West Coast or low-mount type incorporating a wide angle viewing system. The Junior West Coast type shall have an upper mirror of not less than 35 square inches of flat reflective area and a lower mirror of not less than 35 square inches of convex reflective area. The low-mount type shall have an upper mirror of not less than 32 square inches of flat reflective area and a lower mirror of not less than 20 square inches of convex reflective area. The mirror assemblies shall be adjustable and mounted to minimize obstruction of forward lines of vision.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.4.19 Horn. The manufacturer's standard electric horn shall be furnished.

3.5 Cab and body. The vehicle shall be a body-on-chassis with cab design, modified to form an integral cab and body. The vehicle shall be provided with walk-through access between the cab (driver's compartment) and the body. All exterior roof and body seams and joints shall be weatherproof. Materials, fabrication and attachments shall be adequate to withstand working stresses, including dynamic loads encountered in heavy duty off-road operations, without permanent set, loosening of any fastenings, distortion or displacement of any component or loss of weatherproof construction. Dissimilar metals shall be fully isolated from each other to prevent galvanic action.

3.5.1 Cab modification. The original chassis manufacturer's cab roof shall be removed and replaced by a roof of not less than 20 gage (0.0359 inch) sheet steel or 0.040 inch thick aluminum, or molded fiberglass with metal structural support members. The roof shall start at the cab windshield and shall be continuous curving rearward and upward to the exterior height and width of the ambulance body. The sides and floor of the cab shall be similarly blended into the sides and floor of the ambulance body. The modified cab shall be permanently attached to the ambulance body and completely sealed at all points of attachment.

3.5.1.1 Cab interior. Modified cab interior areas shall be paneled with material identical to that used for the ambulance body interior (see 3.5.3.8) or with a one- or two-piece molded fiberglass liner. All areas exposed by cab modification shall be paneled. Fiberglass liner(s) shall be similar in color to the chassis manufacturer's original cab interior color.

3.5.1.2 Cab stowage cabinets. Stowage cabinets shall be incorporated into the paneling above the cab doors, if space permits. A top hinged cabinet door with continuous hinges and a latch at the bottom shall be provided for each cabinet. The cabinet doors shall open to the maximum extent possible, but not less than 90 degrees in any case. The bottom edge of the cabinet openings shall have a l-inch turned up lip to prevent loose items from sliding out of the cabinets. Where the roof structure prevents installation of cabinets above the doors, alternate stowage space in the doors, or to the rear of the doors, shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.5.2 Driver's compartment. The driver's compartment (cab) shall be furnished with a door on each side, and with separate seats for the driver and for the assistant driver. Openings in the floor around levers and pedals shall be sealed. The driver's compartment floor shall be completely covered with a floor mat. Interior lighting shall be provided.

3.5.2.1 Driver's compartment doors. The driver's compartment doors shall be the chassis manufacturer's current standard hinged, automotive, truck cab type. The doors shall be furnished with locks, operable from inside the vehicle through mechanical linkage, and with at least the curbside door equipped with an external, key-operated lock. The doors shall be provided with safety glass in the upper section. A crank type regulating mechanism shall be provided for each door window. In addition to the door operating handles, the doors shall be furnished with grab handles on the inside. Drip rails shall be provided above the doors.

3.5.2.2 Driver's compartment seats. The driver's compartment seats and seat backs shall be constructed on framing with cushioned springs or foam rubber padding to provide maximum riding comfort. The seat and seat back cushions shall be upholstered with washable, artificial leather or plastic, nonabsorbent material. The color of the upholstery and the interior finish shall be compatible with the exterior color (see 3.1.1.1). White upholstery shall not be furnished. The driver's seat shall be adjustable forward and backward. Unless easy access from the driver's compartment to the patients' compartment is possible without special provisions, the assistant driver's seat shall be hinged at the front edge to permit the entire seat to be tilted forward or shall be hinged at the rear to permit the back cushion to be folded forward over the seat cushion. Hinged or folding assistant driver's seats shall be capable of being locked in place for safe use during over-the-road travel. Lap type seat belts shall be installed for the driver's and assistant's seats.

3.5.3 Ambulance body. Except as specified herein, the basic body construction shall be of steel, aluminum or combinations thereof, properly protected to prevent galvanic action. Vertical structural body side posts shall be provided on not more than 21-inch centers and shall be secured to bottom and top rails. Floor crossmembers shall be provided on not more than 16-inch centers. Roof bows shall be provided on not more than 21-inch centers. Openings at doorways shall be framed and reinforced with structural members to provide a rigid structure. The body framing, underbody, and roof shall be welded and reinforced at all joints to fulfill dynamic and static loading requirements as encountered by heavy duty off-road usage. The body shall be completely insulated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.5.3.1 Body exterior. Exterior sheet metal for the ambulance body roof and side panels shall be not less than 20 gage (0.0359 inch) cold-rolled sheet steel or 0.040 inch thick aluminum. The patients' compartment portion of the roof assembly shall be a one-piece panel, welded or riveted to formed metal roof caps at the periphery of the roof. The roof caps, including the sides, rear and rear corners, shall be rounded. The roof shall be crowned or shall have a slight pitch to provide drainage. Drip rails shall be provided over the rear doors. Body side paneling shall be of one piece, down to the rub rail. Body skirting shall be furnished below the rub rail. Circular wheel cutouts at the rear wheels with integral fenders under the body, extending to the bottom of the skirting, shall be furnished. The edges of the skirting, cutouts and fenders shall be beaded, crimped or hemmed. Replaceable rub rails of not less than 16 gage (0.0598 inch) steel shall be installed. When a second rub rail is provided, it shall be located at the bottom of the skirting.

3.5.3.2 Rear doors. Two side hung rear doors with windows shall be furnished. Each door shall be constructed of aluminum alloy structural framing, covered inside and out with a one-piece, not less than 0.125 inch thick, aluminum sheet. The doors shall provide a clear opening not less than 55 inches in height. The width of the door opening shall be great enough to allow the loading of Army litters onto seat mounted lower rack skid strips and upper litter rack mounted skid strips with a straight forward motion, with adequate hand clearance. During such loading, clearance between litter handles and the door, the door frame, and the body side and end panels shall be adequate for an attendant's Arctic gloved hand. Both rear doors shall be hinged at the outer edge with a minimum of three heavy duty hinges; shall open not less than 260 degrees from closed position; and shall be provided with suitable check arms or heavy duty hooks to prevent inadvertent closing from the fully opened position. Both rear doors shall be equipped with cam type vertical upper and lower drawbolts, operable from inside the body. In addition, the curbside rear door drawbolts shall be operable from the outside of the vehicle (by personnel standing on the ground) by a handle with a key operated lock. A single inside handle for release of both streetside door drawbolts shall be located so that an individual standing on the ground can reach it through the open curbside door. Latch plates at both the top and bottom of the door opening shall be mounted flush with and caulked into the door frame. Drawbolt mechanisms shall be enclosed in the doors. A grab handle adequate for closing the door by personnel wearing Arctic gloves shall be furnished on the inside of each rear door. A11 handles shall be mounted so that they do not interfere with the rearmost seated patient. The upper section of each rear door shall include a laminated safety glass window not less than 200 square inches in size.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.5.3.3 Floor construction. The floor of the patients compartment shall be of either: (a) sheet metal reinforced with 1/2-inch thick exterior grade plywood; (b) marine grade plywood not less than 5/8 inch thick; or (c) matched tongue and groove 3/4-inch thick hardwood or dense southern yellow pine. (See 3.1.1.6). The floor shall be supported by crossmembers and shall be capable of withstanding a distributed load of 150 pounds per square foot without failure or permanent set. The junctions of the floor and the body sides and ends shall be sealed. Interior floor covering is required (see 3.5.3.9).

3.5.3.4 Floor pan. An aluminum floor pan not less than 0.040 inch in thickness shall be provided. The floor pan shall be over or under the floor crossmembers, at the manufacturer's option. The floor pan shall be watertight and sealed at all seams and edges. If the floor pan is installed over the crossmembers, separators with a low thermal conductivity shall be furnished above the floor pan and shall be secured to the floor crossmembers. The separators shall provide an insulation cavity not less than one inch in depth which shall be insulated. If the floor pan is installed under the crossmembers, the cavity between the floor pan and the floor shall be insulated.

3.5.3.5 Rear step bumper. A full width rear step bumper with a step depth of not less than 10 inches, and with a nonskid surface shall be furnished. The rear bumper step height shall be approximately midway between the ground and the ambulance floor. The full step of the bumper shall be located to the rear of the rear door.

3.5.3.6 Ambulance body interior. The inside dimensions of the patients' area shall be not less than 113 inches in length, 76 inches in width, and 60 inches in height. The interior of the patients' compartment shall have rounded transitions from vertical to horizontal surfaces and in corners. The complete interior shall be free of sharp corners, sharp edges and other protrusions that could result in injury to personnel.

3.5.3.7 Interior partition and door. A partition (front wall) shall be provided, with an opening for access to and from the attendant's seat in the driver's compartment. The opening shall be centrally located on the longitudinal centerline and shall be not less than 58 inches in height and not less than 20 inches in width. Unless otherwise specified (see 6.2), the opening shall be provided with a sliding access door. The sliding door shall remain fixed in both the open and the closed positions during vehicle travel. In the open position, the door shall fully expose the door frame opening and shall be behind the attendant's seat within the cab. The sliding door shall have a laminated safety glass window in the upper half of the door, with a clear glass area

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

of not less than 100 square inches. One-piece sliding door tracks shall be provided at the top and bottom, and shall provide positive alinement of the door. The bottom door track shall be readily cleanable. End stop with padded faces shall be furnished. Door hangers with double rollers and a mechanical means to adjust door alinement shall be provided. A sliding door lock of the slam type, lockable from both sides of the door, shall be provided. A handle on the driver's compartment side of the door shall be provided. A folding, recessed hand grip shall be provided on the patient compartment side. A striker plate shall be furnished, flush with the door frame.

3.5.3.8 Interior walls and ceilings. All interior surfaces of the ambulance body walls, partition, ceilings and doors shall be paneled with embossed aluminum sheet alloy 3003-H134 diamond M201, or 3003-H254 diamond E-13, and shall be not less than 0.040 inch in thickness (NOTE: this is an embossed, acoustical type of material). The interior panels shall be secured to body structural members. Low thermal conductivity spacers shall be installed between the wall and the ceiling structural members and the interior panels. Each side paneling section shall be of one piece lengthwise for the full length of the body or shall be of one piece the full height vertically from floor to ceiling, at the manufacturer's option. If full length panel sections are used, an upper wall panel shall be secured prior to the installation of a lower panel with the lower panels overlapping the panel above not less than 1 inch. The ends of the wall panels shall have a one-inch lap at the partition and at the rear wall panel and, if full height panels are used, at all vertical seams. Panels shall extend behind the stowage compartments, to the floor. The panels shall be installed free of wrinkles. Panel joints shall not be exposed. Aluminum mouldings shall be provided and secured so as not to display any crevices. Tapping plates shall be provided as required for litter and oxygen tank support and shall be marked as to location and structural integrity. The interior walls, ceiling, rear doors, and stowage cabinets (other than the cabinet doors and drain holes) shall be watertight.

3.5.3.9 Interior floor covering. Interior floor covering shall consist of linoleum, vinyl, rubber or synthetic rubber blend material, not less than 1/8 inch thick. The floor covering shall be installed so that no moisture can seep underneath. The covering shall be applied to all floor areas not covered by the driver's compartment floor mat and also shall extend under the driver's compartment floor mat not less than 2 inches. Linoleum provided shall have a burlap backing. The color of the floor covering shall coordinate with the interior of the patients' compartment and the interior of the driver's compartment. The floor covering shall be bordered on all edges with aluminum or stainless steel moldings, properly sealed. Abrasive type anti-skid strips, not less than 2 inches wide, shall be installed diagonally on not more than 6-inch centers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.5.3.10 Insulation. The body roof, sides, floor, rear end, and rear doors shall be insulated. Insulation shall provide resistance to the transfer of heat equivalent to the protection afforded by a 1-inch thick batt having a thermal conductivity of 0.24 British thermal units per square feet per degrees Fahrenheit per hour per 1-inch thickness in normal ambient air temperatures. Insulation shall be either flexible or batt type, fibrous or cellular material having a moisture absorption capacity of less than 2 percent by weight and shall be asbestos-free. Materials shall be odorless and fire retardant. The insulation shall not breed nor promote the growth of fungus and shall not cause nor accelerate corrosion of steel, copper or aluminum. The insulation shall be cemented to the inner side of the external skin and shall be provided with means to retain the insulation under all operating conditions. Cement shall be waterproof and the resulting bond shall provide shear strength sufficient to prevent sag of the insulation when the assembled vehicle is operated at speeds up to 55 mph over improved roads and at appropriate speeds cross country. All insulation shall be installed prior to the closing of spaces in the body side, roof, floor, front, end, and door panels.

3.5.3.11 Interior arrangement. The patients' compartment shall be furnished with a seat on both sides of the body, each approximately 103 inches in length. Stowage compartments shall be provided under the seats. A space of 8 to 10 inches shall be provided between the seats and the front partition for the placement of an oxygen tank and for other stowage. Litter supports shall be provided for both: (a) four Navy Stokes litters, 84-3/4 inches in length, 23-1/2 inches in width, and 7-1/2 inches in height; and (b) four Army standard litters (STANAG, 2040), 90 inches in length, 23 inches in width, and 6-3/4 inches in height; all in any combination of up to four litters at one time, at the operator's option.

3.5.3.12 Stowage compartments. The underseat stowage compartments shall have an inside width of 20 inches and an interior height of 15 inches, both plus or minus 1/2 inch. The stowage compartments shall be constructed of all aluminum and shall serve as a base for seating, for litters, and for upper litter support racks, each at the operator's option. The stowage compartments shall be provided with complete aluminum structural framing and aluminum seat bases (tops) capable of supporting five, 240-pound, seated ambulatory patients on both sides of the aisle.

3.5.3.13 Stowage compartment construction. Two sliding doors or three pull-out drawers shall be furnished for each compartment, providing access from the aisle. The sliding doors and the drawers shall remain shut during travel, start-up, braking and turning. For sliding doors,

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

upper and lower sliding door tracks shall be provided, shall be of double channel aluminum and shall provide positive alinement of the sliding doors. The sliding door tracks shall be mounted on stowage compartment structural framing. The sliding doors shall be of aluminum not less than 0.090 inch thick with recessed finger cups. When pull-out drawers are furnished in lieu of sliding doors, two drawers shall be full height and depth pull-out type on either side of a full height, bottom hinged, bin type drawer. The drawers shall be of heavy duty aluminum construction. Drawer slides and bin hinges shall be mounted on stowage compartment structural framing. The front and rear end of compartments shall be enclosed with aluminum sheet attached to compartment structural framing. A l/4-inch drain hole from the bottom, rear, wall side corner of each stowage compartment into the patients' area shall be provided.

3.5.3.14 Lower litter racks. Two extruded aluminum alloy guide strips, each the full length of the stowage compartment, shall be mounted on top of both stowage compartments for positioning and guiding the stirrups of an Army standard litter. Each guide strip shall be formed to be one of the longitudinal edges of the stowage compartment top. An aluminum top to the stowage compartment (seat base) shall be provided between and attached to the guide strips. Not less than four aluminum structural member lateral supports shall be provided under the top (seat base). The aluminum top (seat base) between the guide strips shall be recessed to accommodate a removable seat cushion (see 3.5.3.22) when the operator so desires.

3.5.3.15 Guide strips. Each guide strip shall have a horizontal surface not less than 2-3/4 inches wide to support a plastic skid strip and shall have vertical lips approximately 1/2 inch high above the top of the plastic skid strip to provide guides for an Army litter. The extruded aluminum guide strips shall be parallel and separated by 18 inches plus or minus 1/8 inch. The longitudinal centerline of the guide strip nearest the wall shall be not more than 3-3/8 inches inside the edge of the rear door opening. Plastic skid strips conforming to 3.5.3.15 shall be provided in the guide strips.

3.5.3.16 Skid strips. A nominal 2-inch wide by 1/4-inch thick fire-resistant hard plastic skid strip shall be provided centered between the lips of each guide strip. The plastic skid strips shall have a coefficient of friction on steel of not more than 0.25 for ease of sliding a loaded Army litter. The plastic skid strips shall be free of protrusions and seams and shall facilitate the sliding of Army litter supports (stirrups).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.5.3.17 Upper litter racks. Two upper litter racks, each capable of being raised and lowered, each capable of securely supporting, during off-road operations, a 240-pound patient on a litter in the raised position and each capable of supporting five seated personnel when in the lowered position, shall be furnished. Racks shall be constructed to include two extruded aluminum guide strips, conforming to 3.5.3.15, with skid strips conforming to 3.5.3.16. The guide strips shall be formed and installed to be the sides of the racks. The space between the two guide strips shall be recessed to form a rigid, metal well or pocket between them for a removable seat cushion (see 3.5.3.22). The guide strips shall be connected with aluminum structural member end sections and not less than four intermediate aluminum structural member lateral supports. Each upper rack guide strip shall be vertically above that on the corresponding lower rack.

3.5.3.18 Upper litter rack operation. Captive pins to engage upper litter rack supports shall be provided at the forward end of each upper litter rack. Telescopic handles or a full width fixed handle shall be provided at the rear of each upper litter rack to raise and lower the rack with a litter in place. Telescopic handles shall be capable of 12-inch extension. The height from the floor to the top of the upper litter plastic skid strip with the upper litter racks lowered shall be 17-5/8 inches, ± 1/16 inch. The raised upper litter racks shall be 21 inches, plus l/2 inch minus 0 inch, above the lower litter racks, measured from top-to-top of the plastic skid strips. All parts, whether in use or stowed, shall be free of rattles during over-the-road and off-road operations.

3.5.3.19 Upper litter rack front supports. Forward supports for the upper litter racks shall be fabricated of 6061T6 aluminum alloy channels. The supports shall be rigidly attached near the forward end of the stowage compartments with 6061T6 aluminum structural members attached to roof and floor structural members. The forward supports shall accept captive pins to support the forward end of the racks to provide positive retention then the racks are raised and horizontal and also when only the front of the racks are raised and the rear of the racks are lowered onto the lower racks. The loading of Army litters up the incline so formed by the upper racks shall then be possible. Pins shall be integral with the rack supports. There shall be no other moving or loose parts required for retention or pivoting of the upper racks at the forward end. Arrangements shall be made to lower the entire upper litter rack assembly down to a horizontal position on top of the lower litter racks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.5.3.20 Upper litter rack rear supports. Rear supports for holding each upper litter rack in the upper horizontal position shall be a hook pivoted from the wall and a hook suspended from the ceiling. Means for positive retention of these hooks when in use and when in the stowed positions shall be provided. Wall hooks shall be attached to wall structural members. Ceiling hooks shall be attached to roof structural members and shall be recessed when stowed.

3.5.3.21 Resilient bumpers. Resilient bumpers shall be secured to the front of all racks as a forward stop for litters. The bumpers shall be large enough to allow for wide variations in litter handle height and spacing.

3.5.3.22 Seat cushions. Seat cushions shall be provided. The cushions shall be fully supported by, but not secured to, the upper or lower litter racks (at the operator's option) between the guide strips. The cushions shall be 18 inches wide, plus or minus 1/8 inch, by 1-1/2 inches plus 0, minus 1/8 inches thick, and shall extend the full length of the litter racks. All litter racks shall have a recessed pocket so that the top surface of the seat cushions shall be 5/8 inch ± 1/16 inch above the top (sliding) surface of the litter rack plastic skid strips to provide maximum possible comfort yet still clear the spreader bars on Army litters.

3.5.3.23 Seat backs. A seat back shall be provided on both sides and shall run the full length of the seats. The backs shall be not less than 12 inches high by one inch thick with the bottom edge approximately 6 inches above the top of the seat cushion with the seat cushion in place on the lower racks. The seat backs shall be securely and permanently attached to the side walls.

3.5.3.24 Seat and seat back upholstery. The seat cushions and seat backs shall be padded with flexible urethane polyester foam. The foam shall be nonallergenic, flame-resistant, nontoxic, and shall not absorb moisture or body odors. Density shall be a nominal four pounds per cubic foot. The foam padding shall be capable of withstanding 100 percent humidity and of withstanding an ambient temperature of minus 65°F without any evidence of deformation or cell breakdown. Flexible latex polyester foam padding shall not be furnished. The seat cushions and seat backs shall be upholstered with vinyl having a nylon backing of not less than 20 ounces per square yard. The color of the upholstery shall be a near match to the upholstery in the driver's compartment.

3.5.3.25 Litter tiedown and stowage. Web strap holders for 2 inch straps shall be installed. Web strap holders shall be secured with machine screws and locking nuts or "rivnuts." Twenty web strap assemblies, Army P/N 11658584-2 with web strap holders for each shall be furnished and installed as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

(a) Two along the top of the side wall on each side of the patient compartment, arranged to hold folded Army litters in stowed position
(b) Two at the aisle edge and two against the wall, on top of the stowage compartment, on both sides of the body, arranged to hold litters in place on the lower racks
(c) Two along the aisle edge and two against the wall side edge of the guide strips on both upper litter racks, arranged to hold litters in place on the upper racks
(d) The web strap holders shall be placed approximately 76 inches apart, longitudinally.

3.5.3.26 Intravenous hooks. Five small harness hooks which fold or swivel out of the way on impact shall be secured to structural members in the ceiling. The hooks shall be located 8 inches from the longitudinal body centerline, two on the streetside and three on the curbside.

3.5.3.27 Fluorescent light. One 120-volt, 40-watt fluorescent light, with an instant starter, located along the centerline of the patients' compartment, shall be provided. Inverter-ballast devices shall be incorporated into the light fixture to enable the light to be operated from the 12-volt vehicle battery. Light switches shall be provided, one at the rear and one at the front of the patients' compartment. The light shall be provided with guards to prevent breakage and padded bumpers, as required, at the front and rear to prevent injury. The light, fixture, and guards shall project not more than 4 inches below the vehicle roof.

3.5.3.28 Oxygen tank holding devices. Holding devices to secure one "M" size oxygen tank shall be furnished at the front of the patients' compartment. The structural members of the holding devices shall be attached to the roof and floor structural members or to structural tapping plates provided for that purpose. At least two clamping strap or chain devices shall be furnished for holding the oxygen tank in position. The holding devices shall secure the tank in a location where gage and connections are accessible to the attendant, but where the tank does not interfere with the driver's and assistant driver's view of the patients' compartment. A base plate, either round or square, of not less than 3/16 inch thick aluminum with upturned lip(s) shall be furnished for the oxygen tank. The lip(s) shall be of such a height as to hold the oxygen tank securely in place in conjunction with the clamping straps or chain holding devices. The "M" size oxygen tank is approximately 7-1/8 inches in diameter and 46 inches high with valve, with approximately 106-cubic-foot capacity and weighs 75 pounds empty and 83 pounds full. The oxygen tank is not required to be furnished, except for demonstration purposes during inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.5.3.29 Vacuum outlet. Unless otherwise specified (see 3.5.3.32), a single plug-in, vacuum outlet with self-sealing valve connection shall be installed at the front of the patients' compartment toward the left side of the vehicle. The plug-in unit shall prevent the entry of dust without the use of a dust cap or cover and shall allow the attachment and release of secondary equipment with one hand. A mating male outlet fitting shall be furnished for later connection to a medical hose by means of a barbed hose end. When specified (see 6.2), a single Diameter Index Safety System (DISS) vacuum outlet NCG part No. 263764-64 or equal with mating outlet shall be provided in lieu of the plug-in type.

3.5.3.30 Vacuum installation. A suction line shall be connected between a vacuum source and the vacuum outlet. The installed suction shall be powerful enough to provide an air flow of at least 30 liters per minute (1.06 cubic feet per minute) at the end of the delivery tube and shall cause a vacuum of at least 300 millimeters (11.81 inches of mercury) to be reached within 4 seconds after the suction line delivery tube is clamped. The suction line shall use the vacuum of a 12-volt dc pump or, at the manufacturer's option, shall use the vacuum of the engine when a gasoline engine driven vehicle is furnished. When the vacuum system of the gasoline engine driven vehicle is used, it shall be isolated from the brake system to prevent loss of braking power; a cylindrical stainless steel reservoir having a volume of not less than 300 cubic inches shall be provided in the suction line to reduce loss of vacuum during vehicle acceleration; and a check valve, TRlCO part number 85590-42 or equal, shall be installed in the suction line between the reservoir and the vacuum source. All suction lines shall be adequately supported to prevent chafing from movement and vibration. Whenever the line passes through bulkheads, grommets and fastening devices shall be employed to prevent chafing.

3.5.3.31 Vacuum aspirator. When specified (see 6.2), the following minimum vacuum aspirator equipment shall be furnished:

(a) One suction rinsing bottle
(b) One nonmetallic pharyngeal suction tip
(c) Spare suction tip and catheters
(d) One Y-connection
(e) A ten-foot length of transparent, nonshrinking suction tubing with not less than 1/4 inch inside diameter and fittings compatible with the vacuum outlet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.5.3.32 Portable suction aspirator. When specified (see 6.2), a portable, rechargeable, battery powered, suction aspirator with 12-volt dc vehicle receptacle shall be furnished in lieu of the vacuum outlet and installation specified in 3.5.3.29 and 3.5.3.30. The aspirator shall be Laerdal catalog number 790013 or equivalent. The aspirator battery supply shall be capable of recharging from the vehicle's 12-volt electrical system and from 115-volt ac shore power. The portable suction aspirator shall provide an air flow of at least 20 liters per minute and shall cause a vacuum of at least 300 millimeters to be reached within 4 seconds after the tube is clamped. The aspirator, while operating solely from its integral battery supply, shall meet these air flow requirements for at least twenty minutes of continuous operation. The suction tubing shall be translucent and shall not kink or collapse under high suction. The inside diameter of the tubing shall be at least 1/4-inch. The 115-volt ac charging system furnished need not be integral with the portable suction unit. The unit shall be provided with applicable power cords and plugs in accordance with MS3116F1-23P. The polarity of the dc plug shall be as follows: pin A, +12 volts; pin B, ground; pin C, not used. The aspirator and electrical receptacle shall be installed at the front of the patients' compartment, toward the streetside of the vehicle. The electrical receptacle shall be MS3l12E12-3S and shall be wired to the vehicle's 12-volt dc electrical system.

3.5.3.33 Aspirator accessories. Additionally, the portable aspirator shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

(a) One suction rinsing water bottle.
(b) One nonmetallic pharyngeal suction tip.
(c) Spare suction tip and catheters
(d) One Y-connector.

3.5.4 Ventilating and air conditioning system.

3.5.4.1 Ventilators for patients' compartment. One filtered power blower intake ventilator and one power blower exhaust ventilator shall be furnished in the roof of the patients' compartment. The ventilators shall have a streamlined design and shall be rainproof. Each blower motor shall be capable of moving not less than 220 cubic feet of air per minute, shall have one or more speeds and shall be controlled by separate switches mounted in a location easily accessible to the seated driver and assistant driver. The vent openings shall be provided with captive weatherproof covers with means for opening and closing from the inside. Power ventilator openings inside the vehicle shall be furnished with safety grilles and screens.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.5.4.2 Air conditioning. Automotive air conditioner(s) with required allied components shall be furnished to air condition both the driver and the patient compartments. The air conditioner(s) shall have a total rated cooling capacity of not less than 30,000 British thermal units (Btu) per hour at 95°F dry bulb ambient outside temperature and 67°F wet bulb inside vehicle temperature. The air conditioner(s) shall be an integral part of the vehicle and shall be mounted completely within the vehicle. The air conditioning unit(s) shall not be mounted on the body roof. Air conditioner control switch positions shall be identified.

3.5.4.3 Tinted windows. All exterior windows, including the windshield, shall be of tinted, heat absorbing safety glass. Tinting of lamination material is not acceptable.

3.5.5 Heating system.

3.5.5.1 Driver's compartment. A driver's compartment heater shall be provided and shall be of the engine coolant, heavy duty, blower type. The heater shall include a heavy duty windshield defroster to maintain a clear windshield under high humidity conditions and in temperatures down to minus l0°F. The heater shall have separate, readily accessible means for controlling airflow to the heater or to defroster ducts. The blower controls shall be mounted in a location within easy reach of the driver. The heater shall be equipped with an engine coolant shutoff valve, for shutting off the flow of coolant to the heater.

3.5.5.2 Patients' compartment. A patients' compartment heater shall be provided and shall be of the engine coolant, heavy duty blower type. The heater shall be located in an underseat stowage compartment or may be an integral part of the air conditioner. If the heater is located in a compartment, the compartment shall be provided with louvered return air inlet(s) and hot air outlet(s). The heater shall be equipped with an engine coolant shutoff valve with dash-mounted control readily accessible to the driver for shutting off the flow of coolant to the heater. The blower control switch shall be mounted in a location easily accessible to the seated driver and the attendant. Heater and coolant control positions shall be identified.

3.5.5.3 Auxiliary heater booster. When specified (see 6.2), a fuel fired auxiliary heater booster shall be furnished. The auxiliary heater shall provide additional heated coolant to the patient's compartment heater specified in 3.5.5.2. The auxiliary heater booster combustion chamber shall be mounted outside the patient and driver compartments. The heater fuel supply shall be from the vehicle engine fuel supply. The heater and the installation shall be in

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

accordance with Federal Motor Carrier Safety Regulation 393.77. The heater shall have a rated capacity of not less than 25,000 Btu per hour. The heater shall be connected to the engine coolant system and shall be provided with not less than a 6-gallon per minute (gpm) capacity circulating pump. The heater shall be capable of maintaining the temperature inside the vehicle at a minimum of 70°F midway between the floor and the ceiling in an ambient air temperature of 0°F, with no passengers. Controls for operating the heater shall be located in the driver's area and shall be identified as to purpose and position (on-off).

3.5.6 Warning light. Unless two warning lights are specified (see 3.5.7), a single rotating warning light, conforming to MS51317, shall be installed with reinforcement at the point of attachment, on the vehicle centerline where 360-degree visibility is provided. The warning light shall be operated by means of a separate switch with a red indicator light located on the instrument panel and marked to indicate the function of the switch. Unless otherwise specified (see 6.2), the color of the warning light shall be red. At the option of the manufacturer or when specified (see 6.2), the light shall be removed for shipment of the vehicle. When removed, the light shall be stowed within the vehicle and the roof opening shall be provided with a weatherproof cover. Provisions for reinstalling the light, including access to the light wiring and mounting devices from inside the vehicle, shall be provided.

3.5.7 Warning lights. When specified (see 6.2), two rotating warning lights shall be installed, with reinforcements at the point of attachment. The lights shall be mounted on the forward portion of the vehicle roof, one on the streetside and one on the curbside, in a position affording 360-degree visibility. The revolving light base shall be 4 to 5 inches high. Each light shall have a clear dome, and shall have four high intensity, sealed beam lamps, each having a minimum of 35,000 candle power. Unless otherwise specified (see 6.2), two of the lamps shall be white and two shall be red, installed in alternating colors. The lights shall flash across a viewer's line of vision at a minimum flash rate of 80 flashes per minute. The two warning lights shall be operated by means of one separate heavy duty switch. The switch shall be located on the instrument panel, so positioned as to be readily accessible to the driver, and shall be marked to indicate the function of the switch. A red indicator light shall be provided. At the option of the manufacturer or when specified (see 6.2), the lights shall be removed for shipment of the vehicle. When removed, the lights shall be stowed in the vehicle and the roof openings shall be provided with weatherproof covers. Provisions for reinstalling the lights, including access to the light wiring and mounting devices from inside the vehicle, shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.5.8 Siren. When specified (see 6.2), a low frequency type siren shall be installed outside the vehicle or between the grille and the radiator. The siren shall have a chrome or enamel finish. A gasket not less than 1/16-inch thick shall be installed between the siren mounting bracket and the vehicle to minimize drumming. Reinforcement shall be provided, when needed, at the point of attachment. The siren location shall permit servicing of the vehicle without removing the siren.

3.5.8.1 Dual siren controls. The siren shall be capable of being actuated by both a foot operated switch and the standard horn actuator. A separate dash mounted switch, for driver preselection of horn or siren operation, shall be provided. Switch positions shall be identified.

3.5.9 Electronic siren, public address and radio amplifier system. When specified (see 6.2), an electronic siren system with selector controls for siren, public address and radio amplification through an external speaker shall be provided. The system shall be a Federal PA-20A, Dietz 14-450, or Unity SPR73 Model or equivalent. The system shall have a sound intensity of not less than 98 decibels at a distance of 100 feet from the speaker, using a reference pressure of 0.0002 microbar. The amplifier and its controls shall be installed inside the vehicle in a location accessible to the driver and to the assistant driver. A microphone of the magnetic noise canceling type, connected by a coiled core, shall be provided and located in a position convenient for use by both the driver and the assistant driver. Microphone stowage shall be provided on the instrument panel. The system shall permit the broadcasting of routine and emergency radio announcements from an on board vehicle radio to be installed by the Government. A two-way radio audio tap cable, permitting incoming two-way radio messages to be rebroadcast through the public address system, shall be furnished. Dual siren controls (see 3.5.8.1) shall be provided. The amplifier unit shall include volume control and selection of "Radio," "P.A.," and "Siren mode." Siren mode controls shall include "Manual," "Yelp," "Wail," and "Hi-Lo" (European).

3.5.9.1 Speaker. An external weatherproof speaker shall be installed on the centerline of the cab roof or above the front bumper to the rear of the brushguard. Cab roof installation shall be in a location that will not obstruct light from or movement of the roof mounted spotlight. The speaker, when roof mounted, shall be of the low silhouette type, designed for roof mounting. The speaker shall be of metal with a chrome finish or of fiberglass painted to match the vehicle exterior color. A gasket not less than 1/16 inch thick shall be furnished between the speaker mounting bracket and the vehicle to minimize drumming. Reinforcements shall be provided on the vehicle at the point of attachment of the speaker. The speaker location shall permit servicing of the vehicle without removing the speaker.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

3.5.9.2 Plug-in feature. When specified (see 6.2), an electronic siren, public address and radio amplifier system in accordance with 3.5.9 and 3.5.9.1 shall be furnished, except:

(a) A microphone shall not be furnished
(b) The system shall include plug-in features for all connections, including a Government furnished microphone and radio of the type, make and model specified (see 6.2)
(c) The system shall enable a single microphone (to be furnished by the Government) to be used for both public address purposes through the external speaker and return messages through a Government furnished 2-way radio.

3.5.10 Spotlight. Two post mounted spotlights or a single spotlight mounted on the vehicle centerline in the windshield divider strip or directly over the windshield header section, with inside controls easily accessible to the driver and the assistant driver, shall be furnished.

3.5.11 Floodlight. A sealed beam floodlight shall be furnished at the rear of the vehicle. The light shall be wired to the chassis electrical system with a dash mounted switch for driver operation. The switch shall be labeled as to function. The floodlight shall be not less than 30 watts and shall provide not less than 50,000 candle power. The floodlight shall be swivel mounted to provide vertical and horizontal adjustment. The mounting shall include a locking device to secure the floodlight in any selected position. The mounting shall permit directing the light beam to all points two feet or more to the rear of the vehicle. The floodlight shall be mounted on the vehicle centerline.

3.6 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, the contractor shall service and adjust each vehicle and its mounted equipment for operational use including at least the following: alinement of lights; adjustment of the engine, electrical and brake systems; filling and charging of the battery; alinement of the front wheels; inflation of all tires; complete lubrication of chassis, engine, running gear, all vehicle parts, and on-vehicle equipment with grades of lubricants recommended for the ambient air temperature at the delivery point; servicing and adjusting of the heating and air conditioning systems; servicing of the cooling system with a solution of ethylene glycol type antifreeze and water in equal parts by volume; and servicing of the windshield washer reservoir with water and appropriate additives.

3.7 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Cabinetry, interior lining, paneling, upholstery, furnishings, welded, bolted, and riveted construction utilized shall be installed in accordance with the highest standards of the industry. Sharp edges, slit edges, ends, and corners

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

of metal and formica shall be blended for appearance and burred, filed, or rounded to prevent injury to personnel. The general appearance of the vehicle shall show no evidence of poor workmanship.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility for assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance to the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

4.3.1 Vehicle weight. The first production vehicle shall be weighed to determine the curb weight and distribution of the curb weight on front and rear axles. The total imposed loading on front and rear axles shall be computed by the contractor and verified by the Government using the curb weight, the operator and assistant driver weight at 175 pounds each and the minimum payload required to provide the specified GVW (see 3.2.5). The calculated imposed loads on the front and rear axles shall be compared to the suspension, axle, and tire load capacity ratings to determine if these components are of adequate capacity to meet contractual requirements.

4.3.2 Road test. The first production vehicle will be examined and road tested by the contractor, with driver, assistant driver and payload (see 3.2.5). The payload shall be not less than 1,600 pounds. Payload shall consist of four weights of not less than 240 pounds each, placed in each of the four litter rack travel positions plus an evenly distributed load to provide the remainder of the 1,600 pound payload. The road test shall be for a distance of not less than 100 miles. Approximately 60 percent of this mileage shall be on paved streets or highways at speeds of up to at least 55 mph; 30 percent on gravel or dirt roads at speeds of up to at least 35 mph; and not less than 10 percent in simulated or actual cross-country operation at speeds applicable to the terrain. Cross-country operation is defined as travel over open fields, rolling and side sloping hills, and rough and muddy terrain.

4.3.3 Ventilation, air conditioning and heating system. The ventilating, air conditioning and heating system shall be operated to determine that the controls and system are functioning. The contractor shall certify that the supplied systems meet the requirements in 3.5.4.1, 3.5.4.2, 3.5.5.2 and, when applicable, 3.5.5.3. Certification shall be based on test data or calculations showing that the system offered will meet the specified requirements.

4.3.4 Army litter loading. The contractor shall make available four standard Army litter and one Navy Stockes type litter (see 3.5.3.10) and four individual 240-pound weights suitable for placing on the litters. All possible combinations of loading and unloading, raising and lowering of the litter racks, both with and without fully loaded Army and Navy litters, shall be demonstrated successfully.

4.3.5 Water spray test. After the road test, the vehicle body shall be subjected to a water spray test for approximately 15 minutes. The spray shall be delivered by nozzles operating at not less than 25 pounds per square inch (psi) water pressure, sufficient in number and so placed (approximately 3 feet from the body) to afford full coverage of sides, roof, front, rear and undercarriage of vehicle. Evidence of water leakage shall be cause for rejection until leaks are corrected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

4.3.6 Truck body treatment and painting. The certification regarding the body cleaning, treating, prime painting and salt spray resistance testing, as required by MIL-STD-1223, shall be made to Government representatives at the first production vehicle inspection.

4.3.7 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

4.3.8 Wiring capacity. The contractor shall certify or prove by test that the vehicle wiring capacity is adequate for operation of all furnished electrical equipment at the same time.

4.3.9 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

4.4 Inspection of production vehicles. Each production vehicle shall be examined and driven (less payload) for not less than 5 miles at speeds up to 50 mph to assure that the vehicle will operate in accordance with the contractual requirements. Each production vehicle shall be subjected to the water spray test specified in 4.3.4 after the road test. The contractor may authorize the subcontractor who will perform the final assembly work on the vehicle to make such examination and tests, but this shall not relieve the contractor of his obligation to deliver an acceptable vehicle or constitute a waiver of any warranty provision. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.6 have been accomplished.

5. PACKAGING

5.1 Vehicle processing. The vehicle shall be processed for shipment, from the manufacturer's plant to the initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The vehicles covered by this specification are intended for nontactical use by the Government in transporting reclining or sitting patients over highways, unimproved roads, and cross-country terrain. Principal use of the vehicles will be in stop and go, short haul, medium and low speed operations and occasional high speed highway operations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Identification of appropriate service for painting and marking (see 3.1.1.1).
(c) Concealed markings, if required (see 3.1.1.1).
(d) Ambulance markings, if other than as specified (see 3.1.1.1).
(e) Rustproofing, if required (see 3.1.1.4).
(f) Tropical rustproofing, if required (see 3.1.1.4).
(g) Trailer towing package, if required (see 3.1.1.9).
(h) Front winch, if required (see 3.1.1.10).
(i) Silicone brake fluid, if required (see 3.1.1.11).
(j) Gasoline engine, if required (see 3.4.1.2).
(k) Power plant heaters, if required (see 3.4.1.7).
(1) If a battery heater is not required with the power plant heaters (see 3.4.1.7).
(m) A fuel fired engine preheater, if required for a diesel engine driven vehicle (see 3.4.1.8).
(n) Left-dip headlights, if required (see 3.4.2.4).
(o) Alternator capacity, if other than as specified (see 3.4.2.1 and 3.4.2.2).
(p) Automatic transmission, if required (see 3.4.5.3).
(q) Heavy duty springs, if required (see 3.4.8.2).
(r) Traction control, if required (see 3.4.9.1).
(s) Disc type wheels, if required (see 3.4.10).
(t) If other than tube type tires with nondirectional mud and snow tread are required (see 3.4.10.1).
(u) If a carrier is not required (see 3.4.10.3).
(v) If a spare wheel or rim is not required (see 3.4.10.4).
(w) If a spare tire assembly is not required (see 3.4.10.5).
(x) If tools are not required (see 3.4.15).
(y) If a sliding door for driver's compartment access opening is not required (see 3.5.3.6).
(z) Diameter Index Safety System (DISS) vacuum outlet, if required (see 3.5.3.29).
(aa) Vacuum aspirator equipment for use with vacuum outlet, if required (see 3.5.3.31).
(ab) Portable suction aspirator with electrical receptacle, if required (see 3.5.3.31).
(ac) Auxiliary fuel fired patients' compartment heater, if required (see 3.5.5.3).
(ad) Color of warning light(s) required, if not red (see 3.5.6 and 3.5.7).
(ae) Two rotating warning lights, if required (see 3.5.7).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.

(af) Removal of warning light(s) for shipment, if required (see 3.5.6 and 3.5.7).
(ag) Low frequency siren, if required (see 3.5.8).
(ah) Electronic siren, public address, and radio amplifier system, if required (see 3.5.9).
(ai) Plug-in siren, public address, and radio amplifier system, if required (see 3.5.9.2).
(aj) Type of microphone, make and model of Government furnished radio equipment, if plug-in siren system is required (see 3.5.9.2(b)).

6.3 Subject term (key word) listing.
Ambulance marking
Army litter
Aspirator
Litter racks
STANAG 2040
Stokes litter
Truck, ambulance.

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - AT
Navy - YD
Air Force - 99

Review activities:
Army - EL, MD
Navy - MC
Air Force - 84

Preparing activity:
Army - AT

Project No. 2310-0440

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:07Z
Check the source to verify that this is the current version before use.