MIL-R-55016B(EL)
23 July 1963

MILITARY
SPECIFICATION

Superseding
MIL-R-55016A(SigC)
24 January 1961

RADIO SET AN/TRC-68( ) (UNITS OF)

1. SCOPE

1.1 This specification covers the following units of a fixed station, amplitude-modulated (a-m) radio receiving-transmitting set operating on any of 1,750 crystal-controlled channels in the frequency range of 225.0 to 399.9 megacycles (mc). (See 6.1 and 6.7.)

Receiver-Transmitter, Radio RT-441( )/TRC-68
Power Supply PP-1494( )/U
Case, Receiver-Transmitter CY-2712( )/TRC-68
Fan, Centrifugal HD-390( )/U
Mounting MT-2297( )/TRC-68
Case, Accessories CY-2713( )/TRC-68

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-S-571 Solder: Lead Alloy, Tin Lead Alloy, and Tin Alloy; Flux Cored Ribbon and Wire, and Solid Form.

FSC 5820

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS (Contd)

MILITARY

MIL-E-1	Electron Tubes and Crystal Rectifiers
MIL-P-116	Preservation, Methods of.
MIL-B-117	Bags, Interior Packaging.
MIL-V-173	Varnish, Moisture and Fungus Resistant, for the Treatment of Communications, Electronic, and Associated Electrical Equipment.
MIL-T-713	Twine and Tape, Lacing and Tying (For Use in Electrical and Electronic Equipment.
MIL-S-901	Shockproof Equipment, Class HI (High-Impact), Shipboard Installation, Tests for.
MIL-I-3158	Insulation Tape, Electrical, Glass-Fiber (Resin-Filled); and Cord, Fibrous-Glass.
MIL-C-4150	Cases, Carrying and Storage, Shock and Water Proof.
MIL-W-6858	Welding, Resistance, Aluminum, Magnesium, Nonhardening Steels or Alloys, Nickel Alloys, Heat-Resisting Alloys, and Titanium Alloys, Spot and Seam.
MIL-I-7798	Insulation Tape, Electrical, Pressure-Sensitive Adhesive, Plastic.
MIL-M-10578	Metal Conditioner and Rust Remover (Phosphoric-Acid Base).
MIL-M-13231	Marking of Electronic Items.
MIL-M-13787	Motors, Alternating Current, Fractional Horsepower, Squirrel Cage (for Communication and other Electronic and Special Military Applications).
MIL-F-14072	Finishes for Ground Signal Equipment.
MIL-F-14256	Flux, Soldering, Liquid (Rosin Base).
MIL-B-7883	Brazing of Steels, Copper, Copper Alloys, and Nickel Alloys.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS(Contd)

MILITARY

MIL-S-19500	Semiconductor Devices, General Specification for.
MIL-N-25027	Nut, Self-Locking, 250°F, 500°F, and 800°F.

STANDARDS

MILITARY

MIL-STD-22	Welded-Joint Designs.
MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-169	Extreme-Temperature Cycle.
MIL-STD-170	Moisture Resistance Test Cycle for Ground Signal Equipment.
MIL-STD-200	Electron Tubes.
MIL-STD-252	Wired Equipment, Classification of Visual and Mechanical Defects
MIL-STD-681	Identification Coding and Application of Hookup Wire.
MIL-STD-701	Preferred and Guidance List of Transistors.
MS33540	Safety Wiring, General Practices for.

DRAWINGS

SIGNAL CORPS

SC-A-4643°	List of Accessories for Package Tester.
SC-A-46570	Materials and Processes for Printed Wiring Assembly.
SC-GL-57710	Gage Point List for Power Supply PP-1494( )/U.
SC-GL-57711	Gage Point List for Case, Receiver-Transmitter CY-2712( )/TRC-68.
SC-GL-57713	Gage Point List for Radio Set AN/TRC-68( ).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

DRAWINGS (Contd)

SIGNAL CORPS

SC-GL-57714	Gage Point List for Receiver-Transmitter, Radio RT-441( )/TRC-68.
SC-B-61578	Grounding to chassis.
SC-DL-345025	Drawing and Data List for Radio Receiver-Transmitter RT-441( )/TRC-68.
SC-DL-345029	Drawing and Data List for Centrifugal Fan HD-300( )/U.
SC-DL-345106	Drawing and Data List for Mounting MT-2297( )/TRC-68.
SC-DL-345112	Drawing and Data List for Receiver-Transmitter Case CY-2712( )/TRC-68.
SC-DL-345194	Drawing and Data List for Power Supply PP-1494( )/U.
SC-DL-345283	Drawing and Data List for Accessories Case CY-2713( )/TRC-68.
SC-A-362100	Preparation of Preproduction Packs.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer. Both the title and number or symbol should be stipulated when requesting copies.)

2.2 Other publication. - The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL BUREAU OF STANDARDS

Handbook H28 Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D.C.)

3. REQUIREMENTS

3.1 Description. - Using Radio Set AN/TRC-68( ), two-way type A3 (voice) communication can be conducted on any of 19 preset channels, after a 5-second channel selection interval, from a local Microphone M-29( )/U or from the handset of remotely

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

3.1 Description.- (Contd)

located Control Group AN/GRA-6( ). The preset channels may be selected, the set turned on and off, and volume and squelch levels adjusted from another operating position by using Radio Set Control C-1439( )/U. Channel spacing is 100 kilocycles (kc); presetting a channel requires approximately 10 seconds. Nominal transmitter radio-frequency (rf) power output is 16 watts (w).

3.2 Preproduction samples.- The contractor shall furnish two preproduction samples of each unit for approval, if required by the invitation for bids and contract. (See 4.3.)

3.3 Construction.- The units listed shall be constructed in accordance with the applicable drawing and data lists.

Unit	Drawing and Data List
RT-441( )/TRC-68	SC-DL-345025
HD-390( )/U	SC-DL-345029
MT-2297( )/TRC-68	SC-DL-345106
CY-2712( )/TRC-68	SC-DL-345112
PP-1494( )/U	SC-DL-345194
CY-2713( )/TRC-68	SC-DL-345283

3.4 Parts, materials, and processes.-

3.4.1 Deleted.

3.4.2 Finish, protective (see 4.4).- The equipment shall be finished in accordance with Specification MIL-F-14072 and the equipment drawings. The final paint film on Type I surfaces shall be green color (olive drab), semigloss enamel matching a color chip provided by the procuring agency. (See 6.3.)

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:13Z
Check the source to verify that this is the currentversion before use.

3.4.3 Plastic materials and parts. - Where not machined, ...c materials and parts shall have the original smooth or polished surfaces. Surfa... that have been sawed, cut, punched, or otherwise machined shall be as smooth as practicable, in accordance with good manufacturing practice for the intended application.

3.4.4 Cleaning. -

3.4.4.1 Parts. - After fabrication, parts shall be cleaned in accordance with good commercial practice, or as specified in an applicable document. Cleaning processes shall have no deleterious effect. Corrosive material shall be removed completely before the parts are mounted on chassis, panels, etc.

3.4.4.2 Units. - After assembly, units shall be cleaned thoroughly and shall be free from particles of solder, flux, and other foreign material. In addition, when necessary, such cleaning shall also be performed before final assembly of the units.

3.4.5 Marking. -

3.4.5.1 Conformance. - Marking shall conform to Specification MIL-M-13231. (See 4.4.) Front panel marking shall be group I as described in that specification.

3.4.5.2 Visibility of markings. - Wherever practicable, parts shall be so mounted that their identification markings will be readily visible with minimum disassembly of the equipment.

3.4.5.3 Serial numbers. - The following items shall have serial numbers:

Receiver-Transmitter, Radio RT-441( )/TRC-68
Power Supply PP-1494( )/U
Case, Receiver-Transmitter CY-2712( )/TRC-68
Fan, Centrifugal HD-390( )/U
Mounting MT-2297( )/TRC-68
Case, Accessories CY-2713( )/TRC-68

3.4.6 Riveting. - Thickness of countersunk metal which accepts the heads of flush rivets shall be not less than the height of the rivet heads. After riveting, the joints shall be tight, the joined parts shall be undamaged, and the rivet heads shall be properly seated and tight against their bearing surfaces.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the current version before use.

3.4.7 Securing of parts. -

3.4.7.1 Mounting components. - Brackets, lugs, flanges, inserts, bolts, and other mounting arrangements shall be such as to retain items securely when subjected to specified services conditions. Parts shall be so mounted that loosening, wear of mounting arrangements, or permanent separation of parts will not occur when the items in which they are used are subjected to specified service conditions. Any permanent deformation resulting from the tests shall not cause degradation of performance below full specification requirements. Parts shall be secured in such manner that failure of a single rivet or screw will not free the part completely.

3.4.7.2 Securing of parts by threaded fasteners. - Securing of parts by threaded fasteners to hard material, or to soft material (aluminum, magnesium, zinc, plastic, etc) shall conform to the drawings. Except as specified therein, a flatwasher shall be used between any screwhead and soft material unless the shape of the head is such that the flatwasher is unnecessary. Nylok or other screws with plastic devices, and Loctite or similar sealants, shall not be subjected to temperatures in excess of 250° Fahrenheit (as during baking of paint). Locitite or similar sealants shall not be used where the connection must be electrically conductive; where used, such materials shall be applied in accordance with the manufacturer's instructions.

3.4.7.3 Brittle material. - Brittle casting, or parts made of ceramic or other brittle material, shall not be over-constrained by the means used to secure them. Not more than three points of contact shall be used between the brittle part and the mounting surface, unless the mating faces are accurately machined. Mounting washers of suitable plastic, rubber, or soft copper having slight compressibility shall be provided to prevent breakage or cracking of the parts. Lead washers shall not be used. Threaded holes in ceramic material shall not be employed for assembly or mounting of parts.

3.4.7.4 Safety wiring and cotter pins. - Application of safety wiring and cotter pins shall conform to Standard MS33540.

3.4.8 Brazing. - Brazing of steels, copper, copper alloys, and nickel alloys shall conform to Specification MIL-B-7883.

3.4.9 Soldering. -

3.4.9.1 Solder. - Solder shall conform to Specification QQ-S-571. For soldering electrical connections, composition Sn60, type AR or S, shall be used for general purposes; and composition Sn62 or Sn63, type AR or S, for special purposes. When type S solder is used for soldering electrical connections, the flux shall conform to Specification MIL-F-14256.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

3.4.9.2 Acid or acid salts. - No acid or acid salts shall be used in preparation for or during soldering; however, exception is permitted for preliminary tinning of electrical connections and for tinning or soldering of mechanical joints not used to complete electrical circuits, but in no case shall acid or acid salts be used where they can come in contact with insulation material. Where acid or acid salts are used, as permitted above, they shall be completely neutralized and removed immediately after use.

3.4.9.3 Process. - There shall be no sharp points or rough surfaces resulting from insufficient heating. The solder shall feather out to a thin edge, indicating proper flowing and wetting actions, and shall not be crystallized, overheated, or underheated. The minimum necessary amount of flux and solder shall be used for electrical connections. Any means employed to remove an unavoidable excess of flux shall not incur the risk of loose particles of flux, brush bristles, or other foreign material remaining in the equipment; flux being spread over a larger area; or damage to the equipment. Insulation material that has been subjected to heating during the soldering operation shall be undamaged and parts fastened thereto shall not have become loosened.

3.4.10 Tropicalization of material. - Material shall be treated as follows:

3.4.10.1 Treating materials. - Treating materials containing a mercury-bearing fungicide shall not be used. The contractor shall determine that the treating material is compatible with the material or surface to be treated. Selection of treating materials shall be such that any increase in flammability of treated material will be held to the practical minimum.

3.4.10.2 Toxicity. - Treating materials shall cause no skin irritation or other injury to personnel handling the treated material during fabrication, transportation, operation, or maintenance of the equipment or during use of the finished items when used for the purpose intended.

3.4.10.3 Flexibility. - Treatment shall not affect the flexibility of treated materials to the extent that the equipment may fail to meet specified requirements when subjected to specified service conditions.

3.4.10.4 Statement of treatment. - The contractor shall submit for approval, to the contracting officer, a statement describing in detail the materials to be treated and the treating materials and processes that he proposes to use. (See 6.2(j).)

3.4.11 Welding. - Wherever practicable, welded joints shall conform to Standard MIL-STD-22 and shall be such that grinding on the finished weld will be unnecessary. Spot, stich, and seam welds shall conform to Specification MIL-W-6858. Spot or other

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

3.4.11 Welding. -(Contd)

intermittent welds in aluminum or magnesium shall be limited to lightly stressed, noncritical structures. When spot or other intermittent welds are used to hold a part, the number of welds shall be at least two.

3.4.11.1 Cleaning prior to welding. - Surfaces to be welded shall be cleaned in accordance with good commercial practice and shall be free from rust, scale, paint, grease, and other foreign material.

3.4.11.2 Process. - Preheating shall be employed where distortion is likely to result from welding. Welds shall have thorough penetration and good fusion and shall be free from scabs, blisters, abnormal pock marks, cracks, voids, slag inclusion, and other harmful defects. Where undesirable internal stresses are likely to result from welding, welded items shall be stress-relieved. Inert-gas-shielded arc welding of aluminum, magnesium, or stainless steel.

3.4.11.3 Cleaning after welding. - Welded assemblies shall be cleaned to remove rust, scale, oxidation products, and excess flux by sandblasting, wire brushing, or other suitable means. Prior to painting, steel parts that have been arc welded or acetylene welded shall, in addition, be subjected to vat passivation or a phosphoric acid etch in accordance with Specification MIL-M-10578.. Acid used for cleaning shall be completely neutralized and removed.

3.4.12 Wiring and cabling. - Wiring and cabling shall be neat and sturdy. Wiring instructions on drawings take precedence over the paragraphs below.

3.4.12.1 Cabling. - Insulated wires shall be formed into cables except where operation of the equipment would be adversely affected thereby or where it is physically impracticable as in the case where the resulting cables would be excessively large and would interfere with operation or maintenance. The cabling of wires shall be effected by tape or twine conforming to Specification MIL-T-713 or tape conforming to Specification MIL-I-7798; however, cord conforming to Specification MIL-I-3158 shall be used where resistance to heat or chemicals is essential. Individual conductors thus secured shall lie essentially parallel; however, this does not prohibit the use of twisted pairs.

3.4.12.2 Slack. - Wires and cables shall be as short as practical except that sufficient slack shall be provided for the following purposes:

(a) To prevent undue stress on cable forms, wires, and connections, including connections to resiliently supported parts.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the currentversion before use.

3.4.12.2 Slack.(Contd)

(b) To enable parts to be removed and replaced during servicing without disconnecting other parts.

(c) To provide for at least two replacements of the part to which the wire or cable is connected, except for certain rf leads which must be as short as possible for electrical reasons.

(d) To ensure freedom of motion of lugs or terminals normally intended to have some degree of movement (for example, floating contacts on electron tube sockets).

(e) To facilitate field repair of broken or cut wires.

(f) To prevent chafing or breaking of individual wires due to repeated flexing of hinged parts.

3.4.12.3 Protection. - Wires and cables shall be so placed and protected as to avoid contact, under specified service conditions, with rough or irregular surfaces or sharp edges. Wires shall not be bent sharply where they enter insulation material. Where wires run through holes in metal partitions, shields, or similar items less than 1/8 inch in thickness, the wires shall be protected by suitable grommets or bushings. Where wires run through holes in metal 1/8 inch in thickness or greater, the wires shall be protected by grommets or bushings or shall have the edges of the holes rounded to a minimum radius of 1/16 inch.

3.4.12.4 Support. - Wire and cable shall be properly supported and secured, to prevent undue stress on the conductors and terminals and undue change in position of the wire or cable (i) during and after subjection of the equipment to specified service conditions or (ii) after service or repair of the equipment in a normal manner. (Note: When shielding on wire or cable is unprotected by an outer insulation, adequate support is necessary to prevent the shielding from coming in contact with exposed terminals or conductors.) Twine or tape shall not be used for securing wire and cable.

3.4.12.5 Clearance. - Clearance between wires or cables, and parts such as electron tubes, resistors, and dynamotors, shall be provided to avoid deterioration of the wires or cables because of the heat dissipated by such parts when the equipment is subjected to specified service conditions. Clearance between solder connections or bare conductors, on terminal boards, relays, or other parts, shall be such that no accidental contact can occur between adjacent connections when subjected to specified service conditions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

3.4.12.6 Splicing.- Wires in a continuous run between two terminals shall not be spliced during the wiring operation.

3.4.12.7 Insulating sleeving.- Insulating sleeving shall be used only as specified.

3.4.12.8 Inductive and capacitive effects.- Wires and cables shall be so located that inductive and capacitive effects, unless used as a design feature, will be minimum practicable.

3.4.12.9 Connections.- Before being soldered to terminal lugs or fixed terminals, wires shall be mechanically secured so that the connections are not dependent for strength on solder alone. Where practicable, wires soldered to fixed terminals shall be looped at least one-half turn but not more than three-quarters turn around the terminal before soldering. Bared ends of wire leads to be terminated in solder-type terminal lugs shall be tinned, silver-plated, or lead-alloy coated. Electrical connections shall not be made by clamping between a metallic and nonmetallic material. Welded electrical connections shall not be used where it may be necessary to disconnect and reconnect the circuit during servicing. Fraying of textile ends of wires shall be prevented mechanically or by application of varnish conforming to Specification MIL-V-173. No varnish, lacquer, inspection paint, or other coating shall be applied to completed electrical connections.

3.4.12.10 Grounding.- Ground connection to shields and to other mechanical parts, except the chassis or frame, shall not be made to complete electrical circuits but only to eliminate high-potential ac points. Grounding to chassis shall conform to Drawing SC-B-61578.

3.4.12.11 Wire and cable shielding.- Shielding shall end at a sufficient distance from exposed conductors to insure against shorting or arcing between the conductor and the shielding.

3.4.12 12 Identification of wiring.- Wiring shall be identified by color-coding or, if approved by the contracting officer, may be identified by other means such as marking of terminals at both ends of each lead. Color-coding for chassis wiring shall be system I or II conforming to Standard MIL-STD-681, as applicable, except that coding specified in drawings shall not be changed without permission of the contracting officer.

3.4.13 Screws, other threaded devices, and related parts.-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

3.4.13.1 Form and fit. - Unless otherwise specified, screw threads shall conform to Handbook H28; the Unified Thread Form and Series shall be class 2A or 2B fit, and the American National Thread Series shall be class 2 fit.

3.4.13.2 Self-tapping screws. - Chips formed in through holes by thread-cutting screws shall be removed.

3.4.13.3 Nut, self-locking. - Self-locking nuts shall conform to Specification MIL-N-25027. In no case shall locknuts containing plastic inserts be subjected to temperatures in excess of 250° F (during baking of paint).

3.4.13.4 Thread engagement and extension. - The length of thread engagement for tapped holes in steel or hard brass shall at least equal the nominal thickness of corresponding machine-screw nuts in sizes No. 12 and smaller and semifinished hexagon regular nuts in sizes 1/4 inch and larger, as shown in Handbook H28. Thread engagement for tapped holes in aluminum, magesium, or other soft material shall be at least 50 percent greater than the thread engagement specified for steel or hard brass. Where permitted by design of the equipment, screws and bolts shall extend at least 1-1/2 threads beyond the nut, but no more than 1-1/2 threads plus 1/8 inch for screws up to 1 inch in length and 1-1/2 threads plus 1/4 inch for screws over 1 inch in length.

3.13.5 Torque-measuring devices. - Threaded parts of steel shall be tightened to the torque values shown in table I. Threaded parts of other size or material shall be tightened to a suitable design value established by the contractor for the particular application. For critically stressed applications, the torque for tightening threaded parts shall be controlled by use of torque measuring or controlling devices.

Table I. - Torque for tightening steel threaded parts

Thread	Torque (lb - in.)
6-32	7 to 9
8-32	14 to 18
10-24	19 to 23
10-32	25 to 30
12-24	32 to 39

3.4.13.6 Anti-seize compound. - Anti-seize compound shall be used to prevent seizing of threads where the threaded surface is aluminum or magnesium alloy. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

3.4.13.6 Anti-seize compound. (Contd). compound shall be made of equal parts by weight of petrolatum and zinc dust--200 mesh-fine.

3.4.13.7 Adjustment screws. - Adjustment screws and similar devices shall be prevented from rotating except when being adjusted. Loctite sealant, as made by the American Sealants Company, Hartford 6, Connecticut, or equal, may be used for this purpose, if it will not be subjected to temperatures in excess of 250° F (as during baking of paint), or if it cannot inadvertently enter a space where it can harden and interfere with operation of the device. Loctite or similar sealants shall be applied in accordance with manufacturer's instructions.

3.4.13.8 Machine screws. - Unless otherwise specified, the screw heads shall be completely seated in the material.

3.4.14 Tubes, electron; and semiconductors, transistor and diode. - Except as otherwise provided by Standards MIL-STD-200 and MIL-STD-701, these electron devices (tubes and semiconductors) shall conform to Specifications MIL-E-1 and MIL-S-19500.

3.4.14.1 Choice, use, and application. - Except as otherwise specified in (a) and (b) below, the choice, use, and application of these electron devices shall conform to Standards MIL-STD-200 and MIL-STD-701:

(a) When substitution of a preferred or guidance type of electron device for a type required by the equipment specification would degrade equipment performance or ruggedness below specified requirements, pertinent data shall be furnished to the contracting officer, to justify retaining the type required by the equipment specification.

(b) When the foregoing standards require modification of equipment circuitry, the modification shall be subject to prior approval by the contracting officer.

3.4.14.2 Circuit location. - The electron device and non-linear parts furnished in equipment on contract shall be the individual devices used when the equipment was inspected for acceptance and, unless separate packaging of the devices is specified, shall remain in the respective locations occupied during the inspection.

3.4.15 Adjustment and repair. - The equipment shall be so constructed that parts, terminals, wiring, etc, are accessible for circuit checking, adjustment, maintenance, repair, and replacement with minimum disturbance to other parts and wiring. After normal maintenance and repair, the equipment shall meet specified performance requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:13Z
Check the source to verify that this is the currentversion before use.

3.4.16 Fabric and thread. - The color of any required fabric shall be Olive-Drab No.7. The color of thread shall match shade S-1 of the United States Army Standard Color Card for Official Standardization Shades of Sewing Thread. (See 6.8.) Fabric and thread shall be preshrunk, or allowance shall be made for shrinkage, in order to provide for satisfactory fit of finished items both before and after they are immersed in water and then dried.

3.4.17 Interchangeability. - Like units, assemblies, subassemblies, and replaceable parts shall be physically and functionally interchangeable, without modification of such items or of the equipment. (See 4.17.) Individual items shall not be hand-picked for fit or performance; however, matched pairs or sets, when permitted, may be interchangeable as such. Reliance shall not be placed on any unspecified dimension, rating, characteristic, etc.

3.4.18 Controls and rotating components. - Controls shall conform to the following requirements:

3.4.18.1 Effect of vibration, bounce, and shock. - Controls shall maintain their setting when the items in which they are used are subjected to specified operating service conditions.

3.4.18.2 Mechanical operation. - Play and backlash shall not cause poor contact or inaccurate setting. Controls shall operate freely and smoothly, and shall be lubricated when lubrication does not interfere with operation.

3.4.18.3 Locking devices. - Locking devices shall be so adjusted that they are capable of retaining controls in any given setting within the range of the control. The locking and unlocking action shall be easily accomplished and shall not affect the setting of the control. When in the unlocked position, the locking device shall not interfere with the normal operation of the control.

3.4.18.4 Tuning dial stability. - Friction in the tuning dial mechanism shall be sufficient to maintain the tuning knob in any position over the operating range of the mechanism.

3.4.18.5 Gears and cams. - Gears shall be properly alined and meshed, and shall operate without interference, tight spots, or other irregularities.

3.4.19 Printed wiring assemblies. - Printed wiring assemblies shall be processed and fabricated according to SC-A-46570. (See 4.4.)

3.5 Service conditions (see 4.7). - The equipment shall meet the following service conditions; where a test is referenced, meeting the test shall be considered as compliance with the requirement:

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the current version before use:

3.5.1 Operation. - Continuous use for a period of 500 hours, under the worldwide environmental conditions specified in 3.5.2 through 3.5.12, with a duty cycle of 23 hours on and 1 hour off. During the test specified in 4.14, there shall be no replacement of parts. Degradation of sensitivity and transmitter rf power output, at the end of the test, shall not exceed 35 percent. The transmitter shall be capable of continuous operation for 1 hour without replacement of parts and the degradation at the end of the hour shall not exceed 10 percent.

3.5.2 Temperature (see 4.7.1). -

(a) Operating: Ambient temperature in the range of +150° F (Fahrenheit) to -65°F. (The 150°F temperature includes effect of sun load.) Exposure at high temperature extreme need not exceed 4 hours and at the low temperature extreme need not exceed 72 hours.

(b) Nonoperating: Exposure in the range of +160°F to -80°F; exposure at the high temperature extreme need not exceed 4 hours and at the low temperature extreme need not exceed 24 hours.

3.5.3 Relative humidity. - Exposure to 97 percent relative humidity for 20 hours and 100 percent relative humidity (with condensation) for 4 hours for each 24 hour period over the period stated in 3.5.1. Meeting the tests of 4.7.2 shall be considered compliance with this requirement. (See 6.11.)

3.5.4 Elevation (see 4.7.3). -

(a) Operating: Up to 18,000 feet above sea level.

(b) Nonoperating: Up to 25,000 feet above sea level.

3.5.5 Orientation. -

(a) Operating (see 4.7.4). - Any orientation up to 20 degrees from normal operating position (that is: upward, downward, left, or right).

(b) Nonoperating: Storage in any position for a period of two years. Approval of the preproduction sample (see 3.2) shall be considered as compliance with this requirement.

3.5.6 Sand and dust (see 4.7.5). - As encountered during heavy traffic over dry clay roads or in desert areas.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:13Z
Check the source to verify that this is the currentversion before use.

3.5.7 Tumbling (Case CY-2713( )/TRC-68 only).- When tested as specified in 4.7.12, the case shall meet the requirements of the "Tumbling" paragraph of section 3 of Specification MIL-T-4150.

3.5.8 Vibration, internal. - With the equipment shock-mounts blocked, the amplitude of vibration of any part, subassembly, or structural member of the equipment shall not exceed twice the amplitude of the vibration applied to the equipment at any frequency between 10 and 55 cycles per second (cps). (See 4.7.6.)

3.5.9 Vibration, equipment. - The natural frequency of the equipment, mounted on its shock-mounts, shall be between 25 and 35 cps. The amplitude of vibration of the mounted equipment shall not exceed three times the amplitude of the applied vibration at any frequency between 10 and 25, or between 35 and 55, cps. (See 4.7.7.)

3.5.10 Bounce and shock. - Units shall be capable of meeting the requirements of table II:

Table II. - Bounce and shock

Paragraph heading	Para. No.	Performance after test
Bounce	4.7.8	Specified performance. (Note B). No physical damage.
Shock; bench-handling	4.7.9	Specified performance. (Note B). No physical damage.
Shock; ballistic	4.7.10	Operable. (Note A) Any physical damage shall be minor only.

Note A: Minor repairs are permissable. The equipment shall meet the following requirements: 4.16.1, operational test.

Note B: The equipment shall meet specified performance for the following tests: Sensitivity, transmitter rf power output.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the currentversion before use.

3.5.11 Immersion (see 4.7.11). - Three feet of water for 2 hours.

3.6 Preconditioning (see 4.6). -

3.6.1 Bounce preconditioning. - The equipment shall be capable of meeting the requirements specified herein, without subsequent processing, after subjection to the bounce preconditioning of 4.6.1. (Also see 4.5).

3.6.2 Electrical preconditioning. - The equipment shall meet the sensitivity (3.8.1) and transmitter rf power output (3.9.1) requirements after the 36-hour run-in test of 4.6.2. This requirement does not apply to Case, Accessories CY-2713( )/TRC-68 or Mounting MT-2297( )/TRC-68.

3.7 Electrical requirements, receiver-transmitter. -(See 4.8).

3.7.1 Frequency range. - The receiver-transmitter shall be capable of reception and transmission in 100 kc increments from 225.0 to 399.0 mc.

3.7.2 Frequency stability (see 4.8.1). - The frequency stability of any selected channel within the frequency range shall meet the requirements of 3.7.2.1 and 3.7.2.2.

3.7.2.1 Frequency stability vs supply voltage (see 4.8.1.1). - The frequency shall drop not more than 3.5 kc when the nominal supply potential is decreased to 103 (or 207) volts (v), ac; the frequency shall not raise more than 3.0 kc when the supply potential is increased to 127 (or 250) v, ac.

3.7.2.2 Frequency stability vs temperature and time (see 4.8.1.2). - The frequency error, at the applicable test temperature, shall not exceed the following:

Test temperature, °F	Maximum frequency error, kc
+ 150	± 13
+ 100	± 11
Ambient	± 11
- 40	± 18
- 65	± 22

3.7.3 Warm-up (see 4.8.2). - Within 60 seconds after the radio set has been turned on, transmitter rf power output shall be 15 w or greater, and receiver sensitivity shall be 6 microvolts (uv) or less for a signal-plus-noise to noise output ratio of 10 decibels (db).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

3.7.4 Channel changing time (see 4.8.3.) - The length of time required to automatically change from any preset channel to any other preset channel shall not exceed 9 seconds at room temperature and 15 seconds at -65°F.

3.7.5 Resettability (see 4.8.4). - The transmitter rf power output shall change not more than 5 percent and the receiver sensitivity shall change not more than 10 percent when recycled to the same channel. Transmitter frequency error shall not exceed 2 kc.

3.7.6 Transmit-receive interval (see 4.8.5). - The time interval between consecutive receive and transmit periods shall not exceed 0.5 second.

3.7.7 Panel meter. - When tested in accordance with 4.8.6, the panel meter shall indicate as follows for the applicable switch position.

Meter switch position	Meter indication
LINE V	Mid-scale, ±20 percent
LOW B+	Mid-scale, ±20 percent
HIGH B+	Mid-scale, ±20 percent
S-METER	
No signal input	Not more than 20 percent of full scale
10 uv input	At least 15 percent of full scale above no signal reading.
% MOD	Mid-scale, ±20 percent
DVR I_b	Mid-scale, ±20 percent
PA I_b	Mid-scale, ±20 percent
PA I_g	30 to 100 percent of full scale *
SWR (at 16 w and 309.9 mc)	
51.5- ohm termination	Less than 10 percent of full scale.
Open circuit	25 to 50 percent of full scale.
ANT jack short-circuited	Not less than 50 percent of full scale.
PWR (at 16 w and 309.9 mc)	
51.5-ohm termination	50 to 70 percent of full scale
Open circuit	25 to 50 percent of full scale
ANT jack short-circuited	Not less than 50 percent of full scale

* The maximum reading shall, in all operations of end-item equipment, maintain grid dissipation within the maximum permitted for the PA vacuum tube.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the current version before use.

3.7.8 Power drain (see 4.8.7). - Total input power from a 115 (or 230) v, ac primary source shall not exceed 340 w during reception and 460 w during transmission (unmodulated), at 50 cps.

3.7.9 Operating input potential (see 4.8.8). - Nominal input voltages shall be 115 and 230 v, ac at 50 or 60 cps. The equipment shall be capable of performing all its functions, but with reduced performance as permitted with input potentials at 103 (or 207) v, ac. (See 3.8.1, 3.8.2, 3.8.12, and 3.9.1.) It shall also be capable of normal operation without component failure with input voltages up to 127 (or 253) v, ac.(See 3.8.2.)

3.8 Electrical requirements, receiver (see 4.9). -

3.8.1 Sensitivity (see 4.9.2). - An input signal of not more than 6 uv shall be required to produce 250 milliwatts (mw), or greater, output at a signal-plus-noise to noise output ratio of 10 db. Not more than 8 uv shall be allowed at -65°F and +150°F. Not more than 8 uv shall be allowed at low input potential of 103 (or 207) v, ac.

3.8.2 Squelch (see 4.9.3). -

(a) The squelch sensitivity shall be adjustable so that in its maximum sensitivity position (extreme counterclockwise) it will operate with a signal of not more than 3 uv. When the control is in the minimum sensitivity position (extreme clockwise), the signal required to operate the squelch shall be not less than 25 uv. The ratio of uv to operate the squelch light at the least sensitive frequency to the most sensitive frequency shall not exceed 5 to 1.

(b) The operation of the squelch control shall be smooth, and permit threshold adjustment on any channel frequency. The spread between the maximum and minimum squelch sensitivity settings shall be not less than 200 degrees of shaft rotation.

(c) With the squelch control set at the extreme clockwise position, the ratio of uv to operate the squelch shall not vary by more than 9 db, on any one channel, over the input voltage range of 103 and 127 (or 207 to 253) v, ac.

(d) With the squelch control set for operation with a signal of 6 uv, the input signal difference between unsquelched and squelched conditions shall not exceed 2 to 1.

(e) The signal-plus-noise to noise output ratio with the squelch control adjusted to open on a 6 uv input signal shall be within 4 db of that obtained with the squelch control in the OFF position, and shall be not less than 8 db.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the current version before use.

3.8.3 AGC characteristics (see 4.9.4). - The automatic gain control (agc) shall be such that when the signal is increased from 100 uv to 0.5 v, the audio output shall change not more than ± 5 db. When the input signal is decreased to 6 uv, the audio output relative to the 100 uv input level shall not decrease more than 3 db.

3.8.4 AGC time constant (see 4.9.5). - The charge and discharge time constants of the agc circuits shall be not less than 0.03 second nor more than 0.3 second.

3.8.5 Selectivity (see 4.9.6). - The overall intermediate-frequency (i.f.) bandwidth shall be not less than 80 kc at the 6 db points and not greater than 150 kc at the 60 db points. Peak-to-valley ratio within the 3 db bandpass shall not exceed 2 db. The half-bandwidths on each side of resonance shall not differ by more than the following at the applicable attenuation point.

Difference in percent	Attenuation point db
15	6
15	20
20	40
25	60

3.8.6 IF rejection (see 4.9.7). - The i.f. rejection ratiorshall be not less than 100 db down from the desired frequency response.

3.8.7 Image rejection (see 4.9.8). - The first and the 500 kc i.f. images shall be attenuated at least 60 db. All other i.f. image response shall be attenuated at least 80 db.

3.8.8 Spurious response (see 4.9.9). - All spurious responses ± 2 mc or more removed from the desired frequency, excluding image and i.f. responses, shall be attenuated at least 60 db. Spurious responses within the bands starting at ±100 kc and ending at ± 2 mc shall be attenuated at least 40 db.

3.8.9 Internal signals (see 4.9.10). - Internal signals generated by oscillator interaction and harmonics falling on the desired frequency or within the i.f. pass band shall not cause interference on more than 10 channels within the frequency range. Such interference shall not degrade the operating sensitivity by more than 6 db; except that for frequencies of 384, 342, 294, and 276 megacycles 10 db degeneration shall be permitted.

3.8.10 Cross-modulation (see 4.9.11). - An undesired signal of 200,000 uv, removed 1.3 percent in frequency from the desired frequency, shall result in a signal-plus-noise to noise ratio of not less than 6 db.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the currentversion before use.

3.8.11 Desensitization (see 4.9.12). - An undesired signal of 200,000 uv, removed 1.3 percent in frequency from a desired signal of 6 uv, shall not depress the audio reference level produced by the desired signal by more than 6 db. The desired signal, under this condition, shall produce a signal-plus-noise to noise ratio of at least 6 db.

3.8.12 Audio output (see 4.9.13). - With a signal input of 100 uv, 30 percent modulated at 1,000 cps, the following audio levels shall be available when the applicable circuit is loaded individually with 600 ohms. Not more than 3 db decrease in audio level shall be allowed at -65°F and at +150°F. Not more than 3 db decrease in audio level shall be allowed at the low input supply potential of 103 (or 207) v, ac.

Output circuit	Audio level, mw
Loudspeaker	1,000
Headset	250
Remote	600
Fixed level	50
Extended range	1

3.8.13 Audio level adjustment (see 4.9.14). - The front panel VOLUME control shall provide loudspeaker and headset output level adjustment of at least 25 db. The setting of this control shall not affect the output level of the extended range audio circuits by more than ± 2 db, or the fixed level and remote audio circuits by more than ± 3 db.

3.8.14 Audio response characteristcs(see 4.9.15). - The overall audio response measured at the loudspeaker output shall be within the limits specified at the applicable frequencies.

Frequency, cps	Limits, db
300	± 3
1,000	0 (reference)
3,000	± 3
5,000	Not less than 5 down
10,000	Not less than 15 down

The audio response at the headset, remote, and fixed level outputs shall be within ± 2db of the loudspeaker response.

3.8.15 Audio response characteristics, extended range (see 4.9.16). - The overall audio response measured at the extended range output circuit shall be within the limits specified at the applicable frequencies.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:13Z
Check the source to verify that this is the current version before use.

3.8.15 Audio response characteristics, extended range (contd).

Frequency, cps	Limits, db
300	± 3
1,000	0 (reference)
3,000	± 3
5,000	± 3
10,000	± 3
15,000	Not more than 5 down
20,000	Not more than 6 down
25,000	Not more than 7 down

3.8.16 Audio distortion (see 4.9.17). - Total harmonic distortion shall not exceed 10 percent between 300 and 3,000 cps when measured with a constant signal input which at 1,000 cps gives the output levels specified in 3.8.12. Extended range distortion shall not exceed 12 percent.

3.8.17 Noise rejection (see 4.9.18). - The modulation level at which the noise limiter starts to clip, as observed on an oscilloscope, shall be no more than 55 percent and no less than 35 percent.

3.8.18 Blocking (see 4.9.19). - When rf signal of 1 volt, modulated 30 percent at 1,000 cps, is introduced simultaneously with a desired signal of 6 uv (both signals on 399.9 mc), it shall be possible to receive the desired signal within 0.25 second after the 1-volt signal is turned off.

3.8.19 Maximum signal-plus-noise to noise ratio (see 4.9.20). - An input signal of 10,000 uv, modulated 30 percent at 1,000 cps, shall produce a signal-plus-noise to noise ratio of not less than 35 db measured at the loudspeaker output.

3.9 Electrical requirements, transmitter (see 4.10). -

3.9.1 Transmitter rf output (see 4.10.2). - The unmodulated power output shall be not less than 16 w at any channel frequency from 225.0 to 399.9 mc, inclusive. Not less that 12 w shall be allowed at -65°F and + 150°F. Not less than 6 w shall be allowed at the low input supply potential of 103 (or 207) v, ac.

3.9.2 Modulation capability (see 4.10.3). - The rf carrier shall be modulated between 65 and 100 percent at any channel frequency from 225.0 to 399.0 mc, inclusive, with a nominal microphone input potential of 0.2 v, root-mean-square (rms).

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:13Z
Check the source to verify that this is the current version before use.

3.9.3 Automatic modulatic. limiter (see 4.10.4).- The modulator output voltage shall not increase more than 2 db for a 12 db increase above the nominal microphone input potential of 0.2 v, rms. When the nominal microphone input voltage is decreased by 6 db, the modulator output voltage shall decrease by at least 3 db, thereby indicating the threshold of the limiting curve. The internal adjustment shall provide at least a ±6 db range setting of the threshold level.

3.9.4 Audio response (see 4.10.5).- The overall audio response from 300 to 10,000 cps shall not exceed the following limits at the applicable frequency.

Frequency, cps	Limits, db
300	±3
1,000	0 (reference)
3,000	±2
6,000	±3
10,000	Not less than 3 down.

To avoid limiting, the microphone input voltage shall be 6 db lower than the nominal input voltage for these tests.

3.9.5 Audio response, extended range (see 4.10.6).- The overall audio response shall be within ±2 db of the 1,000 cps reference level from 3,000 to 25,000 cps and not more than 3 db down at 300 cps. To avoid limiting during these tests, the microphone input shall be 6 db lower than the nominal input voltage.

3.9.6 Overall distortion (see 4.10.7).- Overall transmitter distortion with an audio input of 0.2 v, rms, shall not exceed 10 percent. With the input increased by 12 db (modulation limiter operative) the distortion shall not exceed 20 percent.

3.9.7 Carrier noise level (see 4.10.8).- Noise and hum modulation of the rf carrier shall be at least 35 db below the maximum sinusoidal modulation obtainable.

3.9.8 Sidetone (see 4.10.9).- Transmitter sidetone levels measured at the headset, remote, and fixed level outputs shall be from 0 to 6 db below the output of a received signal of 100 uv modulated 30 percent at 1,000 cps. Loudspeaker sidetone shall be at least 20 db down from the received signal.

3.9.9 Microphone input impedance (see 4.10.10).- Microphone input impedance shall be 150 ohms ±15 percent from 300 to 3,000 cps.

3.9.10 Spurious radiation (see 4.10.11).- The output level of any radiated frequencies, other than the operating frequency, shall be attenuated below the carrier level by the following amounts at the frequencies specified:

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:13Z
Check the source to verify that this is the current version before use.

3.9.10 Spurious radiation (see 4.10.11).- (Contd)

Frequency, mc	Attenuation, db
20 to 75	Not less than 75
75 to 1,200:	
Carrier frequency harmonics above 500	At least 40 down
Carrier frequency harmonics below 500	At least 30 down
Other frequencies in this range	Not less than 65

3.10 Power Supply PP-1494( )/U.- The power supply shall be capable of performing all its functions over the input range of 103 to 127 (or 207 to 253) v, ac. Under the conditions specified in 4.11, the output voltages shall be as given in 3.10.1 through 3.10.8. Test point pins referred to are on plug P1801 of the PP-1494( )/U.

3.10.1 Transmitter B + power.- When tested as specified in 4.11.1, the potential between pin 11 and ground shall be no less than 288 and no greater than 320v. The ripple shall not exceed 0.5 v.

3.10.2 Low-voltage B + power.- When tested as specified in 4.11.2, the potential between pin 10 and ground shall be no less than 147 and no greater than 163 v. The ripple shall not exceed 0.25 v.

3.10.3 Filament power.- When tested as specified in 4.11.3, potentials at the tube filament pins shall meet the requirements of 3.10.3.1 through 3.10.3.4.

3.10.3.1 26.4 volt circuit.- The potential shall be no less than 26.0 and no greater than 27.0 volts.

3.10.3.2 18.9-volt circuit.- The potential shall be no less than 18.5 and no greater than 19.3 volts

3.10.3.3 12.6-volt circuit.- The potential shall be no less than 12.2 and no greater than 13.0 volts.

3.10.3.4 6.3-volt circuit.- The potential shall be no less than 6.1 and no greater than 6.5 volts.

3.10.4 Blower power.- When tested as specified in 4.11.4, the potential between pins 16 and 13, and that between pins 6 and 14, shall be no less than 112.7 and no greater than 117.3 volts.

3.10.5 Receiver B + power.- When tested as specified in 4.11.5, the potential between pin 9 and ground shall be no less than 255 and no greater than 275 volts. The ripple shall not exceed 0.5 volts.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the current version before use.

3.10.6 Relay power.- When tested as specified in 4.11.6, the potential between pin 2 and ground shall be no less than 25.0 and no greater than 27.0 volts.

3.10.7 B + transient.- When tested as specified in 4.11.7, the maximum potential of the transient shall not exceed 170 volts.

3.10.8 No-load condition.- When tested as specified in 4.11.8, the potential between pin 11 and ground shall not exceed 525 volts; and between pins 10 and 12 shall not exceed 275 volts.

3.11 Case, Receiver-Transmitter CY-2712( )/TRC-68(see 4.12).- The continuity check shall show no shorts, opens, or undue leakage. The injecting-ejecting mechanism shall operate properly.

3.12 Fan, Centrifugal HD-390( )/U.- When tested at the voltages and frequencies specified in 4.13, the blower assembly shall operate without excessive noise or vibration. Sufficient air shall be blown to properly cook the transmitter power output tube during the time the power output is 16 watts. The motor construction shall meet the applicable requirements of Specification MIL-M-13787.

3.13 Case, Accessories CY-2713( )/TRC-68.- This case shall meet the requirements of the sand and dust, tumbling, ballistic shock, immersion, and air seal tests.

3.14 Mounting MT-2297( )/TRC-68.- The mounting shall meet the applicable requirements of 3.19 and the service operation tests.

3.15 Air seal (cases only).- When tested as specified in 4.15, the decrease in vacuum shall not exceed 0.01 pounds per square inch, guage (psig), per minute.

3.16 System operation (see 4.16.- All operations and functions specified shall be satisfactorily performed.

3.17 Operational inspection.- The operational test specified in 4.16.1 shall be performed to determine that the radio set is operable, prior to packaging and at such other times as required.

3.18 Technical literature and running spare parts.- Technical literature and running spare parts shall be furnished if specified in the contract. Running spare parts shall be identical to corresponding parts in the equipment furnished on the order. (See 6.2(h) and (i).)

3.19 Workmanship.- The equipment shall be manufactured and assembled in accordance with the applicable portions of the following paragraphs herein:

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the current version before use.

3.19 Workmanship. - (Contd)

3.4.3 Plastic materials and parts.
3.4.4 Cleaning.
3.4.5.2 Visibility of markings.
3.4.6 Riveting.
3.4.7 Securing of parts.
3.4.8 Brazing.
3.4.9 Soldering.
3.4.10 Tropicalization of material.
3.4.11 Welding.
3.4.12 Wiring and cabling.
3.4.13 Screws, other threaded devices, and related parts.
3.4.15 Adjustment and repair.
3.4.18 Controls and rotating components.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Classification of inspection. - Inspection shall be classified as follows:

(a) Preproduction inspection (does not include preparation for delivery). (See 4.3.)

(b) Inspection covered by subsidiary documents. (See 4.4.)

(c) Quality conformance inspection.

(1) Quality conformance inspection of equipment before preparation for delivery. (See 4.5.)

(2) Quality conformance inspection of preparation for delivery. (See 4.19.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

4.3 Preproduction inspection.- This inspection will be performed by the Government unless otherwise specified in the contract. It shall consist of the preproduction inspection specified in table III; the inspection specified in the subsidiary documents covering the items listed in 4.4; and the inspection specified for group A, group B, and group C (see tables IV, V, and VI, respectively). The preproduction inspection will normally be performed in this order: (1) vibration, (2) bounce, (3) shock, benchhandling, (4) shock, ballistic, and (5) immersion; other preproduction inspection may precede, follow, or be interspersed between the foregoing.

Table III - Preproduction inspection

Inspection (For additional preproduction inspection see 4.3)	Req para	Insp para
Temperature	3.5.2	4.7.1
Relative humidity	3.5.3	4.7.2
Elevation	3.5.4	4.7.3
Orientation	3.5.5	4.7.4
Sand and dust	3.5.6	4.7.5
Tumbling	3.5.7	4.7.12
Vibration, internal	3.5.8	4.7.6
Vibration, equipment	3.5.9	4.7.7
Bounce	3.5.10	4.7.8
Shock, bench-handling	3.5.10	4.7.9
Shock, ballistic	3.5.10	4.7.10
Immersion	3.5.11	4.7.11
Microphone input impedance	3.9.9	4.10.10

4.4 Acceptance inspection covered by subsidiary documents.- The following shall be inspected under the applicable subsidiary documents as part of the acceptance inspection before preparation for delivery:

Item	Where required
Finish	3.4.2
Marking	3.4.5.1
Printed wiring	3.4.19

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance inspection of equipment before preparation for delivery.- Each equipment produced under this specification shall be subjected to a 36-hour electrical preconditioning run-in (see 3.6.2), prior to selection of samples for inspection. The contractor shall perform the inspection specified in 4.4 and 4.5.1 through 4.5.4. This does not relieve the contractor of his responsibility for performing any additional inspection which is necessary to control the quality of the product and to assure compliance with all specification requirements. The Government will review and evaluate the contractor's inspection procedures and examine the contractor's inspection records. In addition, the Government--at its discretion--may perform all or any part of the specified inspection, to verify the contractor's compliance with specified requirements. (See 6.9.) Test equipment for Government verification inspection shall be made available by the contractor. Each unit which will be subjected to group A, group B, or group C inspection shall be bounce preconditioned (see 3.6.1) after final assembly.

4.5.1 Group A inspection.- This inspection, including sampling, shall conform to table IV and the ordinary inspection procedures of Standard MIL-STD-105. Group A inspection shall be performed in any order which is satisfactory to the Government, except that the air-seal test (4.15) shall be next to last and the operational inspection (4.16.1) shall be last. (See 6.6.)

Table IV.- Group A inspection

Inspection	Req para	Insp para	AQL Major	AQL Minor
Visual and mechanical:	3.19	4.18		
Receiver-Transmitter, Radio RT-441( )/TRC-68			1.5 dphu* for all receiver-transmitter units combined	6.5 dphu for all receiver-transmitter units combined
Front panel & relays				
Audio ampl and modulator				
UHF injection system				
RF and PA unit				
20.9-29.9 mc IF ampl				
3.0-3.9 IF mc ampl				
500 kc IF ampl & filter				
Fan, Centrifugal, HD-390( )/U			1.0%	4.0%
Case, Accessories CY-2713( )/TRC-68			1.0%	4.0%
Case, Receiver-Transmitter CY-2712( )/TRC-68			1.0%	4.0%
Mounting MT-2297( )/TRC-68			1.0%	4.0%
Power Supply PP-1494( )/U			1.5 dphu	6.5 dphu
Radio Set AN/TRC-68( ), complete assembly			1.0%	4.0%

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

Table IV.- Group A inspection (Cont'd)

Inspection	Req para	Insp para	AQL Major	AQL Minor
Electrical:				
Receiver-Transmitter, Radio RT-441( )/TRC-68				
Receiver:			1.5 dphu for receiver-transmitter groups combined	
Sensitivity	3.8.1	4.9.2)		
Squelch	3.8.2	4.9.3)		
AGC characteristics	3.8.3	4.9.4)		
Selectivity	3.8.5	4.9.6)		
Audio output	3.8.12	4.9.13)		
Audio level adjustments	3.8.13	4.9.14)		
Audio response characteristics	3.8.14	4.9.15)		
Audio response characteristics, extended range	3.8.15	4.9.16)		**
Audio distortion	3.8.16	4.9.17)		
Noise rejection	3.8.17	4.9.18)		
Signal-plus-noise-to noise	3.8.19	4.9.20)		
Transmitter:				
Transmitter RF power out	3.9.1	4.10.2)		
Modulation capability	3.9.2	4.10.3)		
Automatic Modulation Limiter	3.9.3	4.10.4)		
Audio response	3.9.4	4.10.5)		
Audio response, extended range	3.9.5	4.10.6)		
Overall distortion	3.9.6	4.10.7)		
Carrier noise level	3.9.7	4.10.8)		
Sidetone	3.9.8	4.10.9)		
Power Supply PP-1494( )/U	3.10	4.11	1.0%	
Case, Receiver-Transmitter, CY-2712( )/TRC-68	3.11	4.12	1.0%	
Fan, HD-390( )/U	3.12	4.13	1.0%	**
Air seal	3.15	4.15	1.0%	
Operational	3.16.1	4.16.1		

*Defects per hundred units.
**All electrical defects are considered major.

4.5.2 Group B inspection.- This inspection, including sampling, shall conform to table V and to the special procedures for small-sample inspection of Standard MIL-STD-105. The reduced inspection procedure shall be R-1. Group B inspection shall normally be performed on inspection lots that have passed group A inspection and on samples selected from units that have been subjected to and met the group A inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

4.5.2.1 Group B sampling plan.- The acceptable quality level (AQL) shall be 6.5% defective, as specified in table V, and the inspection level shall be L-7 for normal and L-5 for reduced inspection.

4.5.2.2 Order of inspection within group B.- Group B inspection shall be performed in any order which is satisfactory to the Government.

Table V.- Group B inspection

Inspection	Req para	Insp para	AQL (See 4.5.2.1)
Radio Set AN/TRC-68( )			
Interchangeability	3.4.17	4.17	6.5%
Frequency stability vs supply voltage	3.7.2.1	4.8.1.1)	6.5% for the group combined
Frequency stability vs temperature and time	3.7.2.2	4.8.1.2)	
Warm-up	3.7.3	4.8.2)	
Channel changing time	3.7.4	4.8.3)	
Resettability	3.7.5	4.8.4)	
Transmit-receive interval	3.7.6	4.8.5)	
Panel meter	3.7.7	4.8.6)	
Power drain	3.7.8	4.8.7)	
Operating input potential*	3.7.9	4.8.8)	
System operation**	3.16	4.16)	
Receiver-Transmitter, Radio RT-441( )/TRC-68			
Receiver:			
AGC time constant	3.8.4	4.9.5)	6.5% for the group combined
IF rejection	3.8.6	4.9.7)	
Image rejection	3.8.7	4.9.8)	
Spurious response	3.8.8	4.9.9)	
Internal signals	3.8.9	4.9.10)	
Cross modulation	3.8.10	4.9.11)	
Desensitization	3.8.11	4.9.12)	
Blocking	3.8.18	4.9.19)	
Transmitter:			
Spurious radiation	3.9.10	4.10.11)	6.5%

* Tests made during Group A inspection at normal operating input voltages need not be repeated for Group B inspection.
**Operational tests of 4.16.1 need be repeated.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the current version before use.

4.5.3 Group C inspection.- This inspection shall be as listed in table VI, and shall normally be performed on sample units that have been subjected to and have passed group A and group B inspections.

Table VI.- Group C inspection

Inspection	Req para.	Insp para.
500-hour run----------	3.5.1	4.14

4.5.3.1 Sampling for inspection of equipment.- Two equipments from the first 200, or major fraction thereof, and one from each successive 200, or major fraction thereof, shall be selected for each group C inspection without regard to their quality, except that the units inspected at the start of the contract shall be selected from the first units produced.

4.5.3.2 Noncompliance.- If a sample unit fails group C inspection, the contractor shall immediately investigate the cause of failure and shall report to the Government inspector the results thereof and details of the corrective action taken on the process and all units of product which were manufactured with the same conditions, materials, processes, etc. If the Government inspector does not consider that the corrective action will enable the product to meet specified requirements, or if the contractor cannot determine the cause of failure, the matter shall be referred to the contracting officer. (see 6.5.)

4.5.4 Reinspection of conforming group B and group C sample units.- Unless otherwise specified, sample units which have been subjected to and passed group B or group C inspection, or both, may be accepted on contract, provided that they are resubjected to and pass group A reinspection after repair of all visible and known damage.

4.6 Preconditioning (see 3.6).-

4.6.1 Bounce preconditioning (see 3.6.1).- The unit, with shock mounts (if any) removed or blocked, shall be placed in its normal operation position on the table of the Type 1000-SC Package Tester as made by the L. A. B. Corporation, Skaneateles, New York, or equal. The package tester, shafts in phase, shall have a speed such that it is just possible to insert a 1/32-inch-thick strip of material under one corner or edge of the unit to a distance of 3 inches as the unit bounces. The unit shall be subjected to preconditioning for 1 minute. After bounce preconditioning, the unit shall not be repaired, alined, cleaned, or otherwise changed prior to subjection to acceptance inspection.

4.6.2 Electrical preconditioning (see 3.6.2).- The equipment shall be operated for a period of 36 hours. The ratio of transmit to receive period shall be 1 minute transmit and 9 minutes receive. Transmitter power and receiver sensitivity shall be measured during this period. This test shall precede other electrical tests of the equipment. 100 channel selections shall be made during this period. If the equipment fails, the cause of failure shall be corrected, and the equipment resubjected to the 36-hour run-in.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the currentversion before use.

4.7 Service conditions tests (see 3.5).-

4.7.1 Temperature (see 3.5.2).- The equipment shall be subjected to the temperature cycle shown on Standard MIL-STD-169. Tests shall be made at step 3 and step 7 as well as steps required by Standard MIL-STD-169. Power shall be applied for 20 minutes at step 7 before measurements are made. Specifications of the requirement paragraphs of the following tests shall be met:

Req para	Test para	Measurement
3.7.3	4.8.2	Warm-up
3.7.4	4.8.3	Channel changing time
3.7.5	4.8.4	Resettability
3.8.1	4.9.2	Sensitivity
3.8.2	4.9.3	Squelch
3.8.5	4.9.6	Selectivity
3.8.12	4.9.13	Audio output
3.8.14	4.9.15	Audio response characteristi
3.8.15	4.9.16	Audio response characteristics, extended range
3.8.16	4.9.17	Audio distortion
3.8.19	4.9.20	Signal-plus-noise-to noise ratio
3.9.1	4.10.2	Transmitter rf power output
3.9.2	4.10.3	Modulation capability
3.9.4	4.10.5	Audio response
3.9.7	4.10.8	Carrier noise level

4.7.2 Moisture-resistance test (see 3.5.3).- The equipment shall be tested as follows:

4.7.2.1 Test conditions.-

(a) Do not move equipment from the humidity chamber for measurements.

(b) Start measurements not more than 5 minutes after power is applied to the equipment. Complete measurements as rapidly as possible. Do not leave power on after measurements have been completed.

(c) Test sealed equipment with the seal broken or with the chassis removed from its enclosure.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the currentversion before use.

4.7.2.2 Test method.-

(a) Dry at 130° ±5°F for 24 hours.

(b) Condition at 77° ±5°F and 40 to 50 percent relative humidity for 24 hours.

(c) Take measurements as specified in 4.7.2.3, and readjust or realine as necessary to meet full specification requirements.

(d) Subject to continuous cycling for five 48-hour cycles. Temperature, relative humidity, and period of time for each portion of the cycle shall conform to Standard MIL-STD-170. The measurements specified in 4.7.2.3 shall be made during the periods shown on the standard and shall comply with 4.7.2.3.

(e) After cycling has been completed, condition the equipment for 24 hours at 77° ±5°F and 40 to 60 percent relative humidity. Then adjust for optimum performance using only those means provided by the equipment. No repair or replacement of parts shall be made. After adjustment, the equipment shall meet specified performance for those measurements specified in 4.7.2.3.

4.7.2.3 Performance.- There shall be no mechanical deterioration, as evidenced by corrosion of metal parts or binding of rotating or sliding parts, and there shall be not more than 25 percent degradation in performance from that obtained prior to the five humidity cycles. The following measurements shall be made:

Test par	Measurement
4.8.3	Channel changing time
4.8.4	Resettability
4.9.2	Sensitivity
4.9.3	Squelch
4.9.6	Selectivity
4.9.13	Audio output
4.9.15	Audio response characteristics
4.9.16	Audio response characteristics, extended range
4.9.17	Audio distortion
4.9.20	Signal-plus-noise to noise ratio
4.10.2	Transmitter rf power output
4.10.3	Modulation capability
4.10.5	Audio response
4.10.8	Carrier noise level

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the currentversion before use.

4.7.2.4 Failure.- If any component fails to meet the performance specified in 4.7.2.3 during cycling, it shall be realigned or readjusted once. If the component then fails to meet 4.7.2.3, or fails subsequently during cycling, it does not pass the test. In addition, if the equipment fails to meet specification requirements after conditioning and adjustment, as specified in 4.7.2.2(e), it does not pass the test.

4.7.3 Elevation test (see 3.5.4).- The equipment, placed in its normal operating position in an altitude chamber, shall be tested as follows: (Note: To check temperature stabilization, place a thermocouple on the largest internal mass centrally located within the equipment.)

(a) With the equipment placed in the chamber, operating, and stabilized at room temperature, take the following measurements:

Paragraph	Measurement
4.9.2	Sensitivity
4.10.2	Transmitter rf power output
4.16.1	Operational tests

(b) Reduce the barometric pressure to 13.8 ±0.1 inches of mercury (simulated 18,000 feet above sea level) and, after temperature and pressure stabilization for 2 hours, repeat the measurements specified in 4.7.3(a). The equipment shall meet specified performance for those measurements.

(c) Remove the power from the equipment and further reduce the barometric pressure to 11.0 ±0.1 inches of mercury (simulated 25,000 feet above sea level). Maintain this condition for 2 hours.

(d) Return the chamber to 29.9 ±0.1 inches of mercury. Apply power to the equipment and, after stabilization, repeat the measurements specified in 4.7.3(a). The equipment shall meet specified performance for these measurements.

4.7.4 Orientation test (see 3.5.5(a)).- The equipment shall be inclined for a minimum of 5 minutes in each plane (forward, backward, left, and right) to an angle of 20^{+3}_{-1} degrees. During inclination in each plane, the equipment shall meet specified performance for the following measurements:

Paragraph	Measurement
4.9.2	Sensitivity
4.10.2	Transmitter rf power output

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

4.7.5 Sand and dust test (see 3.5.6).- The equipment shall be tested as follows:

(a) Place the equipment, in its normal operating position, in the test chamber. Raise and maintain the sand and dust density at 0.1 to 0.5 gram per cubic foot within the test space. The relative humidity shall not exceed 30 percent at any time during the test.

(b) The sand and dust shall be of angular structure and shall have a particle size such that the particles can pass through screens as follows:

Screen, U. S. Standard Sieve Series	Percent
100-mesh	100
140-mesh	98 ± 2
200-mesh	90 ± 2
325-mesh	75 ± 2

(c) Chemical analysis of the sand and dust shall be as follows:

Substance	Percent by weight
SiO_2	97 to 99
Fe_2O_3	0 to 2
Al_2O_3	0 to 1
TiO_2	0 to 2
MgO	0 to 1
Ignition losses	0 to 2

(d) Maintain internal temperature of test chamber at 77° ± 4°F for a period of 6 hours, with sand and dust velocity through the test chamber between 100 and 500 feet per minute.

(e) After 6 hours at above conditions, raise the temperature to 160° ± 4°F and maintain it at this value for 6 hours.

(f) Remove equipment from test chamber and allow it to cool to room temperature. The equipment shall meet specified performance for the following measurements:

Paragraph	Measurement
4.9.2	Sensitivity
4.10.2	Transmitter rf power output

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

4.7.5 Sand and dust test. - (Contd)

(g) Open the equipment. There shall be no evidence of deterioration of either external or internal parts.

4.7.6 Test for internal vibration. - Internal vibration of the equipment shall be measured as follows, to determine conformance to 3.5.8:

(a) Secure the equipment (shock mounts removed or blocked) directly to a vibration table that can be controlled within 10 percent of the specified amplitude. Mounting method shall be such that vibration within the equipment can be observed and measured. To facilitate this observation and measurement, subassemblies may be tested separately provided they are secured to the table in a manner similar to that used to mount them in the equipment.

(b) Vibrate the equipment successively in three mutually perpendicular directions over a frequency range of 10 to 55 cps. The total excursion of the applied vibration shall be not less than 0.030 inch.

(c) In each of the three directions, change the frequency in steps of one cps and maintain each frequency for at least 10 seconds.

(d) Measure vibration amplitudes by optical means, or by other means provided that vibration of the part is not affected by the measurement.

4.7.7 Test for equipment vibration. - The receiver-transmitter, in its case, shall be tested as follows, to determine conformance to 3.5.9:

(a) Secure the equipment on its shock mounts (Mounting MT-2297( )/TRC-68), to a vibration table that can be controlled within 10 percent of the specified amplitude. The equipment shall be mounted in its normal operating position with connections (such as cable assemblies) in place.

(b) Vibrate the complete equipment assembly, successively, in three mutually perpendicular directions, over a frequency range of 10 to 55 cps. The total excursion of the applied vibration shall be 0.030 inch; however, this may be reduced, if necessary, to prevent excessive excursion at or near resonance provided that the excursion can still be measured.

(c) In each of the three directions, change the frequency in steps of one cps and maintain each frequency for at least 10 seconds.

(d) Measure amplitude of the applied vibration and the vibration of the equipment, for frequencies between 10 and 25 and between 35 and 55 cps.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

4.7.7 Test for equipment vibration.- (Contd)

(e) Determine the natural frequency of the equipment; the frequency at which the ratio of the equipment vibration to the applied vibration is greatest shall be considered the natural frequency.

4.7.8 Bounce test (see 3.5. 10).- The equipment shall be tested on the package tester, type 1000-SC, as made by the L. A. B. Corporation, Skaneateles, New York, or equal. Accessories shall be selected from those listed on Drawing SC-A-46439. The test shall be as follows:

(a) Secure the equipment to the 48- by 48-inch vehicular adapter plate in the same manner as it would be mounted in a vehicle. The adapter plate shall be free of cracks and broken welds, and all unused holes except the 2-inch breather holes shall be plugged. All parts of the mounted surface shall be less than 7 inches from the edge of the adapter plate.

(b) Cover the tester bed with a panel of 1/2-inch plywood, with the top grain parallel to the drive chain. Space sixpenny nails, with the heads below the surface, at 6-inch intervals around all four edges and at 3-inch intervals in a 6-inch square in the center.

(c) Place the adapter plate on the bed of the package tester. Limit the lateral motion, by wooden fences, to not more than 3 inches and not less than 1 inch. Additional barriers may be used to safeguard personnel, provided that the fore-and-aft motion of the adapter plate against the backstop is not restrained.

(d) Operate the package tester, shafts in phase, for a total of 3 hours at 283 ± 1 revolutions per minute. Turn the adapter plate 90 degrees at the end of each 45 minutes, each time in the same direction. Rest periods may be provided to permit cooling of the resilient mounts, provided that the testing time is not less than 3 hours.

4.7.9 Shock test; bench-handling (see 3.5. 10).- The chassis-and-front-panel assembly shall be removed from its enclosure, as for servicing, and placed in a suitable position for servicing on a solid, 2-inch fir bench top. The test shall ber performed as follows, in a manner simulating shocks liable to occur during servicing:

(a) Tilt up the assembly through an angle of 30 degrees, using one edge of the assembly as an axis, and permit the assembly to drop back freely to the horizontal. Repeat, using other practicable edges of the same horizontal face as axes, for a total of four drops.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

4.7.9 Shock test; bench-handling (see 3.5.10). - (Contd)

(b) Repeat "(a)", with the assembly resting on other faces, until it has been dropped for a total of four times on each face on which the assembly might practically be placed during servicing.

4.7.10 Shock test; ballistic (see 3.5.10). - The test shall be conducted on the "Shock Testing Machine for Light Weight Equipment" shown in Specification MIL-S-901. The equipment, including shock mounts (if any), shall be secured in its normal operating position to the steel test plate by means of the same fasteners used for vehicular installation of the equipment. The test shall consist of a total of 9 blows: one each 1-foot blow, 3-foot blow, and 5-foot blow on the back, side, and top of the test plate. As an alternative to reorienting the test plate for the blows on the side of the plate, equivalent rotations of the equipment under test is permissible.

4.7.11 Immersion test (see 3.5.11). - The equipment, as prepared for field transportation, shall be immersed to a minimum depth of 3 feet of fresh water for 2 hours. Immediately prior to immersion, the temperature of the equipment shall be 40° F, or more, above the temperature of the water. The tank in which the equipment is immersed shall be of sufficient capacity to maintain the water within ± 2°F of its initial temperature, or the temperature of the water shall be maintained within those limits by other means. After completion of the 2-hour period of immersion, the equipment shall be removed from the water and wiped dry on exterior surfaces. When the equipment is opened, there shall be no evidence of leakage.

4.7.12 Tumbling test (Case CY-2713( )/TRC-68 only). - This test shall be made as specified in the "Tumbling" paragraph of Section 4 of Specification MIL-T-4150. (See 3.5.

4.8 Electrical tests, receiver-transmitter (See 3.7). -

4.8.1 Frequency stability tests (see 3.7.2). -

4.8.1.1 Frequency stability vs supply voltage, test. - With the standard input potenti of 115 (or 230)v, ac, and after a 30-minute receiver warm-up period, a portion of the rf power output of the transmitter shall be fed to a transfer oscillator, such as the Hewlett Packard Company 540A, or equal. The frequency of the output voltage of the transfer oscillator shall then be determined by a frequency counter and shall be the reference frequency. The input potential shall then be decreased to 103 (or 207) v and after a five minute period the frequency shall again be recorded. The measurement shall be repeated for an input potential of 127 (or 253) v. The test frequency shall be 399.9 mc. The transmitter shall be turned on one minute prior to measurement. Any transmitter frequency chang shall be within the limits specified in 3.7.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

4.8.1.2 Frequency stability vs temperature and time test.- With the same test set up as in 4.8.1.1, the equipment shall be temperature stabilized at room temperature with the power off. The unit shall then be turned on and the output frequency of the unmodulated transmitter carrier recorded after a one minute warm-up period. Thereafter, the output frequency shall be measured at 5-minute intervals for the first 15 minutes, and at 15-minute intervals thereafter until two hours have elapsed. The procedure and measurements shall be repeated at the following temperatures: -65°F, -40°F, room ambient, + 100°F, and +150°F. The test frequency shall be 399.9 mc. The transmitter shall be turned on for one minute before making the measurement. The frequency error shall be within the limits specified in 3.7.2.2.

4.8.2 Warm-up test.- With the test set up as under "Transmitter rf power output" (4.10.2), the unmodulated rf power output shall be recorded after 60 seconds operation. The equipment shall then be turned off for 30 minutes and the sensitivity recorded as under "Sensitivity" (4.9.2) after 60 seconds operation. The test frequency shall be 399.9 mc. Power output and receiver sensitivity shall be within the limits specified in 3.7.3.

4.8.3 Channel changing time test.- Channels 1 and 2 shall be set to 229.9 and 229.8 mc respectively. The time required to change from channel 2 to channel 1 shall be noted at room temperature and at -65°F. The time shall be within the limits specified in 3.7.4.

4.8.4 Resettability test.- With the standard test conditions (4.9.1 and 4.10.1) prevailing, the rf power output and receiver sensitivity shall be recorded for a total of 4 alternate channel selections approached from both higher and lower frequencies. The test frequencies shall be 389.9, 300.0, and 235.0 mc. Receiver sensitivity, transmitter rf power output, and frequency error shall be within the limits specified in 3.7.5.

4.8.5 Transmit - receive interval test.- A standard rf load and a standard test voltage (4.10.1) equivalent to 6 uv shall be fed into the antenna input through a "T" attenuator network. The headset audio output shall be applied to the vertical input of a long-persistence oscilloscope having a slow sweep. The oscilloscope shall be triggered with a pulse from the keying circuit and the time interval measured by noting the time required for the pattern changes. The requirement of 3.7.6 shall be met.

4.8.6 Panel meter test.- The radio set shall be operated as stated under standard receiver and transmitter test conditions (4.9.1 and 4.10.1). The transmitter shall have a nominal output of 16 w and be terminated as indicated. Meter readings shall comply with the limits specified in 3.7.7.

4.8.7 Power drain test.- With the radio set operating at the standard test conditions specified in 4.9.1 and 4.10.1, except that the transmitter shall be unmodulated, the requirements of 3.7.8 shall not be exceeded.

4.8.8 Operating input potential tests (see 3.7.9):-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

4.8.8.1 Operation with 103 (or 207) v, ac, input test.- The equipment shall be operated with an input of 103 (or 207) v, ac, and tested for compliance with the low operating input potential requirements of the following tests:

Test	Req para	Insp para
Sensitivity	3.8.1	4.9.2
Squelch	3.8.2	4.9.3
Audio output	3.8.12	4.9.13
Transmitter rf output	3.9.1	4.10.2

4.8.8.2 Operation with 127 (or 253) v, ac, input test.- The equipment shall be operated with an input of 127 (or 253) v, ac, and tested for compliance with the high operating input potential requirements of the following tests:

Test	Req para	Insp para
*Frequency stability vs supply voltage	3.7.2.1	4.8.1.1
Squelch	3.8.2	4.9.3

*This test shall be performed only during the test procedures of 4.8.1.1.

4.9 Electrical tests, receiver (see 3.8).-

4.9.1 Standard test conditions.- All measurements shall be made in a well shielded test area, free of interference, under the conditions specified in 4.9.1.1, 4.9.1.2, and 4.9.1.3.

4.9.1.1 Test conditions.-

Temperature	Normal room ambient
Humidity	Normal room ambient
Primary input power	115 or 230 v, ac at 50 to 60 cps, nominal
Warm-up period	5 minutes
Audio load impedance	600 ohms, non-inductive
Test signal modulation	30 percent am at 1,000 cps
RF cable	10 feet of Radio Frequency Cable RG-8( )/U, or equal
Standard audio test signal	0.2 v, rms. 1,000 cps (open circuit)

4.9.1.2 Control settings.-

CHAN SEL	At desired test frequency
SQUELCH	OFF
VOLUME	As required
METER	S-METER
Power	On
Internal volume control	Adjust for 1-w loudspeaker output with standard test voltage of 100 uv, and panel VOLUME control maximum.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the current version before use.

4.9.1.3 Standard test voltage.- For the receive condition, the term "standard test voltage" is defined as an rf carrier, 30-percent amplitude modulated at 1,000 cps, fed to a 50-ohm, 6-db resistive pad in series with the signal source and the receiver.

4.9.2 Sensitivity test.- A standard test voltage shall be applied to the receiver input. The audio power shall be measured at the loudspeaker output, terminated in 600 ohms. The input level and VOLUME control shall be adjusted until the ratio of the audio output power with the standard test voltage to the audio output power with the unmodulated standard test voltage is 10 db and the former power is 250 mw. The requirements of 3.8.1 shall be met. Test frequencies for sensitivity measurements shall be:

*399.9 mc	*300.0
388.8	299.9
377.7	288.8
366.6	277.7
355.5	266.6
344.4	255.5
333.3	244.4
322.2	233.3
311.1	*225.0

*These frequencies to be used for the 103 (or 207) v, ac low input potential measurements.

4.9.3 Squelch test.- With the standard test conditions prevailing and the standard test voltage turned off, the receiver shall be set to 399.9 mcs. The squelch sensitivity control shall be set to the maximum sensitivity position (threshold). The signal level required to deactivate the squelch as indicated by the operation of the squelch light shall be recorded. The measurement shall be repeated for the test frequencies specified under "sensitivity". The squelch sensitivity control shall then be adjusted for minimum sensitivity and the signal level recorded for deactivation of the squelch circuit. The measurement shall be repeated for the above test frequencies. With the receiver set to 399.9 mc and the squelch control adjusted to open on 6 uv the signal-plus-noise-to-noise ratio shall be recorded as measured at the loudspeaker output. The squelch control shall then be set to OFF and the signal-plus-noise to noise again recorded. All of the above tests shall be repeated for input potentials of 103 (or 207) and 127 (or 253) v, ac, at 225.0, 310.0, and 399.9 mc. The requirements of 3.8.2 shall be met.

4.9.4 AGC characteristics test.- The VOLUME control shall be set to produce 250 mw power output at the loudspeaker output circuit terminated in 600 ohms, with a standard test voltage input of 100 uv. Power output shall be recorded as reference at this level. The signal input shall then be varied from 6 uv to 0.5 v and the power output noted. The ratio of the power output at the various input levels to the reference output in db shall be taken as the agc characteristic. Test frequencies shall be 399.9, 310.0, and 225.0 mc. The requirements of 3.8.3 shall be met.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the current version before use.

4.9.5 AGC time constant test.- With a standard test voltage of 10,000 uv applied to the receiver, and the agc voltage applied to the vertical plates of a long persistence oscilloscope having a slow sweep and a dc amplifier, the reference level shall be noted. The signal shall then be disconnected and the discharge time measured. The charge time shall be measured by reconnecting the standard test voltage and recording the rise time on the oscilloscope. The test frequency shall be 399.9 mc. The requirements of 3.8.4 shall be met.

4.9.6 Selectivity test.- An unmodulated 3.5-mc signal shall be coupled to the input grid of the second receive mixer. The input level shall be adjusted to produce a reference agc voltage of -1 v. Increase the signal level 6 db and record the frequencies above and below resonance which will restore the voltage to the reference level, noticing irregularities in the response curve while changing frequencies. The above shall be repeated with the signal level at 20, 40, and 60 db up. The difference in half-bandwidth shall be taken as the numerical difference between the deviations from resonance divided by the average of the deviations at any specified attenuation point. The requirements of 3.8.5 shall be met.

4.9.7 IF rejection test.- With an unmodulated standard test voltage of 10 uv at nominal frequency, record the agc voltage as a reference. Increase the signal level at the specified i. f. frequencies until the referenced agc voltage is restored. The ratio between the nominal and i.f. frequency signal levels shall be recorded as the rejection ratio. The test frequencies shall be:

Nominal frequencies, mc	IF frequencies, mc
399.9	3.9
	29.9
230.0	3.0
	20.0

The requirements of 3.8.6 shall be met.

4.9.8 Image rejection test.- The test procedure shall be identical to that for i.f. rejection. The test frequencies shall be:

Nominal frequencies, mc	Image frequencies, mc
399.9	340.1
310.0	270.0
225.0	175.0

The requirements of 3.8.7 shall be met.

4.9.9 Spurious response test.- With a 10 uv standard test voltage applied to the receiver at the nominal frequency, a reference agc voltage shall be recorded and the speaker output monitored at any convenient level. The signal level shall then be increased by 60 db and the frequency varied from 10 to 420 mc, not including the frequencies from 100 kc below to 100 kc above the nominal frequency. The minimum signal input at any other frequency necessary to produce the reference agc voltage shall be recorded. The ratio of the input of the nominal operating frequency to the input at any other frequency shall be taken as the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

4.9.9 Spurious response test.-(Contd)

spurious rejection ratio. Tests shall be conducted at 390.0, 355.5, and 230.0 mc. The requirements of 3.8.8 shall be met.

4.9.10 Internal signals test.- With a standard test voltage of 6 uv applied to the input of the receiver, the audio output shall be monitored by a loudspeaker connected across the loudspeaker terminals. The headset audio output circuit shall be terminated with an audio power output meter. A search shall be made on all channels for quieting and beat notes and the channel frequency recorded. Whenever interference is noted the signal level shall be increased to 12 uv and the signal-plus-noise to noise ratio recorded. The requirements of 3.8.9 shall be met.

4.9.11 Cross modulation test.- A standard test voltage of 6 uv at the test frequency shall be applied to the receiver input. The VOLUME control shall be set to produce a reference power output of 500 mw as measured at the loudspeaker output circuit. The modulation of the 6-uv test frequency shall then be removed. A standard test of 200, 000 uv from another source shall be injected 1.3 percent above the desired frequency. The signal-plus-noise to noise ratio shall then be recorded. The test shall be repeated at a frequency 1.3 percent below the desired frequency. The test frequencies shall be 395.0, 312. 4, and 230.0 mc; in case a spurious frequency is encountered, the undesired signal shall be moved to the nearest useable channel. The requirements of 3.8.10 shall be met.

4.9.12 Desensitization test.- A standard test voltage of 6-uv at the test frequency shall be applied to the receiver input. The VOLUME control shall be set to produce a reference power output of 500 mw as measured at the loudspeaker output circuit. An unmodulated test voltage of 200,000 uv from another source shall be injected into the receiver input; this signal to be 1.3 percent above the desired frequency. The audio output and signal-plus-noise to noise ratios shall then be recorded. The test shall be repeated at a frequency 1.3 percent below the desired frequency. The test frequencies shall be 395.0, 312.4, and 230.0 mc. In case a spurious frequency is encountered, the undesired signal shall be moved to the nearest useable channel. The requirements of 3.8.11 shall be met.

4.9.13 Audio output test.- A 3.5-mc signal, equivalent to a 100-uv standard test voltage at the receiver input, shall be injected into the third receive mixer circuit. The VOLUME control shall be set to maximum. The power output shall then be measured at the loudspeaker output terminated in 600 ohms. The 600-ohm load shall then be transferred to the headset, remote, fixed level, and extended range output circuits in turn and the power output recorded for each circuit. The requirements of 3.8.12 shall be met.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

4.9.14 Audio level adjustments test.- A standard test voltage of 100 uv shall be applied to the receiver input. The loudspeaker output shall be terminated in 600 ohms. The power output shall be measured for maximum and minimum positions of the VOLUME control. The measurement shall then be repeated with the 600-ohm termination at the headset, extended range, fixed level, and remote outputs. The ratio of maximum to minimum power output shall be taken as the output level adjustment. The requirements of 3.8.13 shall be met.

4.9.15 Audio response characteristics test.- A 3.5-mc signal, equivalent to a standard test voltage of 1,000 uv, shall be injected into the third receive mixer circuit. The VOLUME control shall be adjusted for a reference audio output of 1 w at the loudspeake output terminated with 600 ohms. Without further adjustment of receiver controls, the power output shall be measured at modulation frequencies of 300, 3,000, 5,000, and 10,000 cps. The ratio of the power output at each modulation frequency to 1 w shall be taken as the audio response. The requirements of 3.8.14 shall be met.

4.9.16 Audio response characteristics, extended range test.- A 3.5-mc signal, equivalent to a standard test voltage of 1,000 uv, shall be injected into the third receive mixer circuit. The extended range output shall be terminated with 600 ohms and the reference power output shall be recorded. The power output shall be measured at modulation frequencies of 300, 1,000, 3,000, 5,000, 10,000, 15,000, 20,000 and 25,000 cps. The ratio of the power output at each modulation frequency to the reference output shall be taken as the audio response. The requirements of 3.8.15 shall be met.

4.9.17 Audio distortion test.- A 3.5-mc signal, equivalent to a standard test voltage of 1,000 uv, shall be injected into the third receive mixer circuit. The VOLUME control shall be adjusted for 1 w at the loudspeaker output terminated in 600 ohms. A Distortion Analyzer TS-723B/U, or equal, shall then be connected to the output and the measurement shall be recorded as the total harmonic distortion. Without further adjustment of receiver controls, the measurement shall be repeated individually for the headset, remote, fixed level, and extended range outputs. The requirements of 3.8.16 shall be met.

4.9.18 Noise rejection test.- A 3.5-mc signal, equivalent to a 100 uv standard test voltage at the receiver input, shall be injected into the third receive mixer circuit. An oscilloscope shall be connected across the loudspeaker circuit terminated in 600 ohms. The VOLUME control shall be adjusted for 1 w output. Percentage modulation shall then be adjusted to where clipping just begins to appear on the oscilloscope pattern. The modulation percentage at this point shall be recorded. The requirements of 3.8.17 shall be met.

4.9.19 Blocking test.- With standard test voltages of 1 v and 6 uv fed into the antenna input of the receiver through isolating pad networks, and the agc voltage applied to the vertical plates of a long persistence oscilloscope having a slow sweep and a dc amplifier, the agc reference level shall be noted visually. The 1-v signal shall then be disconnected and the time required for the agc voltage to drop to the 6-uv signal level shall be recorded. The test frequency shall be 399.9 mc. The requirements of 3.8.18 shall be met.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

4.9.20 Maximum signal-plus-noise to noise test.- With a standard test voltage of 10,000 uv applied to the receiver, the VOLUME control shall be adjusted to produce 1 w at the loudspeaker output circuit terminated in 600 ohms. The modulation shall then be removed from the test signal and the power output recorded. The ratio of 1 w to the recorded output shall be taken as the maximum signal-plus-noise to noise ratio. The requirements of 3.8.19 shall be met.

4.10 Electrical tests, transmitter (see 3.9).-

4.10.1 Standard test conditions.- All measurements shall be made in a well shielded test area, under the conditions specified in 4.10.1.1 and 4.10.1.2.

4.10.1.1 Test conditions.-

Temperature	Normal room ambient
Humidity	Normal room ambient
Primary power	115 (or 230) v, ac, at 50 or 60 cps, nominal
Warm-up period	5 minutes
Dummy microphone impedance	150-ohms, non-inductive
Standard audio test signal	0.2 v, rms, 1,000 cps
Loudspeaker output impedance	600 ohms, non-inductive
Dummy antenna load	10 feet of RG-8( )/U terminated in a 50-ohm resistive load such as Bird Electronics 611 wattmeter, or equal.

4.10.1.2 Control settings.-

CHAN SEL	At desired test frequency
SQUELCH	OFF
VOLUME	Maximum
Power	ON
METER	PWR
Internal volume control	Same as for receiver (4.9.1.2)
Internal limiter control	Adjust for 90 percent negative modulation at 399.9 mc with standard test signal
Audio connector	600-ohm loudspeaker output.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

4.10.2 Transmitter rf power output test.- The antenna input jack shall be terminated in the dummy load through a ultra-high-frequency (uhf) low-pass filter. The transmitter shall be keyed and the power output measured on the test frequencies. The requirements of 3.9.1 shall be met. Normal test frequencies for rf power output shall be:

399.9 mc	300.0 mc
388.8 mc	299.9 mc
377.7 mc	288.8 mc
366.6 mc	277.7 mc
355.5 mc	266.6 mc
344.4 mc	255.5 mc
333.3 mc	244.4 mc
322.2 mc	233.3 mc
311.1 mc	225.0 mc

4.10.3 Modulation capability test.- With the standard audio test signal applied to the input, under the standard test conditions, a portion of the transmitter output shall be applied to an oscilloscope and the modulation envelope observed. The percentage of modulation shall be determined by noting the modulation envelope. The test frequencies shall be 399.9, 300.0 and 225.0 mc. The requirements of 3.9.2 shall be met.

4.10.4 Automatic modulation limiter test.- The standard input signal of 0.2 v shall be varied from -6 db to + 20 db. The variation in modulator voltage shall be within the limits specified in 3.9.3.

4.10.5 Audio response test.- The transmitter shall be modulated through the dummy microphone circuit with a 0.1 v input test signal. The transmitter output shall be connected to the dummy antenna load. A portion of the output shall be coupled to a detector circuit and the reference voltage across the detector load recorded. With the amplitude of the test signal held constant, the detector output voltage shall be recorded for signal frequencies of 300, 3,000, 6,000, and 10,000 cps. The ratio of these voltages to the reference voltage in db shall be taken as the response. The test frequency shall be 399.9 mc. The requirements of 3.9.4 shall be met.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the current version before use.

4.10.6 Audio response, extended range test.- With the same test set up as 4.18.5, measurements shall be made at 300, 3,000, 6,000, 10,000, 15,000, and 25,000 cps. The requirements of 3.9.5 shall be met.

4.10.7 Overall distortion test.- With the test set up as under "Audio response", but using a standard input signal, the distortion shall be measured with a distortion analyzer at the detector output. The distortion shall also be measured at signal frequencies of 300, 500, 3,000 and 6,000 cps, using a constant input voltage. Test frequencies shall be 225.0, 310.0, and 399.9 mc. These measurements shall be repeated with the input signal increased by 12 db. The requirements of 3.9.6 shall be met.

4.10.8 Carrier noise level test.- With the test set up as under "Audio response", but using standard audio test input, the voltage across a detector load shall be measured. The modulation shall then be removed and voltage again noted. The ratio of the unmodulated voltage to the modulated voltage in db shall be recorded. The test frequency shall be 399.9 mc. The requirements of 3.9.7 shall be met.

4.10.9 Sidetone test.- With the test setup as under "Modulation capability", the loudspeaker output shall be loaded with 600 ohms and the af power output recorded. The audio load shall then be connected to the headset, remote, and fixed level outputs in turn and the af power outputs recorded. The audio levels, when compared to a received signal of 100 uv, 30-percent modulated at 1,000 cps, shall be within the limits specified in 3.9.8. Test frequency shall be 399.9 mc.

4.10.10 Microphone input impedance test.- The microphone input circuit impedance shall be measured by the resistance substitution method. The requirements of 3.9.9 shall be met.

4.10.11 Spurious radiation test.- The transmitter, housed in a screen room, shall have its output connected to an rf wattmeter through a "T" attenuator, such as a General Radio 874GA, or equal. A portion of the rf output shall be connected from the "T", through a coaxial connector, to a screened and grounded inclosure, containing a suitably calibrated noise meter. With the AN/TRC-68( ) on transmit and the levels properly adjusted, tune the noise meter through its range for each test frequency and note the level and frequency of each spurious radiation. Cross check with an uhf signal generator to determine if the responses are actually emitted from the AN/TRC-68( ) or are generated internally in the noise meter. The uhf generator should be known to have minimum spurious radiation, (such as Hewlett-Packard 608D, or equal) and shall be located in the screened inclosure with the noise meter. Test frequencies shall be 225.0, 300.5, and 399.9 mc. Spurious outputs more than 85 db down need not be recorded. The requirements of 3.9.10 shall be met.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

4.11 Power Supply PP-1494( )/U tests (see 3.10).- For the tests specified in 4.11.1 through 4.11.8, the RT-441( )/TRC-68, or equal, shall be used as a load. Tests shall be made with nominal inputs of 115 and 230 v, ac, at 50 and at 60 cps for each voltage. Input voltages shall be maintained within ± 1 percent of nominal. Test pins referred to are on plug P1801 of the PP-1494( )/U.

4.11.1 Transmit B + power test.- With a current of 380 milliamperes (ma) flowing in the load, the voltage between pin 11 and ground shall be recorded. The requirements of 3.10.1 shall be met.

4.11.2 Low voltage B + power test.- With a current of 150 ma flowing in the load, the voltage between pin 10 and ground shall be recorded. The requirements of 3.10.2 shall be met.

4.11.3 Filament power test (see 3.10.3).- With the RT-441( )/TRC-68 as a load, the potentials shall be measured at the applicable test points specified in 4.11.3.1 through 4.11.3.4.

4.11.3.1 26.4-volt circuit test.- The potential across the tube filament pins shall meet the requirements of 3.10.3.1.

4.11.3.2 18.9-volt circuit test.- The potential across the tube filament pins shall meet the requirements of 3.10.3.2.

4.11.3.3 12.6-volt circuit test.- The potential across the tube filament pins shall meet the requirements of 3.10.3.3.

4.11.3.4 6.3-volt circuit test.- The potential across the tube filament pins shall meet the requirements of 3.10.3.4.

4.11.4 Blower power test.- With the HD-390( )/U as a load, the voltage between pins 16 and 13, and that between pins 14 and 6, shall be recorded. The requirements of 3.10.4 shall be met.

4.11.5 Receiver B + power test.- With 100 ma flowing in the load, the voltage between pin 9 and ground shall be recorded. The requirements of 3.10.5 shall be met.

4.11.6 Relay power test.- With a steady current of 1.22 amperes (a) flowing in the load, the load shall be switched to allow a current of 4 a for 2 seconds and then 6 a for 4 seconds, and afterwards returned to 1.22 a. This cycle shall be repeated five times. The minimum and maximum potentials, between pin 2 and ground noted during the entire test shall be within the limit specified in 3.10.6.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the currentversion before use.

4.11.7 B + transient test.- Connect an oscilloscope probe to pin 11; connect the common lead to ground. With the use of a voltage calibrator (internal to the oscilloscope or external) measure the amplitude of the transient developed as the RT-441( )/TRC-68 is switched from transmit to receive. The requirements of 3.10.7 shall be met.

4.11.8 No-load condition test.- With the nominal input voltage, the unloaded outputs between pin 11 and ground, and between pins 10 and 12, shall meet the requirements of 3.10.8.

4.12 Case, Receiver-Transmitter CY-2712( )/TRC-68 tests (see 3.11).- A check for proper circuit continuity shall be made. The injecting-ejecting mechanism shall be checked for proper operation.

4.13 Fan, Centrifugal HD-390( )/U tests (see 3.12).- Connect the fan to an input of 103 volts, ac, at 50 cps. Check the fan for proper operation. Repeat at 127 volts, ac; then at both voltages at 60 cps. Check fan motor construction against the requirements of Specification MIL-M-13787.

4.14 500-hour test.- The requirements of 3.5.1 shall be met.

4.14.1 Continuous transmitter operation test.- The transmitter shall be operated continuously for a 1-hour period. The rf power output shall be measured at the start and end of the period.

4.14.2 Radio set operating conditions.- After the continuous transmitter operation test (4.14.1), the radio set shall be operated for 500 hours under the following conditions.

Transmit-to-receive time	1 minute transmit to 9 minutes receive.
Input voltage	At 127 v (or 253), 25 percent of the time At 115 v (or 230), 65 percent of the time At 103 v (or 207), 10 percent of the time
Vibration	10 minutes of each hour at 25 ± 5 cps, at 1/32-inch maximum amplitude
Temperature	Between 95° and 113°F
Channel selections	500 each 24 hours of operation, allowing 10 seconds between selections

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the currentversion before use.

4.14.3 Radio set measurements.- The following measurements shall be made daily. Measurements shall be taken so that all tests are recorded under all possible combinations of input voltage and vibration (see 4.14.2) during each 144 hours on test.

Attribute	Reqt para	Insp para
Receiver:		
Sensitivity	3.8.1	4.9.2
Squelch	3.8.2	4.9.3
AGC characteristics	3.8.3	4.9.4
Selectivity	3.8.5	4.9.6
Audio output	3.8.12	4.9.13
Audio response characteristics	3.8.14	4.9.15
Audio distortion	3.8.16	4.9.17
Noise rejection	3.8.17	4.9.18
Signal-plus-noise to noise	3.8.19	4.9.20
Transmitter:		
Transmitter rf power output	3.9.1	4.10.2
Modulation capability	3.9.2	4.10.3
Automatic modulation limiter	3.9.3	4.10.4
Audio response	3.9.4	4.10.5
Overall distortion	3.9.6	4.10.7
Carrier noise level	3.9.7	4.10.8
Sidetone	3.9.8	4.10.9

4.15 Air-seal test (cases only). The equipment shall be opened and closed again in such manner as to break and remake the seal. Immediately thereafter, the equipment as field transported shall be subjected to a vacuum of 1 psig (1 pound per square inch less than the atmospheric pressure surrounding the equipment) applied to the interior of the equipment inclosure. The vacuum then shall be valved-off and the interior pressure measured during the ensuing period of 1 minute. The gage used for measurement of the vacuum shall be of such accuracy that a difference of 0.01 pound can be determined readily. The requirement of 3.15 shall be met.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the current version before use.

4.16 System tests (see 3.16).- The following system tests shall be performed:

4.16.1 Operational tests (see 3.17).- A radio communication circuit consisting of two each Radio Sets AN/TRC-68( ) separated by approximately 50 feet shall be set up. Operational tests of the following shall be made from both the radio set and from Control, Radio Set, C-1439( )/U.

(a) Push-to talk operation.

(b) Squelch tests including threshold adjustment, squelch disable, and squelch light operation.

(c) Power on-off control.

(d) Channel selection.

(e) Audio level adjustment..

(f) Case blower operation.

4.16.2 Remote tests.- Push-to-talk operation through Control Group AN/GRA-6( ) plugged into the audio connector of either the RT-441( )/TRC-69 or the C-1439( )/U.

4.16.3 Retransmission tests.- This is a squelch controlled, 2-way retransmission test with a circuit similar to Radio Set AN/GRC-5( ) but using Radio Set AN/TRC-68( ) in place of Receiver-Transmitter, Radio RT-70( )/GRC. No evidence of audio regeneration or other interaction shall be noted when tested at the following frequencies:

RT-441( )/TRC-68	RT-67( )/GRC
225.1 mc	27.5 mc
241.7 mc	27.9 mc
265.9 mc	30.4 mc
281.4 mc	32.3 mc
305.6 mc	33.0 mc
343.2 mc	38.5 mc

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the current version before use.

4.16.4 Audio and control tests.- With the same set-up as for retransmission, the following tests shall be made from Control, Radio Set C-1439( )/U:

(a) Loudspeaker output adjustable from SPEAKER VOLUME control.

(b) Headset output adjustable from PHONE VOLUME control.

(c) RAD-INT (radio-interphone) position:

1. AN/TRC-68( ) and AN/GRC-5( ) interphone audio output.

2. AN/TRC-68( ) radio transmission with handset.

3. AN/TRC-68( ) radio transmission with chest set in RADIO position.

4. AN/GRC-5( ) interphone operation with chest set in INTERPHONE position.

(d) INT (interphone) position:

1. AN/TRC-68( ) and AN/GRC-5( ) interphone audio output.

2. AN/GRC-5( ) interphone operation with handset.

3. AN/GRC-5( ) interphone operation with chest set in either RADIO or INTERPHONE position.

(e) RAD (radio) position:

1. AN/TRC-68( ) audio output (remote high level).

2. AN/TRC-68( ) radio transmission with handset.

3. AN/TRC-68( ) radio transmission with chest set in RADIO position.

4.17 Inspection for interchangeability.- The points listed in 4.17.1, 4.17.2, and 4.17.3 shall be gaged or measured to determine compliance with the physical interchangeability requirements of 3.4.17. When a listed dimension is not within specified or design limits, it shall be considered a major defect. Gage List SC-GL-57713 covers the AN/TRC-68( ).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:13Z
Check the source to verify that this is the current version before use.

4.17.1 Receiver-Transmitter, Radio RT-441( )/TRC-68.- The following gage points shall meet the requirements of the drawings on Gage List SC-GL-57714:

(a) The maximum length, width, and depth of the chassis.

(b) The location of the power plug at the rear of the chassis and the two guide pins at the bottom of the front panel.

(c) The maximum outside dimensions of the front panel.

(d) The location of two locking bars at the bottom of the front panel (these receive locking devices on the mounting).

(e) The location of four mounting screws on the front panel.

(f) The location of the center-mounted locking device.

(g) The minimum dimensions of the spring on the outside of the chassis.

4.17.2 Case, Receiver-Transmitter CY-2712( )/TRC-68.- The following gage points shall meet the requirements of the drawings on Gage List SC-GL-57711:

(a) Power supply compartment:

(1) Minimum inside dimensions.

(2) Location of power receptacle.

(3) Location of 2 guide pins in rear.

(4) Location of 4 mounting holes.

(5) Location of mounting device.

(b) Receiver-transmitter compartment:

(1) Minimum inside dimension.

(2) Location of receptacle.

(3) Location of 2 guide pin holes in rear.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:13Z
Check the source to verify that this is the currentversion before use.

4.17.2 Case, Receiver-Transmitter CY-2712( )/TRC-68.- (Contd)

(b) (4) Location of 4 mounting holes.

(5) Location of mounting device.

4.17.3 Power Supply PP-1494( )/U.- The following gage points shall meet the requirements of the drawings on Gage List SC-GL-57710:

(a) Chassis width and length.

(b) Location of power receptacle.

(c) Location of the 2 guide pins at the rear.

(d) Location of the 4 mounting holes.

(e) Location of the mounting device on the front panel.

4.18 Visual and mechanical inspection.- Parts and equipment shall be examined for the defects listed in Standard MIL-STD-252.

4.19 Acceptance inspection of preparation for delivery.- Acceptance inspection of preparation for delivery shall be in accordance with the applicable provisions of Drawing SC-A-362100.

4.20 Rough handling test (preparation for delivery).- When a rough handling test in accordance with Specification MIL-P-116 is required by the contract (see 6.2(d)), the following functional test shall be conducted to determine freedom from operational malfunction caused by rough handling:

Operational test (4.16.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with the applicable provisions of Drawing SC-A-362100. (See 6.10.)

6. NOTES

6.1 Intended use.- Radio Set AN/TRC-68( ) is intended to provide radio communication between ground positions and aircraft. It may be used for two-way retransmission of signals with such equipments as Radio Sets AN/GRC-3( ), -4( ), -5( ), -6( ), -7( ), -8( ), AN/VRC-12( ), -13( ), -14( ), and 15( ). The AN/TRC-68 will net with Radio Sets AN/ARC-27( ), -33( ), -34( ), -45( ), -51( ), -55( ), -60( ), AN/GRA-53( ), -54( ), AN/GRC-27( ), and AN/VRC-24( ).

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification and any amendment thereto.

(b) Levels of preservation, packaging, and packing required. Level A, level B, or level C.)

(c) Type required.

(d) If rough handling test or cyclic exposure test is required.

(e) Preproduction inspection:

Detailed requirements covering preproduction pack(s), including inspection to be performed thereon and descriptive details, plans, drawings, etc. (Note: These may be obtained from the Cataloging and Packaging Division, U. S. Army Electronics Materiel Agency, Philadelphia 3, Pennsylvania.)

(f) Marking and shipping of samples.

(g) Place of final inspection.

(h) Technical literature required. (See 3.18.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.- (Contd)

(i) Quantity of running spare parts required. (See 3.18.)

(j) Submission of the statement of treatment referenced in 3.4.10.4 as soon as possible after award of contract. This statement should be submitted to the contracting officer.

6.3 Color (see 3.4.2).- The color chip furnished by the procuring agency will be color chip No. X-24087, and may be obtained upon request to Commanding General, U. S. Army Electronics Materiel Agency, 225 South Eighteenth Street, Philadelphia 3, Pennsylvania, ATTN: SELMA-J4b.

6.4 Definitions.- Interchangeable, substitute, and replacement items are defined in Standard MIL-STD-447.

6.4.1 Equipment divisions.- The terms used herein for equipment divisions conform to Standard MIL-STD-280.

6.4.2 Definitions of inspection terms.- The inspection terms used herein conform to Standard MIL-STD-109. The following are abbreviated definitions selected from those given therein for immediate reference:

6.4.2.1 Inspection.- Inspection is the examination or testing, or both, of supplies to determine compliance with applicable requirements. Sampling is an element of inspection.

6.4.2.2 Examination.- Examination consists of simple, generally nondestructive determinations of compliance, without use of special testing equipment.

6.4.2.3 Testing.- Testing consists of determinations of compliance, using technical means.

6.5 Group C inspection.- Approval to ship may be withheld, at the discretion of the Government, pending the decision from the contracting officer on the adequacy of corrective action. (See 4.5.3.2.)

6.6 Location of air seal and operational inspection.- It is desirable that the air seal test (4.15) and the operational inspection (4.16.1) be performed at a location that will minimize handling (which might cause damage to the equipment) after this inspection is completed. Any preparation for shipment which would require breaking of the equipment seal should be accomplished prior to the air-seal test so that the seal may remain intact thereafter. It is recommended that the entire lot (including all previously inspected sample units) be sampled and inspected immediately prior to packaging.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

6.7 Nomenclature.- The parentheses in the nomenclature will be deleted or replaced by a letter identifying the particular design; for example: AN/TRC-68W. The contractor should apply for nomenclature in accordance with the applicable clause in the contract. (See 1.1.)

6.8 Color of textiles (see 3.4.16).- Standard samples of Olive Drab No. 7 may be obtained from the Sample Loan Unit, Military Clothing and Textile Supply Agency, Philadelphia, Pennsylvania. When requesting samples, indication should be given as to type of material concerned.

6.9 Verification inspection (see 4.5).- Verification by the Government will be limited to the amount deemed necessary to determine compliance with the contract and will be limited in severity to the definitive quality assurance provisions established in this specification and the contract. The amount of verification inspection by the Government will be adjusted to make maximum utilization of the contractor's quality control system and the quality history of the product.

6.10 Dimensional data.- Sizes of packaging materials prescribed in section 5 are based on the dimensions of the equipment cited on the applicable Bill of Material. When the dimensions of the equipment vary from those cited, the sizes of the packaging materials shall be adjusted accordingly. When shown in the Bill of Materials(see section 5), corrugated fiberboard manufactured with A, B, or C fluting may be used at the option of the contractor. When the fluting used is not the same as that cited in the Bill of Material, the dimensions of the affected packaging and packing materials will be adjusted accordingly.

6.10 Humidity.- Natural climatic extremes may include 100-percent relative humidity, with condensation, up to 4 hours at a time. This requirement (see 3.5.3) is specified by Military Standard MIL-STD-210. The moisture-resistance test (see 4.7.2) using Military Standard MIL-STD-170, is a procedure that gives a practical test approximating the natural conditions.

Project 5820-A205

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.