MIL-S-83352B(USAF)
AMENDMENT 3
20 MAY 86
SUPERSEDING
AMENDMENT 2
19 MAY 1977

MILITARY SPECIFICATION

SIGNAL KIT, PERSONNEL, DISTRESS, A/P25S-5A

This amendment forms a part of MIL-S-83352B, dated 11 April 1975, and is approved for use within the OO-ALC/MMEDO, Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Delete section 2 in its entirety and substitute:

"2. APPLICABLE DOCUMENTS.

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specifications to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

L-P-378	Plastic Sheet and Strip, Thin Gauge, Polyolefin
TT-I-548	Ink, Black, for Offset Duplicating Process
PPP-B-601	Boxes, Wood, Crated-Plywood
PPP-B-636	Boxes, Shipping, Fiberboard
PPP-F-320	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes

MILITARY

MIL-P-116	Preservation-Packaging, Methods of
MIL-I-3606	Ink, Printing: Lithographic Offset, with Drier
MIL-C-5040	Cord, Nylon
MIL-A-8625	Anodic Coatings, for Aluminum and Aluminum Alloys

FSC 1370

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-595	Colors

MILITARY

DOD-STD-100	Engineering Drawing Practices
MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of US Military Property
MIL-STD-143	Standards and Specifications, Order of Precedence for the Selection of
MIL-STD-331	Fuze and Fuze Components, Environmental and Performance Test for
MIL-STD-650	Explosive: Sampling, Inspection and Testing
MIL-STD-810	Environmental Test Methods
MIL-STD-882	Systems Safety Program for Systems and Associated Subsystems and Equipment: Requirements of
MIL-STD-889	Dissimilar Metals
MIL-STD-1167	Ammunition Data Cards
MIL-STD-1168	Lot Numbering of Ammunition

2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issue shall be that in effect on the date of the solicitation.

U.S. Department of Commerce

National Bureau of Standards Circular C-429	Photoelectric Tristimulus Colorimetry with Three Filters (R. R. Hunter, 1942)

(Copies of specifications standards and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DoDISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

Journal of the Optical Society of America

The 1931 I. C. I. (International Commission on Illumination) Standard Observer and Coordinate System for Colorimetry (Volume 23, No. 10, 1933)

A Tristimulus Photometer (Volume 41, No. 5, 1951)

(Application for copies should be addressed to the American Institute of Physics, 335 West 45th Street, New York, New York 10017)

American Society for Testing and Materials (ASTM)

Symposium on Color - Specification and Use in Evaluating the Appearance of Materials (1941)

(Application for copies should be addressed to the University Microfilm Inc., 300 North Zeeb Road, Ann Arbor, Michigan 48103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other information services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained."

Add the following note on the bottom center of the first page immediately above the FSC designation. The note shall be boxed for emphasis.

Benefical comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: (OO-ALC/MMEDO, Hill AFB UT 84056-5609) by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter."

PAGE 3

3.2.1 Delete the last line of paragraph and substitute:

"bandoleer and seven signals, red, green or white."

PAGE 4

3.5.3 Renumber to: "3.5.2"

3.5.4 Renumber to: "3.5.3"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

PAGE 5

3.6.3 After the second sentence insert:

"Seven discs (one disc per signal cavity) shall be inserted into the signal cavities or shall be molded in the base of the signal cavities. The discs shall be 0.375 inch from the open end of the signal cavities. The discs shall be 0.484 inch (plus or minus 0.005 inch) in diameter and shall be made of 14-gage (0.0781-inch) sheet steel that conforms to composition 301, condition 1/4 hard or 1/2 hard of MIL-S-5059."

PAGE 7

3.7.3 (d) Delete in its entirety and substitute:

"(d) The apogee of the display when launched vertically, shall be at least 600 feet but not more than 1,600 feet."

PAGE 9

3.9 Delete MIL-STD-100 and substitute:

"DOD-STD-100"

PAGE 10

3.12.1 Delete in its entirety and substitute:

"3.12.1 Marking for signal kit. In addition to the operating instructions shown on figure 4, the following information shall be included on the instruction sheet for the signal kit.

Signal Kit, Personnel, Distress, A/P25S-5A
National Stock Number (NSN)
Lot No. of signal kits in accordance with MIL-STD-1168
or approved marking as specified by the procuring acitivity.
Date of Manufacture (Month and Year)
Manufacturer's Identification and Contract No."

3.12.2 Delete in its entirety and substitute:

"3.12.2 Marking for spare bandoleer assembly. In addition to the operating instructions shown on figure 4, the following information shall be included on the instruction sheet for the spare bandoleer assembly.

Bandoleer Assembly - Signal Flare, (Add Red, Green, or White as appropriate) for use with Signal Kit, Personnel, Distress, A/P25S-5A NSN (as appropriate for red, green, or white)
Lot No. of bandoleers in accordance with MIL-STD-1168
or approved marking as specified by the procuring activity.
Date of Manufacture (Month and Year)
Manufacturer's Identification and Contract No."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

3.12.3 Delete in its entirety and substitute:

"3.12.3 Marking for signal. Each signal shall be marked in permanent ink, with the lot number and the date of manufacture in accordance with MIL-STD-1168, or approved marking with concurrence of procuring agency."

3.12.4 Delete in its entirety and substitute:

"3.12.4 Marking for launcher. Each launcher shall be marked, in accordance with MIL-STD-130, with the manufacturer's identification, the part number, launcher, serial number (if applicable) and the contract number by imprint stamping."

3.12.5 Delete in its entirety and substitute:

"3.12.5 Marking for bandoleer. Each bandoleer shall be marked with the manufacturer's identification."

PAGE 11

4.3.1 Delete 40 degrees and substitute: "45 degrees"

PAGE 20

Table I, footnote 6/, fourth and fifth lines, Delete 40 degrees (all three places) and substitute: "45 degrees"

PAGE 21

4.4.2.1, ninth line, Delete 1.5 percent and substitute: "2.5 percent"

4.4.2.2 At the end of the paragraph insert:

"If any signal or launcher fails any production sampling test that has an acceptance criteria of "Ac 0 Re 1" (See critical defects in table II) or if the apogee of any of the signals deviates more than 45 degrees from veritical (see footnote 7/ of table II), all of the signals and launchers in that lot shall be rejected. Full particulars concerning the falures and action proposed to correct the defect(s) shall be submitted to the procuring acitivity for concurrence and permission to repeat the production test. Any other failure(s) recorded during the course of production sampling tests which exceed the specified acceptance criteria shall require the submission of full particulars concerning the failure(s) and action proposed/taken to correct the defect(s) to the procuring activity for concurrence and permission to repeat the specific test(s) wherein the accpetance criteria was exceeded. The decision whether to allow retesting shall be solely at the discretion of the procuring activity."

PAGE 22

Table II, fifth column, 12th line, Delete 1.5 percent and substitute: "2.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

percent."

Table II, fifth column, 13th line, Delete 2.5 percent and substitute: "4.0 percent."

PAGE 24

Table III, footnote 2/ Delete in its entirety and substitute:

"2/ Nozzle holes should be visually inspected by using a minimum 3-power magnifying glass."

PAGE 25

Table IV, No. 8, under Defects, Delete 40 degrees and substitute: "45 degrees"

Table IV, No. 110, under Defects, Delete and substitute: "Maximum height of display less than 600 feet or more than 1,600 feet."

Table IV, No. 114, under Defects, delete 40 degrees and substitute "45 degrees."

PAGE 32

6.2(b) Delete in its entirety and substitute:

"(b) Specify. Whether signal kit or spare bandoleer assembly is required and specify color (see 1.1, 3.2.2, and 3.11)."

Custodian:
Air Force - 99

Preparing activity:
Air Force - 70

Project No. 1370-F202

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.