INCH-POUND

MIL-PRF-83352C
30 April 1998
SUPERSEDING
MIL-S-83352B
11 April 1975

PERFORMANCE SPECIFICATION

SIGNAL KIT, PERSONNEL, DISTRESS, A/P25S-5A

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for one type of airborne, personnel, distress signal kit, designated A/P25S-5A, and consisting of a hand-fired launcher and a bandoleer assembly containing seven red signals.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are cited in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet the requirements specified in the documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Non-Government publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the applicable issues of the documents that have been adopted by the DoD are those listed in the specific issue of the DoDISS cited in the solicitation. Unless otherwise specified, the documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR QUALITY (ASQ)

ANSI/ASQ Z1.4-1993 - Sampling Procedures And Tables For Inspection By Attributes (DoD-adopted)

(Application for copies should be addressed to American Society for Quality, 611 East Wisconsin Avenue, P.O. Box 3005, Milwaukee, WI 53201-3005, or to the American National Standards Institute, 11 West 42nd Street, New York, NY 10036.)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Airmunitions Division, OO-ALC/LIWCA, 6033 Elm Lane, Hill Air Force Base, UT 84056-5819 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1370

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related or associated specifications or specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.2 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle cost.

3.3 Workmanship. The signal kit, including all parts and equipment, shall be constructed in accordance with commonly accepted industrial workmanship standards. All components of a signal kit shall be functional without sharp edges, burrs, or protrusions.

3.4 Materials. All materials shall be chosen or suitably treated to resist corrosion due to electrolytic decomposition, fungus, salt spray, and any other atmospheric condition that may be encountered during operational use or storage. The use of toxic chemicals, hazardous substances, or ozone depleting chemicals (ODCs) shall be avoided, whenever feasible.

3.5 Interface.

3.5.1 Weight. The weight of the launcher shall not exceed 84 grams. The weight of one signal shall not exceed 20.3 grams.

3.5.2 Size. The signal kit shall fit snugly into a space provided in the survival pack. These dimensions shall be defined by the procuring activity (see 6.2).

3.6 Performance.

3.6.1 Function. The signal kit, when operated at ambient conditions, shall function as follows:

a. A launcher shall require the use of only one hand to fire a signal.

b. The fit of the signal-gripping device of the launcher with a signal shall preclude the signal from falling out of the launcher when the loaded launcher is aimed vertically at the ground.

c. It shall take no more than two attempts to initiate the signal, except when the signal has been subjected to low temperature (see 3.9.1.1), in which case it shall take no more than four attempts.

d. The signal shall not be held captive in the launcher while the rocket motor burns.

e. The signal shall not explode or deflagrate, or the components separate or come apart, within 15 feet of the launcher.

f. Venting of the rocket motor, which results in snuffing out of the propellant system after initial ignition, shall not occur.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

g. The ignition of the candle shall not occur below 400 feet above ground level when fired from a vertically aligned launcher.

h. The minimum burn time and apogee of each display (when fired from a vertically aligned launcher with a wind speed not greater than 10 miles per hour) shall be as specified (see table I). The candle shall burn through apogee and burn out prior to hitting the ground. Non-ignition of the display shall be considered as zero burn time.

i. The apogee of the display shall not deviate more than 30 degrees from vertical, when fired from a vertically aligned launcher with a wind speed not greater than 10 miles per hour.

3.6.2 Burn time, candlepower, and color.

3.6.2.1 Burn time. The candle of the signal shall produce a display that meets the burn time requirements listed in table I.

3.6.2.2 Candlepower. The candle of the signal shall produce a red display that has an average luminous intensity of 26,000 lumen seconds and a minimum candlepower value of 2,500 lumens for the first 7 seconds.

3.6.2.3 Color. The candle of the signal shall produce a red display that has a dominant wavelength of 620 ± 20 millimicrons. The purity of the color of the red display shall be a minimum of 76 percent.

3.6.3 Safety. A signal with no visible sign of damage shall not malfunction in a hazardous manner when operated. A signal with a visible sign of damage shall be safe to handle for disposal.

3.6.4 Penetration. The signal, when fired, shall be able to completely penetrate moderately dense jungle or forest foliage and produce a display.

3.6.5 Jolt. The signal shall withstand at least 1,750 impacts in 3 axially perpendicular orientations consisting of half sine wave pulses having 230g peak acceleration for 2.0 milliseconds and a pulse rate of 35 impacts per minute without burning, exploding, or becoming unsafe to handle. The signal shall not malfunction in a hazardous manner when fired or handled following these impacts.

3.6.6 Jumble. The signal shall withstand repeated random impacts when rotated in a closed box at a speed of 30 ± 2 revolutions per minute (rpm) for a total of 3600 ± 10 revolutions without burning, exploding, or becoming unsafe to handle. The signal shall not malfunction in a hazardous manner when fired or handled following these impacts.

3.6.7 Forty-foot drop. The signal shall withstand a 40-foot drop without burning, exploding, or becoming unsafe to handle. The signal shall not malfunction in a hazardous manner when fired or handled following this drop.

3.6.8 Altitude. The signal shall function as specified (see 3.6.1) after exposure to atmospheric pressure at an altitude of 50,000 feet for 5 minutes.

3.6.9 Water immersion. The signal shall function as specified (see 3.6.1) after being immersed in water for 3 hours.

3.6.10 Firing pin force (launcher). The firing pin force of the launcher shall be sufficient so that the launcher will initiate the signal primer. The firing pin force shall be a minimum of 6 pounds.

3.6.11 Shelf/service life. The signal kit shall be designed for a shelf/service life of 114 months (see 6.3.4).



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

3.7 Item identification. Each signal, launcher, and bandoleer shall be marked for identification (see 6.2).

3.8 Interchangeability. All parts having the same Part or Identifying Number (PIN) within the same lot shall be functionally and dimensionally interchangeable.

3.9 Environmental requirements.

3.9.1 Temperature and humidity. The signal shall function as specified (see 3.9.1.1 and 3.9.1.2) after being subjected to high and low temperature variations (160 to -65°F) for a period of 14 days with at least 95% relative humidity.

3.9.1.1 Low temperature. The launcher shall fire and the signal shall function as specified (see 3.6.1), except for the display burn time and apogee altitude as listed in table I, after the signals and launcher have been conditioned to -65 ± 5°F for 5 hours and immediately fired.

3.9.1.2 High temperature. The launcher shall fire and the signals shall function as specified (see 3.6.1), except for the display burn time and apogee altitude as listed in table I, after the signals and launcher have been conditioned to 160 ± 5°F for 5 hours and immediately fired.

3.9.2 Salt spray (launcher). The launcher shall fire a minimum of 14 signals without requiring maintenance after being exposed to a 5% salt concentration of salt spray for a minimum of 50 hours.

3.9.3 Storage.

3.9.3.1 Extreme high temperature storage. The signal shall withstand storage at a temperature of 200 ± 5°F for a 14-day period without burning, exploding, or becoming unsafe to handle. The signal shall not malfunction in a hazardous manner when function tested at ambient temperature (see 3.6.1) following this storage.

3.9.3.2 High temperature storage. The signal shall function as specified (see 3.6.1), except for the display burn time and apogee altitude as listed in table I, when it has been stored at 160 ± 5°F for 28 days.

3.9.3.3 Low temperature storage. The signal shall function as specified (see 3.6.1), except for the display burn time and apogee altitude as listed in table I, when it has been stored at -65 ± 5°F for 28 days.

3.9.4 Vibration. The signal kit shall withstand a vibration of 10 to 60 Hz, with an amplitude maintained at 0.10 ± 0.01 in. double amplitude up to and including 20 Hz and at 2 ± 0.2g peak for the remaining frequency coverage. The signal kit shall then function as specified (see 3.6.1.)

3.10 Launcher color. The color of the launcher, except for the collet, signal gripping device, firing pin, spring, and actuation knob, shall be black. If aluminum is used for any part of the launcher, it shall be anodized and dyed a lusterless black color.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).

b. Conformance inspection (see 4.3).

4.2 First article inspection. First article inspection shall be performed on signal kits representative of the production units to be supplied by the vendor. The first article tests shall include the tests indicated in table II.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

4.3 Conformance inspection. Conformance inspection shall include the visual examination in 4.6.1 and the sample tests in 4.3.1. Lot size shall be specified by the procuring activity (see 6.2).

4.3.1 Sample tests. The conformance sample plan shall comply with ANSI/ASQ Z1.4-1993 at the inspection level (normal, tightened, or reduced) specified by the procuring agency (see 6.2) and shall include the examinations and tests specified (see table III).

4.4 Test conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in the applicable test method documents or applicable paragraphs in this specification. Suggestions for certain test procedures are provided in section 6.

4.5 Requirements cross-reference matrix. Table IV provides a cross-reference matrix of the section 3 requirements tested or verified in the paragraphs below.

4.6 Tests.

4.6.1 Visual inspection. The signal kit shall be visually examined to determine compliance with section 3 requirements. In particular, this shall include the requirements of 3.2, 3.3, 3.4, 3.6.3, 3.7, and 3.10.

4.6.2 Interface tests.

4.6.2.1 Weight test. The weight of the signal and the launcher shall be checked to determine compliance with the requirement specified (see 3.5.1).

4.6.2.2 Size test. The signal kit shall be inspected to ensure that it fits into a space specified (see 3.5.2.).

4.6.3 Performance tests.

4.6.3.1 Function test. The function of the signal kit shall be determined. Only launchers and flares meeting the safety inspection criteria in 4.6.1 shall be used for this test. The launcher shall be held for firing with only one hand, signal end up in a true vertical position, and a minimum of 12 inches above the head, or the launcher shall be fixed for remote firing in a suitable test fixture.

a. After loading the signal into the launcher, the loaded launcher shall be aimed vertically at the ground to ensure that the signal does not fall out of the launcher.

b. A maximum of two attempts to initiate the signal shall be made, except that a maximum of four attempts shall be made with signals that have been subjected to low temperature (see 3.9.1.1).

c. When the signal is fired, it shall not be held captive in the launcher while the rocket motor burns.

d. When the signal is fired, it shall not explode or deflagrate, and components of the signal shall not separate or come apart within 15 feet of the launcher.

e. The rocket motor shall not vent such that the propellant system is snuffed out after initial ignition.

f. The height at which the candle ignites shall not be below 400 feet above ground level.

g. The burn time of the display shall be in accordance with table I.

h. The apogee altitude of the display shall be in accordance with table I.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

i. The angular deviation from vertical of the signal at apogee shall not exceed 30° with wind conditions of 10 miles per hour or less.

j. The candle shall burn out prior to hitting the ground.

4.6.3.2 Burn time, candlepower, and color tests. Tests for burn time, candlepower, and color shall verify the performance of the candle only and can be accomplished by igniting the candle in a lab environment.

4.6.3.2.1 Burn time test. The burn time of the candle shall be in accordance with table I.

4.6.3.2.2 Candlepower test. The average luminous intensity and minimum candlepower of the candle shall be 26,000 lumen seconds and 2,500 lumens, respectively (see 6.5.1 for a suggested test procedure).

4.6.3.2.3 Color test. The dominant wavelength and the purity of color of the candle shall be 620 ± 20 millimicrons with a purity of 76% (see 6.5.1 for a suggested test procedure).

4.6.3.3 Penetration test. The penetration capability of the signal through a moderately dense jungle or forest foliage shall be demonstrated (see 6.5.2 for a suggested test procedure). After the signal has penetrated a simulated jungle, it shall produce the desired display.

4.6.3.4 Jolt test. The signal shall be subjected to 1,750 impacts in 3 axially perpendicular orientations. These impacts shall consist of half sine wave pulses having 230 ± 34.5g peak acceleration for 2.0 ± 0.2 milliseconds at a pulse rate of 35 impacts/minute. After the jolt test, the signal shall then be tested as specified (see 4.6.3.1.)

4.6.3.5 Jumble test. The signal shall be subjected to random impacts imparted by free-fall inside a rotating, closed, wood (or suitable substitute) material-lined metal box. The lining shall have a minimum thickness of 1/4 inch. The box shall be rotated at a speed of 30 ± 2 rpm for a total of 3600 ± 10 revolutions. After the jumble test, the signal shall then be tested as specified (see 4.6.3.1.)

4.6.3.6 Forty-foot drop test. The signal shall be subjected to a free fall drop onto a steel plate from a height of 40 feet measured from the lowest point of the test item to the plate. The signal shall then be tested as specified (see 4.6.3.1.)

4.6.3.7 Altitude test. The signal shall be subjected to an altitude of 50,000 feet for 5 minutes. The signal shall then be tested as specified (see 4.6.3.1.)

4.6.3.8 Water immersion test. The signal shall be immersed in water to a minimum depth of 11 inches for at least 3 hours at a temperature of 70 ± 10°F. The signal shall then be tested as specified (see 4.6.3.1.)

4.6.3.9 Firing pin force (launcher) test. The launcher shall be actuated by hand, with firing pin fully cocked, and using a test plug to simulate the signal but allowing the measurement and recording of the firing pin force (see 6.5.3).

4.6.3.10 Shelf/service life. Design data shall demonstrate an expected shelf/service life of 114 months.

4.6.4 Interchangeability test. The interchangeability of parts having the same part number within the same lot shall be demonstrated.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

4.6.5 Environmental conditions tests.

4.6.5.1 Temperature and humidity tests. The signals and launchers (quantities of each as determined in accordance with 4.3.1) shall be subjected to one 14-day series of temperature and humidity cycles in which the signals are cycled back and forth between 160 and -65°F with a relative humidity of 95 percent (see 6.5.4 for a suggested test method). At the conclusion of the 14-day temperature and humidity series, 50 percent of the signals and launchers shall be conditioned at 160 ± 5°F for a minimum of 5 hours; the other 50 percent of the signals and launchers shall be conditioned at -65 ± 5°F for a minimum of 5 hours.

4.6.5.1.1 Low temperature test. The signals and launchers that were conditioned in 4.6.5.1 at -65 ± 5°F shall be fired as specified (see 4.6.3.1) within 30 seconds after conditioning. An individual temperature-soaked launcher can be used to fire a maximum of four signals (in close sequence).

4.6.5.1.2 High temperature test. The signals and launchers that were conditioned in 4.6.5.1 at 160 ± 5°F shall be fired as specified (see 4.6.3.1) within 30 seconds after conditioning. An individual temperature-soaked launcher can be used to fire a maximum of four signals (in close sequence).

4.6.5.2 Salt spray (launcher) test. The launcher shall be subjected to salt spray for 50 hours with a minimum salt concentration of 5 percent. After these 50 hours, the launcher shall be rinsed in water and shall then fire a minimum of 14 signals successfully as specified (see 4.6.3.1) without requiring any maintenance.

4.6.5.3 Storage tests.

4.6.5.3.1 Extreme high temperature storage test. The signal shall be subjected to an extreme high temperature test in an enclosed chamber that shall be maintained at 200 ± 5°F for 14 days. At the conclusion of this storage period, the signal shall be tested as specified (see 4.6.3.1.)

4.6.5.3.2 High temperature storage test. The signal shall be subjected to a high temperature storage test at 160 ± 5°F for 28 days. At the conclusion of this storage period, the signal shall then be tested as specified (see 4.6.3.1.)

4.6.5.3.3 Low temperature storage test. The signal shall be subjected to a low temperature storage test at -65 ± 5°F for 28 days. At the conclusion of this storage period, the signal shall then be tested as specified (see.6.3.1.)

4.6.5.4 Vibration tests. The signal kit shall be vibrated at 10 to 60 Hz with an amplitude maintained at 0.10 ± 0.01 in. double amplitude up to and including 20 Hz, and at 2 ± 0.2g peak for the remaining frequency coverage to simulate transportation (see 6.5.5 for a suggested test method). After the completion of the vibration test, the signal shall be immersed in 11 to 13 inches of water for 1 hour. The signal shall then be tested as specified (see 4.6.3.1.)

## 5. PREPARATION FOR DELIVERY

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department or Defense Agency automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature which may be helpful, but is not mandatory.)

6.1 Intended use. The signals covered by this specification are intended to be used by aircrewmen to signal their location as an aid to search and rescue. The signals are intended to penetrate moderately dense jungle foliage and are intended for worldwide application under all anticipated temperature extremes.

6.2 Acquisition requirements. The signals covered by this specification are classified as Common Fireworks, Class C Explosives in accordance with the Code of Federal Regulations 49CFR 171-178. The contract must invoke Special Packaging Instruction (SPI) F00-490-7362. Acquisition documents must specify the following:

a. Title, number, and date of the specification.

b. Issue of the DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.3).

c. If first article is required (see 3.1).

d. The physical dimensions of the survival pack space into which the signal kit fits (see 3.5.2).

e. Item identification instructions (see 3.7).

f. Lot size (see 4.3).

g. Sampling plan inspection level (normal, tightened, or reduced)(see 4.3.1).

h. Packaging requirements (see 5.1).

6.3 Subject term (key word) listing.

Burn time
Candle
Candlepower
Display
Penetration test
Rocket motor
Shelf/service life
Signal

6.4 Suggested test procedures.

6.4.1 Candlepower and color test. A sample of signals is disassembled. The candle of each sample is mounted in a test fixture, positioned vertically with the ignition end up, and the starter composition ignited. The dominant color, purity, and peak and average luminous intensity of the display are determined.

6.4.2 Penetration test. One successful method of simulating a moderately dense jungle or forest foliage is to set up a fixture consisting of three exterior, commercial grade plywood panels spaced 3-1/2 to 3-3/4 inches apart, place this fixture a minimum of 25 feet from the launch site, and fire the signal into the fixture. Each of the three plywood panels should be 4 feet long by 4 feet wide by 1/4 inch thick. The signal is oriented for firing toward the approximate center of the panels in the fixture.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

6.4.3 Firing pin force (launcher). This procedure has been successfully accomplished with a suitable test plug that will simulate the forces required to initiate the primer of the actual signal. With the test plug installed in the launcher and the top of the test plug 1/8 inch from a self-locking force gage (catch gage), the fully cocked firing pin is released, and the reading is recorded. The launcher is actuated by hand.

6.4.4 Temperature and humidity test. This procedure has been successfully accomplished by alternately exposing the signals to temperatures of 160 and -65°F. MIL-STD-331B offers two methods for performing this cycling. In the two-chamber method, items are moved from a cold to a hot chamber and back. The schedule for the two-chamber method is shown in table V. In the single-chamber method, the temperature within the chamber is changed. The schedule for the single-chamber method is shown in table VI. In both cases, note that the schedules call for extended periods at -80 and 160°F.

6.4.5 Vibration test. This procedure has been successfully accomplished using the sweep method and discrete step method. Both methods are discussed in detail in MIL-STD-331B appendix B, paragraph 6.1

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

TABLE I: Burn Time and Apogee Requirements

| Condition Title | Condition Requirement | Display Apogee Minimum & Maximum (feet) | Minimum Burn Time (seconds) |
|---|---|---|---|
| Ambient | None | 600 - 1,600 | 7.0 |
| Low Temperature | -65 ± 5°F | 400 - 1,600 | 4.0 |
| High Temperature | 160 ± 5°F | 600 - 1,600 | 4.0 |
| High Temp Storage | After storage at 160 ± 5°F for a minimum of 28 days | 600 - 1,600 | 4.0 |
| Low Temp Storage | After storage at -65 ± 5°F for a minimum of 28 days | 400 - 1,600 | 4.0 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

TABLE II: First Article Tests

| Test Paragraph | Requirement | Requirement Paragraph |
|---|---|---|
| 4.6.1 | Workmanship | 3.3 |
| 4.6.1 | Materials | 3.4 |
| 4.6.1 | Safety | 3.6.3 |
| 4.6.1 | Item identification | 3.7 |
| 4.6.1 | Launcher color | 3.10 |
| 4.6.1 | Interchangeability | 3.8 |
| 4.6.2.1 | Weight | 3.5.1 |
| 4.6.2.2 | Size | 3.5.2 |
| 4.6.3.1 | Function | 3.6.1 |
| 4.6.3.2.1 | Burn time | 3.6.2.1 |
| 4.6.3.2.2 | Candlepower | 3.6.2.2 |
| 4.6.3.2.3 | Color | 3.6.2.3 |
| 4.6.3.3 | Penetration | 3.6.4 |
| 4.6.3.4 | Jolt | 3.6.5 |
| 4.6.1 | Safety | 3.6.3 |
| 4.6.3.1 | Function | 3.6.1 |
| 4.6.3.5 | Jumble | 3.6.6 |
| 4.6.1 | Safety | 3.6.3 |
| 4.6.3.1 | Function | 3.6.1 |
| 4.6.3.6 | Forty-foot drop | 3.6.7 |
| 4.6.1 | Safety | 3.6.3 |
| 4.6.3.1 | Function | 3.6.1 |
| 4.6.3.7 | Altitude | 3.6.8 |
| 4.6.3.1 | Function | 3.6.1 |
| 4.6.3.8 | Water immersion | 3.6.9 |
| 4.6.3.1 | Function | 3.6.1 |
| 4.6.3.9 | Firing pin force (launcher) | 3.6.10 |
| 4.6.4 | Interchangeability | 3.8 |
| 4.6.5.1 | Temperature and humidity | 3.9.1 |
| 4.6.5.1.1 | Low temperature | 3.9.1.1 |
| 4.6.3.1 | Function | 3.6.1 |
| 4.6.5.1.2 | High temperature | 3.9.1.2 |
| 4.6.3.1 | Function | 3.6.1 |
| 4.6.5.2 | Salt spray (launcher) | 3.9.2 |
| 4.6.3.1 | Function | 3.6.1 |
| 4.6.5.3.1 | Extreme high temperature storage | 3.9.3.1 |
| 4.6.3.1 | Function | 3.6.1 |
| 4.6.5.3.2 | High temperature storage | 3.9.3.2 |
| 4.6.3.1 | Function | 3.6.1 |
| 4.6.5.3.3 | Low temperature storage | 3.9.3.3 |
| 4.6.3.1 | Function | 3.6.1 |
| 4.6.5.4 | Vibration | 3.9.4 |
| 4.6.3.1 | Function | 3.6.1 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

TABLE III: Conformance Sample Tests

| Test Paragraph | Requirement | Requirement Paragraph |
|---|---|---|
| 4.6.3.1 | Function | 3.6.1 |
| 4.6.3.2.1 | Burn time | 3.6.2.1 |
| 4.6.3.2.2 | Candlepower | 3.6.2.2 |
| 4.6.3.8<br>4.6.3.1 | Water immersion<br>Function | 3.6.9<br>3.6.1 |
| 4.6.5.1 | Temperature and humidity | 3.9.1 |
| 4.6.5.1.1<br>4.6.3.1 | Low temperature<br>Function | 3.9.1.1<br>3.6.1 |
| 4.6.5.1.2<br>4.6.3.1 | High temperature<br>Function | 3.9.1.2<br>3.6.1 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

TABLE IV: Requirements Cross-Reference Matrix

| Requirements | Verification |
|---|---|
| 3.1 | 4.2 |
| 3.2 | 4.6.1 |
| 3.3 | 4.6.1 |
| 3.4 | 4.6.1, 4.6.5.2 |
| 3.5.1 | 4.6.2.1 |
| 3.5.2 | 4.6.2.2 |
| 3.6.1 | 4.6.3.1 |
| 3.6.2.1 | 4.6.3.2.1 |
| 3.6.2.2 | 4.6.3.2.2 |
| 3.6.2.3 | 4.6.3.2.3 |
| 3.6.3 | 4.6.1 |
| 3.6.4 | 4.6.3.3 |
| 3.6.5 | 4.6.3.4 |
| 3.6.6 | 4.6.3.5 |
| 3.6.7 | 4.6.3.6 |
| 3.6.8 | 4.6.3.7 |
| 3.6.9 | 4.6.3.8 |
| 3.6.10 | 4.6.3.9 |
| 3.6.11 | 4.6.3.10 |
| 3.7 | 4.6.1 |
| 3.8 | 4.6.4 |
| 3.9.1 | 4.6.5.1 |
| 3.9.1.1 | 4.6.5.1.1 |
| 3.9.1.2 | 4.6.5.1.2 |
| 3.9.2 | 4.6.5.2 |
| 3.9.3.1 | 4.6.5.3.1 |
| 3.9.3.2 | 4.6.5.3.2 |
| 3.9.3.3 | 4.6.5.3.3 |
| 3.9.4 | 4.6.5.4 |
| 3.10 | 4.6.1 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

TABLE V: Two-chamber Method Test Schedule

| Day | Time | | Temperature (degrees Fahrenheit) | Relative Humidity |
|---|---|---|---|---|
| | Start | Stop | | |
| 1 | 0800 | 0900 | Room | |
| 1 | 0900 | 1500 | -65 | |
| 1 | 1500 | 1600 | Room | |
| 1-2 | 1600 | 0800 | 160 | 95% |
| 2 | 0800 | 0900 | Room | |
| 2 | 0900 | 1500 | -65 | |
| 2 | 1500 | 1600 | Room | |
| 2-3 | 1600 | 0800 | 160 | 95% |
| 3 | 0800 | 0900 | Room | |
| 3 | 0900 | 1500 | -65 | |
| 3 | 1500 | 1600 | Room | |
| 3-4 | 1600 | 0800 | 160 | 95% |
| 4 | 0800 | 0900 | Room | |
| 4 | 0900 | 1500 | -65 | |
| 4 | 1500 | 1600 | Room | |
| 4-5 | 1600 | 0800 | 160 | 95% |
| 5 | 0800 | 0900 | Room | |
| 5-8 | 0900 | 0900 | -80 | |
| 8 | 0900 | 1500 | -65 | |
| 8 | 1500 | 1600 | Room | |
| 8-9 | 1600 | 0800 | 160 | 95% |
| 9 | 0800 | 0900 | Room | |
| 9 | 0900 | 1500 | -65 | |
| 9 | 1500 | 1600 | Room | |
| 9-10 | 1600 | 0800 | 160 | 95% |
| 10 | 0800 | 0900 | Room | |
| 10 | 0900 | 1500 | -65 | |
| 10 | 1500 | 1600 | Room | |
| 10-11 | 1600 | 0800 | 160 | 95% |
| 11 | 0800 | 0900 | Room | |
| 11 | 0900 | 1500 | -65 | |
| 11 | 1500 | 1600 | Room | |
| 11-12 | 1600 | 0800 | 160 | 95% |
| 12 | 0800 | 0900 | Room | |
| 12 | 0900 | 1500 | -65 | |
| 12 | 1500 | 1600 | Room | |
| 12-15 | 1600 | 0800 | 160 | 95% |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

TABLE VI: Single-chamber Method Test Schedule

| Day | Time | | Temperature (degrees Fahrenheit) | Relative Humidity |
|---|---|---|---|---|
| | Start | Stop | | |
| 1 | 0800 | 0900 | Room | |
| 1 | 0900 | 1100 | Transition | |
| 1 | 1100 | 1600 | -65 | |
| 1 | 1600 | 1900 | Transition | |
| 1 - 2 | 1900 | 0800 | 160 | 95% |
| 2 | 0800 | 1100 | Transition | |
| 2 | 1100 | 1600 | -65 | |
| 2 | 1600 | 1900 | Transition | |
| 2-3 | 1900 | 0800 | 160 | 95% |
| 3 | 0800 | 1100 | Transition | |
| 3 | 1100 | 1600 | -65 | |
| 3 | 1600 | 1900 | Transition | |
| 3-4 | 1900 | 0800 | 160 | 95% |
| 4 | 0800 | 1100 | Transition | |
| 4 | 1100 | 1600 | -65 | |
| 4 | 1600 | 1900 | Transition | |
| 4-5 | 1900 | 0800 | 160 | 95% |
| 5 | 0800 | 1100 | Transition | |
| 5-8 | 1100 | 0800 | -80 | |
| 8 | 0800 | 1600 | -65 | |
| 8 | 1600 | 1900 | Transition | |
| 8-9 | 1900 | 0800 | 160 | 95% |
| 9 | 0800 | 1100 | Transition | |
| 9 | 1100 | 1600 | -65 | |
| 9 | 1600 | 1900 | Transition | |
| 9-10 | 1900 | 0800 | 160 | 95% |
| 10 | 0800 | 1100 | Transition | |
| 10 | 1100 | 1600 | -65 | |
| 10 | 1600 | 1900 | Transition | |
| 10-11 | 1900 | 0800 | 160 | 95% |
| 11 | 0800 | 1100 | Transition | |
| 11 | 1100 | 1600 | -65 | |
| 11 | 1600 | 1900 | Transition | |
| 11-12 | 1900 | 0800 | 160 | 95% |
| 12 | 0800 | 1100 | Transition | |
| 12 | 1100 | 1600 | -65 | |
| 12 | 1600 | 1900 | Transition | |
| 12-15 | 1900 | 0800 | 160 | 95% |

Custodians:
Air Force - 99
Army – GL

Preparing Activity:
Air Force - 70

Project 1370-0015



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.

## STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

**INSTRUCTIONS**

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waiver any portion of the referenced document(s) or to amend contractual requirements.

| I RECOMMEND A CHANGE: | 1. DOCUMENT NUMBER | 2. DOCUMENT DATE (YYMMDD) |
|---|---|---|
| | MIL-PRF-83352C | 98/04/15 |

3. DOCUMENT TITLE
SIGNAL KIT, PERSONNEL, DISTRESS, A/P25S-5A

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

**6. SUBMITTER**

| a. NAME *(Last, First, Middle Initial)* | b. ORGANIZATION | |
|---|---|---|
| c. ADDRESS *(include Zip Code)* | d. TELEPHONE *(Include Area Code)*<br>(1) Commercial<br>(2) AUTOVON *(If applicable)* | e. DATE SUBMITTED *(YYMMDD)* |

**8. PREPARING ACTIVITY**

| a. NAME | b. TELEPHONE *(Include Area Code)* | |
|---|---|---|
| OO-ALC/LIWCA | (1) Commercial<br>(801) 777-5538 | (2) AUTOVON<br>777-5538 |
| c. ADDRESS *(Include Zip Code)*<br>6033 Elm Lane<br>Hill Air Force Base, UT 84056-5819 | **IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:**<br>Defense Quality and Standardization Office<br>5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466<br>Telephone (703) 756-2340 AUTOVON 289-2340 | |

**DD FORM 1426, OCT 89 *(EF-V1)*** *(PerFORM PRO)* PREVIOUS EDITIONS ARE OBSOLETE.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:50Z
Check the source to verify that this is the current version before use.