INCH-POUND

MIL-C-50330C (AR)
AMENDMENT 1
25 **September 1992**

MILITARY SPECIFICATION

CONVERTER, DC/DC: 10549021

This Amendment forms a part of Military Specification MIL-C-50330C dated, 15 May **1990, and** is approved for use by the U.S. Army Armament, Munitions and **Chemical command, and is available for use by all Departments and . Agencies of the Department of Defense.**

PAGE 2

2.1.1: Delete the following military standard:

"MIL_STD-2000 - Standard Requirements for Soldering Electrical and Electronic Assemblies

2.1.2: Add the following drawing:

"**12950877** - Requirements for Soldering Electrical and Electronic Assemblies"

PAGE 3

3.3.1: Delete paragraph 3.3.1 in its entirety and substitute:

"**3.3.1** Vibration. The de/de converter shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to the equivalent of 6000 miles of track-laying vehicle operational vibration as defined by MIL-STD-810 narrowband random-on-random data for equipment installed on the deck of the M113 armored personnel carrier."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

PAGE 3

3.3.3, 3.3.3.1 and 3.3.3.2: Delete paragraphs in their entirety and substitute:

"3.3*3 **Altitude Operating.** The **dc/dc converter shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg)."**

PAGE 5

3.7: Delete paragraph 3.7 in its entirety and substitute:

"3.7 Soldering. All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877."

PAGE 11

4.7.1.1: Delete first sentence of paragraph and substitute:

"4.7.1.1 Vibration. This test shall **be** performed **as** specified in Method 514, Category 8, Procedure I, of MIIJ-STD-810 and paragraph 3.3.1 herein."

PAGE 12

4.7.1.2: Delete "516.3" and substitute "516"

4.7.1.3: Delete paragraph 4.7.1.3 in its entirety and substitute:

"4.7.1.3 Altitude Operating. This test shall be performed as specified in Procedure II, Method 500, of ~L-STD-810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3."

4.7.1.4.1: Delete "501.2" and substitute "501".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

PAGE 12

4.7.1.4.2: Delete “502.2" and substitute "502”.

4.7.1.5: Delete "507.2" and substitute "507".

PAGE 13

4.8: Delete paragraph 4.8 in its entirety and substitute:

"4.8 **Soldering**. Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.7.”

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1285-A818)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.