MILITARY SPECIFICATION

COUNTER, ELECTRONIC: 10548009

This amendment forms a part of Military Specification MIL-C-50344A(MU), dated 15 April 1971.

Table I, Input and Output Characteristics - Following Requirement "Strobe", page 5, add the following characteristics:

"REQUIREMENT	CHARACTERISTICS	TERMINALS
$\overline{T1}$	20 KHz negative pulse (from not less than +3Vdc level to OV and return), 0.798 usec wide; displaced 258 clock pulses (34.314 usec) from PRF RESET.	P1-22
$\overline{T2}$	Same as $\overline{T1}$, except displaced 266 clock pulses (35.378 usec) from PRF RESET.	P1-16
$\overline{T3}$	Same as $\overline{T1}$, except displaced 274 clock pulses (36.442 usec) from PRF RESET.	P1-15
$\overline{T4}$	Same as $\overline{T1}$, except displaced 282 clock pulses (37.506 usec) from PRF RESET.	P1-17
$\overline{T5}$	Same as $\overline{T1}$, except displaced 290 clock pulses (38.570 usec) from PRF RESET.	P1-7
$\overline{T6}$	Same as $\overline{T1}$, except displaced 298 clock pulses (39.634 usec) from PRF RESET.	P1-3
$\overline{T7}$	Same as $\overline{T1}$, except displaced 306 clock pulses (40.698 usec) from PRF RESET.	P1-13"

* Page 6: Change "$\overline{PRF}$ - delayed approximately 20ns" to "$\overline{PRF}$ - delayed 20 ± 10 ns."

FSC 1285

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:22Z
Check the source to verify that this is the current version before use.

* The outside margin has been marked to indicate where an addition to the previous amendment has been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1285-A363

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:22Z
Check the source to verify that this is the current version before use.