INCH- POUND

MIL-G- 50322B (AR)
AMENDMENT 1
25 September 1992

MILITARY SPECIFICATION

GENERATOR, DIGITAL: 10548613

This Amendment forms a part of Military Specification WL-G-50322B dated, 30 April 1990, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command , and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1: Delete the following military standard:

MIL-STD-2000 - Standard Requirements for Soldering . Electrical and Electronic Assemblies"

2.1.2: Add the following drawing:

"12950877 - Requirements for Soldering Electrical and Electronic Assemblies"

PAGE 3

3.3.1: Delete paragraph 3.3.1 in its entirety and substitute:

"3.3.7 Vibration The 7.5-MHz clock generator shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to the equivalent of 6000 miles of track-laying vehicle operational vibration as defined by MIIJ-STD-810 narrowband random-on-random data for equipment installed on the deck of the M113 armored personnel carrier."

DISTRIBUTION STATEMENT A. Approved for public release:distihtion is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026t0-22T20:21Z
Check the source to verify that this is the currentversion before use.

PAGE 3

3.3.3, 3.3.3.1 and 3.3.3.2: Delete paragraphs in their entirety and substitute:

'3*3.3 Altitude Operating. The 7.5-MHz clock generator shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg)."

PAGE 4

3.8: Delete paragraph 3.8 in its entirety and substitute:

'3.8 Soldering All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877."

PAGE 9

4.7.1.1: Delete first sentence and substitute: "Vibration. This test shall be performed as specified in Method 514, Category 8, Procedure I, of MIL-STD-810 and paragraph 3.3.1 herein."

4.7.1.2: Delete "516.3" and substitute "516"

PAGE 10

4.7.1.3: Delete paragraph 4.7.1.3 in its entirety and substitute:

'4.7.1. 3 Altitude Operating. This test shall be performed as specified in Procedure II, Method 500, of MIL-STD-810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

4.7.1.4.1: Delete "501.2" and substitute "501".

4.7.1.4.2: Delete "502.2" and substitute "502"

4.7.1.5: Delete "507.2" and substitute "507a".

PAGE 12

4.0: Delete paragraph 4.8 in its entirety and substitute:

"4.8 Soldering.- Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.8."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1285-A814)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.