| INCH- POUND |

MIL-P-50321B (AR)
AMENDMENT 1
25 September 1992

MILITARY SPECIFICATION

POWER SUPPlY: 9342815 (KLYSTRON)

This Amendment forms a part of Military Specification MIL-P-50321B dated, 21 September 1990, and is approved for use by the U.S. Army Amament, Munitions and Chemical command, and is available for use by all Departments and Agencies *of* the Department of Defense.

PAGE 2

2.1.1: Delete the following military standard:

MIL-STD-2ooo" - Standard Requirements for Soldering Electrical and Electronic Assemblies"

2.1.2: Add the following drawing:

"12950877 - Requirements for Soldering Electrical and Electronic Assemblies"

PAGE 3

3.3.1: Delete paragraph 3.3.1 in its entirety and substitute:

"3.3.1 Vibration. The klystron power supply shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to the equivalent of 6000 miles of track-laying vehicle operational vibration as defined by MIL-STD-810 narrowband random-on-random data for equipment installed on the deck of the M113 armored personnel carrier."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

PAGE 3

3.3.3, 3.3.3.1 and 3.3.3.2: **Delete paragraphs in their entirety and substitute:**

'3.3*3 Altitude Operating. The klystron power supply shall meet the requirements of 3.4 and *3.5* **during and after exposure to barometric pressure encountered at 10,000 feet above sea level** *(20.6* **inches of Hg)."**

PAGE 7

3.7: Delete paragraph 3.7 in its entirety and substitute:

'3.7 Soldering. All soldering shall be in accordance with the requirements of Note 2 *of* **Drawing 12950877."**

PAGE 13

4.7.1.1: Delete first sentence and substitute:

'4.7.1.1 Vibration. This test shall be performed as specified in Method 514, Category 8, Procedure I of MIL-STD-810 and paragraph 3.3.1 herein."

4.7.1.3: Delete paragraph 4.7.1.3 in its entirety and substitute:

'4.7.1.3 Altitude Operating. This test shall be **performed as specified in Procedure II, Method 500, of MIL-STD-810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3."**

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

PAGE 17

4.8: Delete paragraph 4.8 in its entirety and substitute:

‘4.8 Soldering. Soldering processes shall be inspected by certified inspectors to the requirements and accepted criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.7.”

custodian
Army-AR

Preparing activity:
Army-AR

(Project 1285 -A813)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.