MILITARY SPECIFICATION

REGULATOR, VOLTAGE: 10548988

This amendment forms a part of MIL-R-50327C (AR), dated 30 April 1990, is approved for use by the U.S. Army Armament, **Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of** Defense.

PAGE 2

2.1.1: **Delete the** following **military standard:**

"MIL-STD-2000 - **Standard Requirements for Soldering Electrical and Electronic Assemblies"**

2.1.2: **Add the following drawing:**

"12950877 - Requirements for Soldering Electrical and Electronic Assemblies"

PAGE 3

3.3.1: Delete in its entirety and substitute the following:

"3.3.1 vibration. The 33-volt regulator shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to the equivalent of 6000 miles of track-laying vehicle operational vibration as defined by MIL-STD-810 narrowband random-on-random data for equipment installed on the deck of the M113 armored personnel carrier."

3.3.3, 3.3.3.1 and 3.3.3.2: Delete in their entirety and substitute the following:

"3.3.3 Altitude operating. The 33-volt regulator shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

PAGE 5

3.7: Delete in its entirety and substitute the following:

3.7 Soldering. All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877."

PAGE 10

4.7.1.1: Delete first sentence and substitute:

'4.7.1.1 Vibration. This test shall be performed as specified in Method 514, Category 8, Procedure I of MIL-STD-810 and paragraph 3.3.1 herein."

4.7.1.2: Change "516.3' to "516".

4.7.1.3: Delete in its entirety and substitute the following:

"4.7.1.3 Altitude operating. This test shall be performed as specified in Procedure II, Method 500 of MIL-STD-810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3."

4.7.1.4.1: Change "501.2" to '501".

PAGE 11

4.7.1.4.2: Change "502.2" to "502".

4.7.1.5: Change "507.2" to "507".

PAGE 16

4.8: Delete in its entirety and substitute the following:

"4.8 soldering. Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.7.

Custodian:

Preparing activity:
Army-AR

(Project 1285-A824)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.