MILITARY SPECIFICATION

REGULATOR, VOLTAGE: 10549008

This Amendment forms a part of Military Specification MIL-R-50328B (AR), dated 30 October 1979, and is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.3.5, third line: Correct spelling of the work "humidity".

3.5a, **first line: Delete and substitute:**

a. . 43 ± 7 volts **direct current (Vdc),** regulated to ± 0.5

3.5c, **first line: Delete and substitute:**

"c. 22 ± 4 Vdc, regulated to ± 0.5 percent between P1-7~

3.5d, first line: Delete and substitute:

"d. 22 ± 1 kilohertz (kHz), 71.5 = 12.5 volt (V) peak-to-'"

3.5.1.1, **last sentence: Delete and substitute:**

"The nominal **output voltage shall be 29.30 ± .30 Vdc with a load current of 10.0 ± 0.2 amperes direct current** (Adc)."

PAGE 5

3.5.1.2, fifth and sixth lines: Delete and substitute:

"circuitry and shall not exceed **16.0 Adc** at room ambient and 17.5 Adc at specified temperature extremes. The output shall automatically recover after removal of the short circuits

3.5.1.3, second and third lines: Delete and substitute:

"vary more than ± 0.60 V with an input voltage variation from 36 to 50 Vdc and a constant load current of 10.0 Adc."

FSC 1285

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

"voltage of 43 ± 7 Vdc, the tput voltage shall not vary more than + 0.60 V when the Outyut current is varied frcm 3.0 to 10.0 Ad~.

3.5.1.5, SeCOnd line: Delet e and substitute:

n to" peak when the input voltage is 43*00 + 0.43 vdc and the load

3.5.2.1, third and fourth lines: Delete and substitute:

"The nominal Output voltage shall be 6050 + 0.20 Vdc with a load current of 2.9 ± 01.2 Adc."

3.5.2.2, fifth and sixth lines: Delete and substitute:

'circuitry and shall not exceed 4.0 Adc at room ambient and 4.7 Adc at specified temperature extremes The output shall automatically recover after removal of the short circuit"

*"'3.5.2.3, second, third, and fourth lines: Delete and substitute:

vary more than ± 0.10V with an input voltage variation from 9 to 14 Vdc, a bias voltage of 22 ± 4Vdc, and a constant load current of 2.9 Adc."

3.5.2.4, second, third, and fourth lines: Delete and substitute:

"voltage of 11.5 + 2.5 Vdc and a bias voltage of 22 ~ 4Vdc, the output voltage shall not vary more than ± 0.10v when the output Current is varied from 0.025 to 2.9 Adc."

3.5.2.5, second and third lines: Delete and substitute:

"to-peak-when the input voltage is 11.50 ± 2.50 Vdc, the bias voltage is 22 ± 4 vdc, and the load current is 2.9 Adc."

PAGE 10

TABLE IV Test Equipment List:

Item No 1, Description: Delete and substitute:

Capable of producing a 22 ± 1 kHz, 71.5 ± 12.5 V peak-to-peak square wave. Output independance less than 20 ohms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

Item No. 2, Description: Delete and substitute:

Dc? 9 to 50V. 20A, regulated to 0. 5%."

Item No. 3, first line of description: Delete and substitute:

'Dc, O to 50V, 0.01% accuracy."

Item No. 6, Description: Delete and substitute:

'Dc_t O to $5A_J$ 1% accuracy."

Item No. 7, Description: Delete and substitute:

"Dc, 18 to 26v at lA, regulated to 0.5%."

Item No. 15, Add:

'15. switches S1, S2 SPST, 20A."

PAGE 12

4.6.3.1.1, second and third lines: Delete and substitute:

"Item 1, apply a 22 ± kHz, 71.5 ± 12.5 volt peak-to-peak square wave to P1-4 and P1-5. Using Item 2, apply 43 ± 7 V between"

4.6.3.1.1, last line: Delete and substitute:

E71 (+) and E72 (-) can be adjusted to 29.30 ± 0.30 Vdc with R2."

4.6.3.l.2b: Delete and substitute:

'b. Adjust R2 for voltage indication of 29.30 ± 0.30V.*

4.6.3.l.2k, last line: Delete and substitute:

'returns to within + 0.30 volts of level in "i" above."

4.6.3.1.3, fourth and fifth lines: Delete and substitute:

'Item 2, from 36 to 50 Vdc. Using Item 3, verify that the output voltage does not vary more than ± 0.60 Vdc."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

PAGE 15

4.6.3.1.4, second line: Delete and substitute:

"Item 2, to 43 ± 7 Vdc. With R2 and R17 adjusted as specified in"

4.6.3.1.4, fifth, sixth and seventh lines: Delete and substitute

"close switch s1 and vary the resistive loads, Items 10 and 11, to obtain 10.O& Using Item 3, verify that the output voltage does not vary more than ± 0.60 Vdc."

4.6.3.1.5, second line: Delete and substitute

"set to 43.00 ± 0.43 vdc and with R2 and R17 adjusted as specified"

4.6.3.2.1, second and third lines: Delete and substitute:

"Item 1, apply a 22 ± 1 kHz, 71.5+12.5 volt peak-to-peak square wave to P1-12 and P1-130 Using Item 7, apply 2224 Vdc between"

4.6.3.2.1, seventh line: Delete and substitute:

"between E73 (+) and E74 (-) can be adjusted to 6.5 ± 0.20V"

4.6.3.2.2b, Delete and substitute:

"b. Adjust R25 for voltage indication of 6.50 ± 0.20 Vdc."

4.6.3.2.2h: Delete and substitute:

Vary resistive load to obtain current indication of 2.9 Adc ."

PAGE 16

4.6.3.2.2k: Delete and substitute:

"k. Using Item 3, verify that output automatically returns to within ± 0.20 volts of level in "i" above."

4.6.3.2.3, third line: Delete and substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

'13 and 14, for a current indication of 2.9 Adc. Vary Item 2"

4.6.3.2.3, last line: Delete and substitute:

"does not vary more than ± 0.10 V."

4.6.3.2.4, second line: Delete and substitute:

"Item 7, to 22 ± 4 Vdc and Item 2 to 11.5 ± 2.5 vdc. With R25"

4.6.3.2.4, sixth and seventh lines: Delete and substitute:

'the resistive load to obtain 2.9 Adc. Using Item 3. verify that the output voltage does not vary more than ± 0.10 v."

4.6.3.2.5t first and second lines: Delete and substitute:

'4.6.3.2.5 Output ripple. Set input voltage, Item 7, for 2214 Vdc and Item 2 for 11.5 ± 2.5 Vdc. With R25 and R40"

4.6.3.2.5, fourth line: Delete and substitute:

"13 and 14, for a current indication of 2.9 Adc. Using Item 4."

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1285-A546)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.