INCH-POUND
MIL-T-50320C (AR)
AMENDMENT 1
09 October 1992

MILITARY SPECIFICATION

TRANSMIT GATE: 10549202

This amendment forms a part of MIL-T-50320C (AR), dated 18 May 1990, and is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1:

Delete “MIL=T-50671 and MIL-T-50672" and substitute "MIL-G-50671 and MIL-G-50672a".

Delete the following military standard:

"MIL-STD-2000 - Standard Requirements for Soldering and Electronic Assemblies"

2.1.2: Add the following drawing:

“12950877 - Requirements for Soldering Electrical and Electronic Assemblies"

PAGE 3

3.2: Delete "MIL-T-50671 and MIL-T-50672" and substitute "MIL-G-50671 and MIL-G-50672".

3.3.1: Delete in its entirety and substitute the following:

3.3.1 vibration. The transmit gate shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to the equivalent of 6000 miles of track-laying vehicle operational vibration as defined by MIL-STD-81O narrowband random-on-random data for equipment installed on the deck of the M113 armored personnel carrier.”

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T20:21Z
Check the source to verify that this is the currentversion before use.

PAGE 4

3.3.3, 3.3.3.1 and 3.3.3.2: Delete in their entirety and substitute the following:

3.3.3 Altitude operating. The transmit gate shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg)."

PAGE 5

3.8: Delete in its entirety and substitute the following:

"3.8 Soldering. All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877."

PAGE 15

4.7.1.1: Delete first sentence and substitute the following:

"4.7.1.1 Vibration. This test shall be performed as specified in Method 514, Category 8, Procedure I of MIL-STD-810 and paragraph 3.3.1 herein."

4.7.1.2: Change "516.3" to "516".

4.7.1.3: Delete in its entirety and substitute the following:

"4.7.1.3 Altitude operating. This test shall be performed as specified in Procedure II, Method 500 of MIL-STD-810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3."

4.7.1.4.1: Change "501.2" to "501".

PAGE 16

4.7.1.4.2: Change "502.2" to "502".

4.7.1.5: Change "507.2" to "507".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

PAGE 17

4.8: Delete in its entirety and substitute the following;

"4.8 soldering. Soldering processes shall be inspected by certified inspectors to the requirments and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.8."

Custodian:
ARMY-AR

Preparing activity:
Army-AR

(Project 1285-A812)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.