MIL-C-55486B(CR)
AMENDMENT 1
25 February 1988

MILITARY SPECIFICATION

CABLE ASSEMBLY TELEPHONE
CX-4566( )/G AND CX-4760( )/U

This amendment forms a part of Military Specification MIL-C-55486B(EL), dated 15 May 69, and is approved for use within the Communications Electronics Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, under STANDARDS, MILITARY, delete 'MIL-STD-170 Moisture Resistance Test Cycle for Ground Signal and Electronic Test Equipment.' and substitute 'MIL-STD-810 Environmental Test Methods & Engineering Guidelines'.

PAGE 2

2.1, under DRAWINGS, delete 'SC-GL-323007 Electrical Fixture...etc' and substitute 'GL-SC-B-323236 Electrical Fixture...etc'.

PAGE 7

4.5, delete 'SC-GL-323007' in two places and substitute 'GL-SC-B-323236'

AMSC N/A FSC 5995

DISTRIBUTION STATEMENT A. APPROVED for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:25Z
Check the source to verify that this is the current version before use.

4.9.1, delete paragraph and substitute:

4.9.1 Moisture-Resistance.- Four cable assemblies, two mated, one with protective cover in place and one without protective cover shall be tested per Method 507.2 Procedure III of MIL-STD-810, for 30 continuous 24-hour cycles. Insulation resistance measurements shall be made at the required test steps. For Step 7, insulation resistance measurements shall be made near the end of every fifth cycle while still at 30 C (86 F) and 95% Rel. humidity. The equipment shall meet the requirements of 3.8.2.

Custodian:
Army - CR

Preparing activity:
Army-CR
(Project 5995-A127)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:25Z
Check the source to verify that this is the current version before use.