METRIC

DOD-P-63975(AR)
AMENDMENT 6
15 FEBRUARY 1989
SUPERSEDING
AMENDMENT 5
26 August 1988

MILITARY SPECIFICATION

PRIMER, ELECTRIC, PA520

This Amendment forms a part of Military Specification DOD-P-63975(AR), dated 14 May 1982, and is approved for use within the U.S. Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

STANDARD, MILITARY:

Add "MIL-STD-129 - Marking for shipment and Storage".

Add "MIL-STD-1235 - Single and Multi-Level Continuous Sampling Procedures and Tables for Inspection by Attributes".

Delete "MIL-STD-331".

2.1.2: Drawings, Inspection Equipment

Delete :11825969 - Test Barrel, 30mm Mann (6.5°)" and substitute "9390627 - Barrel, Test, 30mm (ADEN Barrel)".

3.6 Delete in its entirety and substitute:

"3.6 Continuity and resistance. The primer circuit shall be continuous with an electrical resistance of the uncapped primer lot less than 20 no more than 1000 ohms. The electrical resistance of the capped primers shall not be less than 20 no more than 1000 ohms."

PAGE 4

3.9 Delete in its entirety and substitute:

"3.8 The primer shall have an all-fire voltage of 22 volts DC or less and no-fire voltage of 3.0 volts DC minimum. The primer performance shall not be degraded when fired at either 115 volts, 400 HZ or in the circuit of 3.9."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

3.9 Delete in its entirety and substitute:

"3.9 Function time. Testing for function times of 3.9.1 and 3.9.2 shall be conducted in a 163 volt, 400 HZ half wave rectified circuit with a 100 ohm resistor in series with the primer pulse duration shall be 4.0 milliseconds."

Add 3.9.1 as follows:

"3.9.1 Electric primer time. The individual and mean plus three standard deviation primer time values shall not exceed .400 milliseconds."

3.10 should read "3.9.2".

PAGE 5

4.3.1

Delete "125" and substitute "32".

Delete "Insulator" in its entirety.

Delete "1430" and substitute "1312".

Delete "MOD I".

PAGE 7

Table I:

Delete "MOD I".

Delete "125" and substitute "32" wherever it appears.

Delete "Insulator in its entirety.

Add: "Button-cup-insulator sub assembly (reference 11825910) insulation strength. 7/, 32, 100%, 3.5, 4.5.1".

PAGE 8

Change quantities to 32 pieces for: Examination for defects and delete "4.3.2.2" and add "4.4.2.4".

Firing Voltage: Change "600" to "550".

Delete "Insulation strength" in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

Table I: In Requirements paragraph column, Delete "3.9" and "3.10" and substitute "3.9.1" and 3.9.2" respectively.

PAGE 9

Note 5/ : Delete "action time plus four" and substitute "action time plus three".

PAGE 10

4.4.1:

Delete last sentence of first paragraph.

Delete items "a) thru e)".

4.4.2.a:

Add: "or MIL-STD-1235" to the last sentence.

PAGE 11

4.4.2.1, Major 102: Add "/ORD-SIO-S314" to Visual.

PAGE 13

4.4.2.3, Major 102: Add "/ORD-SIO-S314" to Visual.

PAGE 14

4.4.2.4:

Add "11825901" to next high assembly.

Critical 3: Delete "loss" and substitute "loose”.

Critical 8: Delete "600" and substitute "550".

102: Add a “ 3/ ” after missing, misplaced or protruding insulator and the 3/ should read:

“ 3/ Rotation and tilting or primers under magnification may be required to view for presence of insulator."

PAGE 15

4.4.2.4:

Add "11825901" to next high assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

Title: Delete footnote " 1/ ".

Add new Major 106: "Primer time, n = 50, Acc-0, Rej-1, 3.9, 4.5.5".

Notes: Delete " 8/ " and substitute " 2/ ".

Add: "Major 107, Action Time 3/, -54°C, 100, 3.9.2, 4.5.6
+21°C, 25, 3.9.2, 4.5.6
+71°C, 25, 3.9.2, 4.5.6

3/ If the sample average action time plus three standard deviations exceeds 4 milliseconds or if an individual primer time of the test sample exceeds 4 milliseconds, the lot shall be rejected.'

PAGE 16

4.5.4, Delete "If the average . .." in its entirety and substitute:

"If the average critical voltage minus 2 standard deviations is less than 2 volts DC, the lot shall be retested. The retest shall consist of firing a random sample of 100 primers at 3 volts DC with an 8.2 ohm resistor placed in series with the primer. If any primers fire during this test, the lot shall be rejected."

4.5.4, statement "e" should read: "The primer firing device shall be set for a 4 millisecond pulse time".

PAGE 17

4.5.6 Delete "11825969" and substitute "9390627".

4.5.7 Line 11: Delete "busts of 25 rounds" and substitute "20 round minimum burst".

Delete "XM230E1" and substitute "M230".

4.5.8: Delete "in accordance with Table II".

4.5.9.1: Delete "4.5.6" and substitute "4.5.9".

4.5.9.2: Delete first sentence and substitute "The test cartridge(s) shall be subjected to a broad band random vibration profile in accordance with the requirements of MIL-STD-810, Method 514/2, Procedure 1 Car, "C" with the vibration spectrum per Figure 514.2-3 and 514.2.10 of MIL-STD-810."

Second sentence: Delete "AAH magazine" and substitute "M592 Ammo Can".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

4.5.9: Delete "MIL-STD-801" and substitute "MIL-STD-810".

4.5.10: Delete in its entirety.

4.5.11: Delete "4.5.11" and substitute "4.5.10".

* 5.1 The last sentence should read:

"The primers shall be packed in such manner as to be protected from moisture."

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1305-AD08)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.