METRIC

DOD-P-63977A(AR)
AMENDMENT 3
24 July 1996
SUPERSEDING
AMENDMENT 2
18 January 1991

MILITARY SPECIFICATION

PROJECTILE, 30MM, TARGET PRACTICE AND
TARGET PRACTICE ALTERNATE DESIGN FOR
CARTRIDGE, 30MM, M788

This amendment forms a part of Military Specification DOD-P-63977A(AR), dated 7 August 1986, and is approved for use by the US Army Armament, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 2.1.2 Delete:

"9349343 - Body Assembly, Projectile, 30mm, TP M788
11825948 - Projectile, 30mm, Target Practice M788"

PAGE 3

* Delete 3.1.2 in its entirety and substitute the following:

"3.1.2 Projectile. The projectile shall comply with all requirements of Dwg 9399639, as applicable, and with all requirements in applicable specifications."

3.4 Add the following:

"When sectioned along the longitudinal axis, one half of the sectioned projectile body shall be examined for rotating band fill in the undercut areas. Failure of either of the exposed sections to comply with 65% fill in the under cut areas shall be considered a defect."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

* Delete 3.6.1 in its entirety and substitute the following:

"3.6.1 Phosphate coating. The pretreatment process used shall be in accordance with the applicable requirements of Dwg 9399639. The phosphate coating shall be in accordance wit the requirements of TT-C-490 for appearance and minimum weight, as applicable to the type of phosphate coating. Test specimens (panels) shall be in accordance with the type of phosphate requirements of TT-C-490."

* Delete 3.6.2 in its entirety and substitute the following:

"3.6.2 Paint coating. The paint coating shall be in accordance with applicable requirements of DWG 9399639. Exterior paint adhesion shall be in accordance with applicable requirements of TT-C-490."

PAGE 4

* 3.6.3 Delete 24 hours and substitute 48 hours.

PAGE 5

* Delete 4.3.1 in its entirety and substitute the following:

"4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.1. The first article sample shall consist of the following items in sample quantities as indicated:

Part Description	Drawing	Quantity
Blank, Rotating Band for Projectile, 30mm	11825929	32
Nose, Projectile	9399643	32
Projectile Body - TP	9399642	32
Body & Band Assembly TP	9399641	125
Projectile Assembly (unpainted)	9399640	125
Projectile, 30mm - TP (unpainted)	9399639	432
Standard Test Panels (see TT-C-490)		3

Page 7

Delete "Table IA. First article inspection (Classification of Defects and Tests) Sheet 1 of 1" in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

Page 13

Delete "Quality Conformance Inspection (Classification of Defects and Tests)" in its entirety.

Page 14

Delete "Quality Conformance Inspection (Classification of Defects and Tests)" in its entirety.

Page 15

Delete "Quality Conformance Inspection (Classification of Defects and Tests)" in its entirety.

Page 16

Delete "Quality Conformance Inspection (Classification of Defects and Tests)" in its entirety.

Page 17

Delete "Quality Conformance Inspection (Classification of Defects and Tests)" in its entirety.

Page 18

Delete "Quality Conformance Inspection (Classification of Defects and Tests)" in its entirety.

Page 22

Quality Conformance Inspection (Classification of Defects and Tests) delete "Major 104" in its entirety and substitute:

"Major 104.	Band tightness	20	Acc-0 Rej-1	3.1	4.5.1/ Gage."

Page 23

Quality Conformance Inspection (Classification of Defects and Tests) delete "2/" in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

Page 27

Delete 4.5.1.2 in its entirety and substitute the following:

"4.5.1.2 Band tightness. After sectioning along the longitudinal axis, one half of the sectioned projectile body shall be examined for rotating band fill in the undercut areas using a .400mm No-go pin. Failure of either of the exposed sections to comply with the 65% fill requirement shall be considered a defect."

Delete 4.5.4 in its entirety and substitute the following:

"4.5.4 Phosphate coating. The method of test shall be as prescribed by TT-C-490 for the type of coating used (see Dwg 9399639). The prescribed panels shall be processed, with the projectiles to be represented, at the start of daily production and at 4-hour intervals, maximum, thereafter. Appearance and weight of the coating shall be recorded."

Page 29

6.9, Add the following:

"d. Missing paint on the rotating band is not a defect."

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-0131)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.