MIL-I-60016A (AR)
AMENDMENT 3
15 SEPTEMBER 1980
SUPERSEDING
AMENDMENT 2
31 JANUARY 1975

MILITARY SPECIFICATION

INCREMENTS, PROPELLANT
FOR CHARGE PROPELLING M36A1
(MADE FROM PROPELLANT M8)

This Amendment forms a part of Military Specification MIL-I-60016A, dated 7 Nov 1968.

PAGE 1

* Paragraph 2.1, Specifications, Federal:
Add: "PPP-T-60 - Tape: Packaging, Waterproof".

* Paragraph 2.1, Specifications, Military:
Delete: "MIL-B-3106 - Board, Composition, Water - Resistant, Solid".

Add: "MIL-B-131 - Barrier Materials, Watervaporproof, Flexible, Heat-Sealable".

Add: "MIL-F-50449 - Filler, Sheet Form (for use in Ammunition Containers)".

PAGE 3

Paragraph 3.2, Table 1 :
Delete: "±3 grains" and substitute "±2 grains".

Delete: "±12 grains" and substitute "± 5 grains".

PAGE 9

Paragraph 4.2.3.1.2.1 :
Delete: "Code Letter E" and substitute "Code Letter F".

FSC: 1376

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

9370

PAGE 10

Paragraph 4.3.2:
Add the following: "All calibration and test rounds fired from armor plate shall be corrected for velocity plate differential in accordance with Table IV.

TABLE IV

Increment	Differential (fps)
41	-13
10	- 3
5	- 4

These corrections shall be applied before calculation of mean, standard deviation and lot percent defective". (see 6.12)

PAGE 11

Paragraphs 5.1.1, 5.1.2 and 5.1.3:
Delete in its entirety and substitute:

"5.1.1 Level A - Propellant increments shall be packed in case liners conforming to Type 1, Grade A, Style A, of MIL-L-10547; manufactured from barrier material conforming to class 1, of MIL-B-131.

The case liner shall be approximately 14 3/4 inches long by 14 3/4 inches wide by 18 1/2 inches deep. The case liner shall be closed with pressure sensitive tape, Type IV, Class 1 of PPP-T-60. One liner shall be packed in a nailed wood box, complying with Grade A, Type 1, Class 1 of MIL-B-2427. The box shall be completely lined with fillers complying with MIL-F-50449. The box shall be strapped girthwise, between cover cleats with two 5/8 inch by 0.02 inch thick flat steel straps conforming to Type 1, Class A or B, of QQ-S-781. The net weight of the propellant shall not exceed 50 pounds."

5.1.2 Level B - Propellant increments shall be packed in accordance with paragraph 4.3 of MIL-STD-652.

* 5.1.3 Level C - Propellant increments shall be packed in a fiberboard carton conforming to requirements of Drawing 7548645 except that liner shall conform to Type 1, Grade A material of MIL-L-10547. Alternatively, a wood box meeting the requirements of Code of Federal Regulations Parts 0-190 may be used in lieu of fiberboard carton".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.

Paragraph 5.2.1:
Delete: "The ICC nomenclature" and substitute "The DOT marking".

PAGE 12

Add new paragraph as follows:

"6.12 - Calibration tests performed at the Proving Ground show that a velocity differential exists between firings obtained from armor and base-plates. Since all assessments will be conducted from armor plate, this velocity differential must be applied as a correction factor to reflect the velocities that would be obtained from base-plate".

*The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CUSTODIAN:
ARMY-AR

PREPARING ACTIVITY
ARMY-AR
Project No. 1376-A161

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.