A-A-2112A
October 24, 1989
SUPERSEDING
A-A-2112
November 1, 1982

COMMERCIAL ITEM DESCRIPTION

COSTUMER, METAL (CONTEMPORARY STYLE)

The General Services Administration has authorized the use of this commercial item description.

1 Scope. The costumer shall be a contemporary style designed for heavy duty office use, with knock down construction.

2 Salient characteristics:

Type I - Round pole with a circular base.

3 Requirements.

3.1 Metal finish. The exposed metal shall be a satin finish aluminum with a protective coating, satin finish anodized aluminum, satin finish stainless steel, or satin finish chrome plated steel.

3.2 Pole. The pole shall be a minimum of one inch in diameter capped with a metal or high impact plastic cap.

3.3 Hooks The costumer shall have 4 double hooks (hat and coat), through bolted, with matching bolt head and capnut. All ends of the hooks shall have plastic garment protectors. The bottom of the hooks shall be a minimum of 56 inches from the floor. Alternatively, the hooks may have ball ends and be attached to the pole with rivets.

3.4 Identification label. The label shall have the contractor's name or trademark, contract number, NSN (if specified), month and year of manufacture marked with permanent dark ink. The label shall be affixed to the bottom of the base and shall not be removable by hand without defacement after being affixed for 4 hours.

3.5 Workmanship. The edges and corners shall be eased. The metal shall be free of sharp edges and burrs. The metal finish shall be free of pits, blisters, stains, and brush and grind marks. The costumer shall have no defects that affect the appearance or serviceability of the item.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

FSC 7110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

3.6 Performance. Each unit shall comply with the following performance tests. Failure of any costumer to comply with these requirements shall be in accordance with paragraph 4.6.

3.6.1 Stability test. Weights shall be suspended separately from the tip of the coat hook and hat hook. The weights shall not hang more than 15 inches below each hook. One of the top sets of hooks on one side of the costumer shall be loaded as follows: a, the hat hook shall be loaded with 20 pounds; (b), the coat hook shall be loaded with 50 pounds. Any tipping, instability, deformation, or loosening of the pole from the base of the costumer shall be reason for rejection.

3.6.2 Hook test. All four sets of hooks shall be loaded as specified in 3.6.1 for 1 hour. Any permanent set or loosening of the hooks from the pole shall be reason for rejection. In addition, any distortion of the pole loosening of the pole from the base shall be cause for rejection.

3.6.3 Level test. Place the costumer on a level surface plate. If a 1/16 inch thick feeler gauge can be easily inserted under the base at any point, the unit shall be rejected.

3.6.4 Chromium plating test. The plated samples shall be tested for corrosion with the 5 percent neutral salt spray at 95 degrees F in accordance with ASTM test method B-117. The test period shall not be less than 48 hours. After the specified exposure is completed, the specimen shall be visually examined to assure that the plating shows no evidence of peel, chip, uneven color, powder film, pits, or stain. Widely scattered spots of corrosion are permitted, however, none of these spots shall exceed 1/16 inch along the greatest dimension.

4 Quality Assurance Provisions.

4.1 Responsibility for inspection. The contractor shall be responsible for the performance of all inspection and testing in fulfillment of all requirements specified herein. Unless otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities approved by the Government as suitable for the performance of inspections and tests required by this CID. The Government reserves the right to perform any or all of the inspections and/or tests set forth in this CID, as deemed necessary to provide assurance of supply conformance to prescribed requirements.

4.2 First article requirements. The first article inspection shall be in accordance with the solicitation.

4.3 Quality conformance inspection. A sample of the finished product shall be selected in accordance with paragraph 4.6 of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

this CID for quality conformance verification. The sample shall be examined to verify that the requirements referenced in sections 1 and 2 have been met. Any nonconformance with the above requirements shall be considered a defect. All defects found shall be classified as major/minor in accordance with paragraphs 4.4 and 4.5 of this CID.

4.4 Major defects. The following conditions of nonconformance with the stated requirements of the CID shall be considered as major defects which may potentially affect the safety, functionality, durability, usability, and life of the purchased items.

No acceptable evidence of conformance with ASTM Method B-117.
Noncompliance with the stability test.
Noncompliance with the hook test.
Noncompliance with the level test.
Noncompliance with the chromium plating test.
Parts fractured, buckled, bent, punctured, or malformed.
Rivets loose or not set properly.
Sharp edges.
Preservation, packaging, and packing not in accordance with the requirements of the contract or purchase order.
Identification marking missing, wrong, or illegible.

4.5 Minor defects. Nonconformance listed below shall be considered as minor defects affecting the appearance of the finished item.

Rough or slivered surface.
Burrs.
Rough tool markings.
Oversized holes.
Pitted, stained, or blistered surfaces.
Foreign matter embedded in the finish.
Painted surfaces contain sags or runs.
Components and parts covered with film.
Parts, components, overall covered, not free of grease, dirt dust, epoxy, stains, etc.

4.6 Sampling. The sampling plan shall be in accordance with MIL-STD-105 with an inspection level II, Acceptable Quality Level (AQL) of 6.5 percent defective for minor defects and an inspection level of S-2, AQL of 2.5 percent defective for major defects.

4.7 Inspection. Completed costumers shall be sampled in accordance with MIL-STD-105. Examine for visual and dimensional defects using level S-2, AQL of 4.0 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

5 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580, as amended, to the maximum extent practicable.

6 Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

7 Standards. The latest issues of ASTM B-117, MIL-STD-105 and Fed. Std. 595 in effect on the date of the solicitation shall be used to determine compliance with the stated requirements.

8 Notes.

8.1 ASTM test method. Copies of the ASTM Test Method B-117 can be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

8.2 Copies of MIL-STD-105 can be obtained from the Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

8.3 Federal Standard No. 595 is available from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle WA.

PREPARING ACTIVITY

GSA - FSS/FCNE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.