A-A-2351
November 29, 1985

COMMERCIAL ITEM DESCRIPTION

SCALING AND CHIPPING TOOL, ROTARY, PORTABLE, ELECTRIC, AND CUTTER BUNDLES

The General Services Administration has authorized the use of this commercial item description as a replacement for Military Specification MIL-S-19875, Type I, Class B, which is canceled.

This commercial item description covers scaling and chipping tools intended for use in removing rust, scale, paint, and other hard deposits from steel, iron, concrete, and similar surfaces through the action of rotating cutter bundles.

Salient characteristics:

Tool requirements:

The tool shall be of the manufacturer's current design.
All wiring, flexible cord, and attachment plug cap shall meet the requirements of Underwriters' Laboratories Standard No. 45.
The tool shall have basic insulation.
The tool shall have a 2 pole, 3 wire grounding system that meets the requirements of Underwriters' Laboratories Standard No 498.
The motor shall be universal, series wound, operable on 115 VDC or 120 VAC and develop not less than 1/2 horsepower at the cutter bundle shaft.
The tool shall be electromagnetic interference suppressed in accordance with MIL-STD-1337 when specified.
The switch shall be double pole and of the quick break type with provision for looking in the "On" position.
All rotating parts shall be provided with precision quality ball bearings or ball and roller bearings.
The tool shall be of the double cutter type.
The tool shall have a sturdy supporting wheel, or wheels, mounted on the body of the tool.
The handle shall be of the closed grip type incorporating a trigger type switch. A second handle shall be mounted on the tool in such a way as to permit the operator to exert maximum downward pressure on the cutter bundles.
Cutter bundles shall be covered by guards such that the operator is protected from the failure of rotating parts. The guards shall be situated in such a manner that the cutter bundles are exposed for 180 degrees $\pm$10 degrees around the periphery, and the exposed portion faces the work surface. The guard shall not interfere with the tool's operation or with changing the cutter bundles.
The cutter bundle drive spindle shall be 0.5 inch, +0.000, -0.002 inch thick square and shall accommodate 2 cutter bundles.
Cutter bundle rotation shall be parallel to the length of the tool. The fit of the bundles on the drive spindle shall be a sliding fit.
The tool shall be provided with a means of easily regulating the depth of cut. That device shall be wear resistant.
All parts shall be replaceable and adjustable without modification of the parts or the tool.
An identification plate, securely fastened to, or as an integral part of, the housing, shall be provided. The plate shall contain the following information: manufacturer's name, trademark, country of origin, model and serial number, type of current, voltage, load current (rated amperes), and no-load rpm of spindle shaft.
The tool shall be so designed and constructed that it is fully protected from the harmful effects of debris created by the tool's operation. All parts requiring protection from dust and debris shall be enclosed.
The tool shall be provided with one pair of rebuildable cutter bundles.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:22Z
Check the source to verify that this is the current version before use.

The tool shall be supplied with any tools, equipment, and accessories necessary to assure efficient operation in accordance with the operating instructions and any tools, equipment, and accessories normally supplied commercially. The tool shall be supplied with a complete set of the manufacturer's current operating and maintenance instructions, parts list breakdown, and any other information necessary for the safe and efficient operation of the tool.

The tool shall be supplied with a carrying case capable of securely holding and compactly housing the tool and all accessory components.

Cutter bundle requirements:

Cutter bundles shall be of the cage design. Each bundle shall consist of an assembly of steel parts comprised of cutters, side plates, lock plate, restricting and supporting axial members, square bearing tube and additional parts necessary to fabricate a complete unit. Total width of the complete bundle shall not exceed 2-3/8 inches along the axis and 2-1/2 inches along the periphery. Side plates shall not exceed 3-1/4 inches in diameter.

The cutters shall be milled or stamped steel discs with a minimum of 18 teeth equally spaced around the periphery. Diameter of the disc shall be 1-1/4 $\pm$ 1/16 inch. Thickness shall be 1/8 $\pm$ 1/64 inch. Bore shall be 5/8 inch minimum. With cutters mounted, the operational diameter of the bundle shall not exceed 3-7/8 inches. Each bundle shall have a minimum of 6 stacks of cutters. The cutters shall be spaced on the axial members by washers, alternating in relative position with cutters on adjoining axial members. The restricting and supporting axial members of either single or multiple piece construction shall be securely fastened to the side plates and of such diameter that the total operational diameter of the cutters is not exceeded.

The square bearing tube of each bundle shall be permanently fixed to the side plates and shall evenly distribute the driving force to the cutters. The tube shall be designed so that the bundle assembly may be mounted on either end of the square spindle on the scaling tool by means of a sliding fit.

Cutter bundles shall be rebuildable. The bundles shall be so constructed as to permit simple and quick replacement of parts and full use of the cutter teeth to their root diameter. All replacement parts shall be constructed so that worn parts may be replaced without modifications.

As the final step to secure each cutter bundle unit, the cutter bundle components shall be held in place with a lock plate.

Service test. The tool shall satisfactorily complete a service test of at least 100 hours of actual operation.

Workmanship. The scaling and chipping tool and accessory components shall be free of any defects which may impair serviceability, durability, or appearance.

Regulatory requirements. In accordance with the section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Notes:

Assigned National Stock Numbers (NSN's):

5130-01-087-6819 - Electromagnetic interference suppression not required.
5130-00-288-6577 - Electromagnetic interference suppression required.
5130-00-287-5199 - One set of two cutter bundles only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:22Z
Check the source to verify that this is the current version before use.

The issue of UL Standards No. 45 and 498, and MIL-STD-1337, in effect on the date of invitation for bid or request for proposals shall be used to determine compliance with the stated requirements.

Copies of Underwriters' Laboratories Standards may be obtained from Underwriters' Laboratories Inc., 1285 Walt Whitman Road, Melville, Long Island, NY 11747.

Copies of MIL-STD-1337 may be obtained from Commanding Officer, U. S. Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 10120.

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:22Z
Check the source to verify that this is the current version before use.