A-A-2368
August 29, 1985

COMMERCIAL ITEM DESCRIPTION

ROLLING PIN, WOOD

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification LLL-R-530.

This commercial item description (CID) covers four types of wooden rolling pins:

Type I - Rolling pin with stationary handles, 2-3/8 inches minimum diameter, 12 inches minimum barrel length, with 3-1/4 inches minimum handle length.

Type II - Rolling pin with rotating handles, 2-3/16 inches minimum diameter, and 10 inches minimum barrel length. Nylon or corrosion resisting steel bearings, sleeves, or bushings.

Type III - Rolling pin with rotating handles, 3 inches minimum diameter, and 14 inches minimum barrel length. Nylon or corrosion resisting steel bearings, sleeves, or bushings.

Type IV - Rolling pin without handles (pie or pastry pin), 1-1/2 inches minimum diameter and 10-1/2 inches minimum overall length.

Salient characteristics.

The wood shall be birch, beech, maple, or sycamore. It shall be free of shakes, splits, wormholes, decay knots, or loose filler.

The roller body shall be cylindrical with an out-of-roundness not to exceed 1/16 inch and shall be straight within 1/16 inch. All edges shall be beveled.

The handles of the types I, II and III rolling pins shall be attached at the center of each end in accordance with the manufacturer's standard commercial practice and shall not break, crack, permanently deform, or separate from the roller when tested as specified.

All surfaces of the rolling pins shall be finished in accordance with the manufacturer's standard commercial practice.

Workmanship. The rolling pins shall be clean and free of dents, cracks, slivers, splinters, loose grain, loose fillers, knots, bark, and unnatural discoloration or surface bruises. There shall be no defects that adversely affect seviceability or appearance.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:22Z
Check the source to verify that this is the current version before use.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. Inspection records of the examinations or tests shall be kept complete and available to the Government as specified in the contract or purchase order. The Government reserves the right to perform any of the inspections set forth in the CID where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Inspection of the end item. Sampling shall be in accordance with MIL-STD-105, Sampling Procedures and Tables for Inspection by Attributes. The inspection lot shall consist of all rolling pins of one type offered for inspection at one time. The sample unit shall be one rolling pin.

The visual examination of the rolling pin shall be for the finish, splits, splinters, fillers, wormholes on roller surface, not correct species of wood, and broken, missing, or not-glued handles. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 percent defects expressed in terms of percent defective.

The dimensions and strength tests shall be inspection level S-2 with an AQL of 4.0 percent defective expressed in terms of defects per hundred units. Any non-conformance to the requirements shall be classified as a defect.

The body diameter of the rolling pin shall be measured around the circumference at each end and at the center to determine compliance.

Lay the rolling pin on a level surface. Attempt to insert a 1/16-inch feeler gage between the roller body and the surface at each end and the center of the body to determine compliance.

Clamp the rolling pin in a horizontal position and suspend a 75-pound weight from the center of each handle for three minutes. Remove the weights and examine the rolling pin for compliance with the handle requirements specified.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:22Z
Check the source to verify that this is the currentversion before use.

Notes. Purchaser must specify type rolling pin required.

Copies of military standards may be obtained from the procuring activity or as directed by the contracting officer.

WHEN THIS COMMERCIAL ITEM DESCRIPTION IS USED FOR PROCUREMENT, THE COMMERCIAL ITEM CERTIFICATION CLAUSE DOES NOT NEED TO APPEAR IN THE SOLICITATION.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - SA
Air Force - 99

Review Activities

Navy - SA
Air Force - 84, 85, 41
Surgeon General - MD

User Activities

Army - MD
Navy - MC, CG

CIVIL AGENCY COORDINATING ACTIVITIES:

HEW
VA

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:22Z
Check the source to verify that this is the currentversion before use.