[METRIC]
A-A-2854
January 12, 1998
SUPERSEDING
ZZ-M-46C
July 8, 1966

COMMERCIAL ITEM DESCRIPTION

MAT, FLOOR (LINK-TYPE)

The General Services Administration has authorized the use of this commercial item description (CID) for all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1. Scope. This commercial item description covers link-type floor mats for use in corridors and entryways.

1.2 Classification. The mats shall conform to the following class, style and size as specified (see 6.2)

Class 1 - Rubber, Long link, black with red diamond design in the center.
Class 2 - Rubberized fabric, (tire treads), long link.
Class 4 - Rubber or plastic, short link.

Style A - Mats without nosing.
Style B - Mats with end nosing.

Size 1 - 432mm (17.0 inches) X 711mm (28.0 inches)
Size 2 - 457mm (18.0 inches) X 737mm (29.0 inches)
Size 3 - 457mm (18.0 inches) X 762mm (30.0 inches)
Size 4 - 610mm (24.0 inches) X 914mm (36.0 inches)
Size 5 - 610mm (24.0 inches) X 1219mm (48.0 inches)

2. SALIENT CHARACTERISTICS

2.1 Class 1 and 4 Material. The links shall be made from a plasticized polyvinyl chloride; or a compound of natural rubber, synthetic rubber, or a mixture thereof. The links shall contain no material that may stain, damage, or mar the appearance of floors.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Branch (7FXEE), 819 Taylor Street, Fort Worth, TX 76102-6114.

FSC 7220

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.

2.2 Class 2 Material. The links shall be made of superimposed layers of rubberized fabric and shall contain not less than three plies of fabric. As an alternate construction, 2 or more ply side-wall strips measuring 10mm ± 3mm (0.393 ± 0.118 inch) in thickness and 19mm ± 2mm (0.748 ± 0.078 inch) wide, with spacers, cut from truck and passenger tires may be used for the rubberized fabric links. Solid black or alternating side-wall strips of black and white may be used. The links or strips shall be free of objectionable odor and shall contain no material that may stain, damage, or mar the appearance of floors.

2.3 Nosing. The nosing for mats shall be made of the materials specified for links and shall be tapered to prevent tripping. The construction shall ensure that no metal is exposed on the wearing surface of the nosing. The end nosing shall be reinforced with a metal strip entirely encased in rubber or plastic to prevent the corners from curling. The side nosing shall be sufficiently flexible to permit rolling up of the mat without cracking, tearing, or excessive distortion of the nosing.

2.4 Cross wires. The cross wire shall be of corrosion resistant or galvanized spring-steel wire. The wire shall be 2.3mm (0.09 inch) to 3.3mm (0.13 inch).diameter.

2.5 Class 1 and 2 links. Links may be of any length up to 100mm (4.0 inches) as long as the mat remains flexible. The width shall be 14mm (0.55 inch). Class 1 links shall be 14mm at the thickest point. The link ends shall be semicircular and concentric with the cross-wire holes. Class 2 holes shall be 3mm (0.11 inch) in diameter. The links shall have line contact with the floor at not less than three approximately equidistant points. The wearing surface of the links shall be corrugated at a right angle to the length of the links.

2.6 Class 4 links. The links shall be removable and reversible. The links shall be extruded or injection molded uniformly on both sides. Each link shall have uniform holes for supporting the links longitudinally on the wire framework. The wearing surface of the links shall have at least three corrugations on each side and each corrugation shall be tapered; the corrugations shall be at right angles to the length of the links. The number of links per square meter shall be not less than 1290.

2.7 Color. Classes 1 and 4 mat colors shall be as specified (see 6.2). Class 2 mat color shall be naturally produced by the edge surfaces of the rubberized fabric. Either dark or light links may be used in the mat to produce a uniform appearance.

2.8 Dimensions. Unless otherwise specified, dimensions listed shall be considered maximum, with a -3 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.

2.9 Workmanship. The floor mats shall be free from embedded foreign material, cracks, tears, objectionable odor or any other defect affecting appearance or serviceability of the item.

2.10 Measurement system. The values stated in metric units are to be regarded as the standard. The inch-pound values stated in parentheses are for information only.

2.11 Inch-pound products. Products manufactured to inch-pound dimensions will be considered on an equal basis with those manufactured using metric units, providing they fall within the tolerances specified and all other requirements of this document are met. If a product is manufactured to inch-pound dimensions and those dimensions exceed the tolerances specified in the metric units, a request should be made to the contracting officer to determine if the product is acceptable.

3. REGULATORY REQUIREMENTS

3.1 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. QUALITY ASSURANCE PROVISIONS

4.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5. PACKAGING.

5.1 Packaging. Packaging, packing, and marking shall be as specified in the contract or purchase order.

6. NOTES

6.1 Part Identification Number (PIN). Floor mats conforming to this commercial item description are identified by a part number configuration consisting of a portion of the CID number, class, style and size. An example of the part number configuration is shown below. This part numbering system is intended for identification and cross-indexing of the item within the Federal cataloging system. The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.

AA28541B1 Example: (AA28541B1) = Class 1, Style B, Size 1 - 430mm X 710mm

- AA28541B1
  - 1 = Size 1, 2 3, 4 or 5
  - B = Style A or B
  - 5 = Class 1, 2, or 4
  - 4 = Commercial item description number.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number and date of this commercial item description.
b. Class, style and size of mat required.
c. Color of Class 1 or 4 mat.
d. The packaging, packing, and marking desired.

6.3 Referenced National Stock Number (NSN). The following is a list of NSN's assigned which correspond to this CID. The list may not be indicative of all possible NSN's associated with the CID.

NSN number	Class	Style	Size	Part
7220-00-224-6486	2	A	5	AA28542A5
7220-00-238-8852	2	A	2	AA28542A2
7220-00-238-8854	1	A	1	AA28541A1
7220-00-823-7409	4	B	3	AA28544B3
7220-00-823-7412	4	B	4	AA28544B4

MILITARY INTERESTS:

NONE: DOD has determined that no military activity has an official interest in this commercial item description.

Preparing Activity:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.