[METRIC]
A-A-2883A
May 31, 1996
SUPERSEDING
A-A-2883
June 22, 1994

COMMERCIAL ITEM DESCRIPTION

CLOCKS, WALL (QUARTZ CRYSTAL-BATTERY OPERATED)

The General Services Administration has authorized the use of this commercial item description as a replacement for Interim Federal Specification GG-C-001072 which has been canceled.

1. SCOPE. This description covers quartz crystal, battery powered wall clocks having plastic 'slimline' cases.

2. CLASSIFICATION. The clocks shall be furnished in three dial face sizes (diameters) and three dial face types, as specified.

Size I - 20 cm (7.87 in.)
Size II - 30 cm (11.81 in.)
Size III - 16 cm (6.30 in.)

Type A - 12 Hour
Type B - 24 Hour (Single ring)
Type C - 24 Hour (Double ring)

3. SALIENT CHARACTERISTICS.

3.1 General. Clocks shall be completely assembled and ready for operation, requiring only the insertion of one "AA" type dry cell battery (preferably alkaline). It shall not be necessary to perform periodic adjustments to obtain the timing accuracy specified in 3.9.

3.2 Tolerances. The tolerance on dial face diameters for Sizes I and II clocks shall be +/- 2 cm (0.79 in.). For Size III clocks, the tolerance shall be +/- 1 cm (0.39 in.).

3.3 Mounting. The clock unit shall be equipped with a concealed hanging device, suitable for hanging the clock

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited. FSC 6645

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

flush with the wall. Size III clocks shall be supplied with two types of hanging devices: (1) a built-in hook type hanging device, and (2) a velcro-type hanging device suitable for attaching the clock to the fabric surfaces of workstation partitions; the velcro-type device shall allow for secure, non-permanent attachment of the clock such that it can be readily repositioned, as needed, on the fabric surface.

3.4 Cases. Cases shall be of the 'slimline' design, fabricated of plastic and molded in one of the following colors, as specified: bronze, black, white, stone gray, and taupe.

3.5 Dials. Dials shall be fabricated of plastic, white or clear in color, as specified. Markings shall be black in color on white dials or white in color on clear dials. Minute marks shall appear between the numerals.

3.5.1 For Type A & C clocks, the dial shall register 12 hours in one revolution of the hour hand taking 12 hours and one hour in one revolution of the minute hand. All numerals for each hour shall appear on the dial, with the numeral 12 appearing at the top of the dial.

3.5.2 For Type B clocks, the dial shall register 24 hours in one revolution of the hour hand taking 24 hours and one hour in one revolution of the minute hand. The numeral 00 shall appear at the top of the dial in accordance with the manufacturer's standard practice.

3.5.3 For Type C clocks, the dial face shall have an outer ring marked 1-12 and an inner ring marked 13-24, indicating the hours, in accordance with the manufacturer's standard practice. The numerals 12 and 24 shall appear at the top of the dial.

3.6 Dial covers. Dial covers shall be of clear, non-yellowing plastic and be securely positioned to prevent accidental separation.

3.7 Hands. Minute and hour hands shall be black or white, as specified; the second hand shall be a distinguishing color. The length of the hands shall be measured from the center of the shaft hole to the tip of the longest hand side and shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

Dial Size (cm)	Minute Hand Min cm(in)	Minute Hand Max cm(in)	Hour Hand Min cm(in)	Hour Hand Max cm(in)	Second Hand Min cm(in)	Second Hand Max cm(in)
16	5.9 (2.3)	6.5 (2.55)	2.6 (1.0)	4.4 (1.7)	4.4 (1.7)	6.5 (2.55)
20	8.0 (3.1)	8.5 (3.3)	3.6 (1.4)	5.6 (2.2)	5.9 (2.3)	7.1 (2.8)
30	12.0 (4.7)	12.7 (5.0)	5.4 (2.1)	9.1 (3.58)	7.3 (2.87)	9.1 (3.58)

3.8 Resetting. The clock shall have a simple means of resetting.

3.9 Accuracy. The clock shall be accurate to +/- 1 second per 72 hours.

3.10 Workmanship. The units shall be of sufficient quality to ensure trouble-free operation for at least one year. The clock shall operate without objectionable noise or hum and shall not develop such from normal usage. All components shall be compatible, properly fitted and securely attached. The clocks shall be free from rough edges or other defects which may injure the user, impair the smooth operation of the clock, or impair serviceability. Defects which affect the readability of the clock dial from a distance of 2 meters (6.56 feet) shall not be allowed.

4. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulations (FAR).

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The products provided shall conform to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

5.2 The clocks shall be 100% visually inspected and 100% functional tested for a minimum of 4 hours. Final lot sampling tests shall be performed in accordance with ANSI/ASQC Z1.4, "Sampling Procedures and Tables for Inspection by Attributes". The inspection level shall be S-2 with an AQL not greater than 4.0% defective.

5.3 First article sample(s). First article sample(s) for type III clocks only, shall be subjected to the test procedure specified in 5.3.1. A failure of any first article sample to pass the test shall be cause for rejection.

5.3.1 Test procedure for Type III clocks. Two (2) 1-inch by 5/8-inch strips of velcro hook material shall be pressed firmly onto the clock body and allowed to sit for 5 hours before any testing is started. The clock with velcro strips shall then be pressed onto the surface of a loose fiber fabric covered wall divider. A three (3) pound weight shall be suspended from the clock for a period of 5 minutes. The weight shall hang parallel to the surface of the wall divider and if possible shall not touch the wall. The velcro strip shall not come loose from the divider during this time period. Remove the weight from the clock, then remove and reattach the clock to the fabric divider a total of 50 times. A 1.2 pound weight shall be suspended from the clock body and allowed to hang for 7 days. The weight shall hang parallel to the surface of the divider. The velcro strips shall not come loose from the cloth divider or the clock body during this time period.

6. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES.

7.1 Purchasers shall specify by size, type, case color, dial color, color of markings/hands and NSN, as follows:

Size I, Type A, Bronze case, White dial, Black markings/hands, NSN 6645-01-046-8848
Size I, Type A, Black case, White dial, Black markings/hands, NSN 6645-01-389-7956
Size I, Type A, White case, White dial, Black markings/hands, NSN 6645-01-389-7961

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:27Z
Check the source to verify that this is the current version before use.

Size I, Type A, Taupe case, Clear dial, White markings/hands, NSN 6645-01-421-6909
Size I, Type A, Stone Gray case, Clear dial, White markings/hands, NSN 6645-01-421-6905
Size I, Type B, Bronze case, White dial, Black markings/hands, NSN 6645-01-342-5313
Size II, Type A, Bronze case, White dial, Black markings/hands, NSN 6645-01-046-8849
Size II, Type A, Black case, White dial, Black markings/hands, NSN 6645-01-389-7944
Size II, Type A, White case, White dial, Black markings/hands, NSN 6645-01-389-7951
Size II, Type A, Taupe case, White dial, Black markings/hands, NSN 6645-01-421-6898
Size II, Type A, Stone Gray case, White dial, Black markings/hands, NSN 6645-01-421-6901
Size II, Type B, Bronze case, White dial, Black markings/hands, NSN 6645-01-342-5314
Size II, Type C, Bronze case, White dial, Black markings/hands, NSN 6645-01-342-8199
Size III, Type A, Taupe case, Clear dial, White markings/hands, NSN 6645-01-421-6900
Size III, Type A, Stone Gray case, Clear dial, White markings/hands, NSN 6645-01-421-6899

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:27Z
Check the source to verify that this is the current version before use.