[METRIC]

A-A-304C
January 16, 1998
SUPERSEDING
A-A-304B
November 27, 1991

COMMERCIAL ITEM DESCRIPTION

BAG, PAPER (HOSPITAL BEDSIDE WASTE)

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. SCOPE. This description covers flame & moisture resistant paper bags with pressure sensitive adhesive attachment tabs. These bags are primarily designated for hospital bedside use. The bags shall be of the following types, as specified.

Type I - Moisture resistant
Type II - Moisture & heat resistant

2. SALIENT CHARACTERISTICS.

2.1. Construction. Bags shall be formed with a lip not less than 13 mm wide across the entire width of the back face. Seams, made with a water resistant adhesive, shall be located on the back face and, if needed, on the bottom of the bags. Two pressure sensitive adhesive tabs shall be attached at the top of the back face with their center lines 85 ± 15 mm apart. Each tab shall extend beyond the top edge of the bag to provide an area of not less than 325 mm^2 for attaching the bag to horizontal surfaces. The adhesive in the attachment area shall be protected with an easily removable piece of release paper. Bags shall be no more than 2 months old when delivered to the Government.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document, should be sent to: General Services Administration, Federal Supply Service, 26 Federal Plaza, New York N.Y. 10278 ATTN: Engineering Branch (2FYEE).

FSC 8105

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.

2.2. Materials. Type I bags shall be made of latex reinforced kraft paper and be capable to withstand moisture exposure in accordance with normal commercial practice. Unless otherwise specified, Type II bags shall be made of the following options, at the choice of supplier:

Option 1 - Kraft paper, 48.8 g/m^2 (30lb) basis weight minimum, laminated to aluminum foil with a water/heat resistant adhesive. The aluminum foil side of the laminate shall be on the inside of the bags.

Option 2 - Kraft paper, 48.8 g/m^2 (30lb) basis weight minimum, with Mylar brand or equivalent inner coating. The inner layers shall consist of the following:

Layer 1 - 16.3 g/m^2 (10lb) basis weight LDPE
Layer 2 - 0.0072 mm (0.000285") metal foil
Layer 3 - 32.5 g/m^2 (20lb) basis weight LDPE

* LDPE - Low density polyethylene

2.3. Physical characteristics. Before the paper is laminated for Type II bags, it shall be tested for Flame Resistance in accordance with TAPPI T 461 as Type I paper. The Char Length determined by this test shall be not more than 110 mm. The laminated material shall have an Internal Tearing Resistance in the machine direction of not less than 52 grams when tested in accordance with TAPPI T 414.

2.4. Style and capacity. Bags shall be square style or self opening style, at the option of the supplier. The face width shall be not less than 152 mm (6"). The gusset width or the bottom width, which equals 1/2 the perimeter of the top of the bag minus the face width, shall be not less than 76 mm (3"). Unless otherwise specified, the overall height shall sufficient to give a bag capacity of not less than 3.25 Liters. Bag capacity shall be determined through the following equations:

F = face width
P = perimeter of the top of the bag
H = overall height of the bag (excluding the lip)

Capacity of square bags = $F[0.5P - F][H - (0.25P - 0.5F)]$
Capacity of self opening bags = $F[0.5P - F][H]$

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.

2.5. Special Markings. Bags shall have the following legends printed on them in an easily legible color & size in accordance with normal commercial practice. On the back face, below each tab, an arrow pointing up and the legend: **"PULL TAB UPWARD"** shall be printed. The front face, for Type I bags, shall have the legend: **"MOISTURE RESISTANT"**. The front face, for Type II bags, shall have the legend: **"MOISTURE AND FLAME RESISTANT"** printed on it.

2.6. Workmanship. Bags shall be uniformly constructed, free from holes, tears, cuts, splits or defects that might impair their usefulness or appearance. Bags shall not adhere together. All seams shall adhere firmly throughout their area.

3. QUALITY ASSURANCE.

3.1. Product conformance. The product provided shall meet the salient characteristics of this commercial item description, conform to producer's own drawings, specifications, standards, and quality assurance practices and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

3.2. Testing.

Holding Strength and Leakage Test. Attach the bag firmly to the edge of a smooth horizontal surface so that the bag hangs freely from the edge supported only by the pressure sensitive adhesive tabs. Place 225 ± 5 grams of commercial type facial tissues in the bag and carefully pour 225 ± 5 milliliters of water over the tissues. Let the bag hang undisturbed for not less than 16 hours, then examine the bag. If the attachment tabs no longer support the bag, or if water has leaked through the bag, the bag is defective.

4. REGULATORY REQUIREMENTS. The contractor shall certify that the paper used in the manufacture of this item contains a minimum of 5% Post Consumer Material (PCM) in accordance with Title 40 of the Code of Federal Regulations Part 247, Comprehensive Guideline for Procurement of Products Containing Recovered Materials; Final Rule. The Government reserves the right to require proof of such conformance prior to first delivery, and thereafter as may be otherwise provided for under the provisions of the contract.

5. PACKAGING, PACKING, MARKING, AND PALLETIZATION. Packaging, packing, marking, and palletization shall be as specified in the contract or purchase order.

6. REFERENCED DOCUMENTS. The issues of the referenced documents in effect on the date of the solicitation for offers or request for proposals shall be used to determine conformance with the requirements of this Commercial Item Description.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:06Z
Check the source to verify that this is the current version before use.

6.1. CFR, Title 40, Code of Federal Regulations, Protection of the Environment, Part 247. Copies may be purchased with a VISA, Master Card or prepaid check through: Government Printing Office, Washington DC; Phone 202-783-3238. When ordering ask for: Title 40, Parts 190-250; Stock Number: 869-013-00-146-0.

6.2. Industry Standards, TAPPI are available from TAPPI, 15 Technology Parkway South, P. O. Box 105113, Atlanta, GA 30348.

7. Notes.

7.1. Ordering data. Purchasers shall specify the following in the contract or purchase order:

7.1.1. Title, number, and date of this document.
7.1.2. Type of bag required.
7.1.3. Dimensions, capacity.
7.1.4. Packaging, packing, marking & palletization required.

7.2. List of NSNs:

8105-00-726-2242

MILITARY INTERESTS:

No official DOD interest in this Commercial Item Description has been registered.

CIVIL AGENCY COORDINATING ACTIVITY:

VA - OSS

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.