AA-C-00288b(GSA-FSS)
April 1, 1968
SUPERSEDING
AA-C-00288a(GSA-FSS)
May 24, 1965

INTERIM FEDERAL SPECIFICATION

CHAIRS, FOLDING, WOOD, WITHOUT ARMS

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20405, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE

1.1 This specification covers the requirements for one type of wood folding chair without arms.

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following specifications and standards of the issue in effect on the date of the invitation for bids form a part of this specification to the extent specified herein.

Federal Specifications

CCC-A-680 - Artificial Leather (Cloth Coated), Vinyl Resin, Expanded Layer, (Upholstery).

PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple-Wall.

Federal Standards

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).
Fed. Std. No. 175 - Adhesives: Methods of Testing.
Fed. Std No. 601 - Rubber. Sampling and Testing.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S Government Printing Office, Washington, D C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications

MIL-R-5001 - Rubber, Latex Foam Sponge.
MIL-W-6110 - Wood, Determination of Moisture Content of.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

Military Standards

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Commercial Standards:

CS35-61 - Hardwood Plywood.
PS 1-66 - Softwood Plywood.

(Copies of the Commercial Standards referenced above, which are Department of Commerce Publications, may be obtained upon application, accompanied by money order, coupon or cash, to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402. Prices may be obtained from the Superintendent of Documents).

American Society for Testing and Materials (ASTM)

ASTM Designation D 1564-64T - Tentative Specifications and Methods of Test for Flexible Urethane Foam.

(Copies may be obtained upon application to American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103).

3. REQUIREMENTS

3.1 Preproduction sample. Unless otherwise specified (see 6.2), before production is commenced, a sample of the finished item and each component part conforming to the requirements of this specification shall be offered for approval of the contracting officer or his authorized representative. Approval of the preproduction sample authorized the commencement of production, but does not relieve the contractor of responsibility for compliance with all applicable provisions of this specification.

3.2 Materials. The materials used in construction of the chairs shall be of the kind and quality specified herein.

3.2.1 Adhesives. The adhesives to be used and their permitted application shall be as shown in Table I.

TABLE I. Adhesives

Application	Kind of adhesives
All assembly joints, glued laminated stock.	Any adhesive that will develop an average block shear strength of not less than 2,800 pounds per square inch when tested as specified in 4.3.1.1.

3.2.2 Wood.

3.2.2.1 Solid wood. The woods used in the construction of the exposed components shall be northern maple, magnolia, beech, and northern hard birch.

3.2.2.2 Characteristics. The solid wood used for exposed parts shall be bright, well sanded and free from brashness, discolorations, worm holes, honeycomb, splits, and shake and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

other defects which will affect its strength or serviceability. The wood for steam bent parts shall be selected from straight grained uniform stock.

3.2.2.3 Seasoning. All component solid wood parts shall be uniformly kiln-dried to a moisture content of from 6 to 9 percent. They shall be held in properly controlled dry warm storage for a sufficient time to insure uniform distribution of moisture among the pieces. Moisture content shall be determined in accordance with MIL-W-6110.

3.2.2.4 Plywood. Plywood shall be as specified herein and shall be dried to a moisture content not to exceed 12 percent. Moisture content shall be determined in accordance with MIL-W-6110.

3.2.2.4.1 Softwood plywood. Softwood plywood shall be interior type, grade C-D (plugged) sanded 2 sides, group 1, conforming to Product Standard PS 1-66.

3.2.2.4.2 Hardwood plywood. Hardwood plywood shall be constructed according to the requirements of Commercial Standard CS35-61 and as specified herein. Bondage shall be not less than type II. All exposed faces shall have grade 1 veneer plies.

3.2.3 Dowels. Dowels shall be of beech, birch, hickory, or maple and shall be dried to a moisture content not to exceed 5 percent at time of assembly. They shall be spirally and longitudinally grooved. Dowels shall have a minimum diameter of 3/8 inch and the length shall be not less than 4 times the diameter.

3.2.4 Steel. Steel shall be commercial quality, cold rolled, hot rolled pickled and oiled or hot rolled annealed. The steel shall be smooth, free of scale, pits, wrinkles, laps, crimps, and buckles affecting strength or appearance.

3.2.5 Padding material. Unless otherwise specified (see 6.2), padding for chair seats and backs shall conform to any of the following:

3.2.5.1 Bonded shredded cellular rubber. The bonded shredded cellular rubber shall be medium condition, uncored (slab) stock. The individual shredded cellular rubber particles of which the material is composed shall not be over 3/8 inch in diameter. The shredded rubber shall have a vulcanized interconnecting cellular structure with a porous surface and shall be bonded with a suitable adhesive. The density in pounds per cubic inch shall be 0.0065 minimum to 0.0085 maximum. The material shall be free from any objectionable odor, from large voids or seams. The bonded material shall withstand the flexing test specified in Table III without breakdown of physical structure. The set after the specimen has remained at rest for 1 hour shall be not greater than 15 percent. The bonded material shall withstand the accelerated aging test specified in table III without suffering a change in compression resistance greater than 15 percent. The padding shall be in one piece and the minimum thickness shall be 1/2 or 3/4 inch as specified herein.

3.2.5.2 Slab stock latex foam rubber. Slab stock latex foam rubber padding shall conform to type II medium, grade C (grade RC-55 of ASTM D 1055) of MIL-R-5001, except that compression resistance shall be determined by method A in lieu of method B as specified, and low temperature requirement shall be waived. The material shall be in one piece and the minimum thickness shall be 1/2 or 3/4 inch as specified herein.

3.2.5.3 Polyurethane foam. Polyurethane foam shall be grade US 34 and shall conform to the requirements of table II when tested as specified in 4.3.2.1 and the applicable sections of ASTM D 1564-64T. Material shall be in one piece and the minimum thickness shall be 1/2 or 3/4 inch as specified herein.

TABLE II. Physical properties of polyurethane foam

Property	Requirement
25 percent indentation load deflection; pounds	34 ± 4
Indentation load ratio (65 percent/25 percent); minimum	1.9
Original compression set 22 hours/158 degrees F., 90 percent deflection; percent maximum	15

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

TABLE II. Physical properties of polyurethane foam (con't)

Property	Requirement
Steam autoclave test (condition B)	
Percent change in 25 percent compression load deflection; percent maximum	± 20
Compression set 22 hours/158 degrees F. 90 percent deflection; percent maximum	20
Fatigue test	
25 percent Indentation load ratio loss; percent maximum	30
Thickness loss; percent maximum	5
Density, lbs. per cubic foot, minimum	1.8

3.2.5.4 Cellulose fiber. Cellulose fiber shall have a density of 2 pounds per cubic foot. It shall be new material, felted and bonded into a homogeneous mat. The minimum thickness shall be 1/2 or 3/4 inch as specified herein. Commercial tolerances will be acceptable.

3.2.6 Artificial leather. The artificial leather shall conform to class 1 or 2 of CCC-A-680. The requirements for treatments (a) 1, and (b) must be met either by inherent characteristics or treatments. The finish shall be that of simulated top grain leather and the color shall be selected from those specified in 3.5.3 (see 6.2).

3.2.7 Glides. Glides shall be of case hardened nickel, chrome plated steel or corrosion resistant steel. They shall be of the nail or three-prong type and shall have a minimum diameter of 3/4 inch.

3.3 Construction. The chair shall consist essentially of a back section, seat section, front leg section and a folding mechanism. The chair shall be constructed of solid hardwood frames and shall have an upholstered back and seat. With the exception of plywood seat and back panels and plywood seat frame when used, the chair shall be made of like species of wood throughout. Each chair shall be furnished with glides.

3.3.1 Design. When in set-up position, the chair shall form a side-type chair with all legs in a vertical position. The structural design shall be such that any sustained or impact weight shall be distributed uniformly on all supporting parts with no excessive strain under normal usage. The design shall be such that one person can easily unfold and fold the chair. The chair shall fold compactly to permit stacking directly over one another in a free standing pile.

3.3.2 Dimensions. The dimensions of the chair shall be as follows:

Overall height	32-3/8 inches, minimum
Height of seat from floor	18 inches ± 1/2 inch
Back panel	112 square inches, minimum
Seat panel	200 square inches, minimum

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

3.3.3 Tolerances. The following tolerances will be permitted, except where otherwise indicated:

(a)	Dimension of any solid wood part	- plus or minus 1/8 inch.
(b)	Dimension of any plywood part	- plus or minus 1/16 inch.
(c)	Any dimension, not otherwise specified	- Plus or minus 1/8 inch.

3.3.4 Folding mechanism. The folding mechanism shall be of steel, specified in 3.2.4, and shall be a strong, simple, and efficient device capable of being operated with a minimum of effort without the use of tools. The parts of the folding mechanism shall be securely joined together. Folding shall be accomplished by raising either the front or the rear of the seat section, which will cause the upholstered top of the seat or the underside of the seat to fold against the back and cause the front legs to fold in the direction of rear legs so as to permit compliance with the stacking requirement in 3.3.1. The folding mechanism shall be designed to guard against injury and snagging the user's clothing. The surfaces of the mechanism shall be finished as specified in 3.4.2.

3.3.5 Joinery and assembly. Unless otherwise specified herein, all joints shall be tongued and grooved, mortised and tenoned, mitered and splined, or doweled using dowels, specified in 3.2.3. All joints shall be carefully fitted, thoroughly glued, using adhesives specified in 3.2.1. All exposed edges shall be eased to a minimum of 1/16 inch radius.

3.3.6 Seat frames (rails). Seat frames shall be of solid wood, specified in 3.2.2.1, and shall be not less than 3/4 inch thick by 1-5/16 inches high. The frames shall be joined at the corners by tongue and groove joints, full width of material, or by miter and spline, and glued. Alternatively, the frames may be of 7-ply (minimum) hardwood plywood, specified in 3.2.2.4.2, or of steam bent wood (3/4 by 1-5/16 inches) attached to a notched header block by screws and glue. The header block shall be recessed at both ends, in each of which a front leg shall pivot on a 3 inch by No. 16 size screw. The header block shall be 2 inches thick by 1-5/16 inches high.

3.3.7 Back posts. Back posts shall be of solid wood, specified in 3.2.2.1, and shall be not less than 3/4 inch thick by 1 inch wide at the narrowest point. They shall be steam bent to a uniform shape or band sawed from built-up stock and uniformly shaped. Each back post shall be equipped with a glide specified in 3.2.7.

3.3.8 Front legs. Front legs shall be of solid wood, specified in 3.2.2.1, and shall be not less than 15/16 inch thick by 1-1/8 inches wide at the narrowest point. They shall be straight, shaped or tapered. Alternatively, the front legs may be 7/8 inch thick by 1-3/8 inches wide. Each front leg shall be equipped with a glide specified in 3.2.7.

3.3.9 Stretchers (rungs). Stretchers shall be of solid wood, specified in 3.2.2.1, and shall be not less than 3/4 inch square finished. The joining of the stretchers to the back posts or front legs shall be by glue and mortise and tenon or dowels. There shall be two stretchers, properly placed, in each back post and two stretchers in each front leg. Alternatively, one stretcher, 13/16 inch thick by 1-1/2 inches wide, may be used to join the front legs.

3.3.10 Seat panel. Seat panel shall be of 3-ply (minimum) plywood, specified in 3.2.2.4, and shall be not less than 5/16 inch thick. The plywood seat shall be covered with a 3/4 inch (minimum) thick layer of padding material, specified in 3.2.5, a thin layer of cotton, and a final covering of artificial leather, specified in 3.2.6. The final covering shall be secured to the underside of the seat panel by tacks or staples. The seat panel shall be of the slip-seat type and shall be attached in a manner to permit easy removal, recovering, and replacement without special tools.

3.3.11 Back panel. Back panel shall be of 5-ply (minimum) plywood, specified in 3.2.2.4, and shall be not less than 5/16 inch thick. Back panel shall be curved to shape. The inside face of the plywood back shall be covered with a 1/2 inch (minimum) thick layer of padding material, specified in 3.2.5, a thin layer of cotton, and a final covering of artificial leather, specified in 3.2.6. The final covering shall be neatly turned around all edges of the back panel and the outside face of the panel shall be covered with

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

a layer of cotton and a final covering of artificial leather, specified in 3.2.6. The finished back shall be secured to the front of the back posts by screws or bolts. The screws or bolts shall be of sufficient length to penetrate the plywood back panel a minimum of 3/4 of its thickness and there shall be not less than two screws or bolts in each back post. The screw or bolt heads shall be countersunk and concealed by carefully matched flush wood plugs. Alternatively, wood button or brass plugs may be used in lieu of flush wood plugs. The wood button and brass plugs shall be finished the same as the wood surfaces of the chair. Alternatively, the back panel may be of built-up stock. With the exception of an exposed wood border 3/4 inch wide, the inside face of the back panel shall be padded to conform to the outline of the panel. The padded area shall be covered with a 1/2 inch (minimum) thick layer of padding material, specified in 3.2.5, a thin layer of cotton, and a final covering of artificial leather specified in 3.2.6. The upholstery material shall be stapled into a routed outline, with a plastic spline, approximately 1/4 inch in diameter, covering the staples and adding a decorative frame for the upholstery. The outside face of the back panel and the exposed wood border shall be finished as specified in 3.4.1. The finished back shall be secured to the front of the back posts by screws or bolts. The screws or bolts shall be of sufficient length to penetrate the back panel a minimum of 3/4 of its thickness and there shall be not less than two screws or bolts in each back post. The screw or bolt heads shall be countersunk and concealed by carefully matched flush wood plugs. Alternatively, wood button or brass plugs may be used in lieu of flush wood plugs. The wood button and brass plugs shall be finished the same as the wood surfaces of the chair.

3.4 Finish.

3.4.1 Wood surfaces. All wood surfaces of the chair shall be stained, sealed and lacquered or varnished. Chairs shall be evenly finished and sanded between coats. The finishing procedures shall be controlled to produce smooth, uniform surfaces without blisters, pits, wrinkles, runs, tackiness, or more than a trace of orange peel.

3.4.2 Metal surfaces (folding mechanism). A minimum of one coat of lacquer or baking enamel shall be applied to all metal parts of the folding mechanism. The finish shall level out to produce smooth, uniform, exposed surfaces without runs, wrinkles, grit, areas of thin film or no film, and separation of color.

3.5 Color and appearance of finish.

3.5.1 Wood. The color and appearance of the finish of exposed wood surfaces shall be walnut and shall conform to the standard reference panel adopted by Federal Supply Service, General Services Administration for color, texture, and gloss (see 6.3).

3.5.2 Metal (folding mechanism). The color of the finish of metal surfaces shall be black or brown.

3.5.3 Artificial leather. The color of the artificial leather shall be green, FSS-35-3-AL, black, FSS-85-3-AL, tangerine, FSS-15-3-AL, and tan, FSS-70-3-AL. The color, finish, gloss, texture, and appearance shall conform to the standard samples as adopted by the Federal Supply Service, General Services Administration (see 6.3).

3.6 Stability. When in use position, the chair shall not collapse when the weight of the occupant is shifted from one area of the seat to another. Set-up chairs shall be free from excessive play. Chairs shall be capable of being stacked neatly at least ten chairs high, when folded without evidence of shifting or collapsing of the stack.

3.7 Identification marking. Each chair shall be permanently and legibly marked in an inconspicuous place with the specification number, Federal Stock Number, contract number, date of manufacture and the manufacturer's name or trade-mark so that the source of supply may be readily determined.

3.8 Workmanship. The workmanship shall be of a quality to assure sturdiness of construction that will not impair the safety of the occupant, ease of operation and accuracy of moving parts, the stacking feature, and smoothness of materials and finish. Upholstery covers shall be so applied that they are neat and tight, free from wrinkles and bulges.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS.

4.1 General quality assurance provisions.

4.1.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.2 Government verification. All quality assurance operations performed by the contractor shall be subject to Government verification at unscheduled intervals. Verification shall consist of surveillance of the operations to determine whether the practices, methods, and procedures of the written inspection plan are being properly applied, and Government product inspection, to measure quality of product offered for acceptance. Deviation from the prescribed or agreed-upon procedures, or instances of poor practices that might have an effect on the quality of the product will be immediately called to the attention of the contractor. Failure of the contractor to promptly correct the deficiencies discovered shall be cause for suspension of acceptance until the correction has been made or until conformance of product to prescribed criteria has been demonstrated. To avoid interference with operations, the contractor shall designate a responsible official, or officials, to whom the Government inspector will report such instances.

4.2 Preproduction sample inspection. Examination and testing shall be made on the completely fabricated chair for all provisions of this specification.

4.3 Sampling for inspection and acceptance. Sampling and inspection shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Inspection of materials and components. In accordance with 4.1, the supplier is responsible for insuring that materials and components used were manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified, or if none, in accordance with this specification.

4.3.1.1 Testing of components. In addition to the quality assurance testing provisions of the subsidiary specifications, testing of the components shall be performed in accordance with Table III for the characteristics shown therein. The values specified in section 3 of this specification apply to the average determinations made on a sample unit for test purposes as specified in the applicable test method. When the sample size for components covered by the subsidiary specifications is not specified, the sample size for each characteristic shall be in accordance with inspection level S-2 of MIL-STD-105 except that for the lot sizes of 501 (units of products) and over the sample size shall be 5. The lot shall be unacceptable if one or more sample units fail to meet any of the requirements specified.

TABLE III. Instructions for testing components and materials

Component	Characteristic	Requirement Reference	Test Method	Sample Unit
Adhesive	Block shear test	3.2.1	1031 of Federal Test Method Std. No. 175 1/ 2/ 3/	1/2 pint
Polyurethane foam	All characteristics	3.2.5.3	As listed in ASTM Designation D-1564-64T	4 seat pans
Bonded shredded cellular rubber	Flexing endurance	3.2.5.1	12111 of Federal Test Method Std. No. 601	4/
	Accelerated aging	3.2.5.1	12211 of Federal Test Method Std. No. 601	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

1/ The following modifications apply when testing casein-type adhesive. The test blocks shall be placed under pressure between 10 and 20 minutes after spreading the adhesive, the adhering pressure shall be 175 ± 25 pounds per square inch, and the test blocks shall be held under pressure for at least four hours.

2/ The following modifications apply when testing animal adhesive. The moisture content of the wood shall be from 6 to 9 percent. The joints shall be conditioned at a relative humidity of 40 ± 4 percent.

3/ Whenever a specimen fails at a load of less than 2,800 pounds per square inch and the failure occurs 50 percent or more in the wood, the specimen shall be disregarded in computing the average. In case the shearing strength of one or more specimens is 2,800 pounds per square inch or higher, the variation among individual specimens is 10 percent or more (based on the strongest joint) the test shall be run again, provided the average is less than the required 2,800 pounds per square inch.

4/ The sample unit shall be of sufficient size to conduct all tests required.

4.3.2 End item inspection.

4.3.2.1 Visual examination of the end item. The lot size shall be expressed in units of completed chairs. The inspection level for purposes of determining the sample size shall be level II of MIL-STD-105. The unit product shall be one completed chair. The defects found during the examinations shall be classified in accordance with Table IV. The acceptable quality level (AQL) shall be 4.0 for major defects and 10.0 for total defects (major and minor combined) per hundred units.

TABLE IV. Classification of end item defects

Examine	Defect	Major	Minor
		Classification	
Material	Species of wood not as specified.	X	
	Plywood not as specified.	X	
	Dowels not as specified.		X
	Padding material not as specified.		X
	Glides not as specified.		X
Appearance, Construction, and workmanship	General design or styling not as specified or not as on approved preproduction sample	X	
	More than one component missing.	X	
	One component missing.		X
	Component in wrong location.		X
	Component not size and shape specified affecting function or serviceability.	X	
	Component not assembled as specified.		X
	Component out of alignment or out of square affecting serviceability.	X	
	Component loose or insecurely fastened where rigidity is required.	X	
	Component not fabricated of one piece of solid wood where required.		X
	Wood warped, affecting appearance or serviceability.	X	
	Brashness, discoloration, worm hole, honeycomb, split, shake, or other defect which affects appearance or serviceability (wood).	X	
	Scale, pit, wrinkle, lap, crimp, or buckle, affecting strength or appearance (steel).	X	
	Any fracture in metal component.		X
	Loose or open joint in frame assembly.	X	
	Excess glue not removed, affecting appearance.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

TABLE IV. Classification of end item defects (Con't)

Examine	Defect	Major	Minor
		Classification	
Appearance, Construction, and workmanship	Glue line in built-up stock open over 1 inch in length.		X
	Glued-up pieces uneven in built-up stock.		X
	Exposed screw or bolt heads not countersunk when required.		X
	Any burr or sharp edge on metal component.		X
	Metal components not securely fastened in assembly.		X
	Folding members do not articulate freely without binding.	X	
	Any leg split.	X	
	Legs uneven (without glides), i.e., end item rocks more than 1/16 inch when placed on flat surface.	X	
	Seat panels not attached in a manner which will permit easy removal and replacement without the use of special tools.	X	
	Seat padding not uniform and of sufficient thickness.		X
	Any tack or other protuberance that can be felt through the upholstery.		X
	Upholstery not attached securely, uniformly, and neatly, any exposed raw edge of fabric.		X
	Any hole, tear, split, or other defect in upholstery which affects appearance or serviceability.	X	
	Finish does not match standard reference panel with respect to color.	X	
	Exposed corners and edges not eased when required.		X
	Any area of exposed wood surface not sanded to a smooth uniform finish.		X
	Color of finish not homogeneous.		X
	Run, blister, peel, flake, crack, or other defect in finish of exposed surfaces, affecting appearance.	X	
	Foreign matter embedded in surface of exposed area.		X
	Finish of hardware not uniform and complete over entire area.		X
	Finish tacky, i.e., not completely dry.	X	
	Chair not clean.		X
Identification marking	Text incomplete.		X
	Missing, incorrect or illegible.		X
	Marking in wrong location.		X

4.3.2.2 Dimensional examination. The lot size shall be expressed in units of chairs. The inspection level shall be S-2 of MIL-STD-105. The unit of product shall be one chair. Any external overall dimensions that are not within the specified tolerance shall be classified as a defect. The acceptable quality level (AQL) shall be 4.0 defects per hundred units.

4.3.3 Inspection of preparation for delivery requirements. An examination shall be made to determine that packaging, packing and marking requirements of Section 5 of this specification are complied with. Defects shall be scored in accordance with table V. The sample unit shall be one shipping container, fully packed, selected just prior to the closing operation. Closed shipping containers shall be examined for closure defects. The lot size shall be expressed in number of shipping containers. The inspection level shall be S-2 of MIL-STD-105 and the acceptable quality level shall be 4.0 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

TABLE V. Preparation for delivery defects

Examine	Defect
Markings (exterior and interior)	Incorrect; incomplete; illegible; omitted; of improper size, location, sequence, or method of application.
Materials	Any nonconforming component; component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components: such as incomplete closure of case liners, container flaps, loose or inadequate sealing, strapping or stapling; bulged or distorted containers.
Contents	Not as specified.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Each chair shall be individually wrapped and suitably cushioned or separated to prevent damage. Four chairs shall be completely bundled and secured with cotton twine. Each bundle shall be placed in a fiberboard box conforming to Type I or II, Class 2, Style RSC of PPP-B-636 or Grade A, Class 1, Style E of PPP-B-640. Boxes will be closed in accordance with the appendix to the applicable box specifications.

5.1.2 Level B. Chairs shall be packaged as specified in 5.1.1 except that the fiberboard container shall be Class 1.

5.1.3 Level C. Four chairs shall be packaged in accordance with the manufacturers standard commercial practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Chairs packaged in accordance with 5.1.1 will require no overpacking except for the application of steel strapping or fiber reinforced tape in accordance with the appendix of the applicable box specification. Properly closed and reinforced containers may be unitized on pallets to assure safe transportation. Chairs packaged in accordance with 5.1.3 will be packed in wood or wood elasted plywood boxes conforming to PPP-B-621 or PPP-B-601 respectively; closure and reinforcement shall be in accordance with the appendix of the applicable specification.

5.2.2 Level B. Chairs packaged in accordance with 5.1.1 shall require no overpacking.

5.2.3 Level C. Pack to provide physical protection during shipment to the first receiving activity. Containers and methods of blocking, bracing and cushioning shall conform to the Uniform Freight Classification rules and regulations as applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required by the contract or purchase order, marking of shipping containers shall be in accordance with Fed. Std. No. 123.

5.3.2 Military activities. In addition to any special marking required by the contract or purchase order, marking of shipping containers shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The intended use of the folding chairs covered by this specification is for auxiliary seating in open areas and to conserve space by capability of chairs to be stacked in storage areas.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) When preproduction sample is NOT required (see 3.1).
(c) Particular padding material if required (see 3.2.5).
(d) Color of upholstery material (see 3.2.6 and 3.5.3).
(e) Level of packaging (see 5.1).
(f) Level of packing (see 5.2).
(g) Marking requirements (see 5.3).

6.3 Standard sample. Sample panels of the standard color for the walnut finish and artificial leather are obtainable, without charge, from the Business Service Center, Regional Office Building, Federal Supply Service, General Services Administration, Washington, D. C. 20407, or from the Business Service Center of the nearest GSA Regional Office.

GSA DC 88 19882

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.