AA-C-295
INTERIM AMENDMENT-3
October 5, 1961

INTERIM AMENDMENT TO

FEDERAL SPECIFICATION

CHAIRS, ROTARY, STEEL TUBULAR

SPECIAL PURPOSE

This Interim Amendment was developed by the Standardization Division, Federal Supply Service, General Services Administration, Room 4920, Regional Office Building, 7th & D Streets, S. W., Washington 25, D. C., based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized Federal agencies to use this Interim Amendment as a valid exception to Federal Specification AA-C-295, dated August 5, 1955.

Page 1, paragraph 1.2.2, delete and substitute:

1.2.2 Color of finish.- Unless otherwise specified in the invitation for bids, the color of the chairs shall be Gray Color No. 26134 of Federal Standard 595.

(Color chip No. 26134 Gray, of Federal Standard 595 is obtainable from Business Service Center, General Services Administration, Federal Supply Service, Washington 25, D. C. or from Business Service Center of the nearest GSA Regional Offices.)

Page 1, Under Federal Specifications, delete "DDD-S-751 - Stitches; Seams and Stitching".

Page 1, Following "Federal Specifications" add:

Federal Standards:

Fed. Std. No. 102 - Preserving, Packaging and Packing Levels.
Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Use),
Fed. Std. No. 595 - Colors.
Fed. Std. No. 751 - Stitches, Seams, and Stitchings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

Page 1, Military Standards, after "MIL-STD-105" add:

"MIL-STD-109 - Inspection Terms and Definitions"

Page 2, paragraph 3.1.2, fourth line, change "flesh" to "flash".

Page 2, after paragraph 3.1.2, add the following:

3.1.2.1 Foam latex.- When removalbe seat and back covers are furnished, the pads shall be foam latex. The seat pad shall be 2 inches thick (commercial tolerance) and the back pad shall be 1 inch thick (commercial tolerance). The foam latex for seat pads shall be grade RC-25 and grade RU-20 shall be used for back pads, as specified in ASTM Specification Designation D1055-59T.

Page 2, paragraph 3.1.4.1, 19th line after "safety", add new sentence:

"Alternatively, the seat pan as specified in 3.2.2 and the spider may be a one unit permanent mold aluminum casting."

Page 4, paragraph 3.2.4, line 22 after "sockets" add "or the legs may be cast into the hub in a secure manner."

Page 4, paragraph 3.2.6, last sentence, delete "Federal Specification DD-S-751" and substitute "Fed. Std. No. 751".

Page 5, paragraph 3.3.1.3, 6th line after 3.1.2, add: "or foam latex as specified in 3.1.2.1"

Page 5, paragraph 3.3.1.4, fourth line, second column after 3.1.2 add: "or foam latex as specified in 3.1.2.1".

Page 9, paragraphs 4.1, 4.1.1, 4.1.2, 4.1.3, 4.2 and table I, delete in their entirety and substitute the following:

4.1 Sampling for lot acceptance.

4.1.1 Inspection lot.- Normally, the inspection lot size shall consist of all units submitted for inspection at one time.

4.1.2 Sampling for visual and dimensional Inspection.- Sampling shall be conducted in in accordance with Military Standard MIL-STD-105 and MIL-STD-109 shall be used for inspection terms and definitions.

4.2 Inspection.- The chairs shall be inspected to determine compliance with this specification as to workmanship, materials, design, details of construction, hardware, finish, tests, marking and packing. Inspection shall be made at any time during process of manufacture, or at point of delivery.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

4.2.1 Contractor inspection.- Unless otherwise specified herein, the supplier is responsible for the performance of all requirements prior to submission for Government quality control acceptance. Except as otherwise specified, the supplier may utilize his own facilities or any facilities acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order.

4.2.2 Contractor quality assurance system.- The contractor shall provide and maintain an effective quality assurance system acceptable to the Government covering the supplies furnished under this specification. Results of all examinations and tests performed under the contractor's quality assurance system shall be made available to the Government. A current written description of the quality control system shall be submitted to the Government prior to initiation of production. The written description will be considered acceptable then, as a minimum, it provides the quality assurance required by this specification and other documents referenced herein. The contractor will not be restricted to the inspection station or to the method of inspection listed provided that an equivalent control is included in the approved quality control procedure. In cases of dispute as to whether certain procedures of the system provides adequate assurance of acceptable products, the comparable procedure of the detailed specification will be used. The contractor shall notify the Government of and obtain approval for any change to the written procedure that affects the degree of reliability required by this specification or other documents referenced herein.

4.2.3 Government verification.- All quality assurance operations performed by the contractor shall be subject to Government verification at unscheduled intervals. Verification will consist of surveillance of the operations to determine whether the practices, methods, and procedures of the written inspection plan are being properly applied, and the Government product inspection to measure quality of product offered for acceptance. Deviation from the prescribed or agreed-upon procedures; or instances of poor practices which might have an affect upon the quality of the product will be immediately called to the attention of the contractor. Failure of the contractor to promptly correct deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to prescribed criteria has been demonstrated. To avoid interference with operations, the contractor shall designate a responsible official or officials to whom the Government inspector will report such instances.

4.3 Sampling for inspection and acceptance.- Sampling and inspection shall be performed in accordance with the provisions set forth in Military Standard MIL-STD-105, except where otherwise indicated herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

4.3.1 Visual examination for defects in finish, construction, workmanship and marking.- Examination of the end item shall be in accordance with the classification of defects furnished herein. The following AQL's expressed in defects per 100 units shall apply:

Major - 2.5%
Minor - 10.0%

Classification of Defects

Examination	Defects	Major	Minor
Finish Enamel	Wrong color, type or not uniform	X	
	Peeling, blistering flaky or other poor adhesion.	X	
	Tacky (not dry to touch)		X
	Stain, dirt, overspray of other discoloration.	X	
	Orange peel, runs, wrinkles, sags or cracks		X
	Touch-up not neat		X
	Foreign matter-embedded in finish	X	
	Scratches, abrasions, chips, dents, nick or bruise		X
	Area of no coating	X	
	Area of thin coating		X
	Wrong kind	X	
Hardware	Omitted, peeled, blistered, flaky, or other poor adhesion stained, tarnished or discolored.		X
	Casters not type specified	X	
	Bolts, nuts and lockwashers not plated		X
Workmans and Construction	Parts missing or damaged affecting use.	X	
	Welds missing or not sound (broken, cracked, burnt through, poor fusion, etc.)	X	
	Welds not ground smooth, protrudes or pits not filled (outside only)		X
	Spot welds not properly spaced or not of required member		X
	Sharp edges or projection that may cause injury or tear clothing.	X	
	Dimension not within tolerance		X
	Tubes where bent not true and even	X	
	Seat and back pads not latex foam under removable covers	X	
	Seat and back pads not of density specified		X
	Covers not artificial leather or fabric as specified	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

Classification of Defects (Cont'd)

Examination	Defects	Major	Miner
Workmans and Construction	Rubber bumpers under covers missing	X	
	Base tubes not size or thickness specified	X	
	Back frame does not provide for adjustment, horizontally and vertically	X	
	Adjustment of seat and back height not as specified or easily made		X
	Class 1 chair without back tilt adjustment	X	
	Identification marking missing incomplete, illegible or not permanent		X

Page 10, paragraph "4.3", renumber as "4.4" then through the specification where "4.3" is referenced, change to "4.4".

4.4.1 End item testing.- Testing shall be performed on each sample unit. The inspection level (sample size) shall be I-7, Military Standard MIL-STD-105 and acceptable quality level (AQL) shall be 6.5 percent defective. However, at no time shall the sample size be less than 3 units with number 0.

Page 10, renumber the following paragraphs:

"4.3.1" as "4.4.2", "4.3.1.1" as "4.4.2.1", "4.3.1.2" as "4.4.2.2", "4.3.1.3" as "4.4.2.3", "4.3.2" as "4.4.3" "4.3.3" as "4.4.4", "4.3.3.1" as "4.4.4.1", "4.3.3.2" as "4.4.4.2" and "4.3.3.3" as "4.4.4.3".

Page 10, after "Preparation for Delivery" add:

(Levels of preservation-packaging and packing protection used are defined in Federal Standard No. 102 (for civil agencies only.)

Page 10, paragraph 5.2, delete "(immediate use)" and substitute "level C".

Page 10, paragraph 5.3, delete "(storage)" and substitute "Level A or B"

Page 11, paragraph 5.3.2 after "Packaging" add: "level B".

Page 11, paragraph 5.4 after title add "Level D".

Page 11, paragraph 5.5 after title add "Level A".

Page 11, paragraph 5.6, delete and substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

5.6 Marking.

5.6.1 Civilian agencies.- In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with Federal Standard No. 123 and as specified in 5.6.3.

5.6.2 Military requirements.- In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with Standard MIL-STD-129 and as specified in 5.6.3.

Page 11, renumber present "5.6.1" as"5.6.3".

Page 11, paragraph 6.1, delete in its entirety and substitute:

6.1 Ordering data.- Procurement documents should specify the following:

(a) Class and size of chair (see 1.2.1).
(b) If other than standard color is required (see 1.2.2 of amendment).
(c) Type, class, and color of upholstery (see 3.1.3).
(d) If chair parts to be marked to conform to MIL-STD-130.
(e) If contractors inspection is not required (see 4.2.1).
(f) Level of Packaging and Packing required (see 5.1).
(g) If civilian or Military mraking is required (see 5.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.