AA-F-00300(GSA-FSS)
March 9, 1965

INTERIM FEDERAL SPECIFICATION

FILES, ROLL DRAWING

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20407, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers commercially designed files containing cylindrical tubes for the filing of rolled drawings, tracings, blueprints or other documents.

1.2 Classification

1.2.1 Capacity. The files covered by this specification shall be of the capacity specified (see 3.2.1 and 6.2).

2. APPLICABLE SPECIFICATIONS, STANDARDS AND OTHER PUBLICATIONS

2.1 Specifications and Standards. The following specifications and standards of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein.

Federal Specification:

PPP-T-495 - Tubes, Mailing and Filing

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).
Fed. Std. No. 595 - Colors

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-130 - Identification Marking of U. S. Military Property

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. The materials shall be as specified herein. Materials not otherwise referenced to a standard of quality shall be those used in the commercial product of the supplier.

3.2 Design and construction

3.2.1 Filing Units. Except as specified herein, the files shall be constructed of not less than 22 gage furniture steel. They shall be interlocking units, closed on all sides and at the rear. The files shall be designed to hold tubes that conform to 3.2.2 and shall be furnished filled to capacity therewith. The file capacity, as expressed by the quantity and dimensions of tubes it shall hold shall be as specified (see 6.2). When designed to hold a single tube, the file and tube may be one integral unit and the fabricating material may be that specified for the tube. When the single tube unit is so constructed, it shall withstand the static force test specified in 4.3.1. The surface of the steel units shall be thoroughly cleaned of all grease, oil, scales, rust and other extraneous matter and then finished with at least two coats of a baking type enamel. The color of finish shall be gray, color chip No. 26134 of Federal Standard No. 595.

(Sample panels of the standard color are obtainable, without charge, from the Business Service Center, Federal Supply Service, General Services Administration, Washington, D. C. 20407, or from the Business Service Center of the nearest GSA Regional Office.)

3.2.2. Tubes. The tubes shall be either round or square and unless otherwise specified herein the material and quality thereof and the construction requirements shall be not less than the minimum specified in PPP-T-495. When permanently encased in the filing unit, the front end of each tube shall be provided with a metal boarder or ring to reduce the possibility of fraying. Tubes not permanently encased shall have the metal on each end. The inside surfaces shall be smooth to prevent damage to filed material. The finished tubes shall be dust, vermin and moisture resistant.

3.2.2.1 Tube dimensions.

3.2.2.1.1 Diameter. The inside diameter in inches (or square inside dimensions if applicable) shall be 1-3/8, 1-7/8, 2-1/4, 2-5/8, 3-3/8, 3-7/8, 4-3/8 and 4-7/8 as specified (see 6.2). A plus or minus tolerance of 1/8 inch will be permitted.

3.2.2.1.2 Length. The length of the tubes shall range in six inch increments from 18 inches to 60 inches, as specified (see 6.2). A plus or minus tolerance of 1 inch will be permitted.

3.2.2.1.3 Wall thickness. The wall thickness shall be as specified below. All thickness dimensions given are minimum.

INSIDE DIAMETER	WALL THICKNESS
1-3/8, 1-7/8, 2-1/4, 2-5/8	0.060 inch
3-3/8, 3-7/8	.090 inch
4-3/8, 4-7/8	.125 inch

3.2.3 Doors. Unless otherwise specified (see 6.2) each file shall be provided with a zinc die cast or a furniture steel door of the gage and quality of steel as specified in 3.2.1. The furniture steel door, except for plated attachments, shall be finished as specified for the steel filing units. A device shall be provided for keeping the door closed. This may be a spring clip, latch, catch or other positive unit.

3.2.4 Index card and label. Unless otherwise specified (see 6.2) the door of each unit shall be provided with an index card or label. The card or label shall be designed to service each tube in the file.

3.2.5 Stacking. Each file shall be designed to interlock by pins, grooves, or nuts and bolts, both laterally (side by side) and vertically. The stacks so formed shall be rigid, regardless of the number of files contained therein.

3.2.6 Accessories. Tops, bases, locks and other accessories shall be the supplier's standard items that are compatible with the files furnished. The accessories to be provided and the quantities thereof shall be as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:40Z
Check the source to verify that this is the current version before use.

3.3 Identification marking. Unless otherwise specified (see 6.2) each file shall be marked in a permanent and legible manner with the manufacturer's name or trademark of such known character that the source of manufacture can be readily determined. When specified (see 6.2) files shall be marked for identification in accordance with MIL-STD-130.

3.4 Workmanship. The workmanship shall be of a quality to produce a serviceable and neat item that will withstand hard daily usage, the features of which include: smooth, straight bends; neatly closed corners; adequate adhesion of chipboard or kraft plies; accurate forming of interlocking components; and the absence of sharp or rough surfaces that might cause personal injury or damage the filed material. The occurrence of defects which affect the appearance or serviceability of the files shall not exceed the acceptable quality level specified herein.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Inspection responsibility. The supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order (see 6.2). The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except as otherwise indicated.

4.2.1 Component and material inspection. In accordance with 4.1, the supplier is responsible for insuring that components and materials used are manufactured, tested and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified or if none, in accordance with this specification.

4.2.2 Visual examination. The files and the tubes shall be examined in accordance with the classification of defects specified in table I. The lot sizes shall be expressed in units of files filled to capacity with tubes for the purpose of determining the sample sizes in accordance with MIL-STD-105. The sample units for this examination shall be one completely fabricated file of each capacity and one completely fabricated tube of each size.

Table I. - Classification of defects

Examine	Defect	Classification Major	Minor
Enamel finish	Wrong color		X
	Poor adhesion (blistered, checking or peeling)	X	
	Tacky (not dry to touch)		X
	Runs, sags or foreign matter in finish	X	
	Not smooth or uniform		X
	Scratched or bare spots		X
Construction and workmanship	Any component malformed, punctured, dented, buckled or bent affecting serviceability.	X	
	Any component malformed, punctured, dented, buckled or bent but not affecting service-ability.		X
	Tubes dirty		X
	Sharp edge or projection that may cause injury	X	
	Not material specified	X	
	Any component missing	X	
	Improper fit of door	X	

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:40Z
Check the source to verify that this is the current version before use.

Table I. - Classification of Defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Welding or brazing (when used)	Not fused, burned through, cracked or fractured	X	
	Not smooth, flash or spatter not removed		X
	Pitted or not complete		X
	Incomplete, undercut or missing	X	
Identification marking	Missing, illegible, incomplete, not permanent		X

4.2.3 Dimensional examination of tubes. Inspection will be made of tubes for compliance with dimensions specified. Any deviations therefrom shall be classified as a defect.

4.2.4 Inspection levels and AQL's . The inspection levels and the acceptable quality levels as expressed in defects per 100 units, of both the files and the tubes shall be as follows:

For examination in	Inspection level	AQL's Major	AQL's Minor
Table I	II	4.0	6.4
4.2.3 (1 class)	S-4	--	4.0

4.3 Tests. The following test shall be performed on the specified end item using inspection level S-1 for the selection of the number of file units to be tested from any lot. Failure to pass the test shall be cause for rejection of the lot represented by the sample units under test.

4.3.1 Static force test on non-metal filing units. Apply a load of 80 pounds per square inch crosswise, and centered between the ends of the units. Remove load after 30 minutes. There shall be no evidence of any permanent deformation.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Unless otherwise specified (see 6.2) files and accessories shall be packaged in accordance with the supplier's commercial practice, and packed in a manner to to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with rules and regulations of carriers as applicable to the mode of transportation.

5.2 Marking

5.2.1 Civil agencies. In addition to any special markings required by the contract or order, the interior packages and shipping container shall be marked in accordance with Fed. Std. No. 123.

5.2.2 Military activities. In addition to any special markings required by the contract or order, the interior packages and shipping container shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The files covered by this specification are intended for use where it is desirable to file documents in rolls instead of vertically or horizontally. The variety of options offered is intended to permit the ordering agency to select commercially available files conforming to this specification that will meet its particular need.

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(a) Title, number and date of this specification
(b) Tube capacity of files (1.2.1 and 3.2.1)
(c) Length and inside diameter of tubes required (3.2.2.1.1 and 3.2.2.1.2)
(d) When doors are not required (3.2.3)
(e) When index label holders are not required (3.2.4)
(f) Accessories required and quantities thereof (3.2.6)
(g) If special marking is required (3.3 and 5.2)
(h) Inspection record details (4.1)
(i) If special packaging and packing is required (5.1)

GSA DC 83-13884

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.