AA-O-00230/7B (GSA-FSS)
June 15, 1979
INTERIM REVISION OF
Fed. Spec. AA-O-230/7a
October 7, 1964

INTERIM FEDERAL SPECIFICATION

OFFICE FURNITURE   TYPEWRITER STAND, EXECUTIVE OFFICE, WOOD, TRATIONAL (DETAILED SPECIFICATION)

This Interim Federal Specification was developed by the National Furniture Center, Federal Supply Service General Services Administration, Washington DC 20406, based upon currently available technical information It is recommended that Federal agencies use it in procurement and forward recommendation for changes to the preparing activity at the address shown above

The General Services Administration has authorized the use of this Interim Federal Specification as a valid exception to Federal Specification AA O 230/1a dated October 7, 1964.

1. SCOPE AND CLASSIFICATION

1 1 Scope This specification covers the detailed requirements for the executive type office typewriter stand in traditional design General requirements and other information pertaining to the typewriter stands will be found in Interim Federal Specification AA O 00230B, Office Furniture, Executive Type, Wood, Traditional (General Specification).

1 2 Classification The typewriter stand covered by this specification shall be of one type and size (30 inches wide, 20 inches deep, 26 inches high).

2 APPLICABLE DOCUMENTS

2.1 Specifications and standards The specifications and standards, of the issues in effect, on date of invitation for bids, which form a part of this specification, will be found in 2.1 of Interim Federal Specification (AA-O-00230B hereinafter called the General Specification (G S).

2 2 Other publications. The documents which form a part of this specification are listed in 2 2 (G.S)

3 REQUIREMENTS

3 1 Materials Materials used in the construction of the typewriter stand shall be as specified in the applicable paragraphs in the General Specification (see table I).

TABLE I. Materials index

Component	AA-O-00230/GEN Par. No.	Component	AA-O-00230/GEN Par. No.
Adhesive	3.1.1 Gen Spec.	Good grade (1) veneer	3.1.4.5 G S.
Wood species	3.1.4.1 G.S.	Particleboard	3.1.4 6 G.S.
Solid wood requirements	3.1.4.2 G.S.	Face hardware	3.1.5.1 G.S
Wood seasoning	3 1 4.3 G.S.	Adjustable glides, regular	3.1.5.2.2 G.S.
Hardwood plywood	3.1.4.4 G S.	Other hardware	3.1.5.4 G.S.

3 2 Construction General construction requirements for the typewriter stand shall be as specified in the applicable paragraphs of the General Specification (see table II,

TABLE II. Construction requirements index

Requirement	AA-O-00230/GEN Par. No.	Requirement	AA-O-00230/GEN Par. No.
Tolerances	3.2.2 G.S.	Tops	3.2.8 G.S.
Direction of grain	3.2.3 G.S.	Posts	3.2.9 G.S.
Joinery	3.2.4 G.S.	Built-up stock	3.2.13 G.S.

3.2.1 Design. Design of the typewriter stand shall be as shown in figures 1 and 2.

3.2.2 Solid base apron. The apron shall be minimum 5-ply (3.1.4.4 G.S.), 3/4 inch thick and shall have a 3/4-inch moulded upper edge. The overall height of the base, including the moulded edge, shall be 4 inches. The outside base shall be mitred at the corners and secured with glue and screws to the back, end panels, and posts. Mitre joints may be secured with clamp nails. The end caps and inside base shall be secured with countersunk nails and glue. Nail holes shall be filled. Side and back panels shall extend to the bottom of the cabinet.

3.2.3 Side and back panels. Panels shall be minimum 5-ply (3.1.4.4 G.S.), 3/4 inch thick and shall be tenoned into the corner posts (see figures 1 and 2).

3.2.4 Top. Top shall be minimum 5-ply (3.1.4.4 G.S.) 1-3/8 inches thick with solid moulded edges and corners as shown in figure 1. Boarder veneers shall be 2 inches wide. Grain direction shall be as shown in figure 1. Tops shall be positioned and secured as specified in 3.2.6 G.S. Screws shall penetrate top 1 inch minimum.

3.2.5 Front rail. A nosed or quarter-round front rail (1 1/2 inches by 3/4 inch) shall be securely tenoned in the front corner posts.

3.3 Finishing. See 3.3.1 G.S., 3.3.2 G.S. and 3.3.3 G.S.

3.5 Identification marking. See 3.4 G.S.

3.6 Workmanship. See 3.5 G.S.

4. QUALITY ASSURANCE PROVISIONS

4.1 The quality assurance provisions shall be as specified in section 4 of the General Specification and as specified herein.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking. Each typewriter stand shall be packaged, packed, and marked in accordance with PPP-P-1577. Packaging shall be level A, B, or C as specified (see 6.2), packing shall be level A, B, or C as specified (see 6.2), and marking shall be for civil agencies or military activities as specified (see 6.2).

6. NOTES

6.1 Intended use. The executive office typewriter stand in traditional styling was designed for use in executive offices, courtrooms, libraries, and conference rooms of Federal agencies. The typewriter stands should compliment the traditional decor of executive areas when used with other furniture items within the group.

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following.

(a) Title, symbol, and date of this specification.
(b) Title, symbol, and date of the General Specification.
(c) Level of packaging and marking.
(d) Marking requirements.
(e) When palletization is not required.

FIGURE 1

TYPEWRITER STAND - 36" X 20" X 26"

CORNER EDGE LENGTH(1-7/8")
FULL MOLDED APRON BASE
BEADED PANELS
TOP BORDER VENEER 2"
CORNERS REEDED (4)
POSTS 2" X 2"
TOP OVERHANG 3/4" (Four sides)