AA-O-230a
October 7, 1964
SUPERSEDING
Int. Fed. Spec. AA-O-00230
February 7, 1964
(See 6.3)

FEDERAL SPECIFICATION

OFFICE FURNITURE, EXECUTIVE TYPE, WOOD, TRADITIONAL (GENERAL SPECIFICATION)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the general requirements for executive type, wood, traditional office furniture Specific requirements, figures and drawings, and other information pertaining to any individual piece of furniture in this group will be found in the applicable detailed specification

1.2 Classification. The types and sizes of the furniture covered by this specification shall be as specified in the applicable detailed specifications, AA-O-230 1 through AA-O-230/7 as follows

/1 — Bookcase, Executive Office, Wood, Traditional
2 — Cabinet, Telephone, Executive Office, Wood, Traditional
3 — Costumer, Executive Office, Wood Traditional
4 — Desk, Executive Office, Wood, Traditional.
/5 — Table, Executive Office, Wood, Traditional.
/6 — Credenza, Executive Office, Wood, Traditional
/7 — Typewriter Stand, Executive Office, Wood, Traditional

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 Specifications and Standards. The following specifications and standards of the issues in effect on date of invitation for bids, form a part of this specification:

Federal Specifications

DD-G-451 — Glass Flat and Corrugated, For Glazing, Mirrors, and Other Uses.
P-P-553 — Polish, Furniture, Liquid
TT-F-336 — Filler, Wood, Paste
TT-L-57—Lacquer, Rubbing, Clear, (for Wood Furniture).
TT-S-190 — Sealer, Sanding, Lacquer Type, (for Wood Furniture).
TT-S-720 — Stain, Wood, Non-Grain-Raising, Solvent-Dye Type
UU-P-271 — Paper, Wrapping, Waterproofed Kraft.
UU-T-111 — Tape, Paper, Gummed (Sealing and Securing)
MMM-A-100 — Adhesive, Animal-Glue.
MMM-A-125 — Adhesive, Casein-Type, Water- and Mold-Resistant

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

MMM-A-188 — Adhesive; Urea-Resin-Type (Liquid and Powder)
PPP-B-591 — Boxes, Fiberboard, Wood-Cleated.
PPP-B-621 — Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 — Box, Fiberboard
PPP-B-640 — Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-C-843—Cushioning Material, Cellulosic
PPP-T-45 — Tape, Gummed, Paper, Reinforced

Federal Standards:

Fed Std No. 102—Preservation, Packaging and Packing Levels.
Fed Std No 123—Marking for Domestic Shipment (Civilian Agencies)

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D C 20402)

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D C., Atlanta, Chicago Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.)

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies)

Military Specifications:

MIL-A-140 — Adhesive, Water Resistant, Waterproof Barrier Material.
MIL-W-6110 — Wood, Determination of Moisture Content.

Military Standards:

MIL-STD-105 — Sampling Procedures and Tables for Inspection for Attributes
MIL-STD-129—Marking for Shipment and Storage
MIL-STD-130 — Identification Marking of U S Military Property

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following publications, of the issues in effect on the date of invitation for bids, form a part of this specification:

Uniform Freight Classification Rules and Regulations.

(Application for copies should be addressed to the Uniform Freight Classification Committee, 202 Chicago Union Station, Chicago 6, Ill.)

Department of Commerce Publication

Commercial Standard
CS-35-61 — Hardwood Plywood

(Copies may be obtained upon application, accompanied by coupon, money order, or cash, to the Superintendent of Documents, U S Government Printing Office, Washington, D C 20402 Prices may be obtained from the Superintendent of Documents)

Associated Publication

Walnut Veneer Types

(Copies may be obtained from the American Walnut Manufacturers Association, 666 Lake Shore Drive, Chicago 11, Illinois)

3. REQUIREMENTS

3.1 Preproduction sample. Unless otherwise specified (see 6.2), before production is commenced, a sample of the finished item and each component part conforming to the requirements of this specification shall be offered for approval of the contracting officer or his authorized representative Approval of the preproduction sample authorizes the commencement of production, but does not relieve the contractor of responsibility from compliance with all other applicable provisions of this specification

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

3.2 **Materials.** The materials used in the construction shall be of the kind and quality specified herein

3.2.1 *Glass.* Glass shall conform to DD–G–451, type II, A quality, double strength, and shall be ⅛ inch thick, plus or minus 1/32 inch.

3.2.2 *Adhesives.* Adhesives to be used and their permitted application shall be as shown in table I

TABLE I—*Adhesives*

Application	Kinds of adhesives
All glueblocks, assembly joints, glued laminated stock, and edge joining of lumber-core panels	Any adhesive that will conform to or exceed the requirements of the following block shear tests Room temperature — 2800 psi minimum average, 50 percent wood failure minimum average 150° F — Average block shear strength and wood failure shall be not less than 80 percent of the average values obtained at room temperatures
All plywood gluing, edge-joining of veneer plies, and edge banding	Any adhesive that will conform to or exceed the test requirements of the Type II bond as described in the Commercial Standard CS–35–61 for Hardwood Plywood

3.2.2 *Wood*

3.2.3.1 *Kinds of wood.* All exposed surfaces, including shelves and back panels shall be of walnut (Juglans nigra), as specified (see table II) The furniture shall have both solid and plywood parts as shown in the applicable figures The exposed surfaces shall be free of any defects which affect serviceability or finished appearance

3.2.3.2 *Solid wood* The solid wood used for exposed parts, including drawer parts shall be bright, well sanded, and free from brashness discolorations, worm holes, honeycomb, splits and shake A few small burls, pin knots not to exceed two per square foot average, mineral streaks not exceeding 1/32 inch by 4 inches, or 1/16 inch by 2 inches in dimension and occurring not more than one per square foot average will be permitted. The wood used for unexposed parts, including lumber cores, may contain small defects, such as pin knots, sapwood, or mineral streaks provided the strength of the part is not affected.

3.2.3.3 *Plywood* All plywood shall be constructed according to the requirements of Commercial Standard CS–35–61 and as specified herein. Bondage shall be not less than type II Cross banding plies shall be not less than grade 2 quality and not less than 1/20 inch thick. Face and back veneer plies shall be not less than 1/28 inch thick, before sanding. All exposed faces, including drawer fronts, tops, side panels, door panels, and inside face of exposed back panels shall have grade 1 veneer plies, matched for color and grain to present a uniform appearance Grade 2 veneer plies may be used on the face of unexposed panels and drawer bottom faces and backs and unless otherwise specified, for the unexposed backs of all panels and tops. Lumber core panels shall be regular grade except that no end-butt joints will be permitted and the wood for laying up the cores shall be of full length strips not more than 4 inches wide Veneer plies shall be full length and shall be applied in balanced construction form with no ply joints less than 1 inch from the edge of any panel All face veneers shall be edge-glued Full length veneer strips shall be a minimum of 3½ inches wide Trim-off allowance of 3/16-inch shall be permissible on panel sides

3.2.3.3.1 *Matching* Face veneers shall be book-matched for figure and color. The plies shall be carefully selected to insure sameness of grain pattern on the surface of the panels Panels of the same unit, or group of units shall have the same grain pattern. The pattern shall be in accordance with figure No. 22, Plain Quartered, Flat Character, or, figure No 23, Plain Quartered, Stripy, and Broad Character of the pamphlet "Walnut Veneer Types" (see 2.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

TABLE II—*Varieties of wood*

Color of finish	Exposed parts			Unexposed parts			
	All veneers	All solid parts	Drawer parts (except fronts)[2]	Solid[1]	Veneer faces and backs	Corestock[1]	Crossbands
Walnut	Walnut	Walnut	Ash Beech Birch Cherry Maple Oak Walnut	Ash[3] Beech[3] Birch[3] Cherry Hackberry[3] Hickory[3] Magnolia Mahogany Maple[3] Oak[3] Pecan[3] Sweetgum Sycamore Tupelo Walnut[3] Yel Poplar	Alder (red) Ash Aspen Basswood Beech Birch Butternut Cherry Cottonwood Magnolia Mahogany Maple Oak Sweetgum Sycamore Tupelo Walnut Yel. Poplar	Alder[3] Aspen Basswood Butternut Cherry[3] Chestnut Cottonwood Douglas Fir[4] Magnolia[3] Mahogany[3] Maple, soft[3] Ponderosa Pine[4] Redwood[4] Sitka Spruce[4] Sycamore[3] White Pine[4] Yel Poplar[3] Willow	Alder Aspen Basswood Beech Birch Butternut Cherry Chestnut Cottonwood Magnolia Mahogany Maple, soft Oak Sweetgum Sycamore Tupelo Yel. Poplar Willow
	Post overlays						
	Walnut Burl[3] Carpathian Elm Burl[3]						

[1] Only one of the species listed shall be used in any one panel.
[2] Must be the same wood in any one piece of furniture.
[3] Attaching rails and drawer bearers must be of one of these species
[4] Vertical grain only.
[5] Lumber cores of plywood drawer fronts must be of one of these species

3.2.3.4 *Seasoning* Wood parts, including solid wood, plywood veneers and cores shall be uniformly kiln-dried to a moisture content of from 5 to 8 percent dependent upon the manufacturer's best commercial practice, and shall be held in properly controlled, warm, dry storage for a sufficient time to insure uniform distribution of moisture among the individual pieces After gluing, and before planing and sanding for cross-banding and face veneer, all lumber-cores shall be permitted to cure-out by one of the following methods to insure a uniform distribution of the glue-joint moisture and to minimize the occurence of sunken joints, spring back, and stresses:

(*a*) 7 days at 80° F. and 30% relative humidity

(*b*) 4 days at 120° F. and 35% relative humidity

(*c*) 24 hours at 160° F and 44% relative humidity.

(*d*) 16 hours at 200° F and 55% relative humidity

3.2.3.5 *Varieties of wood.* The woods permitted for use in the construction of the furniture shall be as shown in table II

3.2.4 *Filler.* The filler shall conform to TT-F-336

3.2.5 *Lacquer* The lacquer shall be in accordance with type I or type II of TT-L-57

3.2.6 *Hardware*

3.2.6.1 *Face hardware* All face hardware, such as door pulls, drawer pulls and shoes, shall be made of cast brass or cast bronze The

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

color shall be in accordance with the standard sample (symbol U.S. 10).

The castings shall be true without air or sand holes or other defects. All ornamentation on the face of the hardware, such as moldings, beadings, or turnings shall be chased to a clean and even surface. All surfaces shall be smoothly and evenly finished. The face hardware shall receive one coat of clear baked-on synthetic enamel.

3.2.6.1.1 *Door pulls.* The door pulls shall be of the design shown in the applicable figures.

3.2.6.1.2 *Drawer pulls.* Drawer pulls shall be of the design shown in the applicable figures. When specified, wooden pulls of the design shown in the figures shall be supplied.

3.2.6.2 *Locks.* Locks, where shown in the applicable figures, shall be disk tumbler, 7/8-inch diameter tube type, operated by a paracentric key. The locks shall be half mortised and shall have a minimum of 24 key changes. Two brass or bronze keys shall be furnished with each lock. All locks on any one piece shall be keyed alike. The bolt shall be of steel. The finish of the locks shall be as specified in 3.2.6.1.

3.2.6.2.1 *Strike-plate.* All locks shall have a brass-plated strike-plate set in flush to accept the bolt of the lock.

3.2.6.3 *Composition glides.* The composition glides shall have a steel shank and slip socket with a phenolic plastic disk having a self adjusting leveling joint. The sizes of the glides shall be in proportion to the leg or base.

3.2.6.4 *Shelf standards and supports.* The shelf standards and supports shall be cold rolled steel and shall have a statuary bronze finish. The standards shall be of the flat surface, square-edge type, 5/8 inch wide and shall be attached to the surface of the corner posts or interior panel, as shown in the applicable figures. They shall have 1/2-inch adjustments and shall be numbered every inch. Standards for all pieces shall be the full height of the interior. Supports shall be of a type that can be readily and easily adjusted throughout the entire length of the standards. They shall be fastened with brass head screws, a maximum of 6 inches apart starting a maximum of 1 inch from the top and bottom.

3.2.6.5 *Other hardware.* Other hardware, such as hinges, catches and bolts shall be made of brass or bronze, and where exposed shall match the finish of the face hardware. The hinge pin may be made of steel providing the edges of the pin match the hardware and the pin is coated to prevent rusting.

3.3 **Construction.**

3.3.1 *Design.* The design of the furniture shall be traditional, as shown in the figures of the detailed specifications. The case pieces shall have chamfered and reeded corner posts with a bracket foot base except that the typewriter stand shall have a molded plinth base. The tables shall have tapered and reeded legs. All pieces shall have molded tops.

3.3.2 *Tolerances.* The following tolerances will be permitted.

Dimensions of any solid wood part	— Plus or minus 1/16 inch.
Dimensions of any plywood part	— Plus 1/16 inch, minus 1/32 inch
Any other dimension, unless otherwise specified in the detailed specification shall be	— Plus or minus 1/8 inch

3.3.3 *Direction of grain.* The grain pattern shall be as shown in the applicable figures.

3.3.4 *Joining and assembly.* All joints shall be true, and unless otherwise specified, shall be tongue and grooved or mortised and tenoned.

3.3.5 *Gluing of joints.* All joints shall have a thorough application of glue, there shall be complete contact along the joining surfaces and they shall be held under pressure until the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

glue has set properly. The adhesives used shall be as specified in 3.2.2 and table I. Nails or brads used for holding the glue joint shall not be permitted.

3.3.6 *Drawers*. The drawers shall be dovetailed at the front and back. The drawer fronts shall be lumber-core plywood, 13/16 inch thick. The drawer backs shall be 3/4 inch thick, and the sides shall be 1/2 inch thick, of solid wood. The drawer sides and backs shall be made of any of the woods shown for drawer parts in table II. The drawer bottoms shall be 3 or 5 ply, 1/4 inch thick, and shall be set (full thickness) in grooves in the front, sides, and back. The drawer bottoms shall be reinforced with a minimum of six rubbed-in-place glue blocks Each drawer shall be provided with a suitable stop to prevent removal of the drawer without manual operation of the stop Other details, if applicable, will be found in the detailed specification

3.3.7 *Doors* The doors shall be of the design, size, and thickness specified in the detailed specification

3.3.8 *Plywood parts* All details, including the design, size, number of plies, thickness, and the location of the plywood parts shall be as specified in the detailed specification.

3.3.8.1 *Tops*. The design, size, and thickness of the tops shall be as specified in the detailed specifications. All tops shall have holes drilled in the underside, at appropriate locations, a maximum of 1/2 inch in diameter and of the proper depth to accept 1/2 inch of the 1 1/2 inch-long dowels inserted and glued into the top of each of the four corner posts for positioning. The dowels shall be as specified in 3.3 8.2. The tops shall be secured to the framing members with screws, or suitable metal fasteners

Cleats may be used for attachment of the tops in lieu of the steel brackets provided they are securely glued and screwed into place The cleats shall be screwed two ways, into the framing members, and, into the top There shall be no glue applied to the top for attaching or for positioning.

3.3.8.2 *Dowels*. The dowels shall be made of maple, birch, hickory or beech dried to a moisture content of 3 to 5 percent They shall have longitudinal or spiral grooves and shall be beveled at each end The dowels for all tops shall be 3/8 inch by 1 1/2 inches.

3.3.8.3 *Shelves* The edge banded front of all shelves shall match the exposed wood of the piece. All shelves shall be 13/16 inch thick.

3.3.8.4 *Dust shields and bottoms*. Dust shields and bottoms shall be 3 ply, not less than 3/16 inch thick. They shall be applied as specified in the detailed specifications.

3.3.8.5 *Back panels and end panels*. Back panels and end panels shall be as specified in the detailed specifications

3.3.9 *Solid wood parts*

3.3.9.1 *Posts*. All posts shall be of one continuous piece of solid or built-up stock and shall extend from the top to the floor. The built-up stock shall be as specified in 3.3.9.3 Each corner post shall have a 3/8 inch by 1 1/2 inch dowel inserted in the top end for positioning. The dowels shall be as specified in 3.3 8 2, and shall be thoroughly secured and glued 1 inch into the corner posts.

3.3.9.2 *Bases*.

3.3.9.2.1 *Bracket foot base* The bracket foot base shall be 3/4 inch thick and shall be shaped and molded as shown in the applicable figures The base shall be rabbeted into the base rails on three sides and shall be thoroughly secured and glue-blocked to the bottom of the posts. The glue-blocks shall be the full length of the joint and have two sides a minimum of 7/8 inch.

3.3.9.2.2 *Molded plinth base* The molded plinth base applied to the typewriter stand shall be 3/4 inch thick and shall be shaped and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

molded as shown in the applicable figures of the detailed specification It shall be thoroughly glue-blocked to the bottom of the posts

3.3.9.2.3 *Clamp nails.* Clamp nails may be used to secure all mitre joints of the bases

3.3.9.2.4 *Base supports.* The entire base of all units shall be backed with a ¾ by 1 inch (minimum) solid wood support securely screwed and glued to the base and to the bottom frame of the piece.

3.3.9.3 *Built-up stock.* The built-up stock used for exposed walnut components in the construction of the furniture shall consist of not more than three full pieces (full length) each of which shall be approximately the same thickness. They shall be carefully matched for color and figure.

3.4 **Methods of finishing.** All surfaces normally exposed to view shall be finish sanded smooth and all corners and edges eased, and thoroughly cleaned, and finished as specified.

3.4.1 *Tops.* (Procedure for clear finish on open pore wood):

1 Sap stain to equalize color

2 Apply selected colorant to produce color specified. Stain and colorant shall conform to test specified in 4.3 1.1.

3. Wash coat with adhesive sealer Sealer shall withstand test as specified in 4.3 1.2.

4 Scuff sand, using sandpaper grit of fineness to produce proper surface

5 Fill to degree necessary to match standard reference panel. The filler shall conform to the test specified in 4.3.1.1.

6. Seal with adhesive sealer. Sealer to withstand test specified in 4.3.1.2.

7 Sand, using sandpaper grit of fineness needed to give proper surface

8 Shade to tie-in color variation, if necessary Shading shall conform to the test specified in 4.3 1 1.

9. Apply two coats of lacquer. Lacquer and finish shall be of a quality to meet test requirements as specified in 4 3 1.1, 4 3 1.2, and table III.

10 Rub or polish to the degree necessary to match the color, texture, and gloss of the standard reference panel.

Note. Operation No 8 may be performed in the sequence shown, or after operation No. 5.

3.4.1.1 *Exposed body surfaces.* (other than tops). The exposed body surfaces shall be finished as specified in 3.4 and 3 4.1, except the final steps as follows:

9. Apply one coat of lacquer sanding sealer. Sealer to withstand test as specified in 4.3.1.2.

10 Sand, using sandpaper grit of fineness needed to give proper surface

11 Apply two coats of flat lacquer. The lacquer and final finish shall be of the quality to meet the test requirements of 4.3.1.1, 4.3.1.2, and Table III.

The natural grain of the woods shall not be clouded by the finishing materials. Bleaching agents or materials shall not be used The application of materials, drying time, sanding, cleaning and rubbing shall be controlled to produce items with smooth, uniform exposed surfaces without blisters, pits, wrinkles, runs, tackiness or more than a trace of orange peel. All unexposed wood interior parts and surfaces, including the underside of drawers and drawer rails, shall be machined smooth and cleaned, and shall be stained and receive one coat of lacquer sealer and one coat of clear lacquer as specified in 3 2.5

3.4.2 *Shelves.* The shelves shall be finished as specified in 3.4.1.1.

3.4.3 *Interior surfaces.* Interior wood surfaces, including the interior surfaces of doors and drawers and both sides of the drawer sides shall be stained to a uniform color and final coated with a coat of sealer and a coat of flat lacquer. The interior of the drawers and the outside of the drawer sides shall be sanded and waxed

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

3.5 Color and appearance of finish. The color and appearance of the finish for the variety of wood specified in 3.2.3.1 shall conform to the standard reference panel as adopted by the Federal Supply Service, General Services Administration for color, texture, gloss, and appearance.

3.6 Identification marking. Unless otherwise specified in the detailed specification, each unit of furniture shall be permanently marked on the underside, or on the underside of the top or center drawer, in a plain and legible manner with the specification number, Federal Stock number, the month and year of the manufacture, and the contractor's name or trademark. When specified, the identification marking shall be in accordance with MIL-STD-130

3.7 Workmanship. A high degree of craftmanship, with extra care in fabrication and quality control shall be exercised in order to produce superior items of furniture suitable for use in executive offices. The methods of construction, veneering, finishing, assembly, and the appearance of the furniture in general, shall be in strict accordance with the requirements of the specifications. Furniture shall conform to the level of quality established herein

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 General quality assurance provisions.

4.1.1 *Supplier responsibility* The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may use his own or any other inspection facilities and services acceptable to the Government Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to the prescribed requirements.

4.1.2 *Supplier quality assurance system* The supplier shall provide and maintain an effective quality assurance system acceptable to the Government covering the furniture under this specification. Results of all examinations and tests performed under the quality assurance system shall be made available to the Government. A current written description of the system shall be submitted to the contracting officer prior to initiation of production. The written description will be considered acceptable when, as a minimum, it provides the quality assurance required by this specification and other documents referenced herein. The supplier will not be restricted to the inspection station or to the method of inspection listed, provided that an equivalent control is included in the approved quality assurance procedure In cases of dispute as to whether certain procedures of the system provide equal assurance, the comparable procedure of the detailed specification will be used The contractor shall notify the Government of, and obtain approval for, any change to the written procedure that affects the degree of assurance required by this specification or other documents referenced herein

4.1.3 *Government verification.* All quality assurance operations performed by the contractor shall be subject to Government verification at unscheduled intervals. Verification shall consist of surveillance of the operations to determine whether the practices, methods, and procedures of the written inspection plan are being properly applied, and Government product inspection, to measure quality of product offered for acceptance. Deviation from the prescribed or agreed-upon procedures, or instances of poor practices that might have an effect on the quality of the product will be immediately called to the attention of the contractor Failure of the contractor to promptly correct the deficiencies discovered shall be cause for suspension of acceptance until the correction has been made or until conform-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

TABLE III—*Test methods for components*

Component	Characteristic	Requirement reference	Test method	Results reported as	Sample unit
Finish	Spot test	3.2.4	4.2.3.3 of TT-L-57	Pass or fail	One quart
	Alcohol test	3.2.4	4.2.3.3.1 of TT-L-57	Pass or fail	One quart
	Print resistance test	3.2.4	4.2.3.4 of TT-L-57	Pass or fail	One quart
	Ultra-violet resistance test	3.2.4	4.2.3.7 of TT-L-57 and 4.3.1.1 herein	Pass or fail	One quart
	Toughness and adhesion test	3.2.4	4.3.1.2 herein	Pass or fail	One quart

ance of product to prescribed criteria has been demonstrated. To avoid interference with operations, the contractor shall designate a responsible official, or officials, to whom the Government inspector will report such instances

4.2 **Preproduction sample inspection.** Examination and testing shall be made of the completely fabricated item for all provisions of this specification applicable to end product examination and tests

4.3 **Sampling for inspection and acceptance.** Sampling and inspection shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated hereinafter

4.3.1 *Inspection of materials and components* In accordance with 4.1 the supplier is responsible for insuring that materials and components used were manufactured, tested, and inspected in accordance with the specified requirements of referenced subsidiary specifications and standards to the extent specified herein In addition, testing shall be performed on components and materials listed in table III for the characteristics shown therein The inspection level shall be S-1. The acceptable quality level shall be 2.5 defects per hundred units

4.3.1.1 *Ultra-violet light resistance test* Shall be as specified in 4.2.3.7 of TT-L-57, except that panel preparation as specified shall be disregarded, and tests shall be made on completely finished wood panel of the same wood as used in the production procedures used in producing the furniture

4.3.1.2 *Toughness and adhesion test.* Shall be made by using Bell Laboratories Adhesion Tester, U. S Testing Co., Model Number 1001, in accordance with instructions for using, as provided for by the manufacturer of the tester. The panel shall be marred both parallel and perpendicular to the grain. The resulting indentation shall show no whitening which is evidence of film separation and shall not crack in a brittle manner in or along the indentation. The test shall be made on completely finished wood panels of the same wood as used in production. The finish shall be produced in accordance with production procedures used in producing the furniture

4.3.2 *Inspection of the end item*

4.3.2.1 *Visual examination* The defects found during the examination shall be classified in accordance with 4.3.2.1.1. The sample unit for the examination shall be one end item. The lot size shall be expressed in units of completely fabricated end items

4.3.2.1.1 *Examination of the finished end item* The examination of the finished end item shall be for defects in finish, material, construction, and workmanship as specified in table IV

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

TABLE IV—*Classification of end item defects*

Examine	Defect	Classification	
		Major	Minor
Finish and appearance of exposed wood parts visible in normal use position.	Does not match standard reference panel with respect to color, texture, and gloss	X	
	Discoloration (Bleeding) over 1 square inch		X
	Spotted, affecting appearance		X
	Light or dark colored areas, affecting appearance	X	
	Area of no lacquer or varnish film over 1 square inch in area	X	
	Glue stain or glue line clearly showing, affecting appearance		X
	Excess glue not removed		X
	Finish peeling, flaking, blistered, cracked, checked or wrinkled	X	
	Finish cut or rubbed through to wood		X
	Open grain Finishing material not filling pores		X
	Orange peel, affecting appearance		X
	Damage or scratch, less than 1 inch long, or 1 inch square		X
	Damage or scratch over 1 inch square or 1 inch long	X	
	Finish tacky, i e , not completely dry		X
	Rough or gritty surface or foreign matter imbedded in finish		X
	Light colored edge not touched up		X
	Burn-in or repairs not neatly accomplished		X
	Unstained (white) wood visible when item is in normal use position		X
	Not polished where required		X
Finish of exterior wood parts not visible in normal use	Finish not applied where required		X
	Stain or sealer coat omitted where required		X
Finish of interior and concealed wood surfaces	Top edge of drawer front scratched, bruised, or not finished same as exterior wood surfaces		X
	Stain or sealer coat omitted from hinged or bottom edge of drawer		X
	Opening or top edge of door or drawer scratched or bruised, or not finished as the exterior wood surfaces		X
	Interior surfaces of drawers not finished as specified		X
	Drawer interior dirty or roughly finished		X
	Excess glue not removed from drawer interior		X
	Drawer tray not finished		X
	Any surface of drawer tray rough		X
Finish of hardware.	Does not match standard finish	X	
	Component tarnished or stained, affecting appearance		X
	Rusted or corroded		X
	Not coated with protective finish		X
Quality of plywood and laminated wood on exposed surfaces.	Not harmonious grain match between panels on any one item.		X
	Grain pattern not similar to illustrations specified		X
	Species of wood not as specified	X	
	Number of plies not as specified	X	
	Open joint in face veneer	X	
	Face veneer butt-matched		X
	Uneven core surface telegraphing		X
	Any cross break in veneer	X	
	Sanded through face ply		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

TABLE IV—*Classification of end item defects* (continued)

Examine	Defect	Classification	
		Major	Minor
Quality of plywood and laminated wood on exposed surfaces (cont.)	Waves of uneven sanding, affecting appearance		X
	Machine mark, affecting appearance		X
	Veneer blister		X
	Veneer chipped or splintered		X
	Any loose or unsound knot		X
	Conspicuous patch		X
	Decay, affecting appearance		X
	Veneer joint less than 1 inch from edge of panel, except drawer fronts.		X
	Unfilled void at exposed edge		X
	Lumber-core not "clear edge" where required		X
			X
Quality of solid wood or built-up stock on exposed and unexposed surfaces	Species of wood not as specified	X	
	Component not fabricated of one piece solid wood where required		X
	More than 1 species of wood used for exposed wood components of any one item		X
	Direction of grain not as specified		X
	Check or split over 1 inch in length	X	
	Wood warped, affecting appearance or serviceability		X
	Loosened grain or shake on exposed surface		X
	Loosened grain or shake on unexposed surface		X
	Honeycomb		X
	Loose or unsound knot		X
	Hole on exterior surface, affecting appearance	X	
	Glue line in built-up stock open over 1 inch in length		X
	Glued up pieces uneven in built-up stock		X
	Wave of uneven sanding		X
	Machine mark on exposed surface, affecting appearance		X
	Any mineral streak on exposed surface over ½ inch by 4 inches or ⅛ inch by 2 inches.		X
	Wood chipped or splintered on exposed surface of drawer interior		X
	Any manufacturing defect or defect native to the wood filled in with plastic wood or other filler material.	X	
Quality of plywood on unexposed surfaces	Species of wood not as specified	X	
	Number of plies not as specified		X
	Veneer delaminated	X	
	Any knot holes, except in dust shields or dust bottom	X	
	Any manufacturer's defect or defect native to the wood filled with plastic wood or other filler material	X	
Quality of glass in glass doors	Glass cracked or broken	X	
	Surface scratched or edges chipped		X
	Apparent surface distortion	X	
	Bubble larger than ⅛ inch diameter in glass door		X
Quality of metal components (except attaching implements)	Not fabricated of material specified	X	
	Broken, cracked or fractured		X
	Dented or damaged		X
	Nicked, pitted, malformed or bent, affecting appearance		X
	Machine or die marked, affecting appearance		X
	Contains hole where not required, does not have one where required.		X
	Fin, burr, or sharp edge which may cause personal injury or damage to clothes		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

TABLE IV—*Classification of end item defects* (continued)

Examine	Defect	Classification	
		Major	Minor
Workmanship and attachment of screws, bolts, nuts, washers and rivets	Any attachment device not type or size as specified		X
	Material not as specified		X
	More than 1 screw missing		X
	Spacing of screws not as specified		X
	Screw point visibly bulging wood		X
	Wood at insertion point not countersunk when specified		X
	Screws, bolts, or rivets broken off		X
	Screw or bolt in wrong location		X
	More than one screw, bolt, nut, washer or rivet missing		X
	More than one bolt, screw or nut not drawn up tightly.		X
	Threads on nuts or bolts stripped		X
			X
Construction, assembly and attachment of unexposed and exposed parts	Not as specified or not as shown on drawings or figures	X	
	Component not size or shape specified		X
	Component not type or design specified		X
	Component not assembled as specified		X
	Component missing	X	
	Component in wrong location, except attaching implements		X
	Component loose or insecurely fastened where rigidity is required		X
	Component out of alignment or out of square affecting serviceability		X
	Poor fit of component part or on mating part		X
	Defective hinge or other mechanism that does not function properly.		X
	Wood component not glued as specified		X
	Solid wood used in place of veneer or vice versa		X
	Wood component damaged or not properly machined		X
	Molding, fluting, routing, or beading not uniform or uneven		X
	Component not chamfered where required		X
	Edges not "eased off" where required		X
	Any loose or unsound glued joint		X
	Wood joint not as specified		X
	Glue joint open over 1/16 inch on exposed part		X
	Glue joint open over 1/8 inch on unexposed part		X
	Top panels warped over 1/4 inch in width or length		X
	Overhang of top panel uneven or not as specified		X
	Door or drawer clearance not as specified		X
	Door or drawer does not close completely		X
	Door or drawer binds when opening or closing		X
	Door catch does not operate smoothly		X
	Drawer tray too small to set evenly on tray guides		X
	Glides improperly positioned		X
	Legs or base uneven		X
Identification marking	Missing, incorrect, or illegible		X
	Text incomplete		X
	Marking in wrong location		X
	Size of lettering not as specified		X
	Color of marking not black		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 *Assembly examination.* Examination of the assembly of the legs to the tops of the tables and shelves to the bookcases as applicable for defects in ease of assembly and fit of components.

(*Note.* Unassembled end items, selected by the Government inspector, shall be fully assembled by the contractor. The inspector shall witness the assembly of the end item and shall observe the ease of assembly and fit of components).

TABLE V—*Assembly defects*

Examine	Defect
Assembly of end item and fully assembled end item.	Not easily assembled, i.e., assemblying required realignment of parts, drilling or enlargement of holes, use of hammer, drift pin or other mechanical means Legs uneven, i e , item rocks more than 1/16 inch when on flat surface Shelf standards or brackets out of alignment. Shelf support does not fit into slot in standard Shelf support too loose in standard, i.e , falls out easily Shelf wobbles on shelf support or bracket (when in horizontal plane) Shelf does not fit neatly on support or bracket Shelf tilted over 1/4 inch when in use position Shelf standard not adjustable to positions as specified End edge of shelf not flush with side panels by more than 1/8 inch

4.3.2.1.3 *Examination of the end product for dimensions.* Any dimension that is not within the specified tolerances shall be classified as a defect.

4.3.2.1.4 *Inspection of preparation for delivery requirements* An inspection shall be made to determine that packaging, packing, and marking requirements of section 5, of this specification are complied with. Defects shall be scored in accordance with table VI. For examination of contents the sample unit shall be one shipping container fully prepared for delivery, selected just prior to closure operations. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units. See table VII.

TABLE VI—*Classification of preparation for delivery defects*

Examine	Defect
Markings (Interior and exterior)	Omitted, incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, or damaged
Workmanship	Inadequate application of components such as: Incomplete closure of container flaps, loose strapping, inadequate stapling. Bulging or distortion of containers.
Contents	Not as specified

4.3.2.1.5 *Inspection levels and acceptable quality levels (AQL's)* Inspection levels and acceptable quality levels expressed in defects per hundred units shall be as shown in table VII

TABLE VII—*Acceptable quality levels*

	Inspection levels	Major	Minor	Total
For defects listed in 4.3.2.1.1	II	2.5	~~4.5~~	10.00 4.0
For defects listed in 4.3.2.1.2 and 4.3.2.1.3	S3			4.0
For defects listed in 4.3.2.1.4.	S2			

5. PREPARATION FOR DELIVERY

For civil agency procurement the definitions and application of levels of packaging and packing shall be in accordance with Fed Std No 102

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.

5.1 **Preparation for delivery description** shall be as specified in section 5, of the applicable detailed specifications

6. NOTES

6.1 Intended use. The traditional executive furniture items covered by this general specification in conjunction with the applicable detailed specifications are designed for use in executive offices, courtrooms, libraries, and conference rooms of Federal agencies. (See 1.2.)

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following

(*a*) Title, symbol, and date of this specification.

(*b*) Title, symbol, and date of the detailed specification

(*c*) Type and size required if applicable

(*d*) When preproduction samples are not required.

(*e*) Level of packaging.

(*f*) Level of packing.

(*g*) Marking requirements

6.3 Supersession data. This general specification and the applicable detailed specifications referenced herein supersede the following:

AA-O-00230—Office Furniture, Executive Type, Wood, Traditional, February 7, 1964.

AA-B-564—Bookcase, Wood, Executive Office Type, December 4, 1950.

AA-C-35—Cabinet, Telephone, Wood, Executive Office Type, September 7, 1950.

AA-C-555—Costumer, Wood, Executive Office Type, July 28, 1949.

AA-D-198—Desk, Wood, Executive Office Type, March 6, 1951.

AA-T-108a—Table, Wood, Executive Office Type, May 25, 1954.

6.4 Transportation description. Transportation description shall be as specified in the applicable detailed specifications

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:39Z
Check the source to verify that this is the current version before use.