AA-S-00300a(GSA-FSS)
February 17, 1967
SUPERSEDING
Int. Fed. Spec. AA-S-00300(GSA-FSS)
January 28, 1964

INTERIM FEDERAL SPECIFICATION

SHELF, FILING

This Interim Federal Specification was prepared by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers filing shelves for attachment to a file drawer pull by means of a hooklike device.

1.2 Classification.

1.2.1 Types. The shelves shall be of the following types, as specified (see 6.2):

Type I. Hardboard type.
Type II. Wire-mesh type.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

LLL-B-810 - Building Board, (Hardboard) Hard Pressed, Vegetable Fiber.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.
PPP-B-640 - Boxes, Folding, Fiberboard, Corrugated, Triple Wall.
PPP-B-665 - Boxes; Paperboard, Metal Stayed (Including Stayed (Including Stay Material).
PPP-B-676 - Boxes, Setup.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:40Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-P-116 - Preservation, Methods of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The materials shall conform to the applicable specifications and requirements specified herein. When materials are not definitely specified, they shall be of the quality normally used for the purpose in commercial practice.

3.1.1 Hardboard. Hardboard (building board) shall conform to the requirements of LLL-B-810, types I or II, smooth two sides, unfinished surface, plain board design. Hardboard shall be 3/16 ± 1/32 inch thick.

3.1.2 Wire mesh. The wire mesh shall be made of welded steel wire not less than 0.088 inch in diameter. When measured on wire centers, openings of the wire mesh comprising the working surface shall be not more than 1-1/4 inches in either direction.

3.1.3 Wire. The wire shall be made of steel. The minimum diameter of the frame wire shall be 0.159 inch, and of the attachment hook 0.189 inch.

3.2 Color. The color of the filing shelf, except uncoated metal parts, shall be gray.

3.3 Finish. Hardboard shall be finished with paint, lacquer, or enamel. The finish shall be free from runs, wrinkles, and thin spots. The finish shall not peel and shall resist chipping. Uncoated metal shall have an electrodeposited finish, unless the metal is corrosion resistant.

3.4 Identification marking. Each shelf shall be marked with the manufacturer's name or trademark.

3.5 Instructions for assembling. When disassembled for packaging, an instruction data sheet outlining the steps for assembling shall be furnished with each shelf.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:40Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. All parts shall be free of burrs and sharp edges, and all corners shall be rounded. Shelves shall be free from defects and imperfections which affect appearance or which might impair serviceability.

3.7 Type I, hardboard type. The type I filing shelf shall consist of hardboard not less than 12 inches wide and not less than 10 inches deep; attachment hook; spring clamp for holding down loose file material on the working surface of the shelf; bumpers; and hardware for assembling the components. The hardboard shall be drilled for attaching the hook and clamp. A cutout at least 1/2 inch deep shall be made in the center of the rear edge of the hardboard to allow clearance for the knob of a drawer guide rod. When the performance test is conducted as described in 4.4.1, the difference between the first dimension and the second dimension shall be not more than 1/2 inch.

3.7.1 Attachment hook. The attachment hook shall be a means for hanging the shelf from a file drawer pull and to prevent the shelf from tilting during filing operations. The hook shall be of metal.

3.7.2 Bumpers. Two rubber or plastic bumpers shall be securely fastened with good quality adhesive to the rear edge of the hardboard. The bumpers shall hold the shelf in a near level position and protect the finish of drawer fronts.

3.8 Type II, wire-mesh type. The type II filing shelf shall consist of wire mesh; frame; attachment hook; and provision for holding down loose file material on the working surface of the shelf. The wire mesh shall be welded to the frame in a manner to provide the shelf with a flat, useful, working surface not less than 12 inches wide and not less than 10 inches deep. When the performance test is conducted as described in 4.4.1, the difference between the first dimension and the second dimension shall be not more than 1/2 inch.

3.8.1 Attachment hook. The attachment hook shall be a means for hanging the shelf from a file drawer pull and to prevent the shelf from tilting during filing operations. The hook shall be formed from one continuous piece of wire into a "U-shape" with 2 parallel sides. The center to center distance between the parallel sides of the hook shall be not less than 2 inches. The hook wire shall extend for at least 5 inches under the shelf's working surface perpendicular to the 12-inch dimension.

3.8.2 Plastic coating. Except where metal is coated with an electrodeposited finish or the metal is corrosion resistant, the filing shelf shall be coated with vinyl plastic. The coating shall be free from wrinkles, thin spots, or area of no plastic. The coating shall not peel.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. For purposes of sampling, a lot shall consist of all filing shelves offered for inspection at one time.

4.2.2 Sampling for visual and dimensional inspection. A random sample of filing shelves shall be taken from each lot in accordance with MIL-STD-105, inspection level S-4, Acceptable Quality Level (AQL) 6.5 percent defective. The sample unit shall be one filing shelf.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.

4.2.3 Sampling for test. A random sample of filing shelves shall be taken from each lot in accordance with MIL-STD-105, inspection level S-1, AQL 4.0 percent defective. The sample unit shall be one filing shelf.

4.2.4 Sampling for preparation for delivery. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery, and selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 2.5 defects per hundred units.

4.3 Visual and dimensional examination. Samples taken in accordance with 4.2.2 shall be examined for defects listed in table I. Any filing shelf in the sample containing one or more defects shall be rejected. The Government reserves the right to classify as a defect any departure from the specification not listed in table I.

Table I. Classification of filing shelf defects

Examine	Defects
Materials:	
Hardboard	Not thickness specified.
Wire mesh	Not of welded steel wire. Wire less than minimum specified. Openings on working surface more than 1-1/4 inches in either direction.
Wire	Wire less than minimum specified for frame and attachment hook.
Color	Not as specified.
Finish:	
Hardboard	Not finished with paint, lacquer, or enamel. Runs, wrinkles, area of thin film, or no film.
Metal parts	Not finished as specified.
Identification marking	Missing or incomplete.
Instructions for assembling	Missing or incomplete, when required.
Workmanship	Burrs, sharp edges, corners not rounded.
Type I:	
Shelf size	Smaller than minimum specified.
Attachment hook	Missing or not as required.
Spring clamp	Missing or not as required.
Bumpers	Missing or not as required.
Hardware	Missing or not as required.
Hardboard	Not drilled as specified.
Cut-out	Size and location not as specified.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:40Z
Check the source to verify that this is the current version before use.

Table I. Classification of filing shelf defects (cont'd)

Examine	Defects
Type II:	
Components	Not made from materials specified. Provision for holding down file material missing.
Wire mesh, frame, and hook	Not welded together to provide shelf with flat working surface.
Size of shelf working surface	Smaller than minimum specified.
Attachment hook	Not in conformance with 3.8.1.
Plastic coating	Not in conformance with 3.8.2.

4.4 Testing of end item. Samples taken in accordance with 4.2.3 shall be tested as described in 4.4.1.

4.4.1 Performance test. If furnished disassembled, assemble the filing shelf in accordance with the instruction data sheet. Position the attachment hook on a drawer pull of a file cabinet. Measure the distance from the floor to the edge of the working surface opposite the attachment hook. Record this measurement as the first dimension. Place four pounds of paper, size 8 by 10-1/2 inches, on the shelf, so that the 10-1/2-inch dimension is not more than one inch from the edge of the working surface opposite the attachment hook. Measure the distance from the floor to the edge of the working surface opposite the attachment hook. Record this measurement as the second dimension.

4.5 Inspection of preparation for delivery. An inspection shall be made to determine that the packaging, packing, and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table II.

Table II. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Distortion of container.
Contents (exterior container)	Number per container is more or less than required. Net weight exceeds requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:40Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Type I. The hook, clamp, hardware and instruction sheet shall be packaged together in accordance with method IC-I of MIL-P-116. Each shelf furnished disassembled, with components, hardware and instruction sheet shall be packaged in accordance with method IC-2 of MIL-P-116.

5.1.1.2 Type II. No packaging required.

5.1.2 Level B.

5.1.2.1 Type I. The hook, clamp, hardware and instruction sheet shall be packaged together in a kraft paper bag. The bag shall be closed with staples or tape. Each shelf furnished disassembled, with components, hardware and instruction sheet shall be packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665 or PPP-B-676. Cushioning shall be provided.

5.1.2.2 Type II. No packaging required.

5.1.3 Level C. The shelves shall be packaged to afford protection against corrosion and damage during shipment from the supplier to the initial destination.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Type I or II. Type I or type II shelves in quantities as specified (see 6.2) shall be packed in a close-fitting box conforming to PPP-B-585, class 3, PPP-B-591, class II, PPP-B-601, overseas type, PPP-B-621, class 2, PPP-B-636, class weather resistant or PPP-B-640, class 2, grade A. The boxes shall be closed in accordance with the applicable specification or appendix thereto. The gross weight of the triple-wall fiberboard box and the wood boxes shall not exceed 200 pounds. The gross weight of the PPP-B-636 box shall not exceed the weight limitations of the box specification. Strapping shall be in accordance with the appendix to the applicable box specification.

5.2.2 Level B.

5.2.2.1 Type I or II. Twelve type I unit packages of shelves or twelve type II shelves shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with method I of the appendix to the box specification.

5.2.3 Level C. The shelves shall be packed to insure carrier acceptance and safe delivery at destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Filing shelves covered by this specification are intended to serve as a filing aid. When attached to drawer pulls of file cabinets, the shelves support loose file material during filing operations.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:40Z
Check the source to verify that this is the currentversion before use.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type of filing shelf required (see 1.2.1).
(c) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).
(d) Quantity of shelves required in level A shipping containers (see 5.2.1.1).
(e) Any special marking required (see 5.3).

DOD coordination has been waived.

67-13787

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:40Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:40Z
Check the source to verify that this is the current version before use.