MILITARY SPECIFICATION

BROILER, SELF-CLEANING, ELECTRIC; COUNTER MODEL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers two sizes of electric self-cleaning broilers, counter model.

1.2 Classification. Broilers covered by this specification shall be of the following sizes as specified (see 6.2):

Size 1 - Single section grid
Size 2 - Two section grid

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATION

MILITARY

MIL-R-11337 - Ranges, Packaging and Packing Of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-130 - Identification Marking of U. S. Military Property

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:44Z
Check the source to verify that this is the current version before use.

American Society for Testing and Materials (ASTM)

Designation No. A167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip, Standard Specification for

Designation No. A463 - Aluminum-Coated Steel Sheets, Type I for Heat-Resisting Applications in Coils and Cut Lengths

Designation No. B456 - Electrodeposited Coatings of Nickel Plus Chromium, Standard Specification for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

National Electrical Manufacturers Association (NEMA)

(Information regarding NEMA standards can be obtained form the National Electrical Manufacturers Association, 155 East 44th Street, New York, NY 10017.)

National Sanitation Foundation (NSF)

Standard No. 4 - Commercial Cooking and Hot Food Storage Equipment

Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, MI 48106.)

Underwriters' Laboratories, Inc. (UL)

Standard No. 197 - Commercial Electrical Cooking Appliances

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 207 East Ohio Street, Chicago, IL 60611; 1285 Walt Whitman Road, Melville, L.I., NY 11746; 1655 Scott Boulevard, Santa Clara, CA 95050.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the supplier shall furnish a sample of the item to be procured under this specification for first article inspection and approval (see 4.3 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:44Z
Check the source to verify that this is the current version before use.

3.2 Standard product. The broilers shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features needed to comply with the requirements of this specification. Modifications to add features shall not incorporate different parts unless such parts are used on other current commercial models. Standard or modified commercial products furnished in accordance with this specification shall be identifiable by all regular manufacturer's or commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair services on models furnished to the government consistent with their normal commercial practices.

3.3 Codes and standards. The broilers shall comply with the applicable requirements of NSF Standard No. 4 and UL Standard No. 197.

3.3.1 Compliance. Prior to approval of the first article, if one is submitted, or prior to commencing production, the supplier shall submit to the contracting officer or his authorized representative satisfactory evidence that the broilers he proposed to furnish under this specification meet the applicable requirements of NSF and UL as follows:

3.3.1.1 NSF. Acceptable evidence of meeting the requirements of NSF shall be:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished broiler, or

(2) A certification for the broilers issued by NSF under their special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the broilers are being procured, indicating that the broilers have been tested and conform to NSF Standard No. 4.

3.3.1.2 UL. Acceptable evidence of meeting the requirements of UL shall be the UL label, a UL listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the broilers have been tested and conform to UL Standard No. 197.

3.4 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial broilers provided the completed item complies with all provisions of this specification.

3.4.1 Steel, sheet and strip.

3.4.1.1 Stainless steel. Stainless steel sheet shall conform to any type in the 300 series of ASTM A-167.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:44Z
Check the source to verify that this is the current version before use.

3.4.1.2 Chromium-nickel plated steel sheet and strip. Chromium-nickel plated steel sheet and strip shall conform to ASTM B-456.

3.4.1.3 Aluminum-coated steel. The aluminum-coated steel shall conform to type I of ASTM A-463.

3.5 Design. Broilers shall be designed for counter use. Sizes 1 and 2 broilers shall have a single grid section and two grid sections, respectively. Size 1 broilers shall consist essentially of a body, grid section, heating units, heat control, self-cleaning control, power ON-OFF switch, indicating lights, drip chute, grease drawer, locking lever, and legs. Size 2 broilers shall be provided with two grid sections with each section individually controlled. Like components, as for size 1 broilers specified above, shall be provided with the addition of a 3-position selector switch clearly marked indicating that either the left or right grid is capable of being cleaned and an additional grease drawer.

3.5.1 Dimensions. Broilers shall be within the dimensional limits shown in table I.

TABLE I. Dimensions (inches minimum)

Measurements	Size 1	Size 2
Height 1/	13-1/2	13-1/2
Width	21	37-1/2
Depth	23-1/2	23-1/2
Grid cooking area	16 x 16 (256 sq.in.)	16 x 32 (512 sq.in.)
Grid height (raised position)	23	23

1/ Height from countertop including legs.

3.6 Construction. All broiler components shall be fabricated of stainless steel, chromium-nickel plated steel or aluminum-coated steel conforming to 3.4.1.1, 3.4.1.2, 3.4.1.3, respectively.

3.6.1 Body. The body shall be of a frame or shell construction. When frame construction is used, the frame shall consist of a base frame, top frame and vertical angles welded together, or by any other means used by the manufacturer's, to form a rigid assembly with exterior sheets welded to the frame, inclosing it therein. When of a shell construction, the broiler body shall be totally

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:44Z
Check the source to verify that this is the current version before use.

enclosed and the outer shell shall be stiffened and reinforced as required. A control panel shall be provided on the front of the body. The exterior surfaces of the body shall be fabricated from chrome-nickel plated steel specified in 3.4.1.2. The body shall be reinforced at the body top for mounting the grid bearing support.

3.6.1.1 Size 1. The size 1 body top shall be of a one-piece construction fabricated from chrome-nickel plated steel specified in 3.4.1.2. The body top shall be formed with a single hopper, sized to fit under the grid cooking surface. The bottom of the hopper shall be provided with slotted drain holes. The hopper shall direct the grease drippings into the grease drawer. The control panel shall incorporate controls, switches, indicating lights and grease drawer (see 3.5).

3.6.1.2 Size 2. The size 2 body top shall be constructed similar to size 1 (see 3.6.1.1) except that the body top shall be formed with two hoppers, sized to fit under each cooking surface. Each hopper bottom shall be provided with slotted drain holes. The control panel shall incorporate controls, switches, indicating lights, grease drawers and a single timer capable of controlling each grid section independently.

3.6.2 Grid assembly. Each grid section shall be hinged at the rear and shall consist of grids, heating elements, handle unit(s), grid unit support(s), grid bearing support(s), splash guard(s), and locking lever(s). Sizes 1 and 2 broilers shall be provided with one and two grid sections, respectively.

3.6.2.1 Grid. Grids shall be fabricated of cast iron and shall be designed to enclose the heating elements so that grease drippings cannot contact the heating elements. Each grid section shall consist of two units attached at the rear to a grid unit support and at the front to the handle unit. Each grid shall be supported at the rear by grid bearing supports. Each grid section shall be provided with a locking lever.

3.6.2.2 Handle unit. A handle unit shall be provided for each grid section and the handle unit shall consist of a front support mounting plate incorporating two front legs and handle. The front support mounting plate shall be fabricated from stainless steel specified in 3.4.1.1 and the handle shall be fabricated from stainless steel rod. The handle shall be welded to the front support mounting plate so than when gripped, there shall be clearance between hand and mounting plate. The handle unit shall be secured to the front end of the grids with stainless steel screws. The handle unit shall be used for raising and lowering the grid assembly from the normal down position to the raised and lock position and return. The handle temperature shall not exceed 90F when tested as specified in 4.6.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:44Z
Check the source to verify that this is the current version before use.

3.6.2.3 Splash guards. Splash guards for sizes 1 and 2 broilers shall be of a one-piece and two-piece construction, respectively. Splash guards shall be fabricated of chrome-nickel plated steel specified in 3.4.1.2. The splash guard shall be formed to fit the perimeter of the grid section at both sides and back. The front of the grid section shall open. Both sides of the splash guard shall be tapered at least 4 inches, front and rearwards to the top edge. The tapered sides shall be flanged outwards 90 degrees. The flange shall be of sufficient size for gripping by hand(s). Splash guards shall be provided with means for securing, to the grid section, without the use of fasteners. Splash guard(s) shall be removable for cleaning. The two-piece splash guard for the size 2 broilers shall be constructed the same as for the size 1 broiler splash guard specified above except that splash guard shall be formed to fit perimeter at one side and back of each splash guard section. Each splash guard section shall be secured to each separate grid section.

3.6.3 Grease drawer. Grease drawer for the broilers shall be of one-piece construction and shall be fabricated from aluminum-coated steel specified in 3.4.1.3. Grease drawer(s) shall be provided with two each anti-splash vertical baffles. The baffles shall be evenly spaced and shall be mounted flush with the top edge of the sides and extended into the drawer at least one-half of the drawer depth. Sizes 1 and 2 broilers shall be provided with one and two grease drawers, respectively. The front face of each grease drawer shall be fabricated from chrome-nickel plated steel specified in 3.4.1.2 and shall be secured to the grease drawer. Each grease drawer shall be provided with a finger pull or handle and a vent. Finger pulls, when provided, shall be located at the top and shall extend the width of the grease drawer. Each grease drawer shall be removable without binding and shall remain level while being withdrawn when tested as specified in 4.6.1. The grease temperature in the grease drawer shall not exceed 150F when tested as specified in 4.6.3. Grease drawer capacity shall be 1 gallon when tested as specified in 4.6.1.

3.6.4 Drip chute. Drip chute(s) shall be of a one-piece construction and shall be provided with four legs. Drip chute(s) shall be fabricated from stainless steel specified in 3.4.1.1. Each corner of the drip chute shall be provided with legs fabricated from stainless steel wire. Each drip chute shall be formed with a funnel-like hopper to match the contour of the body top. Each drip chute bottom shall be provided with drain holes. The drip chute shall not contact the grids when placed on the body top.

3.6.5 Legs. Each broiler shall be provided with four legs. The legs shall be attached to the bottom four corners of the body. The legs shall be adjustable and removable and shall be a minimum of 4 inches in length.

3.7 Electrical characteristics. Unless otherwise specified (see 6.2), broilers shall operate on a nominal 208 volt, 1-phase, 60-hertz (Hz), alternating current (a.c.) system. Broilers shall be provided with provisions for grounding.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:44Z
Check the source to verify that this is the current version before use.

3.7.1 Controls.

3.7.1.1 Size 1. Size 1 broilers shall be provided with an infinite heat switch, 3-position selector switch with "OFF", "SPOIL" and "CLEAN" settings, timer (0-20 minutes) and indicating lights (see 3.7.1.6).

3.7.1.2 Size 2. Size 2 broilers shall be provided with the components specified in 3.7.1.1 for each grid section with the exception that an additional selector switch shall be provided. The selector switch shall be of the 3-position type marked with "OFF" and arrows indicating either "LEFT", and "RIGHT" grid sections.

3.7.1.3 Contactors. Sizes 1 and 2 broilers shall be provided with one and two contactors, respectively. The contactors shall be mounted on the broiler and shall conform to the applicable National Electrical Manufacturer's Association (NEMA) Standards. Contactors shall be of the 4-pole magnetic type. One each contactor shall be installed in each of the two individually controlled electrical heating element system of the size 2 broiler grid sections.

3.7.1.4 Safety switch. Each grid section shall be provided with a safety switch of the tilt type installed in the grid section. The electrical clean cycle shall be activated when the grid section is in the raised and lock position and tilt switch is actuated, timer actuated, and selector control set at clean setting. Each grid section of the size 2 broilers shall be cleaned individually.

3.7.1.5 Heating elements. The heating elements shall be of the enclosed tubular type with a nickel-chromium steel sheath. Each grid section shall be provided with four separate heating units. Each grid section shall be separately controlled by a 3-position switch (see 3.7.1.1). Heating elements shall be securely fastened or clamped to the underside of the grid section. Heating elements shall be readily accessible for replacement.

3.7.1.6 Indicating lights. Broilers shall be provided with two indicating lights that glow whenever each separately controlled electrical system, either (a) or (b), is energized: (a) Power "ON", broiler selector switch turned "ON" and broiler heat control set to desired setting, while heating elements are energized broiler indicator light shall illuminate and go "OUT" when desired setting is reached; or (b) Power "ON", broiler selector switch set to clean, grid in raised and lock position, timer set to desired time setting, clean indicating light shall remain illuminated during clean cycle and go out when clean cycle is complete or when power is turned "OFF". All indicating lights shall be mounted adjacent to the heat control switch or timer, as applicable.

3.8 Identification marking. Each broiler shall be permanently and legibly marked in accordance with MIL-STD-130 with the manufacturer's name or trade-name and model number readily identifiable with said manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:44Z
Check the source to verify that this is the current version before use.

3.9 Instruction plates. Instruction plates indicating special procedure and precautions for operating or servicing the unit shall be permanently attached to each broiler.

3.10 Operation. Each broiler heating element indicating light (s), controls and heating elements shall operate satisfactorily and each moving component shall fit and operate smoothly when tested as specified in 4.6.1.

3.11 Performance. The broiler, when operating at "Lo", "intermediate" and "Hi" infinite heat control switch settings, shall have average temperatures of 205F, 350F, and 550F, respectively, when tested as specified in 4.6.2. The grid temperature during cleaning cycle shall be at least 950F and the test air temperature shall not exceed 330F when tested as specified in 4.6.3.

3.12 Finish. Broilers shall be smooth on all surfaces and edges and shall be free from discoloration or stains. The broiler components shall be finished in accordance with the manufacturer's standard practice for aluminum-coated steel, chrome-nickel plated steel or stainless steel.

3.13 Workmanship. All components and assemblies of the broiler shall be free from dirtt and other harmful extraneous material, burrs, slivers, rough die, tool and grind marks, dents and cracks. Castings, molded parts, and stampings, if used, shall be free of sand, fins, pits, blow holes, and sprues. External surfaces shall be free from sharp edges and corners, except when corners are required.

3.13.1 Metal fabrication. Metal used in the fabrication of the broiler shall provide for original quality surface finish and shall be free from kinks and unspecified bends. Forming and shearing shall not cause damage to the metal and shall be done neatly and accurately. Corners shall be square and true and all bends of a major nature shall be made with dies or fixtures to insure uniformity of size and shape.

3.13.2 Welding. The surfaces of parts to be welded shall be free from rust, scale, paint, grease and other foreign matter. Welds shall be smooth and free from cracks, burn holes, undercuts or incompleted fusion. All scale and flux shall be removed from the finish weld area.

3.13.3 Fastening devices. Threaded fastener and rivet holes shall be accurately punched or drilled and shall have burrs removed. Threaded fasteners shall not be broken, cracked or stripped and shall be securely torqued. Rivets shall fill the hole completely and the heads shall be in full contact with the surface of the member and concentric with the hole.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:44Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3).
2. Quality conformance inspection (see 4.4).

4.3 First article. When a first article is required, it shall be examined for the defects in table II, compliance with dimensions specified in 3.5.1 and tested as specified in 4.6.1, 4.6.2, and 4.6.3. Failure of any test shall be cause for rejection of the first article. The presence of any defect listed in table II or any dimension not within specified requirements shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.4.1 Component and material inspection. The supplier shall insure that all components and materials used are manufactured, examined and tested in accordance with referenced specifications and standards unless excluded, amended, modified or qualified in this specification or applicable purchase document.

4.4.2 Inspection of the end product. The inspection lot shall consist of all broilers of one size offered for inspection at one time. The sample unit shall be one completely fabricated broiler.

4.4.2.1 Visual examination. Examination shall be made of the completely assembled broiler for the defects listed in table II. The inspection level shall be level II with AQL's of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:44Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects

Examine	Defect	Classification Major	Minor
Standard product	Item not in accordance with manufacturer's standard product	X	
Finish	Not as specified	X	
	Edges and surfaces not smooth	X	
	Not free of discoloration or stains		X
Construction and workmanship general	Component missing	X	
	Any wearing part not accessible for adjustment or replacement	X	
	Any component fractured or malformed	X	
	Any component misplaced or not in alignment	X	
	Any burr, sliver, sharp edge, rough die, tool, gouge, trim, or grind marks	X	
	Any component fractured, buckled, bent, dented, punctured, or malformed	X	
	Functioning component that is inoperative or will not operate as intended	X	
	Functioning component that required abnormal force to operate		X
	Any adjustable assembly not properly adjusted to perform the intended function		X
	Not constructed as specified	X	
	Not fabricated of material specified	X	
Detail construction	Not fully enclosed	X	
Body	Body top not one piece construction	X	
	Body top not provided with drain hole	X	
	Hopper not formed to fit under grid section	X	
	Two hoppers not provided for size 2 broilers	X	
Grid	Each grid section not secured	X	
	Each grid section not provided with locking lever (raised position)	X	
Handle	Not secured	X	
	Loose		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:44Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Splash guard	Not removable without the use of tools	X	
	Not one piece construction (size 1)	X	
	Not two piece construction (size 2)	X	
	Loose		X
Grease drawer	Not one piece construction	X	
	Not provided with drawpull or handle	X	
	Not provided with vertical splash baffles	X	
	Not provided with face plate and vent	X	
	Binds when withdrawn	X	
Drip chute	Not fabricated of one piece	X	
	Not provided with drain holes	X	
	Does not seat properly on body top		X
	Drip chute hits grid section	X	
Legs	Not adjustable	X	
	Not removable	X	
	Loose		X
Electrical switches, controls, and other components (as applicable)	Missing, not type specified, or do not function as intended	X	
	Not accessible to operator	X	
Heating element	Not sheathed tubular type	X	
	Not readily accessible for replacement	X	
	Not secured to grid	X	
	One mounting clip to grid missing		X
Indicating lights	Not type specified	X	
	Not visible to operator	X	
Welding	Missing	X	
	Not free from rust scale, paint, grease and other foreign matter	X	
	Scale and flux deposits not removed		X
	Weld not smooth and free of cracks, burnholes, undercuts or incomplete fusion		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:44Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Fastening devices	Missing, cracked, or stripped		X
	Fastener, loose		X
	Fastener improperly torqued	X	
	Rivet holes not accurately punched	X	
	Rivet not peened properly		X
Castings	Miscast, blowholes, or incomplete, not free of sand, fins, pits, and sprues	X	
Marking identification	Missing, incomplete, not legible, not corrosion-resistant metal	X	
Instructions	Missing, incomplete, not legible	X	

4.4.2.2 Dimensional examination. The broilers shall be examined for compliance with dimensions specified. Any dimension not within the specification tolerance shall be a defect. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units.

4.4.2.3 End item testing. Each broiler shall be tested as specified in 4.6.1. Failure of this test shall be cause for rejection of the unit. When a first article is not required, the first produced broiler shall be tested as specified in 4.6.2 and 4.6.3. Failure of any test shall be cause for rejection of the lot.

4.4.3 Examination of preparation for delivery. An examination shall be made to determine that preparation for delivery as specified in section 5 is in conformance with MIL-P-11337.

4.5 Certificate examination. Certificates of compliance, certified test reports, approved labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with the specification requirements shall be examined and validated.

4.6 Tests.

4.6.1 Operational test. Connect the broiler to an appropriate electrical power source. Check to assure that indicator lights, heat controls, and switches function as indicated. Observe that indicator lights go "ON" when the heating elements are activated and go "OUT" whenever the control setting is attained or when power is turned OFF. During cleaning cycle, observation shall be made to see that indicating light glows constantly while heating

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:44Z
Check the source to verify that this is the current version before use.

elements are activated and goes "OUT" at end of clean cycle when power is turned "OFF" to determine conformance with 3.10. Drip drawers shall be pulled out to check for conformance with 3.6.3. Any nonconformance with the requirements specified shall constitute failure of this test.

4.6.2 Functional test. The broiler shall be instrumented to measure grid, handle, and grease temperature by means of an indicating potentiometer and thermocouples. Readings of the grid section shall be taken in five locations, one at each of the four corners, 1-inch in from all sides and one at the center intersection of diagonal lines from corner to corner. Preheat broiler grid section in accordance with manufacturer's standard practice. With power ON, set selector switch to broil position, set infinite heat control switch to "LO" position, after temperature is stabilized, record readings. Repeat procedure for "Hi" position and "Intermediate setting" (midway between "Lo" and "Hi"). Between each control setting, allow broiler to cool. Temperature readings shall be averaged to determine conformance with the requirements of 3.11. Any nonconformance with the requirements specified shall constitute failure of this test. Fill grease drawer with liquid and pour contents in a measured beaker for compliance with 3.6.3.

4.6.3 Self-cleaning test. This test may be performed in conjunction with 4.6.2. Each grid section shall be instrumented to measure the grid temperature by means of an indicating potentiometer and thermocouple(s) (two thermocouples for size 2 broilers). The thermocouple shall be located at the center of the grid. Directly above the center thermocouple, a distance of 6 inches, a second thermocouple shall be used to measure the test air temperature. During this test, the test air temperature shall not exceed the temperature requirements of 3.11. Prior to self-cleaning test, coat the grid surface with salad oil. Raise grid section to its locked position, turn power ON, set selector to clean position and turn timer to 20 minutes. Readings shall be taken for five 20-minute cycles. This procedure shall be repeated twice for the size 2 broilers (one for each grid section). After completion of this test, there shall be no evidence of salad oil on grids and the grid handle and grease temperature shall conform to 3.11, 3.6.2.2 and 3.6.3, respectively. Any nonconformance with the requirements specified shall constitute failure of this test.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing and marking. Each complete broiler shall be preserved, packaged, packed and marked in accordance with the applicable requirements of MIL-R-11337. Preservation and packaging shall be level A or C, and packing shall be level A, B, or C, as specified (see 6.2).

6. NOTES

6.1 Intended use. The broilers covered by this specification are intended for use in military kitchens for broiling of various food products.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:44Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Size broiler required (see 1.2).
(c) When a first article is required (see 3.1, 4.3 and 6.3).
(d) When other than 208-volt, 60 hertz, 1-phase operation is required (see 3.7).
(e) Selection of the applicable level of preservation and packaging and packing (see 5.1).

6.2.1 Contract data requirements. Any data items to be delivered under any contract for the items covered by this specification should be specifically called for in the contract in accordance with the applicable regulations of the procuring activity.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be a preproduction sample, initial production item or other specific item described under the definition of a first article in the ASPR. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

Custodians:

Army - GL
Navy - YD
Air Force - 84

Review activities:

Army - MD
Navy - MC
DSA - GS

User activity:

Army - CE

Preparing activity:

Army - GL

Project No. 7310-0447

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

BROILER, SELF-CLEANING, ELECTRIC; COUNTER MODEL MIL-B-43878

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:44Z
Check the source to verify that this is the current version before use.