MIL-F-43883A

8 December 1975
SUPERSEDING
MIL-F-43883
21 March 1974
(see 6.3)

MILITARY SPECIFICATION

FOOD WARMER, INFRA-RED, ELECTRIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers electrically heated one and two bulb infra-red food warmers.

1.2 Classification. Food warmers shall be of the following types, as specified (see 6.2):

Type I	-	Two infra-red bulbs with adjustable self-supporting frame
Type II	-	One infra-red bulb with rigid support stem

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing

MILITARY

MIL-P-116	-	Preservation Packaging, Methods of

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:46Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

LAWS AND REGULATIONS

29 CFR 1910 - Occupational Safety and Health Act (OSHA) Standards

(The Code of Federal Regulations (CFR) and Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof).

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or requests for proposal shall apply:

American Society for Testing and Materials (ASTM)

A - 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip
A - 176 - Stainless and Heat-Resisting Chromium Steel Plate, Sheet and Strip
A - 619 - Carbon Steel Sheet, Cold-Rolled, Drawing Quality
A - 621 - Carbon Steel Sheet and Strip, Hot-Rolled, Drawing Quality
B - 209 - Alumium-Alloy Sheet and Strip
B - 210 - Aluminum-Alloy Drawn Seamless Tubes
B - 456 - Electrodeposited Coatings of Nickel Plus Chromium
B - 483 - Aluminum-Alloy Drawn Tubes for General Purposes Applications

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA. 19103).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:46Z
Check the source to verify that this is the current version before use.

National Sanitation Foundation (NSF)

Standard No. 4 - Commercial Cooking and Hot Food Storage Equipment

Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, MI 48105).

Underwriters' Laboratories, Inc. (UL)

No. 197 - Commercial Electrical Cooking Appliances

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 207 East Ohio Street, Chicago, IL 60611; 1285 Walt Whitman Road, Melville, LI, NY 11746; 1655 Scott Boulevard, Santa Clara, CA 95050).

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036).

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606).

(Technical Society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies).

3. REQUIREMENTS

3.1 Standard product. The food warmer shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features needed to comply with the requirements of this specification. Modifications to add features shall not incorporate different parts unless such parts are used on other current commercial models. Standard or modified commercial products furnished in accordance with this specification shall be identifiable by all regular manufacturer's or commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair services on models furnished to the government consistent with their normal commercial practices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:46Z
Check the source to verify that this is the current version before use.

3.2 Codes and standards. The food warmer shall comply with the applicable requirements of UL No. 197, NSF Standard No. 4, and OSHA Standards 29 CFR 1910, promulgated under the Occupational Safety and Health Act.

3.2.1 Compliance. Prior to commencing production, the supplier shall submit satisfactory evidence to the contracting officer or his authorized representative that the food warmers he proposes to supply under this specification meet the applicable requirements of UL No. 197, NSF No. 4 and OSHA Standards, 29 CFR 1910 as follows:

3.2.1.1 UL. Acceptable evidence of meeting the requirements of UL shall be the UL label, a UL listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the food warmers have been tested and conform to UL No. 197.

3.2.1.2 NSF. Acceptable evidence of meeting the requirements of NSF shall be:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished food warmer, or

(2) A certification for the food warmers issued by NSF under their special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the food warmers are being procured, indicating that the food warmers have been tested and conform to NSF Standard No. 4.

3.2.1.3 OSHA. Acceptable evidence of meeting the applicable safety and health standards of OSHA shall be a certificate of compliance, certifying that the food warmers furnished conform to subpart I, section 1910.137 and subpart S, section 1910.309 of OSHA Standards, 29 CFR 1910.

* 3.3 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial food warmers provided the completed item complies with all provisions of this specification.

3.3.1 Stainless steel sheet and strip. Stainless steel sheet and strip shall conform to type 302 or 304 of ASTM A - 167; or types 409, 410 or 430 of ASTM A - 176.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:46Z
Check the source to verify that this is the current version before use.

3.3.2 Carbon steel cold-rolled sheet. Carbon steel cold-rolled sheet shall conform to ASTM A - 619.

3.3.3 Carbon steel hot-rolled sheet and strip. Carbon steel hot-rolled sheet and strip shall conform to ASTM A - 621.

3.3.4 Electrodeposited coatings of nickel plus chromium. Electrodeposited coatings of nickel plus chromium shall conform to service condition SC2 of ASTM B - 456.

3.3.5 Aluminum-alloy sheet and plate. Aluminum-alloy sheet and plate shall conform to types 3003, 5052 or 6061 of ASTM B - 209.

* 3.3.6 Aluminum-alloy drawn tubes. Aluminum-alloy drawn tube shall conform to type 5052, 6061 or 6063 of ASTM B - 210 or ASTM B - 483.

* 3.4 Design and construction. Type I food warmers shall be designed with an adjustable self-supporting frame with two infra-red bulbs. Type II food warmers shall be designed for ceiling mounting, fixed rigid stem type with one infra-red bulb.

3.4.1 Type I. The type I food warmer shall consist of an adjustable self-supporting frame, two infra-red bulbs, two lamp shades, an "ON-OFF" switch, a base shelf and a holding pan when required. The food warmer shall accommodate a pan 20 $^{+1}_{-0}$ inches long by 12 $^{+1}_{-0}$ inches wide by 2-1/2 inches high (minimum). The food warmer shall be opened on all sides to allow removal of warmed product without removing the pan. The bulbs and shades shall be vertically mounted on the upper horizontal frame. The frame shall have a minimum adjustable height range from the top of the base shelf to the bottom of the shades of 10 inches to 16 inches. Means shall be provided to hold the frame at any intermediate height within the adjustment range. The projected heated area shall be 20 $^{+1}_{-0}$ inches long by 12 $^{+1}_{-0}$ inches wide at the lowest adjustment range. The lamps shall be operated by one or two "ON-OFF" switch(s). The lamp shall operate whenever switch is turned "ON" when tested as specified in 4.4.2. The switch shall be visible and easily accessible to the operator. When the switch is in the "OFF" position, all ungrounded lines shall be deactivated. Switches shall be easily accessible for service or replacement.

3.4.1.1 Frame. The frame shall be stainless steel having a thickness not less than 22-gauge (nominal 0.0312 inches) conforming to 3.3.1, or aluminum having a thickness of not less than 14-gauge (nominal 0.064 inches) conforming to 3.3.5, or carbon steel having a thickness not less than 22-gauge (nominal 0.0312 inches) conforming to 3.3.2 or 3.3.3 and coated in accordance with 3.3.4.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:46Z
Check the source to verify that this is the currentversion before use.

3.4.1.2 Base shelf. The base shelf shall protect the counter from the heat of the bulbs. The base shelf shall be the same size as the projected heated area at the lowest adjustment height within the adjustment range. The base shelf shall be stainless steel having a thickness not less than 22-gauge conforming to 3.3.1 or aluminum having a thickness not less than 14-gauge conforming to 3.3.5.

3.4.1.3 Bulbs and shades. Unless otherwise specified (see 6.2) the bulb shall be a red colored infra-red bulb. The infra-red bulbs used shall have a rating of 250-watts each. The lamp shades shall be constructed of stainless steel having a thickness not less than 22-gauge conforming to 3.3.1 or aluminum having a thickness not less than 16-gauge (nominal 0.051 inches) conforming to 3.3.5. The lamp shades shall be designed to offer bulb protection. The bulbs shall not extend beyond the shades.

3.4.1.4 Holding pan. When specified (see 6.2), a holding pan shall be provided. The pan shall be standard size that is 20 inches long by 12 inches wide by 2-1/2 inches deep. The pan shall be type 302 or 304 stainless steel having a thickness not less than 20-gauge (nominal 0.0375 inches) conforming to 3.3.1 or aluminum having a thickness not less than 16-gauge (nominal 0.051 inches) conforming to 3.3.5. The pans shall have a removable drain plate of the design that permits drainage. The plate shall allow drainage of grease. The top of the drain plate shall be 1/2 ± 1/8 inch above the bottom of the pan. The drain plate shall be type 302 or 304 stainless steel having a thickness not less than 22-gauge conforming to 3.3.1, or aluminum having a thickness not less than 14-gauge (nominal 0.064 inches) conforming to 3.3.5.

* 3.4.2 Type II.

3.4.2.1 Type II. The type II food warmer shall consist of a terminal box and cover plate, a ceiling mounting block, a rigid stem tube, a lamp shade, one (1) infra-red bulb, and an "ON-OFF" switch. When specified (see 6.2) for shipboard use, overall length shall be 60 ± 1.0 inch. All other installations overall length shall be 50 ± 1.0 inch. The overall length shall include the ceiling mounting block, the lamp shade and the stem.

3.4.2.2 Terminal box, ceiling mounting block (canopy). The terminal box shall be a standard 4 inch box with 1/2 inch knockouts. The terminal box shall be supplied with a compatible cover plate. The ceiling mounting block (canopy) shall be constructed of aluminum having a thickness not less than 22-gauge (nominal 0.025 inch) conforming to 3.3.5. The ceiling mounting block or steel hanger bar with decorative cover plate shall be designed to accommodate the stem tube.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:46Z
Check the source to verify that this is the current version before use.

3.4.2.3 Stem tube. The stem tube shall be aluminum tubing having an outside diameter of 5/8 inch and a thickness not less than 18-gauge (nominal 0.04.9 inch) conforming to 3.3.6. When specified (see 6.2) for shipboard use the stem tube shall be furnished in four (4) sections of equal length, threaded at both ends and readily joined by threaded couplings. All other installations the stem shall be one piece. The stem length shall be sized to attain the overall dimension specified in 3.4.2.1. Provisions shall be made to allow cutting of the stem or provide means to attain overall lengths of less than 50 ± 1.0 inch.

3.4.2.4 Lamp shade, infra-red bulb and "ON-OFF" switch. The lamp shade shall be constructed of aluminum having a thickness not less than 22 gauge (nominal 0.025 inch) conforming to 3.3.5. The lamp shade opening diameter shall be 7-1/6 ± 1/8 diameter. The bulb shall not extend beyond the shade. Unless otherwise specified (see 6.2), the bulb shall be a red colored infra-red bulb. The bulb shall have a rated capacity of 250 watts. The lamp shall be operated by an "ON-OFF" switch. The lamp shall operate whenever switch is turned on when tested as specified in 4.4.2. The switch shall be visible and accessible to the attendant. The switch shall be located to prevent direct contact with the lamp shade.

3.4.3 Electrical characteristics. Unless otherwise specified (see 6.2) the food warmer shall be designed for operation on 60-hertz, 120 volts power supply. The type I food warmer shall be provided with an attached power supply cord compatible with the item being furnished. The power supply cord shall be a UL approved 3-wire cord complete with 3-prong grounding type attachment plug. The power supply cord shall be not less than five (5) nor more than six (6) feet long.

* 3.5 Performance. Type I and type II food warmers shall be capable of maintaining fried foods (such as chicken, potatoes and shrimp) and bakery products at serving temperatures (140 F) when tested as specified in 4.4.1.

3.6 Repair and maintenance. Provision shall be made to allow easy access for adjustment, repair or replacement of electrical and other components.

* 3.7 Marking. Identification and, if applicable, operating instructions shall be permanently amrked directly on the item or on an aluminum, brass, or stainless steel plate firmly affixed to the item. Marking shall be stamped, embossed, engraved or photosensitive. The plate thickness shall be not less than 0.012 inch.

3.7.1 Identification marking. Each food warmer shall be permanently and legibly marked with the manufacturer's model and name, trade name or trademark easily identified with said manufacturer.

Source: https://assist.dla.mil -- Downloaded: 20261O-21T22:46Z
Check the source to verify that this is the currentversion before use.

* 3.8 Finish. All surfaces shall comply with NSF Standard No. 4. The food warmer shall be smooth on all surfaces and edges and shall be free from discoloration or stains. Aluminum food warmers shall have the manufacturers standard finish.

* 3.9 Workmanship. The finished food warmers shall be clean and shall not contain any burrs, slivers, breaks, sharp corners, sharp edges, deformities, dents or rough die or grind marks. Welds shall be sound, smooth and free from pits, fractures, burn-through, or fissures. Bolt holes and rivet holes shall be accurately punched or drilled and shall have burrs removed. All bolts, nuts and screws shall be drawn tight. Rivets shall be tightly driven and fully peened. Electrical wiring shall be provided with adequate slack to relieve strain, and the wiring shall not be abraded, poorly joined, or loose at terminals.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.2.2 End item inspection. The inspection lot shall be all the food warmers offered for inspection at one time.

* 4.2.2.1 Visual examination. The completely assembled food warmers (type I and type II, as applicable) shall be examined for the defects listed in table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:46Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Standard product	Item not in accordance with manufacturer's standard product	X	
Finish	Not smooth	X	
	Evidence of discoloration, or stains		X
Workmanship	Dirty		X
	Any rough or sharp edges, scratches, burrs, slivers, breaks, sharp corners, deformities, dents, rough die or grind marks	X	
Welding and brazing	Not continuous, not smooth, not uniform, burn holes, cracks, fissures, incomplete fusion	X	
	Not finished to blend with adjacent metal surfaces	X	
	Flux or scale not removed	X	
Soldering	Incomplete, not adherent	X	
	Dirty, pin holes, flux not removed	X	
Threaded fasteners	Missing, stripped, cross-threaded, or fractured	X	
	Loose		X
Rivets	Loose, not in full contact with members riveted	X	
Design and construction	Not designed as specified	X	
	Maintenance access not provided	X	
ON-OFF switch	Missing. Not accessible and not visible to operator	X	
	Not located to prevent direct contact with bulb	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:46Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Pan (when applicable)	Missing	X	
	Not standard shallow size pan	X	
Bulbs	Missing, not infra-red	X	
	Not 250-watts	X	
Power supply cord and plug	Not three-wire grounding type cord	X	
	Not three-prong grounding plug	X	
Lamp shades	Missing	X	
	Does not extend beyond bulb(s)	X	
Terminal box and cover (type II)	Missing	X	
	Does not accommodate rigid stem tube	X	
Marking	Missing, not permanent, not legible, marking not as specified	X	

* 4.2.2.2 Dimensional examination. The food warmers shall be examined for compliance with dimensions specified in 3.4.1 through 3.4.2.4. Any dimension not within the specified requirements shall be a defect. The inspection level shall be S-4 with an AQL of 6.5 expressed in defects per hundred units.

4.2.2.3 End item testing. One representative production unit shall be tested as specified in 4.4.1. Failure of the test shall be cause for rejection of the inspection lot. Each food warmer shall be tested as specified in 4.4.2. Failure of this test shall be cause for rejection of the unit.

* 4.2.3 Examination of preparation for delivery requirement. An examination shall be made to determine that packaging, packing and marking complies with section 5 requirements of this specification. Defects shall be as indicated in table II. The sample unit shall be one shipping container fully prepared for delivery except that it need not be closed. The lot shall be the number of containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 2.5 defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:46Z
Check the source to verify that this is the current version before use.

TABLE II. Examination of preparation for delivery

Examine	Defect
Markings, exterior and interior	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, loose strapping, improper taping or inadequate stapling Bulged or distorted containers
Contents	Number of food warmers per container is more or less than required
Materials	Any component missing, damaged or otherwise defective

4.2.3.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing and strapping shall be in accordance with PPP-B-636.

4.3 Certificate examination. Certificates of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with the specification requirements shall be examined and validated.

4.4 Test methods.

* 4.4.1 Functional test. Connect the food warmer to an appropriate power source. Place "ON-OFF" switch in "ON" position. Check to assure light bulbs are operating and serving temperature specified in 3.5 is maintained. Check for frame adjustment requirements specified in 3.4.1. Check that provisions have been made to hold frame at any intermediate height within the adjustment range. Check wattage rating of light bulbs. Check to assure that ungrounded lines are deactivated when the "ON-OFF" switch is in the "OFF" position. Using a 12 inch by 20 inch by 2-1/2 inch pan, check for pan accessibility requirements specified in 3.4.1. Non-conformance with any requirements of 3.4.1 and 3.5 shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:46Z
Check the source to verify that this is the current version before use.

* 4.4.2 Operational test. Connect the type I and type II food warmer to an appropriate power source. Place "ON-OFF" switch in "ON" position and check for light bulb operation requirements specified in 3.4.1 and 3.4.2.4. Check type I food warmers for holding feature at five increments of height adjustment within the adjustment range. Failure of light bulb operation or failure of holding feature for frame adjustment shall constitute failure of this test.

5. PREPARATION FOR DELIVERY

* 5.1 Packaging. Packaging shall be level A or Commercial as specified (see 6.2).

* 5.1.1 Level A. Each food warmer shall be packaged in accordance with method III of MIL-P-116 in a snug-fitting fiberboard box conforming to style RSC, type CF, (variety SW), class domestic, grade 200, of PPP-B-636. Box closure shall be secured with 2-inch minimum width gummed tape conforming to type III, grade A, of PPP-T-45.

* 5.1.2 Commercial packaging. Each food warmer shall be packaged to afford adequate protection against physical damage during shipment from the supply-source to the first receiving activity. The package shall be the same as that normally used by the supplier for retail distribution.

* 5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

* 5.2.1 Level A. Two type I food warmers, or six type II food warmers, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, V3s of PPP-B-636. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636.

* 5.2.2 Level B. Two type I food warmers, and six type II food warmers packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic, grade 275, of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

* 5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be grade V3c, V3s, or V4s, fiberboard box, fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:46Z
Check the source to verify that this is the current version before use.

* 5.2.3 Commercial packing. Food warmers, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transporation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the supplier for retail distribution. Containers shall comply with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

* 6.1 Intended use. The food warmer covered by this specification is intended for use in military dining facilities. The type I food warmer will accommodate the shallow full size steam table pan specified in S-S-710.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Type required (see 1.2).
(c) When other than a red colored infra-red bulb is required (see 3.4.1.3 and 3.4.2.4).
(d) When a holding pan is required (see 3.4.1.4).
(e) When other than 120 volts, 60 Hz is required (see 3.4.3).
(f) When shipboard requirements are applicable (see 3.4.2.1 and 3.4.2.3).
(g) Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
(h) When weather-resisting grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.2.1 Contract data requirements. Any data items to be delivered under any contract for items covered by this specification should be specifically called for in the contract in accordance with the applicable regulations of the procuring activity.

6.3 Supersession data. This specification includes the requirements of Interim Purchase Description, Food Warmer, Infra-Red, Electric, Rigid Stem IP/DES S-10-3, dated 4 December 1973 and is identified in this specification as type II.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:46Z
Check the source to verify that this is the currentversion before use.

6.4 The margins of this specification have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - YD

Review activities:

Army - MD
Navy - SA, MS, CG

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 7310-0513

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-F-43883A - FOOD WARMER, INFRA-RED, ELECTRIC

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:46Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK DEVELOPMENT CENTER
NATICK, MA 01760
OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

AMXNM-TDC

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

Commander
US Army Natick Development Center
ATTN: AMXNM-TDC
Natick, MA 01760

NATICK OP 1 MAY 75

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:46Z
Check the source to verify that this is the current version before use.