INCH-POUND

MIL-K-43911B
15 August 1994
SUPERSEDING
MIL-K-43911A(GL)
19 August 1977

MILITARY SPECIFICATION

KITCHEN, FIELD, TRAILER MOUNTED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers an expandable, self-contained, trailer mounted field kitchen.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-WEE, Natick, MA 01760-5018, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7360

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

A-A-52190 - Dispenser, Liquid, Insulated
A-A-52193 - Food Container, Insulated, With Inserts
V-T-285 - Thread, Polyester
PPP-T-60 - Tape: Packaging, Waterproof

MILITARY

MIL-T-704 - Treatment and Painting of Material
MIL-C-5541 - Chemical Conversion Coatings on Aluminum and Aluminum Alloys
MIL-A-8625 - Anodic Coatings, For Aluminum and Aluminum Alloys
MIL-D-43916 - Dispenser, Liquid, Insulated
MIL-O-44368 - Opener, Can, Hand, for Tray Packs and Round Cans
MIL-C-46168 - Coating, Aliphatic Polyurethane, Chemical Agent Resistant

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams And Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables For Inspection by Attributes
MIL-STD-129 - Marking For Shipment and Storage
MIL-STD-370 - Visual Acceptance Criteria for Inspection of Aluminum Alloy Welds

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094, or from the Federal Supply Service Bureau, Specification Section (3FPB-W), Suite 8100, 470 East L'Enfant Plaza, SW., Washington, DC 20407.)

2.1.2 Other Government, documents, drawings, and publications. The following Government documents, drawings, and publications form a part of this specification to the extent specified herein Unless otherwise specified, the issues are those cited in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

Department of the Army Technical Manual

TM 10-7360-206-13 - Operator's-Organizational and Direct Support Maintenance Manual for Kitchen, Field, Trailer Mounted.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-13-2500 - Kitchen, Field, Trailer Mounted- Drawing List

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-WEE, Natick, MA 01760-5018.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

ASSOCIATION OF AMERICAN RAILROADS (AAR)

Loose-Leaf Section No. 6 - Loading of Department of Defense Material on Open Top Cars

(Application for copies should be addressed to the Association of American Railroads, 50 F Street, N.W. Washington, DC 20001.)

AMERICAN WELDING SOCIETY (AWS)

Standard Qualification Procedure of the American Welding Society

(Application for copies should be addressed to the American Welding Society, 550 N.W. LeJeune Road, P.O. Box 33126, Miami, FL 33135.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3950 - Strapping, Nonmetallic (and Joining Methods)
E 165 - Liquid Penetrant Inspection

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Welding Qualifications of the American Society of Mechanical Engineers

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:55Z
Check the source to verify that this is the currentversion before use.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Samples.

3.2.1 Initial production testing sample. When specified (see 6.2), the contractor shall furnish a sample for initial production inspection and approval (see 4.4 and 6.4).

3.2.2 Comparison production testing sample. When specified (see 6.2), the contractor shall furnish a sample for comparison inspection and approval (see 4.5 and 6.5).

3.3 Materials and components. The materials and components used shall conform to the applicable referenced specifications, standards, and requirements specified herein. Where materials are not definitely specified, they shall be of the quality normally used for the purpose in commercial practice provided the completed items comply with all provisions of this specification. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3.1 Alternate components. Components offered as equivalent to components specified hereinafter and on the referenced drawings as a specific manufacturer's part or model number or equal, shall be functionally equal to the manufacturer's model number identified and of equal or better quality. The incorporation and inclusion of such a component in the design of the specified end product shall not require modification or change to any other specified component, and shall not reduce ease of maintenance to it or any other components, unless such modification or change is specially approved by the contracting officer. Prior to the manufacture of the first article, or if none is required, prior to commencing production, the contractor shall submit for the contracting officer's approval, a list identifying each component, together with proof that each listed component complies with requirements specified above. The contracting officer, at his option, may require a physical sample of the proposed substitution. Approval of the submitted listing, together with

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:55Z
Check the source to verify that this is the current version before use.

the necessary supporting data, authorizes commencement of manufacture but does not relieve the contractor of responsibility that these components perform in accordance with specified requirements when incorporated into the end product.

3.3.2 Paint. The paint for metal surfaces shall conform to type II, camouflage green 383 of MIL-C-46168, or black as specified on the applicable drawings.

3.3.3 Thread, polyester. Thread shall conform to type I, class 1, sub-class B, dyed shade S-1 (CA No. 66022) of V-T-285. The dyed thread shall show fastness to weathering equal to or better than the standard shade sample (see 6.6). Thread sizes shall be as follows:

For type 301 stitching - size FF for needle and bobbin

For type 401 stitching - size FF for needle, size F for looper

3.3.4 Kitchen components. The following components shall be provided with each kitchen in the quantities indicated:

Item	Identification	Quantity
Dispenser, liquid, insulated	A-A-52190, size 2, class 2	12
Lifter, tray pack	Drawing 5-13-3961	2
Lifter, tray pack, serving	Drawing 5-13-3859	2
Opener, can, mounted	Drawing 5-13-3969	1
Opener, can, hand	MIL-O-44368	8
Adapter, warmer	Drawing 5-13-3962	2

3.4 Design and construction. Design and construction for the kitchen shall be as specified herein and as shown on the drawings listed on Drawing 5-13-2500.

3.4.1 Welders. Prior to assigning any welder to structual welding on kitchens to be furnished under this specification, the contractor shall provide the contracting officer or his authorized representative with the names of the welders to be employed in the work, together with certification (see 4.1.3) that each of these welders has passed qualification tests as prescribed by either of the following codes for the type of welding operation to be performed.

a. Standard Qualification Procedures of the American Welding Society

b. Welding Qualification of the American Society of Mechanical Engineers

Source: https://assist.dla.mil -- Downloaded: 202640-21T22:55Z
Check the source to verify that this is the current version before use.

3.4.2 Stitches, seams, and stitching. All stitching shall conform to type 301 or 401 of FED-STD-751 with 5 to 7 stitches per inch. Thread tension shall be maintained so that there is no loose stitching. All thread ends shall be trimmed.

3.4.2.1 Thread lubrication. The addition of any lubricant to the polyester sewing thread prior to or during the sewing operation is prohibited. Water or air spraying for needle cooling is permissible.

3.4.2.2 Thread breaks. Thread breaks in stitching shall be overstitched not less than 1-inch at each break on type 301 stitching and not less than 1-1/2-inches at each break on type 401 stitching.

3.4.2.3 Stitching ends. Stitching at the ends on type 301 stitching shall be backstitched or back tacked not less than 1-inch except where ends are turned under in a hem or held down by other stitching.

3.4.3 Setting grommets. Holes punched to receive grommets shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole. The grommets shall be securely clinched without cutting the material.

3.4.4 Fusing of synthetic webbing and cord. The cut ends of synthetic webbing and cords shall be fused to prevent fraying.

3.4.5 Attachment of slide fasteners. Care shall be exercised to trim all thread ends to 1/2-inch or less and to maintain specified distances between edges of fabric attached to slide fastener tape so that there will be no interference with the operation of the slider. The length of the slide fastener chain shall be such that after the slide fastener is sewed on, the tape shall not be puckered and the slider shall operate freely.

3.4.6 Electrical. The electrical circuits shall maintain continuity from end to end without evidence of internal or external shorts during all operating conditions. All lights shall operate in accordance with requirements specified on the applicable wiring diagram and assembly drawings.

3.4.7 Shock absorber kit assembly. The shock absorber kit assemblies shall be in accordance with requirements on Drawings 5-13-2507 and 5-13-2508 and positioned in accordance with requirements on Drawing 5-13-2509. The shock absorbers shall not leak any oil after mounting and after road testing of the kitchen trailer (see 4.7.1).

3.4.8 Travel cover. The travel cover shall adequately enclose the collapsed kitchen and the tensioning cord shall be connected to prevent any baggy or loose areas in the cover.

3.4.9 Platform assembly. The ramp hinges or fold out braces shall provide free movement to the ramps during deployment and striking of the kitchen. The leveling jacks shall freely move from the retained, travel position to the

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

erection, support position. The latch mechanisms of the ramps and corner posts shall freely latch and unlock with the mating component. The nine ladder positions in the ramps shall readily accept each of the three ladders interchangeably.

3.4.10 Fabric support poles. The fabric support poles shall be adjustable to pull the fabric tight when in the expanded configuration. The poles shall be straight with fixed upper and lower pins and shall be of the quantity specified on the applicable drawings.

3.4.11 Handrails. The handrails shall be firmly retained by the mounting brackets to prevent accidental release during movement of the fabric support pole.

3.4.12 Roof fabric assemblies. The zippers of the roof fabric shall be assembled with zippers facing inward. The mosquito netting and foul weather curtains shall be fabricated in accordance with their applicable drawings and shall assemble with their mating component and shall enclose the kitchen as specified on the applicable drawings.

3.4.13 Roof vents. The roof vents shall operate smoothly, without binding, from fully closed to completely open. The skylight operator and the cover shall not be loose and the screen shall not be damaged or interfere with the operation of the vent.

3.4.14 Struts. The curtain hold out struts shall be furnished in the quantity specified and shall assemble with their mating components.

3.4.15 Cargo strap ratchets. The cargo strap ratchets shall operate freely until all slack is removed and then the locking mechanism shall retain the ratchet in this position until manually released.

3.4.16 Rain trough. The rain trough shall be as specified on the applicable drawings and with the mating hook and pile fasteners aligning properly.

3.4.17 Tables. The drop leaf tables shall not bind during erection or collapsing and the detent pins shall adequately lock into position.

3.4.18 Cooking rack/frame. The cooking rack/frame shall support the griddle without any binding and it shall provide sufficient clearance in the front with the burner unit.

3.4.19 Drawers and doors. All drawers and doors shall have latches that engage and disengage under light pressure (showing correct alignment of latch), opening and closing without binding, and no loose components. The drawer joints and seams shall be sealed. The space between the doors and frame and the drawers and cabinets shall be in accordance with the requirements of the applicable drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

3.4.20 Leveling bubbles. The leveling bubbles shall be located in accordance with the applicable drawings and shall indicate the horizontal position of the kitchen during erection.

3.4.21 Floor mat. The floor mat shall be in accordance with the applicable drawing and shall not contain any tears or holes.

3.5 Finish.

3.5.1 Metal surface preparation. Aluminum alloy surfaces other than those specified in 3.5.3 shall have a chemical conversion coating in accordance with class 1A of MIL-C-5541. Metals other than aluminum shall be free of grease, oil, dirt, rust and other foreign matter.

3.5.2 Treatment and painting. The portions of the kitchen trailer to be painted shall be cleaned, treated and painted in accordance with type F or type G of MIL-T-704. Painting shall be as specified in 3.3.2. The word "CARC" with the month and year of coating application shall be stenciled in 1 inch high block letters using lusterless black paint conforming to type II of MIL-C-46168 and shall be located near the identification plate.

3.5.3 Anodic coatings. Components and assemblies requiring anodizing, as specified on the applicable drawings, shall conform to type I, class 1 of MIL-A-8625. Dyed anodic coatings shall conform to type I, class 2 of MIL-A-8625 with color similar to Camouflage Green 383 of MIL-C-46168 (see 6.8). Corner roof support posts and threaded portions of fabric support poles shall be anodized in accordance with type III, class 1 coatings of MIL-A-8625 with a minimum coating thickness of 2.0 mils, unsealed. Griddle surface shall be anodized in accordance with type III, class 1 coatings of MIL-A-8625 with a minimum thickness of 2.0 mils, unsealed using the Sanford process or equal.

3.6 Performance.

3.6.1 Over road. The kitchen, in the travel configuration, shall travel 5 miles on paved roads at up to 50 mph, 5 miles on gravel roads at 30 mph, 5 miles on level cross-country roads at 5 mph, and 5 miles on hilly cross-country roads at 5 mph without any damage to components when tested as specified in 4.7.1. The trailer shall be towed by a 2-1/2 ton truck (see 3.8).

3.6.2 Erection and component operation. The kitchen shall be capable of being erected in accordance with TM 10-7360-206-13. No component used in erection, or noticed during erection, shall be missing, defective, or incorrectly fabricated when inspected as specified in 4.6.3.1.

3.6.3 Rainproof. The kitchen, expanded and secured for foul weather, shall not have rain leakage in areas where food preparation or holding equipment is located when subjected to the rain test specified in 4.7.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

3.7 Government furnished property. The following property in the quantities indicated will be furnished by the Government (see 6.2 and 6.7):

Item No.	Description	Identification (NSN)	Quantity/Each End Item
1	Chassis, Trailer,	2330-00-141-8052	1
2	Cloth, Duck, cotton, plied yarns, fire, water, weather and mildew resistant treated, light dry finish (36 inches wide)	8305-00-926-6171	132 yards
3	Bracket Assy, Liquid, Cont, 5-Gallon	2590-00-473-6331	3
4	Technical Manual	TM 10-7360-206-13	1
5	Case, Maintenance and Operational Manuals	7520-00-559-9618	1
6	Webbing, Nylon, 1 inch	8305-00-261-8579	47 yards
7	Tape, Textile, Nylon, 1 inch	8305-01-062-7050	26 yards
8	Cloth, Coated	8305-00-286-7034	2 yards
9	Cloth, Duck, Nylon 12.5 oz.	8305-00-107-0079	40 yards
10	Tape, Nylon, 1 inch	8315-00-231-8531	10 yards
11	Webbing, Nylon, 1-1/2 inches	8305-00-263-2472	52 yards

3.8 Government-loaned property. The following property in the quantity indicated will be loaned by the Government:

Item No.	Description	Identification (NSN)	Quantity/Each End Item
1	Truck with heater, 2-1/2 ton, M35,	2320-00-835-8463	1
	or		
	Truck with heater, 2-1/2 ton, M135	2320-00-835-8351	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

Item No.	Description	Identification (NSN)	Quantity/Each End Item
2	Range Outfit, M-59, w/Burner Unit	7360-00-082-2153	2
3	Burner Unit M-2A w/Safety Device	7310-01-113-9172	4
4	Can, Water, Plastic, 5-Gallon	7240-00-089-3827	8
5	Can, Gasoline, Plastic, 5-Gallon	7240-01-337-5269	3
6	Table, Field	7105-00-269-9275	2
7	Food Container, Insulated or Food Container, Insulated with Inserts per A-A-52193, size 1, class 2	7330-00-238-2411	16

3.9 Lubrication.

3.9.1 Corner posts and fabric support poles. Corner posts and all threaded portions of the fabric support poles, both male and female, shall be coated with a commercial silicone lubricant.

3.10 Workmanship.

3.10.1 Finish. All components and assemblies of the kitchen shall be free from dirt, rust or any extraneous material, burrs, slivers, rough die, tool or grind marks, dents and cracks. External surfaces shall be free from sharp edges and corners. Painted surfaces shall be smooth, uniformly coated, free from runs, wrinkles, peeling, and areas of no film. Any painted coating damaged during assembly or examination shall be touched-up by priming and painting (see 3.7.2).

3.10.2 Welding. The surfaces of parts to be welded shall be free from oxide, scale, paint, grease and other foreign matter. Completed weldments shall have the visual appearance of a MIL-STD-370, grade C weldment. All scale and flux depposits (when flux is used), shall be removed from the finished weld area.

3.10.3 Fastening devices. Threaded fastener and rivet holes shall have burrs removed. Threaded fasteners shall not be broken, cracks, or stripped and shall be securely torqued. Rivets shall fill the hole completely and the heads shall be in full contact with the the surface of the riveted members.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

3.10.4 Fabric. All seams shall be tightly sewn, and shall not have areas of pulled-out stitching. There shall be no tears or holes in the fabric. All grommets or other fasteners shall be securely set.

3.11 Identification markings.

3.11.1 Manufacturer markings. Marking shall be as specified on component drawings. An aluminum identification plate shall be riveted to the front skirt in the location shown on Drawing 5-13-2512. The plate shall include the following permanent marking:

KITCHEN, FILED, TRAILER MOUNTED
US
NSN
CONTRACT NO.
SERIAL NO.
MODEL NO.
MANUFACTURER'S NAME AND ADDRESS

3.11.2 Helicopter transportability marking. Marking shall be as specified on component drawings. An aluminum identification plate shall be riveted to the front skirt in the location shown on Drawing 5-13-2512. The plate shall include the permanent marking as shown on Drawing 5-13-3995.

3.12 Arrangement of components and equipment. For test purposes, the components and equipment of the kitchen shall be arranged in accordance with the applicable illustrations of TM-10-7360-206-13.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of section 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certification. When certifications are submitted, the Government reserves the right to inspect such items to determine the validity of the certification (see 3.4.1).

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)
b. Initial production inspection (see 4.4)
c. Comparison sample inspection (see 4.5)
d. Quality conformance inspection (see 4.6)

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be inspected as specified in 4.6.3.1 and 4.6.3.2 and tested as specified in 4.7.1 and 4.7.2. The presence of any defect or failure of any test shall be cause for rejection of the first article.

4.4 Initial production sample inspection. When an initial production sample is required, the kitchen(s) shall be inspected as specified in 4.6.3.1 and 4.6.3.2 and tested as specified in 4.7.1 and 4.7.2. The presence of any defect or failure of any test shall be cause for rejection of the initial production sample.

4.5 Comparison sample production. When a comparison production sample is required, the kitchen(s) shall be inspected as specified in 4.6.3.1 and 4.6.3.2 and tested as specified in 4.7.1 and 4.7.2. The presence of any defect or failure of any test shall be cause for rejection of the comparison sample.

4.6 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.6.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.6.2 In-process inspection.

4.6.2.1 Visual examination of process. Examination shall be made of the following fabrication processes to establish conformance with specified requirement. Whenever non-conformance is noted, correction shall be made to the process and all affected items processed.

Source: https://assist.dla.mil -- Downloaded: 202640-21T22:55Z
Check the source to verify that this is the currentversion before use.

a. Thread lubricant is not used during stitching (see 3.4.2.1)
b. Metal surface preparation for welding (see 3.10.2)
c. Surface preparation for painting (see 3.5.1)
d. Treatment and painting (see 3.5.2)

4.6.2.2 Dimensional examination of process. All component parts, prior to assembly, shall be examined for compliance with dimensions specified on the applicable drawings. Any dimension not within dimensional tolerance shall be a defect and shall be cause for rejection of the applicable component parts. The inspection level shall be II.

4.6.2.3 In-process testing.

4.6.2.3.1 Ice chest insulation density. Prior to the start of production on each day that ice chests are to be produced, the density test of foamed -in-place insulation used in the ice chest shall be performed as specified in 4.7.3. The inspection lot shall be the amount of material used in one day's production. The sample unit shall be a 6-inch cube of each density specified on Drawing 5-13-2544. If the sample does not conform to the specified density, adjustments shall be made to the foaming equipment and the test repeated. No insulation shall be installed until the density of the foam conforms with the requirements on Drawing 5-13-2544.

4.6.2.3.2 Ice chest inner body skin. The ice chest inner body skin with coupling as shown on Drawing 5-13-2544 shall not leak when tested as specified in 4.7.4. The inspection level shall be II. Any evidence of water leaks shall be cause for rejection of the lot

4.6.2.3.3 Liquid penetrant weld inspection. Prior to any surface treatment, sample kitchens shall have a liquid penetrant weld inspection in accordance with ASTM E 165, Visible Water Washable Penetrant, on all kitchen frame structual welds. Kitchen frame structural welds shall be separated into the following categories for inspection purposes.

(1) Platform frame and ramp assemblies, less deck plates.
(2) Shock absorber kit brackets.
(3) Levelling jack assembly brackets and struts.
(4) Corner post assemblies.
(5) Roof frame assembly.
(6) Ladder assembly.

Each of the categories shall be inspected separately. One sample item from each category shall be inspected for each lot of 15 completed items. A lot of less than 15 items shall be considered a full lot. Evidence of any weld cracks shall constitute a defect and shall be cause for rejection of the lot. The inspection level shall be II.

4.6.3 End item inspection. The inspection lot shall be all the completed kitchens offered for inspection at one time.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

4.6.3.1 Visual examination. From the closed travel configuration, the kitchen shall be expanded, and during and after expansion, examined for the defects listed in table I. The inspection level shall be II. The finding of any major or minor defect shall be cause for rejection of the lot.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Workmanship			
Finish	Extraneous material, such as dirt, grease, rust, epoxy		201
	Rough tool, die or grind marks		202
	Dents, scratches, cracks not affecting serviceability		203
	Dents, scratches, cracks affecting serviceability	101	
	Burrs or slivers which may inflict injury	102	
	Sharp edges, sharp corners	103	
	Extraneous holes	104	
Painted surface	Film not uniform, not smooth		204
	Runs, wrinkles, peeling		205
	Areas of no film		206
Welding	Cracks, burn holes, undercutting over-lapping, piling up	105	
	Irregular bead, non-uniform cross section	106	
	Scale, flux, splatter not removed		207
Fasteners			
Threaded	Broken, cracked, stripped	107	
	Loose, rusted		208
Rivets	Loose, head not in full contact with member		209
	Not sealed, when applicable		210
Fabric assemblies	Holes or tears	108	
	Thread breaks not over stitched at least 1 inch (type 301 stitching) or 1-1/2 inches (type 401 stitching)		211
	Loose stitching, untrimmed		212

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

	thread ends		
	Grommets or other fasteners not securely set		213
	Stitching at ends not backstitched		214
	Not correctly marked		215
Construction and workmanship (applicable to all components)	Any burr or rough edge	109	
	Any component fractured or malformed	110	
	Any component not in proper alignment or located as specified	111	
	Functioning component that is inoperative or will not operate as intended	112	
Travel cover	Hook and pile fasteners do not mate; excessive overlap		216
	Fabric too loose, or baggy		217
Leveling jacks	Binding during operation		218
	Release pin detent balls defective		219
	Release pins bind during removal		220
Ramps	Ramp hinges or fold out braces bind		221
	Latch slides bind		222
Corner posts	Latches fail to latch	113	
	Not lubricated		223
	Binding during operation	114	
Fabric tent poles	Cannot be adjusted to pull roof fabric tight		224
	Missing, bent, upper or lower pin missing	115	
	Threads not lubricated, evidenced by squeaking or difficult turning		225
	Not anodized		226
Handrails	Handrails fall out when fabric support pole is bumped		227
	Not anodized		228
Roof fabric	Zippers do not face inward		229
Cargo strap ratchets	Binding in operation or failure to lock tightly		230
Mosquito netting and foul weather curtains	Construction defects, incompatible fit		231

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

Foul weather curtain hold out struts	Not number specified		232
	Do not fit in attachment holes		233
Rain trough	Missing		234
	Hook and pile fasteners do not mate		235
Drop leaf tables	Bind during set up		236
	Defective detent pins		237
	Spring catch missing		238
Ladders	Do not fit in holes in ramps in all 9 locations (see TM 10-7360-206-13)		239
Roof vents	Binding during operation		240
	Skylight operator loose or missing or does not lock		241
	Screen damaged, sags, missing; cover loose		242
Shock absorber kit assembly	Incorrect position of mounting bracket	116	
	Damage to brake line during assembly	117	
	Leaking of shock absorber fluid	118	
	Incorrect orientation of shock absorber	119	
Griddle	Does not fit on cooking racks	120	
	Not anodized as specified	121	
Burner units	Does not fit into cooking racks	122	
Cabinet drawers, doors, including ice chest	Binding in opening or closing		243
	Improper latch alignment or engagement		244
	Defective or loose parts		245
	Excessive space between doors and frame		246
	Drawer joints and seams not sealed		247
Leveling bubbles	Missing, broken or not parallel with platform when in operating position	123	
Floor mat	Sized wrong, torn, holes		248
Identification marking	Omitted incorrect, illegible or misplaced	124	
Components (other than GFP items)	Missing or not specified quantity		249
All GFP items (see 3.7)	Any item missing or not furnished in quantity specified		250

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

4.6.3.2 Dimensional examination. The complete kitchen including all manufactured components, but excluding all GFP items shall be examined for compliance with dimensions specified. Any dimension not within the specification tolerance shall be a defect and shall be cause for rejection of the lot. The inspection level shall be II.

4.6.3.3 End item testing. The tests as specified in 4.7.1 and 4.7.2 shall be performed on one complete kitchen from every lot of fifty, or fraction thereof, but not more than one months production of completed kitchens. Failure to pass these tests shall be cause for rejection of the lot.

4.6.4 Packaging inspection. An examination shall be made to determine whether the packaging, packing, and marking complies with section 5 requirements. Defects shall be scored in accordance with table II. The lot size shall be the number of kitchens in the end item inspection lot. The sample unit shall be one kitchen fully packaged, except that it may be expanded. The inspection level shall be S-4. The finding of any defect shall be cause for rejection of the lot.

TABLE. II Inspection of packaging defects

Examine	Defect
Marking	Omitted, incorrect, illegible, of improper size, location, sequence or method of application.
Materials	Any component missing, damaged or not as specified.
Workmanship	Strapping or edge protectors incorrectly applied.
Content	Component and equipment not arranged, or protected and secured as specified. Packing list not inside specified envelope and envelope not in manuals case.
Packing	Kitchen not in accordance with the applicable mode of shipment
Precautionary sign	Missing, incorrectly worded, or not secured in a conspicuous place in the locations specified.

4.7 Tests.

4.7.1 Road and terrain tests. The complete trailer-mounted kitchen, packed and closed for travel, as shown in TM 10-7360-206-13 using components loaned by the Government (see 3.8), with water and gas cans filled, shall be towed over not less than 5 miles of paved roads at speeds up to 50 mph; over not less than 5 miles of graveled roads at speeds averaging 30 mph; over not less than 5

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

miles of level cross-country roads at 5 mph average speed to determine compliance with 3.4.7 and 3.6.1. Prior to road test the tail light assemblies shall be checked for electrical continuity and proper operation and the trailer chassis shall be checked for proper lubrication and brakes tested for proper operation. Failure to conform to 3.4.7 and 3.6.1 shall determine failure of this test.

4.7.1.1 Paved and graveled roads. The paved and graveled road tests shall each include not less than 10 quick starts and stops.

4.7.1.2 Level cross-country roads. Level cross-country roads shall be dirt roads with surface irregularities such as pot holes, mounds, rocks and tree roots randomly spaced. The roads shall not include any grades greater than 5 percent.

4.7.1.3 Hilly cross-country roads. Hilly cross-country roads shall be dirt roads with surface irregularities as specified in 4.7.1.2, but with numerous grades both ascending and descending including but not exceeding 15 percent. The grades shall be approximately one-half ascending and one-half descending.

4.7.2 Rain test. The kitchen in the expanded configuration and secured for foul weather, shall be exposed to simulated rainfall at the rate of 3 inches + 1 inch per hour as measured 6 inches from the surface of the kitchen roof by a U.S. Weather Bureau type gage. The rain shall fall vertically for 15 minutes, and at a 30 to 45 degree angle from the vertical for 20 minutes. The orientation of the kitchen during the angle rainfall shall be such that the long side of the kitchen faces directly into the rain for 10 minutes, and one front corner of the kitchen faces directly into the rain for 10 minutes. Examination of the kitchen interior shall be made during testing to determine compliance with 3.6.3. Nonconformance with 3.6.3 shall constitute failure of this test.

4.7.3 Density test for ice chest insulation. A minimum 8-inch sample cube of urethane foam shall be taken from its center, a 6-inch cube shall be carefully cut and weighed. The weight, 1/8 of a cubic foot shall be multiplied by 8 to determine conformance to density requirements specified on Drawing 5-13-2544 (see 4.6.2.3.1).

4.7.4 Ice chest inner body skin leakage test. The ice chest inner body coupling shall be plugged and the inner body with sides braced shall be filled with water. All exterior surfaces shall be examined to determine compliance with 4.6.2.3.2. Any evidence of water leakage shall constitute failure of this test.

5. PACKAGING

5.1 Preservation. Preservation shall be level A.

5.1.1 Level A. The components and equipment of the kitchen shall be packed in the center aisle and arranged and secured at the option of the contractor. The components and equipment of the kitchen shall be adequately protected and

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

secured to prevent being damaged or causing damage while in transit. The kitchen, in travel configuration, shall be horizontally strapped with one 1/2-inch by 0.020-inch nonmetallic strap conforming to type II or III of ASTM D 3950. The straps shall divide the height of the kitchen into approximately equal parts. Edge protectors shall be placed under the straps at the corners of the kitchen. Edge protectors shall be of commercial construction or be made from 3 by 3-inch weather-resistant solid fiberboard material. The slack portions of the air hose and electrical cable shall be secured to the respective lift loops on each side of the trailer tongue with 2-inch minimum width tape conforming to type IV of PPP-T-60.

5.2 Packing. Packing shall be level A.

5.2.1 Level A. Kitchens, preserved as specified in 5.1, shall be packed for shipment as specified herein.

5.2.1.1 Railway shipment. For railway shipment, tire pressure shall be increased 10 pounds over the required running pressure. Loading of vehicles for railway shipment shall be on open-top cars in accordance with rules governing the loading of Department of Defense materials on open-top cars and Loose Leaf Section No. 6 of the Association of American Railroads.

5.2.1.2 Highway haulaway shipment. The units shall be placed on the bed of rails of haulaway vehicles so that the load is evenly distributed and secured. Parking brakes shall be locked and the levers wired or blocked in position. Loading of units for haulaway shall be in accordance with Department of Transportation Safety Regulations. Tire pressure shall be increased to 10 pounds over the required running pressure (16 g/m^2).

5.2.1.3 Highway towaway shipment. No processing of the trailer units running gear shall be performed prior to highway shipment that would impair necessary operation or safety during transit. Wheel bearings and other fittings shall be lubricated to capacity and brake fluid reservoir shall be filled prior to towing. Towaway rules for shipment by driveaway shall be in accordance with the Department of Transportation Safety Regulations. Tire pressure shall be the required running pressure. Processing of the trailer units running gear, not accomplished prior to highway shipment, shall be performed at intermediate destination when vehicles are to be placed in storage or shipped overseas.

5.3 Marking. In addition to any special marking required by the contract or order, the trailer mounted units shall be marked in accordance with MIL-STD-129. The packing list required shall be placed inside a water-resistant envelope. The envelope shall be placed in the maintenance and manuals case.

5.3.1 Humping precaution. A large sign containing the words "DO NOT HUMP" shall be secured in a conspicuous place on each side of the open-top car.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The trailer mounted field kitchen is intended for use in feeding personnel in the field where mobility is required. It replaces the M-1948 Kitchen Tent.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. When initial production testing sample is required (see 3.2.1, 4.4, and 6.4).
e. When comparison inspection testing sample is required (see 3.2.2, 4.5, and 6.5).
f. Source and delivery of government furnished property (see 3.7 and 6.7).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Initial production test. When an initial production test sample is required, the contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the initial production test sample.

6.5 Comparison production test. When a comparison test sample is required, the contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the comparison test sample.

6.6 Thread sample. For access to a standard shade sample of thread, address the contracting activity issuing the invitation for bids or request for proposal.

6.7 Notes. The contracting officer shall insure all components of the M-59 field ranges and M-2 burner units are included as specified in 3.8 prior to supplying them to the contractor. Also the contracting officer shall insure that the trailer chassis, item 1 of 3.7 GFP, includes the brake handle Ordance part no. 11652179, composite lights Ordance part no 11614157, and painted color Camouflage Green 383 of MIL-C-46168.

Source: https://assist.dla.mil -- Downloaded: 202640-21T22:55Z
Check the source to verify that this is the current version before use.

6.8 Color chip. For access to color chip sample of paint specified in 3.3.2 address the contracting activity issuing the invitation for bids or request for proposal.

6.9 Subject term (key word) listing.

Burner Unit, M-2
Chassis
Mobile
Personnel feeding
Range outfit, M-59
Tray pack
Truck, 2-1/2 ton

6.10 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - AV, MD, QM
Air Force - 35, 84

Preparing activity:

Army - GL

Project No. 7360-A168

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-K-43911B	94-08-15

3. DOCUMENT TITLE: KITCHEN, FIELD, TRAILER MOUNTED

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S. Army Natick RD&E Center	(1) Commercial 508-651-5175	(2) AUTOVON/DSN 256-5175
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-WEE Natick, MA 01760-5018	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 NATICK FIPI 111E.01 Previous editions are obsolete. 198.

Source: https://assist.dla.mil - Downloaded: 2026-10-21T22:55Z
Check the source to verify that this is the current version before use.