# MILITARY SPECIFICATION

## OVEN, PIZZA, COUNTER-TOP, ELECTRIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers two types of electrically heated counter-top pizza ovens capable of baking two (2) 16-inch pizzas or four (4) 8-inch pizzas.

1.2 Classification. The pizza ovens shall be of the following types as specified (see 6.2 and 6.4):

Type I - 120 volts, 60 hertz, single phase
Type II - 208 volts, 60 hertz, single phase

## 2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-B-2316 - Bakery Equipment, Including Units, Assemblies, Repair Parts and Tools, Preparation for Delivery of

MIL-V-173 - Varnish, Moisture and Fungus Resistant (for Treatment of Communications, Electronic and Associated Equipment)

STANDARD

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection of Attributes

LAWS AND REGULATIONS

29 CFR 1910 - OCCUPATIONAL SAFETY AND HEALTH ACT (OSHA) STANDARDS



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:47Z
Check the source to verify that this is the current version before use.

(The Code of Federal Regulations (CFR) and Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20242. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof)

PUBLICATIONS

US Department of Health, Education and Welfare

Federal Food, Drug and Cosmetic Act and Regulations Promulgated Thereunder.

(Application for copies should be addressed to the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

American National Standards Institute (ANSI)

Standard C73 - Dimensions of Caps, Plugs and Receptacles

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10019.)

American Society for Testing and Materials (ASTM)

Designation A167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip.

Designation A176 - Stainless and Heat-Resisting Chromium Steel Plate, Sheet and Strip.

Designation A463 - Aluminum-Coated Steel Sheets, Type I for Heat-Resisting Applications in Coils and Cut Lengths.

Designation A619 - Carbon Steel Sheet, Cold-Rolled, Drawing Quality.

Designation A621 - Carbon Steel Sheet and Strip, Hot-Rolled, Drawing Quality.

Designation B456 - Electrodeposited Coatings of Nickel Plus Chromium.



Source: https://assist.dla.mil -- Downloaded: 202610-21T22:47Z
Check the source to verify that this is the currentversion before use.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

National Sanitation Foundation (NSF)

Standard No. 4 - Commercial Cooking and Hot Food Storage Equipment. Listing of Food Service Equipment.

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, MI 48105.)

Underwriters' Laboratories, Inc., (UL)

Standard No. 197 - Commercial Electric Cooking Appliances.

(Applications for copies should be addressed to the Underwriters' Laboratories, Inc., 207 East Ohio Street, Chicago, IL 60611; Walt Whitman Road, Melville, L.I., NY 11749; or 1655 Scott Boulevard, Santa Clara, CA 95050.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the supplier shall furnish a sample of the oven to be procured under this specification for first article inspection and approval (see 4.3 and 6.3).

3.2 Standard product. The (pizza oven) shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features needed to comply with the requirements of this specification. Modifications to add features shall not incorporate different parts unless such parts are used on other current commercial models. Standard or modified commercial products furnished in accordance with this specification shall be identifiable by all regular manufacturer's or commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair services on models furnished to the Government consistent with their normal commercial practices.

3.3 Codes and standards. Pizza ovens shall comply with the applicable requirements of UL Standard No. 197, NSF Standard No. 4, OSHA Standards 29 CFR 1910, promulgated under the Occupational Safety and Health Act and the Food Additives Amendment of the Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder.

3.3.1 Compliance. Prior to approval of the first article, if one is submitted, or prior to commencing production, the supplier shall submit to the contracting officer or his authorized representative satisfactory evidence



Source: https://assist.dla.mil -- Downloaded: 202610-21T22:47Z
Check the source to verify that this is the current version before use.

that the pizza ovens he proposes to furnish under this specification meet the applicable requirements of UL, NSF, OSHA Standards, 29CFR 1910 and the Food Additives Amendment of the Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder as follows:

3.3.1.1 UL. Acceptable evidence of meeting the requirements of UL shall be the UL label, a UL listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the pizza ovens have been tested and conform to UL Standard No. 197.

3.3.1.2 NSF. Acceptable evidence of meeting the requirements of NSF shall be:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished pizza oven or

(2) A certification for the pizza ovens issued by NSF under their special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the pizza ovens are being procured, indicating that the pizza ovens have been tested and conform to NSF.

3.3.1.3 OSHA. Acceptable evidence of meeting the applicable safety and health standards of OSHA shall be a certificate of compliance, certifying that the pizza ovens furnished conform to the applicable requirements for bakery equipment 1910.263 of OSHA Standards, 29CFR 1910.

3.3.1.4 Federal Food, Drug and Cosmetic Act. Acceptable evidence of meeting the requirements of the Federal Food, Drug and Cosmetic Act shall be a certified statement that the asbestos board binder cement and the high-temperature corrosion-resistant pain he proposes to supply under this specification comply with the Food Additives Amendment of the Federal Food, Drug and Cosmetic Act and Regulations Promulgated Thereunder. The certified statement shall include information as to formulation in sufficient detail to establish the fact of nontoxicity. Questions pertinent to this effect shall be referred by the procuring activity to the appropriate department medical service who will act as an advisor to the procuring agency.

3.4 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial pizza ovens provided the completed item complies with all provisions of this specification.

3.4.1 Stainless steel sheet and strip. Stainless steel sheet and strip shall conform to type 302 or 304 of ASTM A167, or types 409, 410 or 430 of ASTM A176.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:47Z
Check the source to verify that this is the current version before use.

3.4.2 Carbon steel cold-rolled sheet. Carbon steel cold-rolled sheet shall conform to ASTM A619.

3.4.3 Carbon steel hot-rolled sheet and strip. Carbon steel hot-rolled sheet and strip shall conform to ASTM A621.

3.4.4 Electrodeposited coatings of nickel plus chromium. Electrodeposited coatings of nickel plus chromium shall conform to ASTM B456.

3.4.5 Aluminum-coated steel. Aluminum-coated steel shall conform to ASTM A463.

3.5 Design and construction. The pizza ovens shall consist of a one compartment body with two (2) metal decks, a door opening on the front, heating elements positioned under the roof and under each of the two (2) decks, a mechanical timer, electrical controls and connections. The outside of the compartment body shall be constructed of stainless steel conforming to 3.4.1 or carbon steel conforming to 3.4.2 or 3.4.3 and treated in accordance with 3.4.4. Supporting members and frames shall be constructed of stainless steel conforming to 3.4.1 or carbon steel conforming to 3.4.2 or 3.4.3. Any metal within the food splash zone shall be made of stainless steel conforming to 3.4.1 or carbon steel conforming to 3.4.2 or 3.4.3 and teated in accordance with 3.4.4. Stainless steel shall have a thickness not less than 22-gauge (nominal 0.0312 in.); carbon steel shall have a thickness not less than 19-gauge (nominal 0.0437 in.). The decks shall be made of stainless steel specified in 3.4.1, carbon steel specified in 3.4.2 and 3.4.3, or aluminum-coated steel specified in 3.4.5. Decks made of carbon steel shall be treated in accordance with 3.4.4 or at the option of the manufacturer painted using paint conforming to 3.3.1.4. The deck clearance shall be not less than 3-inches. Each deck shall be a minimum of 16-1/4 inches wide by 16-1/4 inches deep to allow baking of 16-inch pizzas. Each deck shall have a sheet of asbestos board not less than 1/4 inch thick covering the entire surface of the deck. The asbestos board shall have a density of not less than 90 lbs/ft$^3$ and it shall be capable of being used in an ambient temperature of 800 F degrees without breaking or warping. The asbestos board binder cement shall conform to the requirements of 3.3.1.4. The outside dimensions of the oven shall not exceed 23-1/2 inches wide by 23-1/2 inches deep by 18-1/2 inches high. Each pizza oven shall have a mechanical timer graduated in minutes from 0 to 15 minutes.

3.5.1 Warm-up time and baking cycle of type I pizza oven. The type I oven warm-up time shall not exceed 60 minutes. The warm-up range shall be from ambient to an operating temperature of 650 F degrees. The pizza cooking cycle shall not exceed 7 minutes per load for 16-inch frozen pizzas when tested as specified in 4.6.3.



Source: https://assist.dla.mil -- Downloaded: 202640-21T22:47Z
Check the source to verify that this is the currentversion before use.

3.5.2 Warm-up time and baking cycle for type II pizza oven. The type II oven warm-up time shall not exceed 45 minutes. The warm-up range shall be from ambient to an operating temperature of 650 F degrees. The pizza cooking cycle shall not exceed 5 minutes per load for 16-inch frozen pizzas when tested as specified in 4.6.3.

3.5.3 Insulation and exterior temperature requirements. Blanket or batt type insulation shall be provided of sufficient thickness to meet the specified temperature requirements when tested in accordance with 4.6.1. The insulation shall not be the loose fill type and it shall not settle during transportation and normal operation. In an ambient of 75 $\pm$ 5 F degrees all handles and knobs shall be constructed to meet the following temperature requirements: 45 F degrees above ambient for metallic handles and knobs and 65 F degrees above ambient for nonmetallic handles and knobs.

3.5.4 Controls. Each pizza oven shall have a thermostatic temperature control, a pilot light, an "ON-OFF" power supply switch and a cord and plug assembly. The thermostatic control shall be a rotating dial type with a range from 300 F to 700 F. The pilot light shall go "out" when the power is turned "OFF" and when the selected temperature is attained. The "ON-OFF" switch may be a separate component or, at the option of the manufacturer, it may be integral to the thermostatic control. When the switch is placed in the "OFF" position, all ungrounded lines shall be broken. The pilot light and all controls and switches shall be clearly visible and easily accessible to the operator.

3.5.5 Electrical characteristics. Unless otherwise specified (see 6.2), the pizza ovens shall be designed for operation on a 60 Hz, 120 volts or 208 volts power supply, as applicable (see 1.2). An attached power supply cord compatible with the item furnished shall be provided. The power supply cord shall be a UL approved 3-wire cord complete with attachment plug cap. The power supply cord shall not be less than 6-feet long. When 50 Hz operation is required, a UL approved, 3-wire power supply cord without an attachment plug shall be provided, except when an attachment plug is specified (see 6.2), the supply cord shall be provided with an attachment plug in accordance with ANSI C73. Maximum allowable wattage for type I pizza ovens shall be 2000 watts and for type II ovens 3500 watts when tested as specified in 4.6.1.

3.5.6 Fungus and moisture resistance of electrical components. When specified (see 6.2), the pizza ovens shall be treated for fungus and moisture resistance. The electrical circuitry, including all components and connections, shall be protected from the effects of moisture and fungus growth by an overall treatment with a varnish conforming to MIL-V-173 with the exception:

(a) Component or circuit elements which are inherently fungus and moisture resistant or which are hermetically sealed need not be treated.



Source: https://assist.dla.mil -- Downloaded: 202640-21T22:47Z
Check the source to verify that this is the currentversion before use.

(b) Component of circuit elements whose functions will be adversely affected by the varnish shall not be treated.

3.6 Repair and maintenance. Provision shall be made to allow access to permit adjustment, repair or replacement of electrical and other components.

3.7 Marking. Each pizza oven shall be permanently and legibly marked with the manufacturer's model and name, trade name or trademark easily identified with said manufacturer.

3.8 Finish. All surfaces shall comply with NSF Standard No. 4.

3.9 Workmanship. The pizza ovens shall be neatly finished and all burrs or rough edges shall be removed. Welds shall be sound, smooth and free from pits, fractures, burn-through, or fissures. Bolt holes and rivet holes shall be accurately punched or drilled and shall have burrs removed. Lockwashers shall be provided in accordance with standard commercial practice, and all bolts, nuts, and screws shall be drawn tight. Rivets shall be tightly driven and fully peened. Electrical wiring shall be provided with adequate slack to relieve strain, and the wiring shall not be abraded, poorly joined, or loose at terminals.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classed as follows:

1. First article inspection (see 4.3).
2. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required, it shall be examined for the defects listed in table I and for compliance with dimensions specified in 3.5 and tested as specified in 4.6.1 and 4.6.3. Failure of any test shall be cause for rejection of the first article. The presence of any



Source: https://assist.dla.mil -- Downloaded: 202610-21T22:47Z
Check the source to verify that this is the currentversion before use.

defect listed in table I or any dimensions not within specified requirements shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 In-process examination.

4.4.2.1 Process examination. Examination shall be made of the following operations to establish conformance to specified requirements. Whenever non-conformance is noted, correction shall be made to affected items and lot in process.

(a) Thermal insulation. Installation of insulation shall be examined for compliance with 3.5.3. Particular attention shall be given to the type of insulation used and method of application.

(b) Fungus and moisture proofing. Inspection shall be made for the fungus and moisture proofing to determine conformance with 3.5.6.

4.4.3 End item inspection. The inspection lot shall be all pizza ovens of one type offered for inspection at one time.

4.4.3.1 Visual examination. The pizza ovens shall be examined for the defects listed in table I. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects expressed in terms of defects per hundred units.

TABLE I. Classification of defects

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Standard product | Item not in accordance with manufacturer's standard product. | X | |
| Finish | Not as specified. | X | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:47Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Workmanship | Dirty. | | X |
| | Scratches, burrs, slivers, breaks, sharp corners, sharp edges, deformities, dents. | X | |
| Welding and brazing | Not continous, not smooth, not uniform, burn holes, cracks, fissures, incomplete fusion. | X | |
| | Not finished to blend with adjacent metal surfaces. | X | |
| | Flux or scale not removed. | X | |
| Soldering | Incomplete, not adherent. | X | |
| | Dirty, pin holes, flux not removed. | X | |
| Threaded fastener | Missing, stripped or crossthreaded, fractured. | X | |
| | Loose. | | X |
| Rivets | Loose, not in full contact with members riveted. | X | |
| Design and construction | Not designed as specified. | X | |
| | Maintenance access not provided. | X | |
| ON-OFF switch | Missing, not accessible to operator, not as specified. | X | |
| Thermostatic control | Missing, not accessible to operator, not as specified. | X | |
| Pilot light | Missing, not readily visible to operator. | X | |
| Power supply cord and plug | Not as specified, missing. | X | |
| Marking | Missing, not permanent, not legible, marking not as specified. | X | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:47Z
Check the source to verify that this is the current version before use.

4.4.3.2 Dimensional examination. The pizza ovens shall be examined for compliance with dimensions specified in 3.5. Any dimension not within the specified requirements shall be a defect. The inspection level shall be S-4 with an AQL of 6.5 expressed in defects per hundred units.

4.4.3.3 End item testing. When a first article is not required, the first produced pizza oven shall be tested as specified in 4.6.1 and 4.6.3. Failure of any test shall be cause for rejection of the inspection lot. Each pizza oven shall be tested as specified in 4.6.2. Failure of this test shall be cause for rejection of the unit.

4.4.4 Examination of preparation for delivery. An examination shall be made to determine that preparation for delivery is as specified in section 5 and is in conformance with MIL-B-2316.

4.5 Certificate examination. Certificates of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with the specification requirements shall be examined and validated.

4.6 Tests.

4.6.1 Functional test. The pizza oven shall be instrumented to measure handle and knob temperatures (see 3.5.3) by means of an indicating potentiometer and appropriate thermocouples. The thermocouple junction shall be fastened in direct contact with the objects that are being checked for temperature. The pizza oven shall be connected to an appropriate electrical source. Allow the oven to warm up to 650 F degrees. Allow the oven to remain at 650 F degrees for at least one hour. Take temperature readings at the end of the hour and check for compliance with requirements of 3.5.3. Check for proper operation of pilot light, "ON-OFF" switch and thermostate. Check for wattage requirements specified in 3.5.5, as applicable. Check manual timer for compliance with 3.5. Non-conformance with any requirements shall constitute failure of this test.

4.6.2 Operational test. Connect the pizza oven to an appropriate power source. Turn the power supply switch "on" and set the temperature control to 400 F degrees. Check to assure that pilot light goes "on" and that all heating elements heat up. Check for operation mechanical timer. Failure of heating elements to heat up; of pilot light to go "on"; of power supply switch to supply power; or operation of timer shall constitute failure of this test.

4.6.3 Production test. Connect the pizza oven to an appropriate power supply. Set thermostat to 650 F degrees and record time elapsed for oven to attain the temperature setting. Three separate warm-up checks shall be made. The average warm-up time shall conform to the requirements of 3.5.1 or 3.5.2, as applicable. Bake not less than six (6) loads of 16-inch frozen pizzas. Pizzas shall be prepared with sauce and cheese according to standard



Source: https://assist.dla.mil -- Downloaded: 20261O-21T22:47Z
Check the source to verify that this is the current version before use.

practice. After the initial load, subsequent pizzas shall be loaded in not more than thirty (30) seconds. Check for conformance with baking-cycle times specified in 3.5.1 or 3.5.2, as applicable.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing and marking. Each complete oven shall be preserved, packaged, packed and marked in accordance with the applicable requirements of MIL-B-2316. Preservation and packaging shall be level A or C, and packing shall be level A, B, or C (see 6.2).

6. NOTES

6.1 Intended use. The pizza ovens covered by this specification are intended for use in military dining facilities.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Type of oven required (see 1.2 and 6.4).
(c) When a first article is required (see 3.1, 4.3 and 6.3).
(d) When other than specified power operation is required (see 3.5.5).
(e) When an attachment plug is required for 50 Hz operation (see 3.5.5).
(f) When fungus and moisture treatment of electrical components is required (see 3.5.6).
(g) Selection of the applicable level of preservation and packaging, and packing (see 5.1).

6.2.1 Contract data requirements. Any data items to be delivered under any contract for items covered by this specification should be specifically called for in the contract in accordance with the applicable regulations of the procuring activity.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Armed Services Procurement Regulations ASPR 7-104.55. The first article should be a preproduction sample, initial production item, or other specific item described under the definition of a first article in the ASPR. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

6.4 User note. When warm-up time, production rate or recovery time are prime concerns to the user, type II should be specified provided a compatible power source is available.



Source: https://assist.dla.mil -- Downloaded: 202610-21T22:47Z
Check the source to verify that this is the currentversion before use.

Custodians:

Army - GL
Navy - YD
Air Force - 84

Review activities:

Army - MD
Navy - MS, SA
DSA-GS

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 7310-0422



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:47Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
Oven, Pizza, Counter-Top, Electric MIL-O-43884

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 20261O-21T22:47Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK LABORATORIES
NATICK, MA 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314




STSNLT-EQS

Commander
US Army Natick Laboratories
ATTN: STSNLT-EQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:47Z
Check the source to verify that this is the current version before use.