31 December 1975
SUPERSEDING
MIL-P-43918(GL)
24 March 1975

MILITARY SPECIFICATION

PAD, LINER, PARACHUTIST'S HELMET

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type and size of helmet liner pad.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

UU-P-268	-	Paper, Kraft, Wrapping
PPP-B-636	-	Boxes, Shipping, Fiberboard

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads for 40 x 48 Inch Pallets

DRAWING

US ARMY NATICK DEVELOPMENT CENTER

2-3-411	-	Pad, Liner, Parachutist's Helmet

FSC 8470

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:58Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N. W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Freight Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Material. The material for the pad shall conform to Uniroyal, Inc. Ensolite, type ALG, or equal. If the supplier proposes to use an "or equal" material, prior to its use the supplier shall furnish a sample of the material with supporting data to the contracting officer for subsequent evaluation by the responsible Military agency (see 4.2.1).

3.2 Construction. The construction of the pad shall conform in all respects to Drawing 2-3-411 and as specified herein.

3.2.1 Finish. The pads shall be uniformly coated on the sides, front and back surfaces with Uniroyal, Inc. liquid Ensocote 4519, or equal, color olive drab, except a yellow iron oxide pigment shall be substituted for the yellow lead chromate pigment. If the supplier proposes to use an "or equal" coating, prior to its use, the supplier shall furnish the formulation of the coating to the contracting officer for subsequent evaluation by the responsible Military agency (see 4.2.1).

3.3 Marking. The markings shown on Drawing 2-3-411 shall be applied with a black marking medium. The marking shall be well defined, clearly legible

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:58Z
Check the source to verify that this is the current version before use.

and shall not show smearing, bleeding or offsetting. The marking medium shall not in any way affect the pad material.

3.4 Workmanship. The pad shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Quality conformance inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except when otherwise indicated hereinafter.

4.2.1 Certification. The supplier shall furnish a certificate certifying that the pad material conforms to the requirement specified in 3.1 and the finish coating conforms to 3.2.1.

4.3 Examination of the pad. The pad shall be examined for defects indicated in 4.3.1 and 4.3.2. The sample unit for these examinations shall be one pad. The inspection levels and acceptable quality levels shall be as indicated in 4.3.3.

4.3.1 Visual examination.

Examine	Defect
General	Any cut, tear or hole
Finish	Omitted or any area of no coating
Markings	Omitted, incomplete, mislocated, illegible, or not black
Cleanness	Grease or oil stain

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:58Z
Check the source to verify that this is the current version before use.

4.3.2 Dimensional examination. Examination shall be made for compliance wi the specified dimensions. Any dimension exceeding the specified tolerance shall be scored as a defect.

4.3.3 Inspection levels and acceptable quality levels. The inspection levels and acceptable quality levels (AQL's) expressed in defects per hundred units shall be as follows:

Examination	Inspection level	AQL
For defects applicable to 4.3.1, visual examination	I	6.5 (one class)
For defects applicable to 4.3.2, dimensional examination	S-2	15.0 (one class)

4.3.4 Examination of preparation for delivery requirements.

4.3.4.1 Examination for packaging, packing and marking. An examination shall be made to determine that packaging, packing and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery except that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Any component missing, damaged or not as specified.
Workmanship	Inadequate application of components, such as: Open and non-continuous heat sealed seams and closure of polyethylene bag. Incorrectly fabricated bag. Alternative polyethylene bag not provided with mechanical tie specified. Incomplete closure of container flaps, improper taping, inadequate stapling, or loose strappin Bulged or distorted container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:58Z
Check the source to verify that this is the current version before use.

Examine	Defect
Content	Number of pads per package is more or less than specified. 1/ Number of packages per shipping container is more or less than specified.

1/ For this defect, three packages from each container in the sample shall be examined.

4.3.4.2 Examination for palletization. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully prepared for delivery. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 and the AQL shall be 6.5 defects per 100 units.

Examine	Defect
Finished dimension	Length, width, or height exceeds specified maximum requirement.
Palletization	Not as specified. Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Ten pads shall be evenly stacked and inserted in a close-fitting clear polyethylene film bag of 0.00125-inch thickness (± 25 percent tolerance). The polyethylene bag shall be formed with heat sealed seams that are straight, continuous, and parallel to each other and the formed edges of the bag. The bag may be fabricated from polyethylene film, tubing or sheeting. The opening of the plastic bag shall be heat sealed or secured with a mechanical tie (paper or plastic covered soft steel wire aluminum band, etc.). Prior to or during the closure operation, excess air within the bag shall be expelled.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:58Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. Pads shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. Seven hundred and twenty pads (72 bundles), packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety SW, grade V3c of PPP-B-636. Level A packages shall be packed flat, eight in length, three in width and three in depth within a shipping container. Inside dimensions of each shipping container shall approximate 25-1/2 inches in length, 16 inches in width and 15-1/4 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636.

5.2.2 Level B. Seven hundred and twenty pads (72 bundles), packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 200 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety SW, grade 200 of PPP-B-636. Level A packages shall be packed flat, eight in length, three in width and three in depth within a shipping container. Inside dimensions of each shipping container shall approximate 25-1/2 inches in length, 16 inches in width, and 15-1/4 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.1 When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the box specification.

5.2.3 Level C. Pads, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:58Z
Check the source to verify that this is the current version before use.

5.3 Palletization. When specified (see 6.2), pads, packed as specified in 5.2, shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or order, interior packages, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The helmet liner pad is intended for use by parachutists to provide impact protection.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
(c) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(d) When palletization is required (see 5.3).

Custodian:

Army - GL

Review activity:

Army - MD

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 8470-0056

U.S. GOVERNMENT PRINTING OFFICE 1975- 603 766 2168

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-P-43918A - PAD, LINER, PARACHUTIST'S HELMET

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:58Z.
Check the source to verify that this is the current version before use.