MIL-S-43880C
AMENDMENT-1
5 September 1985

MILITARY SPECIFICATION

SLEEPING BAG, EXTREME COLD WEATHER (DOWN AND POLYESTER BATTING)

This amendment forms a part of Military Specification MIL-S-43880C, dated 12 March 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.3, after the first sentence: Delete the remainder of the paragraph.

3.3.2: Delete and substitute:

"3.3.2 Cloth nonwoven. The material for the diaphragms for the outer panels shall be a nylon nonwoven which conforms to the physical properties listed below when tested as specified in 4.4.1,

Diaphragm Cloth Physical Properties

Weight: oz/sq yd	2.1 max
Thickness: in 00.6 psi	0.1 max
Air Permability: $ft^3/min/ft^2$	290 max
Breaking strength: lbs.	
Machine/cross machine	50/28 min
Shrinkage	4 percent maximum"

PAGE 5 and 6

3.3.10: Delete "100 percent".

3.3.12 thru 3.3.12.5: Delete and substitute the following:

"3.3.12 Fastener, slide interlocking. The slide fastener shall be nylon or polyester continuous element (spiral, serpentine or scoop type) size MHS, conforming to type III, style 1 of V-F-106, with the exception that the slider on chain initial operating force shall be as specified in 3.3.12.5 and the operating force after salt spray shall not apply.

FSC 8465

DISTRIBUTION STATEMENT A. Approval for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:45Z
Check the source to verify that this is the current version before use.

PAGE 5 and 6 (cont'd)

3.3.12.1 Slide fastener tape. The slide fastener tape shall be 1 ± 1/16 inch width and dyed to match Olive Drab S, C. A. 66519. The tape shall be durable water repellent treated as specified in V-F-106. The tape shall show fastness to laundering equal to or better than the standard sample (see 6.3). When no standard sample is available, the tape shall show good fastness to laundering.

3.3.12.2 Color. The color of the element, element sewing threads, and thongs shall match the olive drab fastener tape. While the slider, stops, and stirrup pulls may be either olive drab or black..

3.3.12.3 Fastener stops. The stops shall be of a plastic (nylon or polyester), brass, aluminum, or other non-corroding material and shall meet V-F-106 holding strength requirements. The closed bottom stop shall enclose the sides and ends of the fastener chain.

3.3.12.4 Fastener length. The fastener length shall be such as to provide a smooth and secure closure and meet the requirements specified in Drawing 2-2-329.

3.3.12.5 Fastener slider and stirrup pulls. The fastener shall have a reversible double-pull, non-locking, slider with wire stirrup pulls and thongs attached. The slider shall properly fit the fastener chain and shall have an initial slider on chain operating force of not more than 22.9 oz. (650 gms). The stirrup pulls shall be fabricated from brass or corrosion resistant steel wire at 0.058 inches minimum diameter.

3.3.12.6 Slider identification. For purposes of aiding in end-item inspection testing and possible field end-item repair situations, the slider shall be identified with a symbol or marking as to identify the fastener manufacturer.

PAGE 31

4.4.1: Delete second sentence and substitute "In addition, testing shall be performed on the heat-sealed label (when used) and non-woven diaphragm cloth as specified in table II."

PAGE 32

Delete heading and substitute "Table II Component Testing of Nonwoven Cloth and Labels (heat sealing)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:45Z
Check the source to verify that this is the current version before use.

PAGE 32 (cont'd)

Before the coated weight entry and under the appropriate category heading:

Add:

"Weight	3.3.2	5041 1/	Sample unit	1	0.1 oz/yd^2	5	Specimens
Thickness	3.3.2	5030 1/	Sample unit	1	0.01 in.	5	Specimens
Air permeability	3.3.2	5450 1/	Sample unit	1		5	Specimens
Breaking strength	3.3.2	5100 1/	Sample unit	1	Whole lb.	5	ea. direction
Shrinkage	3.3.2	5556 3/	Sample unit	1	0.1 %	3	Specimens

After 2/: Add: "3/ Wool procedure".

PAGE 47

4.4.7, line 4, under defect: Delete "Interlocking of loads not as specified."

Line 5, under defects, after bonded: Delete "with required straps."

PAGE 48

5.1.1.2, line 3, after the first sentence: Add "The approximate dimensions of the bag shall be 24 inches in length and 32 inches in width. Approximate dimensions are furnished as a guide only."

5.2.1, line 3, after the first sentence: Add "The approximate inside dimensions of the shipping container shall be 25-1/2 inches in length, 17-1/2 inches in width and 17-3/4 inches in depth. Approximate dimensions are furnished as a guide only."

Delete the third sentence.

PAGE 49

5.2.2, line 3, after the first sentence: Add "The approximate inside dimensions of the shipping container shall be as specified in 5.2.1."

Delete the third sentence.

5.2.2.1, at the end of paragraph: Add "The approximate inside dimensions of the shipping container shall be as specified in 5.2.1."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:45Z
Check the source to verify that this is the current version before use.

TABLE IV. End item dimensional defects. (cont'd)

5.3: Delete and substitute:

"5.3 Palletization. When specified (see 6.2), sleeping bags, packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be pattern number 90 in accordance with the appendix of MIL-STD-147."

PAGE 50

6.2: Add the following:

"e. When palletization is required (see 5.3)."

6.6: Delete in its entirety and substitute"

"6.6 Nonwoven cloth suppliers. Materials specified in 3.3.2 have been found to be satisfactory from the following suppliers:

Monsanto Company, New Enterprises Div., St. Louis, MO.
Pellon Corporation, Industrial Div., New York, NY."

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Army - MD
Navy - MC
Air Force - 82
DLA - CT

Preparing activity:

Army - GL

Project No. 8465-0907

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:45Z
Check the source to verify that this is the current version before use.