MIL-S-43912

1 May 1975
(See 6.4)

MILITARY SPECIFICATION

STRAP, CHIN, PARACHUTIST'S; HELMET, STEEL, M-1

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of chin strap assembly for use with the Parachutist's M-1 Steel Helmet.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

V-T-285	-	Thread, Polyester
UU-P-268	-	Paper, Kraft, Wrapping
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-W-530	-	Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-F-10884	-	Fasteners, Snap
MIL-H-43178	-	Hardware for Helmets, Helmet Liners and Bands

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads for 40" x 48" Pallets

FSC 8470

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:56Z
Check the source to verify that this is the current version before use.

DRAWING

US ARMY NATICK DEVELOPMENT CENTER

2-1-1174 - Strap, Chin, Parachutist's;
Helmet, Steel, M-1

(Figure 1 is a miniature reproduction of referenced drawing and is attached for information only.)

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the supplier shall furnish a sample for first article inspection and approval (see 4.3 and 6.3).

3.2 Materials.

3.2.1 Webbing, cotton. The cotton webbing shall conform to type IIa, class 3, 3/4 inch wide, Olive Drab-7, MIL-W-530.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:56Z
Check the source to verify that this is the current version before use.

3.2.2 Thread, polyester. The polyester thread shall conform to type I or II, class 1, sub-class A, size E, shade Olive Drab S-1, cable no. 66022 of V-T-285. The thread shall show fastness to weathering and perspiration.

3.2.3 Buckle, chin strap. The chin strap buckle shall conform to type IV of MIL-H-43178.

3.2.4 Ball, chin strap release. The chin strap release ball shall conform to type V of MIL-H-43178.

3.2.5 Hook, chin strap release. The chin strap release hook shall conform to type VI of MIL-H-43178.

3.2.6 Clip, end, flat type. The flat type end clip shall conform to type VII of MIL-H-43178.

3.2.7 Clip, chin strap. The chin strap clip shall conform to type XI of MIL-H-43178.

3.2.8 Fastener, snap. The male snap fastener shall conform to style 2A, finish 2 of MIL-F-10884. The size of the eyelet component shall be selected by the supplier and shall be of sufficient length to effect a secure clinch of the assembled components.

3.3 Construction. The construction shall conform in all respects to Drawing 2-1-1174 and as specified herein.

3.3.1 Bartacks. Bartacks shall be as specified on the drawing and shall contain 42 stitches. The bartacks shall be free from thread breaks and loose stitching. All thread ends shall be trimmed to a length of not more than 1/4 inch.

3.3.2 Setting and clinching of flat end clip. With the orientation of the clip as shown on Drawing 2-1-1174, the webbing end shall be inserted within the end of the end clip and the end of the end clip shall be securely clinched over the webbing end. The tabs of the clip shall be folded over the adjacent ply of webbing as shown on the drawing with the tabs visually in line with each other and parallel to the bottom surface of the clip and such that the webbing is free to slide within the clip tabs.

3.3.3 Setting of snap fasteners. A hole shall be prepunched to receive the eyelet component of the snap fastener. The hole shall be smaller than the outside diameter of the eyelet barrel so that the barrel must be forced through the hole. The hole shall not be punched in the setting operation with the eyelet barrel. The fasteners shall be securely clinched without cutting the adjacent webbing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:56Z
Check the source to verify that this is the current version before use.

3.4 Replacement of defective components. During the cutting and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3.1 shall be removed from production and replaced with non-defective components.

3.5 Workmanship. The chin strap assembly shall conform to the quality and grade of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article. When required, the preproduction sample submitted in accordance with 3.1, shall be inspected as specified in 4.4.3 for compliance with design, construction, workmanship, dimensional, and assembly requirements.

4.4 Quality conformance inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except when otherwise indicated hereinafter.

4.4.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be tested in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:56Z
Check the source to verify that this is the current version before use.

4.4.2 In-process inspection. In-process inspection shall be made to assure that holes for snap fasteners are prepunched and are of the required size and also the cut lengths of the straps shall be inspected during the cutting process to determine if the straps are cut to the specified length. Whenever nonconformance is noted, corrections shall be made to the straps affected and lot in process. Straps which cannot be corrected shall be removed from production.

4.4.3 Examination of the end item. The defects found during examination shall be classified in accordance with 4.4.3.1 and 4.4.3.2. The sample unit for this examination shall be one chin strap assembly. The inspection levels and acceptable quality levels for these examinations shall be as specified in 4.4.3.3.

4.4.3.1 Visual examination.

Examine	Defect
Webbing	Any hole, cut, tear or frayed edge
Hardware (general)	Broken or malformed; corroded area, burr or sharp edge Finish omitted Not specified type or style
Snap fastener	Clinched excessively tight, cutting webbing Clinched loosely, permitting stud component to rotate freely Improper or insecure clinching
NOTE:	Incomplete roll of eyelet barrel is evidence of improper or insecure clinching
Bartacks	Any bartack omitted Stitching loose, incomplete or broken Needle chews
Construction and assembly	Any hardware component not attached as specified
Cleanness	Grease or oil stain clearly noticeable Thread ends not trimmed as specified

4.4.3.2 Dimensional examination. Examination shall be made for compliance with dimensions specified. Any dimension that is not within the specified tolerance shall be classified as a defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:56Z
Check the source to verify that this is the current version before use.

4.4.3.3 Inspection levels and acceptable quality levels (AQLs). The inspection levels and AQLs expressed in defects per hundred units shall be as follows:

Examination	Inspection level	AQL
For defects applicable to 4.4.3.1, visual examination	II	4.0
For defects applicable to 4.4.3.2, dimensional examination	S-3	4.0

4.4.4 Examination of preparation for delivery requirements.

4.4.4.1 Examination of packaging, packing and marking. An examination shall be made to determine that the packaging, packing and marking complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be closed. Defects of closure listed below shall be examined on containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Examine	Defect
Marking (interior and exterior)	Omitted; incorrect; illegible; of improper size, location, sequence or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete closure of container flaps, improper taping, inadequate stapling, or loose strapping. Bulged or distorted container

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:56Z
Check the source to verify that this is the current version before use.

Examine	Defect
Content	Number of chin straps per package is more or less than specified 1/ Number of packages per shipping container is more or less than specified

1/ For this defect, three packages from each container in the sample shall be examined.

4.4.4.2 Examination for palletization. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully prepared for delivery. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 and the AQL shall be 6.5 defects per 100 units.

Examine	Defect
Finished dimension	Length, width, or height exceeds specified maximum requirement
Palletization	Not as specified. Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence or method of application

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Twenty-five chin straps folded in half with hardware in place and chin strap clips not secured shall be neatly stacked to form a bundle. The bundle shall be securely tied with cotton tape or twine.

5.1.2 Level C. Chin straps shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:56Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. One thousand chin straps packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636.

5.2.2 Level B. One thousand chin straps packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.1 When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the box specification.

5.2.3 Level C. Chin straps, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Palletization. When specified (see 6.2), chin straps, packed as specified in 5.2 shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or order, interior packages, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:56Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The chin strap is intended for use with the M-1 Steel Helmet used by parachutists.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) When a first article sample is required (see 3.1, 4.3 and 6.3).
(c) Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(e) When palletization is required (see 5.3).

6.3 First article. When a first article sample is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be a preproduction sample consisting of one chin strap assembly. The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for inspection and approval of the first article.

6.4 Supersession data. This specification includes the requirements for the type II chin strap previously covered in MIL-H-1988E for Helmets, Soldier's, Steel, M-1.

Custodians:

Army - GL
Navy - SA
Air Force - 82

Preparing activity:

Army - GL

Project No. 8470-0054

Review activities:

Army - MD
Air Force - 45
DSA - CT

User activity:

Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-S-[illegible]12 - STRAP, CHIN, PARACHUTIST'S; HELMET, STEEL, M-1

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:56Z
Check the source to verify that this is the current version before use.