
INCH-POUND
MIL-PRF-15160/15E
7 July 2006
SUPERSEDING
MIL-PRF-15160/15D
25 October 2000

PERFORMANCE SPECIFICATION SHEET

FUSES, INSTRUMENT, POWER, AND TELEPHONE (NONINDICATING), STYLE F15

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-15160.




Inches	mm
0.008	.20
0.031	.78
0.500	12.70
0.562	14.27
2.00	50.80

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

FIGURE 1. Style F15, characteristics A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:42Z
Check the source to verify that this is the current version before use.



DETAIL OF REJECTION GROOVE

Inches	mm	Inches	mm
0.008	0.20	0.130	3.30
0.016	0.40	0.150	3.81
0.031	0.79	0.156	3.96
0.070	1.78	0.50	12.70
0.085	2.16	0.562	14.27
0.115	2.92	2.00	50.8

NOTES:
1. Dimensions are in inches.
2. The diameter of the rejection ferrule shall be within zero and minus 0.050 inch of the diameter of the main contact area.
3. The end of the ferrule shall be flat with not greater than 0.015 inch concavity.

FIGURE 2. Style F15, characteristic BR.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:42Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Interface and physical dimensions: See figures 1 and 2.

Case: Fiber or alternate material.
(Alternate to fiber material (tube) shall have an average burst strength of 2,100 pounds per square inch with a value of not less than 1,450 pounds per square inch).

Ferrule: Brass.

Finish: Nickel, bright alloy, or bright dipped, silver plated when specified.

Terminal strength: Method 211 of MIL-STD-202, test condition E, 5 inch-pound torque between ferrules and fuse body.

Electrical:

Electrical requirements shall be as specified in table I.

Shock: MIL-STD-202, method 207, HI shock.

Vibration: MIL-STD-202, method 204, test condition A (except 5g peak).

TABLE I Electrical requirements.

	Characteristics	
	A	BR
Voltage rating	250 V ac 250 V dc 450 V rms ac	250 V ac 250 V dc N/A
Overload test 1/ 135% 500%	 0 – 1 hour N/A	 0 – 1 hour 10 – 25 seconds
Short circuit test at 250 V dc at 250 V ac	 10,000A N/A	 10,000A 200,000A (20% PF max.)
at 450 V rms ac 2/ 0 – 20A fuse 25 – 30A fuse	(50% PF max.) 3/ 8,000A 1,500A	 N/A N/A

1/ Overload is shown as a percentage of the current rating of the fuse.
2/ Characteristic A fuses may be used for 450 V rms ac.
3/ Power factor (PF).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:42Z
Check the source to verify that this is the current version before use.

Type designation: Type designation shall be as specified in table II.

TABLE II Type designations and electrical rating. 1/

Style	Characteristic	Maximum voltage	Current rating
F15	A	250V	1A
F15	A	250V	3A
F15	A	250V	6A
F15	A	250V	10A
F15	A	250V	15A
F15	A	250V	20A
F15	A	250V	25A
F15	A	250V	30A
F15	BR 2/	250V	1A
F15	BR 2/	250V	1 6/10A
F15	BR 2/	250V	2A
F15	BR 2/	250V	2 1/2A
F15	BR 2/	250V	3 2/10A
F15	BR 2/	250V	4A
F15	BR 2/	250V	5A
F15	BR 2/	250V	6 1/4A
F15	BR 2/	250V	8A
F15	BR 2/	250V	10A
F15	BR 2/	250V	12A
F15	BR 2/	250V	20A
F15	BR 2/	250V	25A
F15	BR 2/	250V	30A

1/ For silver plated terminals, the designator “S” is added after the current rating.

2/ The characteristic B fuse has been discontinued. The characteristic BR fuse may be used to replace the old characteristic B fuse of the same current rating.

VERIFICATION:

Qualification inspections: The number of qualification samples required shall be:

a. 24 samples maximum current rating of each voltage and design.

b. 24 samples minimum current rating of each voltage and design.

NOTE: If labels are used, five additional samples of any rating are required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:42Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-PRF-15160, this document references the following:

MIL-STD-202

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - SH
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5920-2005-011)

Review activities:
Army - AR, AT, CR4, MI
Navy - AS, CG, MC, OS
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:42Z
Check the source to verify that this is the current version before use.