INCH-POUND
MIL-PRF-15160/9D
AMENDMENT 1
31 March 1998

PERFORMANCE SPECIFICATION SHEET

FUSES: INSTRUMENT, POWER, AND TELEPHONE
(NONINDICATING), STYLE F09

This amendment forms a part of MIL-PRF-15160/9D, dated 29 October 1990, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

REQUIREMENTS, design and construction, electrical, overload interrupt, characteristic B: Delete and substitute:

"Characteristic B:

1/10A through 30A	-	Maximum 1 hour at 135 percent of rated current.
1/10A through 2 8/10A	-	Minimum of 5 seconds at 200 percent of rated current.
3 2/10A through 30A	-	Minimum of 12 seconds at 200 percent of rated current."

REQUIREMENTS, design and construction, electrical, shock: Delete and substitute:

"Shock:

F09A 1A through 30A	-	MIL-STD-202, method 207 (HI shock).
F09B 1/10A through 1 6/10A	-	MIL-STD-202, method 213, test condition I.
F09B 1 8/10A through 30A	-	MIL-STD-202, method 207 (HI shock). "

Custodians:
Army - CR
Navy - SH
Air Force - 85

Preparing activity:
DLA - CC

(Project 5920-0557)

Review activities:
Army - AR, AT, CR4, MI
Navy - AS, CG, MC, OS
Air Force - 17, 19, 99

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:41Z
Check the source to verify that this is the current version before use.