MILITARY SPECIFICATION

CONNECTORS, ELECTRIC, RECTANGULAR, NONENVIRONMENTAL, MINIATURE, POLARIZED SHELL, RACK AND PANEL, GENERAL SPECIFICATION FOR

This amendmment forms a part of MIL-C-24308C, dated 26 January 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2.1, delete and substitute:

"1.2.1 Classes. Connectors covered by this specification shall be of the following classes:

G - General purpose connectors, see 3.3.5.1. 1/
N - Nonmagnetic connectors, see 3.3.5.1. 1/
H - Hermetic connectors.
M - Same as N except see 2/.
D - Same as G except see 2/.
K - Same as H except see 2/."

Footnote 1/, delete and substitute:

"1/ Classes G and N, zinc plated parts are not to be used on aerospace or missile applications in accordance with MIL-S-5002C.

2/ Classes D, K, and M are intended for space missions where high reliability is required."

PAGE 6

3.3.5.1, delete title and substitute:

"3.3.5.1 Finish (classes G and N). 3/"

Add the following footnote to bottom of page:

"3/ Cadmium finished parts (F suffix part numbers) can be used interchangeably for non-F suffix parts."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:01Z
Check the source to verify that this is the current version before use.

PAGE 12

Add the following new paragraph and associated footnotes:

"3.8 Part or Identifying Number (PIN). The PIN shall consist of the letter "M", the basic number of the specification sheet, an assigned dash number (see 3.1), and as shown in the following example:

M	24308/1	-1	F
Military designation	Specification sheet number	Dash number	Finish

For class N:
F = Cadmium 4/.
P = Passivated stainless steel.
No suffix = Cadmium or zinc 4/ 5/.
For classes G and H:
F = Cadmium 4/
No suffix = Cadmium or zinc 4/ 5/.
For classes D and K:
Class D and class K connectors have a nickel finish, no suffix is required.
For class M:
Class M connectors have a gold finish, no suffix is required.

4/ F suffix part numbers are to be used for cadmium finished parts after 1 July 1987.
5/ Zinc finish is inactive for new design effective as of the date of MIL-C-24308C."

PAGE 13

4.1.4, change paragraph wording from "effective 12 months after the date of this document" to "effective 30 months after the date of this document."

PAGE 26

6.6, delete in its entirety, including associated footnotes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:01Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, AV, MI
Navy - AS
Air Force - 11, 99
DLA - ES

User activities:
Army - AT, ME
Navy - CG, MC, OS

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5935-3775)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:01Z
Check the source to verify that this is the current version before use.