INCH - POUND
MIL-PRF-24308D
AMENDMENT 1
23 April 1997

PERFORMANCE SPECIFICATION

CONNECTORS, ELECTRIC, RECTANGULAR, NONENVIRONMENTAL,
MINIATURE, POLARIZED SHELL, RACK AND PANEL,
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-PRF-24308D, dated 15 July 1996, and is approved for use by all departments and Agencies of the Department of Defense.

PAGE 6

3.4.2, Delete and substitute:

"3.4.2 Insert design and construction. Inserts shall be designed with suitable sections and radii such that they will not readily chip, crack, or break in assembly or in normal service. Inserts shall be molded or bonded with a bond barrier between all adjacent contacts and outside edge, one-piece construction, except for IDC. Pin entry openings on socket insert faces shall be as small as practicable. Socket inserts shall provide adequate protection against a pin contacting a socket before the mating pair of connectors has been polarized. The inserts shall be so designed that the inserts cannot be removed from the shells. The contact retaining system shall be free of foreign material, adhesive, or any obstruction that would prevent smooth contact insertion and positive retention. The contact retention system for removable crimp contact connectors shall be a metal retention clip or other contact retention method which will enable the contacts to meet the contact retention requirements specified in Paragraph 3.5.5. All contact retention systems shall utilize a common contact insertion/removal tool. See paragraph 3.3.1."

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA-NA

Preparing activity:
DLA - CC

Review activities:
Army - AT, ME, MI
Navy- AS, CG, MC, SH
Air Force - 17, 99

(Project 5935-4080)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:00Z
Check the source to verify that this is the current version before use.