MILITARY SPECIFICATION

TUB, STATIONARY, LAUNDRY

1. SCOPE

1.1 Scope. - This specification covers stationary laundry tubs for shipboard use.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-N-281 - Nickel-Copper-Alloy Bar, Plate, Rod, Sheet, Strip, Wire, Forgings and Structural and Special Shaped Sections

QQ-S-766 - Steel Plates, Sheets, and Strip—Corrosion Resisting

MILITARY

MIL-C-15726 - Copper-Nickel Alloy, Rod, Flat Products (Flat Wire, Strip, Sheet, Bar and Plate) and Forgings

2.2 Other publications. - The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE
Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, 516 West Jackson Blvd., Chicago, Ill. 60606.)

3. REQUIREMENTS

3.1 Material. -

3.1.1 Tubs. - Tubs shall be made of one of the following materials as specified (see 6.1).

(a) Corrosion-resisting steel conforming to class 304 of QQ-S-766.
(b) Copper-nickel alloy, conforming to alloy 70-30 of MIL-C-15726.
(c) Nickel-copper alloy in accordance with QQ-N-281.

If material is not specified, corrosion-resisting steel shall be furnished.

3.1.2 Legs. - Legs shall be fabricated of galvanized steel or corrosion-resisting steel.

3.1.3 Fittings shall be made of commercial brass.

3.2 Size and type. -

3.2.1 Each tub shall be 24 by 24 inches ± 1/2 inch at the top, and 16 ± 1/2 inch deep. Tubs shall be made in single or double units as specified (see 6.1). Material shall be not less than 0.033 inch thick and suitably stiffened.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:55Z
Check the source to verify that this is the current version before use.

3.2.2 Legs. - At least four rigid legs shall be securely attached to the tub or tubs. The legs shall be provided with feet with drilled holes for bolting to the deck. The length of the legs shall be such that the height of the tubs will be 33 to 36 inches above the deck.

3.2.3 Construction. - Tub seams shall be welded and finished smooth. The top edge shall be flanged outward 1 inch and turned down approximately 3/8 inch, or rolled outward to a diameter of 1 inch.

3.2.4 Drain. - The bottom of each compartment shall be fitted with a strainer and a drain connection for a 1-1/2 inch pipe. For double tubs the drain from each tub shall be connected to a common 1-1/2 inch brass pipe located under the tubs.

3.2.5 Waste plug. - A corrosion-resistant metal or rubber waste plug with a corrosion-resistant metal chain shall be provided in each tub.

3.2.6 Mounting. - Tub supporting frames or legs shall be designed for an acceleration of 20 times gravity, with a factor of safety of 1.0 based on the yield strength of the metal. For design purposes, the tubs shall be considered to be 2/3 filled with water.

3.2.7 Workmanship. - The workmanship shall be in accordance with commercial practice. Sharp edges shall be rounded off and welding shall be ground smooth. Tubs shall be free of defects affecting appearance or that might affect serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Inspection. - Each tub shall be inspected to determine conformance with the requirements of this specification. Each tub which fails to conform to the requirements shall not be offered for delivery.

4.3 Additional inspection. - Where other specifications form a part of this specification, sampling, and inspection, for chemical composition shall be conducted as required in the referenced specification. Physical tests will not be required.

5. PREPARATION FOR DELIVERY

5.1 Domestic shipment and early equipment installation. -

5.1.1 Tubs. -

5.1.1.1 Preservation and packaging. - Preservation and packaging which may be the supplier's commercial practice, shall be sufficient to afford adequate protection against corrosion, deterioration and physical damage during shipment from the supply source to the using activity and until early installation.

5.1.1.1.1 Fittings. - Fittings shall be packaged as specified in 5.1.1.1 except that when they are included with the tub they shall be securely attached to each tub in such a manner as to prohibit damage to the tub or fittings.

5.1.1.2 Packing. - Packing shall be accomplished in a manner which will insure acceptance by common carrier at the lowest rate and will afford protection against physical or mechanical damage during direct shipment from the supply source to the using activity for early installation. The shipping containers or method of packing shall conform to the Uniform Freight Classification Rules or other carrier regulations as applicable to the mode of transportation and may conform to the suppliers commercial practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:55Z
Check the source to verify that this is the current version before use.

5.1.1.3 Marking.- Shipment marking information shall be provided on interior packages and exterior shipping containers in accordance with the contractor's commercial practice. The information shall include nomenclature, Federal stock number or manufacturer's part number, contract or order number, contractor's name and destination.

5.2 Domestic shipment and storage or overseas shipment.- The requirements, and levels of packaging, packing and marking for shipment shall be specified by the procuring activity (see 6.1).

5.2.1 (The following provides various levels for protection during domestic shipment and storage or overseas shipment, which may be required when procurement is made.)

5.2.1.1 Packaging.-

5.2.1.1.1 Level A.-

5.2.1.1.1.1 Tubs and fittings.- Tubs and fittings shall be individually packaged in accordance with method III of MIL-P-116. When fittings are included with the tub they shall be securely attached to each tub in such a manner as to prohibit damage to the tub or fittings.

5.2.1.2 Packing.-

5.2.1.2.1 Level A.-

5.2.1.2.1.1 Tubs and fittings shall be packed in boxes conforming to any of the following specifications at the option of the supplier:

Specification	Class
PPP-B-636	weather-resistant
PPP-B-591	class II

5.2.1.2.2 Level B.-

5.2.1.2.2.1 Tubs and fittings shall be packed separately in boxes conforming to any of the following specifications at the option of the supplier:

Specification	Class
PPP-B-636	Domestic
PPP-B-591	Class I

5.2.1.2.3 Level A or B.-

5.2.1.2.3.1 Cushioning, anchoring, blocking, and bracing shall be in accordance with MIL-STD-1186. Box closure and strapping shall be in accordance with the applicable box specification or appendix thereto, except fiberboard boxes (PPP-B-636) shall be reinforced with reinforced, pressure-sensitive tape in lieu of steel strapping.

5.2.1.3 Marking.- In addition to any special marking required by the contract or order, or herein, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.)

6. NOTES

6.1 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Material required (see 3.1.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:55Z
Check the source to verify that this is the current version before use.

(c) Whether single or double units are required (see 3.2.1).
(d) Packaging, packing, and marking requirements other than those required by 5.1 (see 5.2).

Preparing activity:
Navy - SH
(Project 4510-0083)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:55Z
Check the source to verify that this is the current version before use.