MIL-B-44129
20 June 1984

MILITARY SPECIFICATION

BROCCOLI, DEHYDRATED, COMPRESSED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers dehydrated, compressed broccoli in disc form for use by the Department of Defense as an item of general use.

1.2 Classification. The broccoli shall be of the following types as specified (see 6.1).

Type I - Short spears or florets
Type II - Cut

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-C-495	-	Coatings, Exterior, For Tinned food Cans
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-C-29	-	Canned Subsistence Items, Packaging and Packing Of
PPP-C-96	-	Cans, Metal, 28 Gage and Lighter

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8915

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit; Preparation of Nonperishable Subsistence Items; General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

OTHER GOVERNMENT DOCUMENTS

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder (21, CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

U.S. Standards for Grades of Frozen Broccoli

(Application for copies should be addressed to the Chief, Processed Products Branch, Fruit and Vegetable Division, Agricultural Marketing Service, U.S, Department of Agriculture, Washington, DC 20250.)

United States Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Interim Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water WH550, Environmental Protection Agency, Washington, DC 20460.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

AMERICAN DRY MILK INSTITUTE, INC.

Standards for Grades of Dry Milks, Including Methods of Analysis, Bulletin 916

(Application for copies should be addressed to the American Dry Milk Institute, Inc., 130 North Franklin Street, Chicago, IL 60606.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 No. 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Suite 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Bid sample approval. Unless otherwise specified (see 6.1), six hermetically sealed cans, of each type product of at least 8 avoirdupois ounces, each representative of the product which the contractor proposes to furnish under contract, shall be packaged under nitrogen gas or 27 inches of vacuum and shall be submitted to the contracting officer. One or more of the samples will be tested to determine whether the product has the desired subjective quality characteristics specified in 3.4. The remaining samples shall be used as a reference standard for determining compliance of deliveries with subjective quality requirements. Bid samples submitted by the contractor shall be held at 40°F or lower until used. Additional samples may be withdrawn from accepted lots of materials for use as reference standards as deemed necessary by the inspecting agency. The contracting officer's approval of the bid samples does not relieve the contractor from complying with all requirements of this document not stipulated above.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, free from foreign materials, evidence of rodent and insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Broccoli. The broccoli shall be from the latest harvest and shall meet the requirements of U.S. Grade A of the U.S. Standards for Grades of Frozen Broccoli. Type I shall be prepared from the style "Short Spears" or "Florets" and type II shall be prepared from the style "Cut".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

3.2.2 Sodium sulfite or sodium acid sulfite. The sulfite(s) shall meet the requirements of the Food Chemicals Codex (F.C.C.).

3.2.3 Water. Water used for formulation and washing shall conform to the National Primary Drinking Water Regulations.

3.3 Preparation and processing.

3.3.1 Blanching. If the frozen broccoli has not been blanched to the point of peroxidase enzyme inactivation, it shall be blanched until the peroxidase enzyme has been inactivated.

3.3.2 Sulfiting. The broccoli shall receive a sulfite treatment by such method(s) as will insure a reasonably uniform distribution throughout the product and a residual sulfur dioxide content in the dehydrated product within the limitation specified in 3.4.1. Contact of the wet broccoli with iron, subsequent to the sulfiting operation, shall be strictly avoided.

3.3.3 Freezing. The sulfited broccoli shall be quick frozen as expediously as possible after sulfiting and held in the frozen state until dehydrated.

3.3.4 Dehydration. The product shall be freeze-dehydrated at an absolute pressure not exceeding 1.0 millimeter of mercury. At no time shall there be evidence of thawing in the product. After dehydration has been completed, the pressure in the freeze-drying chamber shall be equalized to atmospheric pressure with nitrogen and the product shall be held under an atmosphere of nitrogen (not more than 2 percent oxygen) until compression can be effected.

3.3.5 Conditioning. The freeze-dried broccoli shall be conditioned by adding moisture sufficient to make the product pliable so that it will not be crushed or ground under high pressure. (Note: Satisfactory compressed broccoli has been produced by spraying with moisture to increase the weight by 9 to 12 percent and then applying microwave energy for approximately 1 minute in an open ended bag in order to equilibrate the moisture in the broccoli.)

3.3.6 Mechanical pressing. The moistened and sulfited broccoli shall be placed immediately into a 3-5/8 ± 1/8 inch diameter mold and compressed into disks by applying approximately 300 to 500 pounds per square inch pressure on each disk for a dwell time of approximately 5 to 10 seconds depending on the variety and maturity of the broccoli.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

3.3.7 Redrying. The compressed broccoli shall be redried within a minimum of time so that the finished product complies with 3.4.1.

3.4 Finished product.

3.4.1 Compressed dehydrated product. The compressed dehydrated product shall be free from hay-like, scorched, oxidized, rancid, musty, or other objectionable odors; shall not exceed 3.0 percent by weight of moisture; and shall contain a sulfite level (calculated as sulfur dioxide) of 500 ± 250 ppm, by weight.

3.4.2 Rehydrated product. Types I and II shall be rehydrated by adding eight parts of tap water (60°F) to one part of broccoli, by weight, and allowing to stand for approximately 1 hour or until fully rehydrated. The rehydrated product shall possess the color, odor, flavor and appearance, typical of cooked frozen broccoli and a texture which is tender but not mushy.

3.5 Plant qualification. The product shall be prepared, processed, and packaged under sanitary conditions in accordance with good manufacturing practice. The product shall be processed in establishments meeting the sanitary requirements of the applicable Government inspection agency.

3.6 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and acceptance service. Product acceptability shall be determined by the USDA. The USDA will determine the degree of acceptance service necessary to assure compliance with the requirements of this document. The cost of grading and acceptance services performed by the USDA involving inspection, official documentation, and related services shall be borne by the contractor.

4.3 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.3.1.1 Ingredient examination. Conformance of ingredients to identity and condition requirements shall be determined by examination of pertinent labels, markings, U.S. Grade certificates, invoices, certificates of analysis, or other valid documents. In addition, each ingredient shall be examined organoleptically as necessary to determine conformance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient lot or of any involved product.

4.3.1.2 Can tin coating weight testing. The cans shall be tested in accordance with PPP-C-96 for conformance to the tin coating weight requirement in 5.1.1.

4.3.2 In-process inspection.

4.3.2.1 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.3.2.2 In-process testing. As each production run is initiated, a sample of the blanched broccoli prior to sulfiting, shall be tested in accordance with 4.4.4. A test result indicating active peroxidase enzymes shall be cause for reblanching of the affected lot of broccoli until the peroxidase enzymes have been inactiviated.

4.3.3 Net weight examination. The cans of product shall be examined for net weight. Any individual sample unit having a net weight of less than 13.75 ounces shall be scored as a minor defect. The lot size shall be expressed in units of cans. The sample unit shall be one can of product. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5. In addition, the lot shall be rejected if the sample average net weight is less than 14.0 ounces.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

4.3.4 Product examination. The finished product shall be examined for the defects listed in table I. The lot size shall be expressed in cans of one type product only. The sample unit shall be the contents of one filled and sealed can. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.5.

TABLE I. Product defects 1/ 2/

Category	Defect
Major	Dehydrated product
151	Presence of hay-like, scorched, rancid, oxidized, musty, or other objectionable odors.
	Rehydrated product 3/
152	Mushy or tough texture.
153	Color, odor, flavor, or appearance not as specified.

1/ The presence of any foreign material (e.g. glass, dirt, insect parts, hair, wood, metal, etc.), foreign odor or flavor (e.g. burnt, scorched, moldy, rancid, sour, stale, etc.) or foreign color shall be cause for rejection of the lot.

2/ Defects not applicable when bid sample is required as a reference sample.

3/ The dehydrated compressed broccoli shall be rehydrated by adding 8.0 parts of tap water to 1.0 part of broccoli, by weight. Allow to fully rehydrate (approximately 1 hours). Drain thoroughly.

4.3.5 Moisture and sulfur dioxide content testing. The finished product shall be tested as specified in 4.4.1 and 4.4.2 for conformance to the moisture and sulfur dioxide requirements in 3.4.1. The sample for testing shall be a 1-pound composite, derived from the number of cans indicated by inspection level S-2. The lot size shall be expressed in units of cans of one type product only. Results shall be reported to the nearest 0.1 percent for moisture and to the nearest 10 ppm for sulfur dioxide. A test failure for either moisture or sulfur dioxide content shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

4.3.6 Oxygen in headspace testing. The filled and sealed cans shall be tested as specified in 4.4.3 for conformance to oxygen in headspace requirement in 5.1.1. The lot size shall be expressed in cans of one type of product only. The sample unit shall be one filled and sealed can. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.3.7 Can condition examination. Examination of filled and sealed cans shall be in accordance with the United States Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

4.3.8 Leakage inspection. Inspection for leakage shall be in accordance with PPP-C-29 (see 5.1.1).

4.3.9 Shipping container examination. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in assembly, closure and reinforcement shall be in accordance with the appendix of PPP-B-636. In addition, the following defects shall be classified as follows:

Major:	National stock number, item description, contract number or date of pack markings missing, incorrect, or illegible.
	Arrangement or number of cans not as specified.
Minor:	Other required markings missing, incorrect, or illegible.
	Reinforcement with nonmetallic strapping or tape is not used.
	Tiered cans not separated as specified.

Level C shipping containers shall be examined for the marking arrangement, and number of cans defects specified above and for the closure method specified in 5.2.3.

4.3.10 Unit load inspection. Inspection of unit loads shall be in accordance with quality assurance provisions of MIL-L-35078.

4.4 Method of inspection.

4.4.1 Moisture content test. Prepare a clean, dry Waring blender or similar mill by grinding a sample and discarding it. Grind approximately 100 grams of a well mixed sample in the prepared blender. Sieve the ground material

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

through a U.S. Standard No. 20 sieve and collect that portion which passes through in a clean, dry, tightly closed container. Weigh two samples, approximately 2 grams each of the sieved material, into tared, dry, aluminum weighing dishes (approximately 2 or 2-1/2 inches in diameter and 3/4 inch in depth) with tight-fitting covers. Place the dishes with cocked lids in a vacuum oven and dry for 6 hours at 70°C under a pressure of not more than 100 mm mercury. During drying, admit to the oven a slow current of air (approximately two bubbles per second) dried by passing through concentrated sulfuric acid. Remove the dishes and allow them to cool in a desiccator before weighing. Calculate the percent of moisture in the original samples.

4.4.2 Sulfur dioxide content test. Sulfur dioxide content of the ground sample shall be determined in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, chapter: Food Additives; Direct, section: Chemical Preservatives, method: Total Sulfurous Acid, Modified Monier-Williams.

4.4.3 Oxygen content test. Oxygen content of head space gas shall be determined in accordance with the American Dry Milk Institute, Inc., Bulletin 916, Standards for Grades of Dry Milks, Including Methods of Analysis: Determination of Oxygen. The result of each determination shall be reported to the nearest 0.1 percent for each can. Alternatively, the head space oxygen content may be determined by an Instrumentation Laboratories Oxygen Analyzer or equivalent instrument. Test results shall be reported to the nearest 0.1 percent for each can. When referee testing is necessary, the American Dry Milk Institute method shall be followed.

4.4.4 Peroxidase activity test. The test to show adequate blanching shall be made in accordance with one of the following precedures:

a. Reagents. (Reagents shall be reagent grade, Analytical Reagent or Chemically pure as defined by the American Chemical Society in the A.C.S. Analytical Reagents or meet the requirements of the Food Chemicals Codex.)

Distilled water.
0.5 percent guaiacol in 50 percent ethyl alcohol solution.
0.08 percent hydrogen peroxide (22.8 mL of 30 percent hydrogen peroxide per liter.) Keep in refrigerator in dark bottle and renew solution each week or two.
Clean sand.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

b. Apparatus:

Test tubes, 3/4 or 7/8 inch in diameter.
3 or 4-inch diameter funnels.
6 or 7-inch cotton milk filters.
Waring blender or similar mixer or porcelain mortar (4 to 6-inch diameter) and pestle.
50-mL graduated cylinder.
1 and 2-mL pipettes.
Timer or watch with second hand.
Test tube rack.
Balance which will weigh 200-gram samples to ± 0.1 gram (A triple-beam style balance is recommended).
If blender is used, a larger sample will permit use of less sensitive balance.

c. Procedure, using blender:

1. Weigh out representative 100 to 200-gram sample.
2. Place in blender with 3 mL of water to each gram of vegetable.
3. Grind for 1 minute at moderate or high speed.
4. Filter through cotton milk filter.
5. Add 2 mL of filtrate to 20 mL of distilled water in test tube.
6. Prepare a blank by adding 2 mL of filtrate to 22 mL of distilled water in a second test tube, mix and use as a color comparison tube. (Do not add any guaiacol or peroxide to this tube.)
7. Add 1 mL of 0.5 percent guaiacol solution to first test tube without mixing.
8. Add 1 mL of 0.08 percent hydrogen peroxide to the same tube without mixing.
9. Mix contents thoroughly by inverting and watch for development of any color differing from the blank, regardless of hue, but of sufficient intensity to show an obvious contrast. Development of color is a positive test and indicates inadequate blanching. If no color contrast develops in 3-1/2 minutes, consider the test negative and the product adequately blanched. If color develops after 3-1/2 minutes, it is to be disregarded and the test still considered negative (for further information see full report, Masure, M.P. and Campbell, H., "Rapid Estimation for Peroxidase in Vegetable Extracts - An Index of Blanching Adequacy for Frozen Vegetables." Fruit Prod. Jour. and American Food Mfr. 23:369-375, 384, Aug. 1944).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

d. Procedure, using mortar:

1. Slice product to be tested into small pieces and weigh representative 10-gram sample.
2. Place 30 mL of distilled water in graduated cylinder.
3. Place sample in mortar with a little clean sand, add minimum amount of water from graduated cylinder to give best consistency for thorough maceration, and grind for 3 minutes. Add remainder of water from cylinder and mix.
4. Proceed as under c. above, 4 though 9 inclusive.

NOTE: Because of the limits of mortar grinding when using motar with 10-gram samples, special attention should be given to assuring representative samples. Sample size can be increased to 20 to 30-grams with additional time given to grinding, or the number of units represented can be increased by halving or quartering, if the sample is uniform.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A or C, as specified (see 6.1).

5.1.1 Level A. A net weight of 14.0 ounces type I or type II of compressed discs of the product shall be unit packed in a size 401 by 411 can. A minus tolerance of 0.25 ounce will be permitted in any individual can provided that the average net weight of cans examined in accordance with 4.3.3 is not less than 14.0 ounces. The can shall be an open top style, round, metal can with soldered or welded side seam and compound-lines, double-seamed ends. The can shall be made throughout from lot less than commercial 0.25-pound per base box electrolytic tinplate (see 4.3.1.2), and shall be coated overall on the outside with a coating conforming to type I or when specified type III (see 6.1) of TT-C-495. The can shall have a sufficient base plate weight and temper to protect the product during shipment and storage. The can shall be hermetically sealed under an atmosphere of nitrogen so that the oxygen content of the headspace gases in the filled and sealed container shall not exceed 2.0 percent when tested in accordance with 4.3.6. The can shall not leak when examined in accordance with 4.3.8.

5.1.2 Level C. The product shall be preserved as specified in 5.1.1 except that cans with or without commercial exterior coating will be acceptable. Alternatively, cans may be made from 0.20 pound per base box electrolytic tinplate, provided the cans have an exterior commercial coating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

5.2 Packing. Twenty-four cans of product, of one type only arranged 4 in length, 3 in width, and 2 in depth, shall be packed on end in a snug-fitting shipping container in accordance with level A, B or C as specified (see 6.1).

5.2.1 Level A packing. The shipping container shall be a fiberboard box, constructed and closed in accordance with style RSC, V2s of PPP-B-636. The tiered cans shall be separated with a full length and width fiberboard pad made of the same material as the box. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive filament reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). Strapping shall be limited to nonmetallic strapping, except for type V, class F loads.

5.2.2 Level B packing. The shipping container shall be a fiberboard box, constructed and closed in accordance with style RSC, V3c, V3s, or V4s of PPP-B-636. The tiered cans shall be separated with a full length and width fiberboard pad made of the same material as the box. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive filament reinforced tape in accordance with the appendix of PPP-B-636.

5.2.3 Level C packing. The shipping container shall comply with the National Motor Freight Classification or Uniform Freight Classification, as applicable, except fiberboard containers shall be closed in accordance with Method II as specified in the appendix of PPP-B-636. The tiered cans shall be separated with a full length and width pad made of the same material as the box.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

5.4 Labeling and marking.

5.4.1 Cans. Can shall be labeled in accordance with MIL-L-1497 and shall include the following information:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

For type I:

BROCCOLI, SHORT SPEARS OR FLORETS, DEHYDRATED, COMPRESSED
Net Weight
Name and address of supplier
Date Packaged
Preserved with Sulfur Dioxide
GAS-PACKAGED

For type II:

BROCCOLI, CUT, DEHYDRATED, COMPRESSED
Net Weight
Name and address of supplier
Date Packaged
Preserved with Sulfur Dioxide
GAS-PACKAGED

DIRECTIONS FOR USE - Types I and II

Broccoli, dehydrated, compressed	14 oz. (1 No. 2-1/2 can)
Water, tap (60°-80°F)	6 qts
Salt	2 tbsp

Place broccoli discs evenly in 4-inch steam table pan. Pour salted water over discs. Cover and refrigerate until rehydrated (approximately 1 hour or overnight). Drain thoroughly and use in desired recipe.

Yield 33 - 1/2 cup servings

5.4.2 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129.

5.4.3 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this document.
b. When other than six bid samples are required (see 3.1).
c. Type of product required.
d. Levels of preservation and packing required (see 5.1 and 5.2).
e. When type III exterior coating of cans is desired (see 5.1.1).
f. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the contracting activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 Commercial packing. Packing specified in 5.2.3 is intended for direct shipment from the supply source to the first consuming activity within CONUS for immediate consumption.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Preparing activity:

Army - GL

Project No. 8915-A781

Review activities:

Army - MD, TS
Navy - MC, MS
DP - SS

Source: https://assist.dla.mil -- Downloaded: 20261O-22T00:04Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-44129	Broccoli, Dehydrated, Compressed

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:04Z
Check the source to verify that this is the current version before use.