MIL-B-44158
21 February 1985
SUPERSEDING
(See 6.5).

MILITARY SPECIFICATION

BACON, SLICED, PRECOOKED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers sliced, precooked bacon in cans.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-C-495	-Coatings, Exterior for Tinned Food Cans
PPP-B-636	-Boxes, Shipping, Fiberboard

MILITARY

MIL-L-35078	-Loads, Unit: Preparation of Nonperishable Subsistence Items; General Specifications For

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8905

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 -Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 -Marking for Shipment and Storage

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

OTHER GOVERNMENT DOCUMENTS

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder (21 CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Meat and Poultry Inspection Regulations

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, Department of Agriculture, Washington, DC 20250.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:17Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Applications for copies should be addressed to the Uniform Classification Committee, Suite 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.4, 6.1, and 6.4).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Pork bellies. The bellies shall be fresh (not previously frozen) unformed, rind-on bellies weighing not less than 8 nor more than 14 pounds. The belly shall be separated from the fat back on a straight line not more than 1.5 inches beyond the outermost curvature of the scribe line. The anterior and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

posterior edges shall be at approximately right angles to the ventral and dorsal edges. The teat line (or evidence thereof) must be present. The bellies shall be in excellent condition; i.e., exposed lean and fat surfaces shall be of a color and bloom normally associated with the class and grade of bellies and typical of bellies which have been properly stored and handled. Cut surfaces and naturally exposed lean surfaces shall show no more than slight darkening or discoloration due to dehydration, aging or microbial activity. The fat shall show no more than a very slight discoloration due to oxidation or microbial activity. No odor foreign to fresh pork shall be present. The pork shall show no evidence of freezing, defrosting, or mishandling. Oily, dark, coarse-textured, and pale, soft and exudative (PSE) meat is not acceptable. Alternatively, skinless bellies may be used provided they weigh not less than 7 pounds nor more than 12.5 pounds. The bellies shall meet all requirements stated above except that the teat line need not be present. The rectus abdominus muscle shall be present.

3.2.1.1 Trimming. The bellies shall be boneless and shall be trimmed to remove objectionable material such as cartilage, bruises, exposed glandular tissue, hair roots, leaf fat and other abdominal fat, and enlarged, soft, porous, dark or seedy mammary tissue. The boneless, trimmed bellies shall meet the limitations specified in tables II and III.

3.2.1.2 Handling and storage. Handling and storage of the boned and trimmed bellies prior to processing into the finished product shall be in accordance with the following requirements:

a. Holding in the fresh chilled state for not more than 4 days is permitted provided that the pork is maintained at a temperature not to exceed 40°F at all times prior to processing.

b. Holding trimmed bellies in the frozen state is permitted provided that the pork is:

- placed in the freezer within 4 hours after certification and frozen to 0°F within 72 hours after placement in the freezer
- stored at 0°F or lower at all times
- held for not more than 45 days
- protected from freezer deterioration and damage
- stored in containers that are adequate to maintain product excellence
- maintained without defrosting until time of processing into the finished product and shall not exceed 40°F at any time prior to further processing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

3.2.1.3 Transportation of bellies. The transportation of bellies between plants shall be in accordance with the Meat and Poultry Inspection Regulations.

3.2.2 Other ingredients. All other ingredients, frying fat, antioxidants, etc., shall be as permitted in the Meat and Poultry Inspection Regulations. Frying fat, if used, shall be rendered pork fat or hydrogenated vegetable fat or oil with or without antioxidants.

3.3 Preparation and processing.

3.3.1 Belly skinning. The skinning of bellies may be accomplished at the option of the contractor.

3.3.2 Belly curing and smoking. The bellies shall be cured and smoked to produce slabs that have a well smoked appearance and aroma. The cured and smoked slabs shall be moderately firm or firmer.

3.3.3 Slab pressing and slicing. The cured and smoked slabs shall be pressed (formed) and mechanically sliced at 12 to 15 slices per inch.

3.3.4 Cooking. Cooking shall be accomplished by any acceptable commercial method which yields uniform, untangled slices that are not less than 4.5 inches in length. In addition, the cooked slices shall not be overcooked (brittle) or have burnt edges or areas and shall not be cut or torn.

3.3.5 Handling of cooked and sliced bacon. Handling of the cooked sliced bacon shall be by personnel using protective hand covering.

3.4 Filling and sealing. Each can (see 5.1.1) shall be filled with 300 or 75 (as applicable) whole slices of cooked bacon and sealed such as to meet the following requirements:

a. Prior to placing the product in the 603 by 700 can approximately 12 slices of bacon shall be placed (edges of slices abutting) on a sheet of vegetable parchment, parchmentized paper, or commercial paper. Prior to placing the product in the 401 by 411 can, approximately 8 slices of bacon shall be placed (edges of slices abutting) on a sheet of vegetable parchment, parchmentized paper, or commercial paper. The commercial paper shall possess both a grease proof and wet strength characteristic. The sheets of bacon shall be layered neatly, rolled, and placed in each can with the length of the slices parallel with the depth dimension of the can.

b. The filled can shall be sealed under a vacuum of not less than 20 inches of mercury.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

c. The filled and sealed cans shall not be heat processed but may be washed with hot water or steam to remove external grease.

3.5 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material, such as, but not limited to dirt, insect, insect parts, hair, wood, paper, paint, glass, or metal.

b. There shall be no foreign odor or flavor, such as, but not limited to burnt, scorched, stale, sour, rancid, musty, or moldy.

c. There shall be no color foreign to the product.

d. There shall be no glandular tissue measuring 0.5 inch or more in any dimension.

e. There shall be no bone, cartilage, skin, or bruises measuring 0.3 inch or more in any dimension.

f. Slices shall not break or crack when the ends are brought together.

3.5.1 Water activity. The mean water activity of the bacon (see 6.3) shall not exceed 0.80 and the unbiased standard deviation for the calculated mean shall not exceed the applicable unbiased standard deviation value specified in table I.

TABLE I. Water activity values

Mean value	Maximum Unbiased standard deviation values
0.80	0.0104
0.79	0.0131
0.78	0.0157
0.77	0.0183
0.76	0.0209
0.75	0.0236
0.74	0.0262
0.73	0.0288
0.72	0.0314

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

TABLE I. Water activity values

Mean value	Maximum Unbiased standard deviation values
0.71	0.0341
0.70	0.0367
0.69	0.0393
0.68	0.0419
0.67	0.0446
0.66	0.0472
0.65	0.0498
0.64	0.0524
0.63	0.0551
0.62	0.0577
0.61	0.0603
0.60	0.0629

3.6 Plant qualification. The pork component and the finished product shall originate and be produced, processed, and stored in plants regularly operating under Meat and Poultry Inspection Regulations of the U.S. Department of Agriculture.

3.7 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and acceptance service. Product acceptability shall be determined by the USDA. The USDA will determine the degree of acceptance service necessary to assure compliance with the requirements of this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

The cost of grading and acceptance services performed by the USDA involving inspection, official documentation, and related services shall be borne by the contractor.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this document or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.5.1.1 Boned and trimmed belly examination. After boning and trimming and prior to any further processing or to any freezing, the bellies shall be examined for the defects listed in table III. The lot size expressed as number of bellies shall be declared to the Agricultural Marketing Service (AMS) agent by the contractor. However, the AMS agent reserves the right to declare as a lot a portion of a declared lot, if, in his or her opinion, that portion may be out of compliance with any requirements. The sample unit shall be one uncured belly and the sample size shall be as specified in table II. Failure of the bellies to meet the acceptance criteria as indicated in table II shall be cause for rejection of the lot. Except for bellies rejected because of freezing, defrosting, or presence of any off-condition, the bellies may be reworked by the contractor and reoffered for examination. For reexamination, the sampling plan used shall be the one in table II designed for the next larger lot size than the one under which the lot was initially rejected. Product shall not be reexamined more than one time.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

TABLE II. Sampling and acceptance criteria for boned and trimmed bellies

Lot size (bellies)	Sample size (number of sample units)	Defect category Major AC	Major RE	Minor AC	Minor RE
150 or less	20	1	2	2	3
151 to 280	32	2	3	3	4
281 to 500	50	3	4	5	6
501 to 1200	80	5	6	7	8
1201 to 3200	125	7	8	10	11
Reinspection of 1201 to 3200	200	10	11	14	15

TABLE III. Boned and trimmed belly defects 1/ 2/ 3/

Category		Defect
Major	Minor	
151		Belly separated from the fat back more than 1.5 inches beyond the outermost curvature of the scribe line.
152		Anterior and posterior edges not approximately at right angles to the ventral and dorsal edges.
153		Weight of rind-on bellies less than 8 or more than 14 pounds, or weight of skinless bellies less than 7 or more than 12.5 pounds, as applicable. 4/
154		Teat line or rectus abdominus muscle not in evidence, as applicable.
155		Presence of enlarged, soft, porous, dark, or seedy mammary tissue (e.g., dark red, brown, black).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

TABLE III. Boned and trimmed belly defects 1/ 2/ 3/(cont'd)

Category		Defect
Major	Minor	
	201	Presence of snowball (back fat exposed through lean side) measuring 3.0 square inches or more (not applicable to area outside of scribe line).
	202	Presence of leaf, lumbar, or pelvic fat measuring 3.0 square inches or more in one dimension and 0.3 inches in depth.

1/ Acceptability of product with respect to the presence of foreign material (for example: glass, dirt, insect parts, hair, wood, metal) shall be determined by a Meat and Poultry Inspection Operations employee.

2/ Evidence of freezing or defrosting or presence of any off-condition (including but not restricted to being off-odor, slightly sticky, gassy, rancid, or sour, or showing discoloration) shall cause rejection of the involved lot.

3/ Presence of oily, dark, coarse textured, or pale, soft and exudative (PSE) meat shall cause rejection of the involved lot.

4/ The AMS agent may weigh as many bellies as deemed necessary to assure compliance with the weight requirement.

4.5.1.2 Ingredient examination. Conformance of ingredients to identity and condition requirements shall be determined by examination of pertinent labels, markings, invoices, certificates of analysis or other valid documents. In addition, each ingredient shall be examined organoleptically as necessary to determine conformance to the condition requirements. Any nonconformance to an identity or condition requirement shall be cause for rejection of the involved product.

4.5.1.3 Unfilled can inspection. Conformance of unfilled cans to the requirements specified in 5.1.1 shall be determined by examination of certificates of conformance or other valid documents. Any nonconformance shall be cause for rejection of the can lot or of any involved product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, filling, vacuum sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 End item inspection. The inspection lot shall include only product produced in one workshift. The AMS agent reserves the right to declare as a lot a portion of the contractor's declared lot, if in his or her opinion, that portion may be out of compliance with any of the requirements.

4.5.3.1 Product examination. The filled and sealed cans shall be examined for the defects listed in tabale IV. The lot size shall be expressed in cans. The sample unit shall be one filled and sealed can. Cans selected for examination must be free of damage. The inspection level shall be S-2 and the AQL, expressed as defects per hundred units, shall be 2.5 for major defects and 6.5 for minor defects.

TABLE IV. Product defects 1/

Category		Defect
Major	Minor	
151		Can vacuum less than 20 inches of mercury. 2/
152		Slice count less than 300 or 75 (as applicable) whole slices per can.
	201	Product not arranged on parchment paper or layered as specified.

1/ Defects shall be scored once per sample unit.

2/ The vacuum reading shall be taken with a puncture type vacuum gauge making the puncture as near as posible to the double seam to minimize error due to distortion of the end. A correction of 1 inch of vacuum shall be added to the gauge reading for each 1,000 feet above sea level at which the determination is made.

4.5.3.2 Slice examination. The finished product shall be examined for the defects listed in table V. The lot shall be expressed in slices (300 or 75 (as applicable) slices x number of cans in lot). The sample unit shall be one slice. Slices shall be selected proportionately from the cans used in the slice count examination or from the number of cans necessary to comply with the sample size. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for minor defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

TABLE V. Slice defects 1/ 2/

Category		Defect
Major	Minor	
151		Presence of bone measuring more than 0.3 inch in any dimension.
152		Presence of cartilage measuring more than 0.3 inch in any dimension.
	201	Presence of skin measuring more than 0.3 inch in any dimension.
	202	Presence of bruise measuring 0.3 inch or more in any dimension.
	203	Presence of glandular tissue measuring 0.5 inch or more in any dimension.
153		Burnt edge or burnt area measuring 0.3 inch or more in any dimension. 3/
154		Slice which breaks or cracks when the ends are brought together.
	204	Slice cut or torn more than 1/2 the width of the slice.
	205	Slice less than 4.5 inches in length.

1/ The product shall be examined at a temperature of 70° to 80°F. Acceptability with respect to the presence of foreign material (i.e. dirt, hair, insects, insect parts, metal) shall be made by an AMS agent.

2/ Presence of foreign taste or odor (e.g. musty, stale, or rancid) shall cause rejection of the involved lot.

3/ A burnt edge is one in which the black color of carbonation is evident to the eye.

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:17Z
Check the source to verify that this is the current version before use.

4.5.3.3 Recanning procedure. Bacon used for end item inspection may be recanned provided recanning is completed within 2 hours after opening of the cans. If the lot from which the cans were selected is accepted, then the recanned product may be included in a subsequent lot. Recanned sampled product from more than one acceptable lot may be combined into one or more lots.

4.5.3.4 Water activity testing. Six filled and sealed cans shall be randomly selected from each production lot and individually tested for water activity. The water activity shall be determined in an AMS laboratory in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists; Chapter: Vegetable Products, Processed; Method: Water Activity - Official First Action, using a Hygrodynamic hygrometer system or an equivalent instrument. The sample unit shall be the contents of a whole can and the bacon shall not be ground prior to analysis. The lot shall be rejected if the mean of the water activity values exceeds 0.80 or if the unbiased standard deviation of the six cans exceeds the applicable value specified in table I. If the mean lies between given values, the standard deviation must comply with the value given for the higher mean.

4.5.3.5 Can condition examination. Examination of the filled and sealed cans for external condition shall be in accordance with the U.S. Standards for Condition of Food Containers.

4.5.4 Shipping container examination. When shipping containers are required to be in accordance with PPP-B-636, examination for construction, closure and reinforcement shall be in accordance with the appendix of PPP-B-636. In addition, the following defects shall apply:

Major

National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Box liner, divider or tier pad missing, when applicable.
Not snug fitting or evidence of bulging.

Minor

Other required markings missing, incorrect, or illegible.
Arrangement or number of cans not as specified.
When applicable, reinforcement with nonmetallic strapping or tape is not used.

Level C containers shall be examined for the defects specified above and for the closure method specified in 5.2.3.

4.5.5 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or C as specified (see 6.1).

5.1.1 Level A. Three hundred whole slices of product shall be unit packed into a size 603 by 700 can or 75 whole slices of product shall be unit packed into a size 401 by 411 can and sealed as specified in 3.4. The can shall be an open-top style, round metal can, with soldered or welded side seam and compound-lined, double-seamed ends. The can shall be made throughout from not less than 0.25 pound per base box electrolytic tin plate. The can shall have a sufficient base plate weight and temper to protect the product during shipment and storage. In addition, the cans shall be beaded to provide paneling resistance. The body and ends of the cans shall be fully enameled on the inside. The can shall be coated overall on the outside with a coating conforming to type I or when specified (see 6.1), type III of TT-C-495.

5.1.2 Level C. The product shall be unit packed as specified in 5.1.1 except commercial tinplate or electrolytic chromium coated steel (ECCS) plate cans normally used for the product are acceptable and the requirement for exterior coating is not applicable for tinplate cans. The ECCS cans shall have an exterior commercial coating. Alternatively, the product shall be unit packed in accordance with 5.1.1 except that cans may be made from 0.20 pound per base box electrolytic tinplate and be coated with a commercial exterior coating.

5.2 Packing. The product shall be packed in accordance with level A, B or C as specified (see 6.1).

5.2.1 Level A packing. Six 603 by 700 cans or twenty-four 401 by 411 cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting, fiberboard shipping container constructed and closed in accordance with style RSC-L, grade V2s of PPP-B-636. The 603 by 700 cans shall be packed three in length and two in width within the container. The 401 by 411 cans shall be arranged four in length, three in width and two in depth within the container. The tiered cans shall be separated with a full length and width pad fabricated of the same material as the box. Each shipping container shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). Strapping shall be limited to nonmetallic strapping except for type II, class F loads.

5.2.2 Level B packing. Six 603 and 700 cans or twenty-four 401 by 411 cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container constructed and closed in accordance with style RSC-L, grade V3c, V3s, or V4s of PPP-B-636. The 603 by 700 cans shall be three in length and two in width within the container. The 401 by 411 cans shall be arranged four in length, three in width and two in depth within the container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

The tiered cans shall be separated with a full length and width pad fabricated of the same material as the box. Each shipping container shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament tape in accordance with the appendix of PPP-B-636.

5.2.3 Level C packing. Six 603 by 700 cans or twenty-four 401 by 411 cans of product, preserved as specified in 5.1, shall be packed in fiberboard containers in accordance with National Motor Freight Classification or Uniform Freight Classification, as applicable, except that the closure of the fiberboard boxes shall be in accordance with method II as specified in the appendix of PPP-B-636 and the divider or tier pads may be fabricated of paperboard material.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

5.4 Labeling and marking.

5.4.1 Cans. Cans shall be labeled in accordance with the requirements of the Meat and Poultry Inspection Regulations. Paper labels are not permitted. The name of the product or abbreviation thereof and date of pack (month and year) shall be embossed or lithographed on the can. The label shall contain the following information:

Precooked Bacon (Direction for use)

(1) Open can at both ends and push out bacon. (For easy removal, place closed cans in hot water for a few minutes before opening).

(2) Invert each layer, bacon side down on a grill or baking sheet. Peel off paper.

(3) Heat until bacon starts to crisp, (350°F grill; 375°F oven). Do not overcook, as bacon is fully cooked.

CONTAINS: Approximately 100 servings or 25 servings (as applicable) of 3 slices per serving).

5.4.2 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129. In addition, the following precautionary marking shall appear on the top of the shipping container in letters 1-inch high, all letters being the same height.

HANDLE WITH CARE
CANS UNDER VACUUM

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

5.4.3 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.4 and 6.4).
c. Levels of preservation and packing (see 5.1 and 5.2).
d. When type III exterior coating of cans is required (See 5.1.1).
e. Type and class of unit load required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling and storage of the specific item being procured, the contracting officer should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 Salt content of cured bellies. Bellies having a salt content of not less than 2.5 percent after curing have been known to meet the water activity requirements of 3.5.1.

6.4 First article. When a first article sample is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample consisting of 12 cans. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.5 Supersession data. This document supersedes LP/P DES 4-82, Bacon, Sliced, Precooked, dated 30 September 1982.

Custodians:

Army - GL
Navy SA
Air Force - 50

Preparing activity:

Army - GL

Project No. 8905-B009

Review activities:

Army - MD, TS
Navy - MC, MS
DP - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use submitting comments and suggestions for improvements. All users of military standardization documents are invited to prov suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, a mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
JS Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTA
NECESSAI
IF MAILE
IN THE
UNITED STA

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-44158	Bacon, Sliced, precooked

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.