INCH-POUND

MIL-B-44158B
19 February 1992
SUPERSEDING
MIL-B-44158A
29 December 1988

MILITARY SPECIFICATION

BACON, SLICED, PRECOOKED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers sliced, precooked bacon in cans.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.1).

SPECIFICATIONS

FEDERAL

TT-C-495 - Coatings, Exterior, for Tinned Food Cans
PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5018 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8905

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Copies are available from the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Meat and Poultry Inspection Regulations

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

U.S. Standards for Condition of Food Containers

(Copies are available from the Chairperson, Condition of Container Committee, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2506, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES (HHS)

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of documents cited in the solicitation (see 6.1).

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 2200 Wilson Boulevard, Suite 400-CD, Arlington, VA 22201-3301.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 2200 Mill Road, Alexandria, VA 22314.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, 222 South Riverside Plaza, Suite 1120, Chicago, IL 60606.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified (see 6.1), a sample shall be subjected to first article inspection (see 6.2) in accordance with 4.4.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Pork bellies. The pork bellies shall be made boneless and shall be trimmed to remove objectionable material such as cartilage, bruises, exposed glandular tissue, hair roots, leaf fat and other abdominal fat, and enlarged, soft, porous, dark, or seedy mammary tissue (see 6.4.1).

3.2.2 Other ingredients. All other ingredients, such as frying fat and antioxidants, shall be in accordance with the Meat and Poultry Inspection Regulations. Frying fat, if used, shall be rendered pork fat or hydrogenated vegetable fat or oil with or without antioxidants.

3.2.3 Water. Water used for formulation and washing shall conform to the National Primary Drinking Water Regulations.

3.3 Preparation and processing. Pork bellies shall be prepared, processed, and packaged (see 6.4.2 and 6.4.3) to ensure compliance with finished product requirements.

3.4 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, paper, paint, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, musty, or moldy.

c. There shall be no color foreign to the product.

d. There shall be no glandular tissue measuring 0.5 inch or more in any dimension.

e. There shall be no bone piece, cartilage, skin, or bruises measuring 0.3 inch or more in any dimension.

f. Slices shall not break or crack when the ends are brought together.

g. The average total slice count shall be 300 slices.

h. No individual can shall contain less than 297 bacon slices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

i. The average fat content of the cooked bacon shall be not greater than 50.0 percent.

j. The fat content of the product in any individual can shall be not greater than 60.0 percent.

k. The salt content of the cooked product in any individual can shall be not greater than 6.5 percent.

l. Slices shall be not less than 4.5 inches in length.

m. There shall be no slices exceeding 1-1/2 inches in width.

n. The cooked slices shall not be overcooked (brittle) or have burnt edges or areas and shall not be cut or torn.

3.4.1 Water activity. No individual sample shall have a water activity value exceeding 0.860. The unbiased standard deviation(s) for the calculated mean shall not exceed the value specified in table I. For calculated means lying between the tabular values, use the next higher tabular value.

TABLE I. Water activity values

Calculated Mean (X)	Maximum unbiased standard deviations
0.860	0.0000
0.855	0.0013
0.850	0.0026
0.845	0.0039
0.840	0.0052
0.835	0.0066
0.830	0.0079
0.825	0.0092
0.820	0.0105
0.815	0.0118
0.810	0.0131
0.805	0.0144
0.800	0.0157
0.795	0.0170
0.790	0.0183
0.785	0.0197
0.780	0.0210
0.775	0.0223
0.770	0.0236
0.765	0.0249

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

TABLE I. Water activity values (cont'd)

Calculated Mean (X)	Maximum unbiased standard deviations
0.760	0.0262
0.755	0.0275
0.750	0.0288
0.745	0.0301
0.740	0.0314
0.735	0.0328
0.730	0.0341
0.725	0.0354
0.720	0.0367
0.715	0.0380
0.710	0.0393
0.705	0.0406
0.700	0.0419
0.695	0.0432
0.690	0.0445
0.685	0.0459
0.680	0.0472
0.675	0.0485
0.670	0.0498
0.665	0.0511
0.660	0.0524
0.655	0.0537
0.650	0.0550
0.645	0.0563
0.640	0.0576
0.635	0.0590
0.630	0.0603
0.625	0.0616
0.620	0.0629
0.615	0.0642
0.610	0.0655
0.605	0.0668
0.600	0.0681

3.4.2 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.5 Plant qualification. The pork component and the finished product shall originate and be produced, processed, and stored in plants regularly operating under the Meat and Poultry Inspection Regulations of the U.S. Department of Agriculture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

3.6 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall ensure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection and supervision necessary to ensure compliance with the requirements of this specification.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, and compliance shall be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.1.2 Unfilled can inspection. Conformance of unfilled cans to the requirements specified in 5.1.1 shall be determined by examination of certificates of conformance or other valid documents. Any nonconformance shall be cause for rejection of the can lot or of any involved product.

4.5.2 End item inspection. The inspection lot shall include only products produced in one workshift. The Agriculture Marketing Service (AMS) agent reserves the right to declare as a lot a portion of the contractor's declared lot, if in his or her opinion that portion may be out of compliance with any of the requirements.

4.5.2.1 Product examination. The sample size and acceptance and rejection criteria shall be as indicated by table II. The sample unit shall be one filled and sealed can. Cans selected for examination must be free of damage. The product shall be examined for defects listed in table III.

TABLE II. Sampling plan for product examination

Lot size (cans)	Sample size (No. of cans)		Defect categories			
			Major		Minor	
	Major	Minor	AC	RE	AC	RE
2 to 150	5	2	0	1	0	1
151 to 35000	5	8	0	1	1	2

TABLE III. Product defects 1/

Category		Defect
Major	Minor	
101		Less than 297 bacon slices in any individual can 2/
	201	Product not arranged on parchment paper or layered as specified

1/ Defects shall be scored once per sample unit.

2/ The lot shall be rejected if the average total slice count is less than 300 slices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

4.5.2.2 Slice examination. The sample size and acceptance and rejection criteria shall be as indicated by table IV. The slices shall be examined for defects listed in table V. Slices shall be selected proportionately from the cans used in the product examination or from the number of cans necessary to comply with the sample size.

TABLE IV. Sampling plan for slice examination

Lot size (slices)	Sample size (No. of slices)		Defect categories			
			Major		Minor	
	Major	Minor	AC	RE	AC	RE
501 to 1200	80	80	5	6	10	11
1201 to 3200	125	125	7	8	14	15
3201 to 10000	200	200	10	11	21	22
10001 to 35000	315	200	14	15	21	22
35001 or more	500	200	21	22	21	22

TABLE V. Slice defects 1/ 2/ 3/

Category		Defect
Major	Minor	
101		Presence of a bone piece measuring 0.3 inch or more in any dimension
102		Presence of cartilage measuring 0.3 inch or more in any dimension
103		Burnt edge or burnt area measuring 0.3 inch or more in any dimension 4/
104		Slice which breaks or cracks when the ends are brought together
	201	Presence of skin measuring 0.3 inch or more in any dimension
	202	Presence of bruises measuring 0.3 inch or more in any dimension
	203	Presence of glandular tissue measuring 0.5 inch or more in any dimension
	204	Slice cut or torn more than 1/2 the width of the slice

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

TABLE V. Slice defects 1/ 2/ 3/ (cont'd)

Category		Defect
Major	Minor	
	205	Slice less than 4.5 inches in length
	206	Slice exceeding 1-1/2 inches in width
	207	Separation of more than 1/2 the length of the slice

1/ The presence of foreign material (for example, dirt, insect parts, hair, wood, paper, paint, glass, metal), foreign odor or flavor (for example, moldy, rancid, sour, stale, burnt, scorched, musty), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot (see 3.4.2).

3/ The product shall be examined at a temperature of 70°F to 80°F.

4/ A burnt edge is one in which the black color of carbonation is evident to the eye.

4.5.3 Recanning procedure. Bacon used for end item inspection may be recanned provided recanning is completed within 2 hours after opening of the cans. If the lot from which the cans were selected is accepted, then the recanned product may be included in a subsequent lot. Recanned sampled product from more than one acceptable lot may be combined into one or more lots.

4.5.4 Analytical laboratory testing. Six filled and sealed cans shall be randomly selected from each production lot and individually tested first for water activity and then for salt and fat content.

4.5.4.1 Water activity testing. The water activity shall be determined in an AMS laboratory in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists (Test No. 978.18); Chapter: Vegetable Products, Processed; Method: Water Activity - Official First Action, using a Hygrodynamic hygrometer system or an equivalent instrument. The sample unit shall be the contents of a whole can and the bacon shall not be ground prior to analysis. Water activity values shall be reported to the nearest 0.001. Any water activity results failing to conform to the requirements in 3.6.1 and table I criteria shall be classified as a critical defect and shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

4.5.4.2 Fat and salt content testing. After water activity testing has been completed, the six cans shall be individually tested for fat content in an AMS laboratory in accordance with the Fosslet Method (Test No. 976.21) or the Crude Fat or Ether Extract Method using petroleum ether (Test No. 960.39), and for salt content (Test No. 935.47) in an AMS laboratory in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, Chapter: Meat and Meat Products, except that preparation of the samples shall be as follows: The cans shall be tightly covered if preparation for fat and salt content testing is more than 2 hours after completion of water activity testing. The entire contents of each can shall be separately blended in a Waring Blendor or equivalent. The test results shall be reported to the nearest 0.1 percent. Any result failing to conform to the fat and salt requirements in 3.4 shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.5 Can vacuum examination. Five filled and sealed cans selected for the product examination (see 4.5.2.1) shall be examined for vacuum. The cans and contents shall be allowed to reach 70°F to 80°F. The vacuum reading shall be taken with a puncture-type vacuum gage making the puncture as near as possible to the double seam to minimize error due to distortion of the end. A correction of 1 inch of vacuum shall be added to the gage reading for each 1000 feet above sea level at which the determination is made. Failure of any can to meet the vacuum requirement shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.6 Can condition examination. Examination of filled and sealed cans shall be in accordance with the United States Standards for Condition of Food Containers, except that the inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4.1).

4.5.7 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Reinforced with other than nonmetallic strapping or tape.
Not snug-fitting or evidence of bulging.

Minor: Other required markings missing, incorrect, or illegible.
Arrangement or number of cans not as specified.

Level C shipping containers shall be examined for the marking, arrangement, and number of can defects specified above and for the closure method specified in 5.2.3.

4.5.8 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A or C, as specified (see 6.1).

5.1.1 Level A. Three hundred whole slices of product shall be packed layout style (15 slices with edges abutting) on a sheet of vegetable parchment, parchment, or commercial-style paper into a size 603 by 700 can and hermetically sealed under a vacuum of not less than 20 inches of mercury. The commercial paper shall possess grease-proof and wet-strength characteristics. The can shall be an open-top style, round metal can, with welded side seam and compound-lined, double-seamed ends. The can shall be made throughout from not less than 0.25 pound per base box electrolytic tin plate. The base plate of the can shall be of sufficient temper to protect the product during shipment and storage. In addition, the can shall be beaded to provide paneling resistance. The entire inside area of the can shall be coated with enamel. Scratches or fractures shall not penetrate through the interior can coating. The interior can coating shall not peel or blister when in contact with the product. The interior can coating shall neither affect nor be affected by the packaged product. A certificate of conformance shall be furnished to certify compliance with the interior can coating requirements. The can shall be coated overall on the outside with a coating conforming to type I or, when specified (see 6.1), type III of TT-C-495.

5.1.2 Level C. The product shall be preserved as specified in 5.1.1, except that cans with or without commercial exterior coating will be acceptable. Alternatively, cans may be made from 0.20 pound per base box electrolytic tin plate provided the cans have an exterior commercial coating.

5.2 Packing. The product shall be packed in accordance with level A, B, or C, as specified (see 6.1).

5.2.1 Level A packing. Six size 603 by 700 cans of product, preserved as specified in 5.1, shall be packed in a fiberboard box, constructed and closed in accordance with style RSC, grade V2s of PPP-B-636. The size 603 by 700 cans shall be packed on end three in length, two in width, and one in depth, within a snug-fitting shipping container. Each shipping container shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Six size 603 and 700 cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:17Z
Check the source to verify that this is the current version before use.

5.2.3 Level C packing. Six size 603 by 700 cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1, within a snug-fitting container in accordance with the National Motor Freight Classification or Uniform Freight Classification, as applicable, except the closure of the fiberboard boxes shall be in accordance with method II as specified in the appendix of PPP-B-636.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 or 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.4 Labeling and marking.

5.4.1 Cans. Cans shall be labeled in accordance with MIL-L-1497. Paper labels are not permitted. The name of the product or abbreviation thereof and date of pack (month and year) shall be embossed or lithographed on the can. The label shall contain the following information:

PRECOOKED BACON
(Directions for use)

1. Open can at both ends and push out bacon. (For easy removal, place closed cans in hot water for a few minutes before opening.)

2. Invert each layer, bacon side down on a grill or baking sheet. Peel off paper.

3. Heat until bacon starts to crisp (350°F grill or 375°F oven). Do not overcook, as bacon is fully cooked.

YIELD: Serves 100 portions of 3 slices each.

5.4.2 Shipping containers. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129. The following precautionary marking placed on top of each container in capital letters larger than other markings shall be included:

HANDLE WITH CARE
CANS UNDER VACUUM

5.4.3 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078.

Source: https://assist.dla.mil -- Downloaded: 202640-22T00:17Z
Check the source to verify that this is the currentversion before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.4, and 6.2).
d. Provisions for approved preproduction samples (see 3.6.1 and 6.2).
e. Levels of preservation and packing required (see 5.1 and 5.2).
f. When type III exterior coating of cans is required (see 5.1.1).
g. When unit loading is required (see 5.2.1 and 5.3).

6.2 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.3 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.4 Ingredient and processing information.

6.4.1 Slab weight of pork bellies. Pork bellies (rind on) having a weight range of 8 to 14 pounds or skinless bellies having a weight range of 7 to 12.5 pounds have produced precooked bacon meeting the fat requirements of 3.4.

6.4.2 Salt content of raw, cured bellies. Bellies having a salt content of not less than 2.5 percent after curing have been known to meet the water activity requirements of 3.4.1.

6.4.3 Slab pressing and slicing. The cured and smoked slabs which have been pressed (formed) and mechanically sliced at 12 to 15 slices per inch have produced precooked bacon meeting the finished product requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:17Z
Check the source to verify that this is the current version before use.

6.5 Subject term (key word) listing.

Canned foods
Pork bellies

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Preparing activity

Army - GL

(Project 8905-1103)

Review activities:

Army - MD, QM
Navy - MC
DP - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-B-44158B	1992 February 19

3. DOCUMENT TITLE

BACON, SLICED, PRECOOKED

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4501	256-4501
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-WTP Natick, MA 01760-5018	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil/ Downloaded: 2026-10-22T00:17Z
Check the source to verify that this is the current version before use.