MIL-C-44122
27 March 1984
SUPERSEDING
(see 6.5)

MILITARY SPECIFICATION

CABBAGE, DEHYDRATED, COMPRESSED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers dehydrated, compressed, cabbage in disc form, for use by the Department of Defense as an item of general issue.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-C-495	-	Coatings, Exterior, For Tinned Food Cans
PP-C-96	-	Cans, Metal, 28 Gage and Lighter
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-C-29	-	Canned Subsistence Items, Packaging and Packing of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8915

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-D-43266 - Desiccants and Desiccation, Method of; For Packaging Subsistence
MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit; Preparation of Nonperishable Subsistence Items; General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

OTHER GOVERNMENT DOCUMENTS

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder (21, CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

United States Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Interim Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water WH550, Environmental Protection Agency, Washington, DC 20460.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 No. 19th St., Suite 210, Arlington, VA 22209.)

AMERICAN DRY MILK INSTITUTE, INC.

Standards for Grades of Dry Milks, Including Methods of Analysis, Bulletin 916

(Application for copies should be addressed to the American Dry Milk Institute, Inc., 130 North Franklin, Chicago, IL 60606.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex (F.C.C.)

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Suite 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and techical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.4, 6.1 and 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Cabbage. The cabbage shall be clean, sound, and mature, and one of the green varieties of Danish, Domestic, Pointed, or Savoy type. Varieties such as the Copenhagen Market and the Glory of Enkhuizen will be acceptable. Cabbage of the red varieties shall not be used.

3.2.2 Sodium sulfite or sodium acid sulfite. The sulfite(s) used shall meet the requirements of the Food Chemicals Codex (F.C.C.).

3.2.3 Wetting agent. Wetting agent, polyoxyethylene (20) sorbitan mono-oleate shall meet the requirements of the Food Chemicals Codex (F.C.C.).

3.2.4 Water. Water used for formulation and washing shall conform to the National Interim Primary Drinking Water Regulations.

3.3 Preparation and processing.

3.3.1 Cabbage preparation. The cabbage heads shall be properly trimmed to remove discolored, damaged, or diseased portions and shall be cored. The cabbage shall be washed with potable cold water to remove soil and foreign materials. The cabbage shall be processed through a slicer adjusted to yield shreds 3/16 $\pm$ 1/16 inch. If necessary, the cabbage may be halved or quartered before slicing. Cabbage shall not be subjected to any heat treatment such as blanching or cooking prior to dehydration.

3.3.2 Sulfiting. The cut fresh cabbage shall receive a sulfite treatment by such method(s) as will insure a reasonably uniform distribution throughout the product and a residual sulfur dioxide content in the dehydrated product within the limitation specified in 3.4.1. Contact of the wet cabbage with iron, subsequent to the sulfiting operation, shall be strictly avoided.

3.3.3 Dehydration. Dehydration conditions shall be such that the product is not scorched or otherwise damaged by heat and shall produce a product complying with 3.4.

3.3.4 Conditioning. The dehydrated shredded cabbage shall be conditioned by spraying with water containing 0.10 percent polyoxyethylene (20) sorbitan mono-oleate to a moisture content of 10 to 15 percent, by weight. The cabbage shall be tumbled while spraying to insure thorough wetting and then heated in a closed container at 150°F for 5 minutes to equilibrate the moisture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

3.3.5 Mechanical pressing. The moistened cabbage shall be placed in a 3-3/4 ± 1/8 inch diameter mold and compressed into discs by applying 200 to 400 pounds per square inch of pressure for a dwell time of 5 to 20 seconds depending upon the variety and maturity of the cabbage.

3.3.6 Redrying. The compressed cabbage shall be redried with a minimum of delay so that the finished product complies with 3.4.

3.4 Finished product.

3.4.1 Compressed product. The moisture content shall not exceed 5.0 percent, by weight, and the sulfite content (calculated as sulfur dioxide) shall be 1500 ± 500 parts per million (ppm), by weight. The compressed product shall be free from hay-like, scorched, musty, or other objectionable odors.

3.4.2 Rehydrated product. The compressed cabbage shall rehydrate to approximately its original shredded form when 1 avoirdupois ounce of dehydrated compressed product is added to 16 fluid ounces of cold water and allowed to soak for 2 to 3 hours. The rehydrated product shall have a color, flavor and texture typical of raw cabbage and shall contain no more than 2.0 percent, by weight, of defective pieces. A piece shall be considered defective if it has been damaged by insect or pathological injury, decay, scorch, bruise, tray blackening, dirt, discoloration or any other abnormalities.

3.4.3 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.5 Plant qualification. The product shall be prepared, processed, and packaged under sanitary conditions in accordance with good manufacturing practice. The product shall be processed in establishments meeting the sanitary requirements of the applicable Government inspection agency.

3.6 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

4.2 Inspection and acceptance service. Product acceptability shall be determined by the USDA. The USDA will determine the degree of acceptance service necessary to assure compliance with the requirements of this document. The cost of grading and acceptance services performed by the USDA involving inspection, official documentation, and related services shall be borne by the contractor.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)
b. Quality conformance inspection (see 4.5)

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this document or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.5.1.1 Ingredient examination. Conformance of ingredients to identity and condition requirements shall be determined by examination of pertinent labels, markings, U.S. Grade certificates, invoices, certificates of analysis, or other valid documents. In addition, each ingredient shall be examined organoleptically as necessary to determine conformance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient lot or of any involved product.

4.5.1.2 Unfilled can inspection. Conformance of unfilled cans to the requirements specified in 5.1.1 shall be determined by examination of certificates of conformance or of other valid documents. Any nonconformance shall be cause for rejection of the can lot or of any involved product.

4.5.2 In-process inspection.

4.5.2.1 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or other valid documents shall be cause for rejection of the involved product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

4.5.3 Net weight examination. The cans of product shall be examined for net weight. Any individual sample having a net weight of less than 12.0 ounces of product shall be scored as a minor defect. The lot size shall be expressed in units of cans. The sample unit shall be one can of product. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5. In addition, the lot shall be rejected if the sample average net weight is less than 13.0 ounces.

4.5.4 Product examination. The finished product shall be examined for the defects listed in table I. The lot size shall be expressed in cans. The sample unit shall be enough product to produce 2 pounds of rehydrated product, representative of one filled and sealed can. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.5.

TABLE I. Product defects 1/ 2/

Category	Defect
Major	Dehydrated product
101	Hay-like, scorched, musty, or other objectionable odor.
	Rehydrated product 3/
102	Cabbage does not rehydrate to approximately its original shredded form.
103	More than 2.0 percent by weight, of pieces which have been damaged by insect or pathological injury, decay, scorch, bruise, tray blackening, dirt, discoloration or other abnormalities.
104	Color, flavor and texture not typical of raw cabbage.
	Desiccant
105	Bag missing.
106	Bag has tear, hole or open seal.

1/ The presence of any foreign material (e.g. glass, dirt, insect parts, hair, wood, metal, etc.), foreign odor or flavor (e.g. burnt, scorched, moldy, rancid, sour, stale, etc.) or foreign color shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

2/ Product not equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an AMS agent).

3/ Sufficient product to yield 2 pounds of drained rehydrated cabbage shall be rehydrated on the basis of 1 avoirdupois ounce of cabbage to 16 fluid ounces of cold water for 2 to 3 hours.

4.5.5 Moisture and sulfur dioxide content testing. The finished product shall be tested as specified in 4.6.1 and 4.6.2 for conformance to the moisture and sulfur dioxide requirements in 3.4.1. The sample for testing shall be a 1-pound composite, derived from the number of cans indicated by inspection level S-2. The lot size shall be expressed in cans. Results for moisture shall be reported to the nearest 0.1 percent, and for sulfur dioxide to the nearest 10 ppm. A test failure for either moisture or sulfur dioxide content shall be cause for rejection of the lot.

4.5.6 Oxygen in headspace testing (when applicable). The filled and sealed cans shall be tested as specified in 4.6.3 for conformance to the oxygen in headspace requirement in 5.1.1. The lot size shall be expressed in cans. The sample unit shall be one filled and sealed can. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.5.7 Can condition examination. Examination of filled and sealed cans shall be in accordance with the United States Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

4.5.8 Leakage and vacuum (when applicable) inspection. Inspection for leakage and vacuum shall be in accordance with PPP-C-29 (see 5.1.1).

4.5.9 Shipping container examination. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in construction, closure, and reinforcement shall be in accordance with the appendix of PPP-B-636. In addition, the following defects shall be classified as follows:

Major:	National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Minor:	Other required markings missing, incorrect, or illegible. Reinforcement with nonmetallic strapping or tape is not used. Arrangement or number of cans not as specified. Tiered cans not separated with pad as specified.

Level C shipping containers shall be examined for the closure method specified in 5.2.3 and for the defects specified above, except for the reinforcement defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

4.5.10 Unit load inspection. Inspection of unit loads shall be in accordance with quality assurance provisions of MIL-L-35078.

4.6 Methods of inspection.

4.6.1 Moisture content test. Prepare a clean, dry Waring blender or similar mill by grinding a sample and discarding it. Grind approximately 100 grams of a well mixed sample in the prepared blender. Sieve the ground material through a U.S. Standard No. 20 sieve and collect that portion which passes through in a clean, dry, tightly closed container. Weigh two samples, approximately 2.0 grams each of the sieved material, into tared, dry, aluminum weighing dishes (approximately 2 or 2-1/2 inches in diameter and 3/4 inch in depth) with tight-fitting covers. Place the dishes with cocked lids in a vacuum oven and dry for 6 hours at 70°C under a pressure of not more than 100 mm mercury. During drying, admit to the oven a slow current of air (approximately two bubbles per second) dried by passing through concentrated sulfuric acid. Remove the dishes and allow them to cool in a desiccator before weighing. Calculate the percent of moisture in the original samples.

4.6.2 Sulfur dioxide content test. Sulfur dioxide of the ground sample shall be determined in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, Chapter: Food Additives: Direct, section: Chemical Preservatives, method: Total Sulfurous Acid, Modified Monier-Williams.

4.6.3 Oxygen content test. Oxygen content of head space gas shall be determined in accordance with the American Dry Milk Institute, Inc., publication, Bulletin 916, Standards for Grades of Dry Milks, Including Methods of Analysis: Determination of Oxygen. The result of each determination shall be reported to the nearest 0.1 percent. Alternatively, the head space oxygen content may be determined by an Instrumentation Laboratories Oxygen Analyzer or equivalent instrument. Test results shall be reported to the nearest 0.1 percent for each can. The lot shall be rejected if any of the cans exceeds 2.0 percent oxygen. When referee testing is necessary, the American Dry Milk Institute method shall be followed.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A or C, as specified (see 6.1).

5.1.1 Level A. A net weight of 13.0 ounces of dehydrated compressed cabbage discs together with sufficient desiccant shall be unit packed in a size 401 by 411, open top style, round, metal can with soldered or welded side seam and compound-lined, double-seamed ends. A minus tolerance of 1 ounce will be permitted in any individual can provided the average net weight of cans inspected is not less than 13.0 ounces. The can shall be made throughout from not less than 0.25 pound per base box electrolytic tin plate. The can

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

shall have a sufficient base plate weight and temper to protect the product during shipment and storage. The can shall be coated overall on the outside with a coating conforming to type I, or when specified (see 6.1), type III of TT-C-495. The desiccant shall meet the requirements of MIL-D-43266 (except that it need not be placed in any particular position) and shall be used in such quantities as to be capable of reducing the moisture content of the cabbage to not more than 1.5 percent, by weight. The can shall be sealed under an atmosphere of nitrogen so that the oxygen content of the gases in the filled and sealed container shall not exceed 2.0 percent when tested in accordance with 4.6.3. The nitrogen packed cans shall be hermetically sealed and shall not show leakage when tested in accordance with 4.5.8. Alternatively, the cans may be hermetically sealed under a vacuum of not less than 27 inches of mercury when examined in accordance with procedures in PPP-C-29. When cans are closed under vacuum, the oxygen requirement is not applicable.

5.1.2 Level C. The product shall be preserved as specified in 5.1.1, except that cans with or without commercial exterior coating will be acceptable. Alternatively, cans may be made from 0.20 pound per base box electrolytic tinplate provided the cans have an exterior commercial coating.

5.2 Packing. Twenty-four cans of product, preserved as specified in 5.1, arranged 4 in length, 3 in width, and 2 in depth, shall be packed on end in a snug-fitting shipping container in accordance with level A, B or C, as specified (see 6.1).

5.2.1 Level A packing. The shipping container shall be a fiberboard box, constructed and closed in accordance with style RSC, V2s of PPP-B-636. The tiered cans shall be separated with a full length and width fiberboard pad made of the same material as the box. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive filament reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). Strapping of unit loads shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. The shipping container shall be a fiberboard box, constructed and closed in accordance with style RSC, W5c or W5s of PPP-B-636. The tiered cans shall be separated with a full length and width fiberboard pad made of the same material as the box. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive filament reinforced tape in accordance with the appendix of PPP-B-636.

5.2.3 Level C packing. The shipping container shall comply with the National Motor Freight Classification or Uniform Freight Classification, as applicable, except fiberboard containers shall be closed in accordance with Method II as specified in the appendix of PPP-B-636. The tiered cans shall be separated with a full length and width pad.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

5.4 Cans. Cans shall be labeled in accordance with MIL-L-1497 and shall include the following:

Cabbage, Dehydrated, Compressed
Net Weight 13.0 oz. (dry solids basis)
Name and address of supplier
Date packaged
Preserved with Sulfur Dioxide
Gas packed (if applicable)
Remove and Discard Desiccant Bag

Directions for Use

Cabbage, dehydrated, compressed	13.0 oz. (401 by 411 can)
Water, cool	6-1/2 quarts
Cole slaw dressing	1 quart

Break each disc into 4 or 5 pieces. Add water and let stand 2 to 3 hours or until cabbage is rehydrated, stirring occasionally to separate the cabbage. Drain and combine cabbage with dressing. Yield: 33 (1/2 cup portions).

Creamy cole slaw dressing:

	Weights	Measures	Method
Salad dressing	1 lb.	2 cups	1. Combine salad dressing, sugar, salt, mustard and pepper. Mix well.
Sugar, granulated	6 oz.	3/4 cup	
milk,			
Salt	1 oz.	1-1/2 tablespoons	
Mustard, prepared		1 tablespoon	
Pepper, black		1 teaspoon	
Vinegar		1/2 cup	2. Add vinegar gradually. Blend well.
Milk* whole or skim		1 cup	3. Pour dressing over drained cabbage; toss lightly until well mixed.

*If using nonfat dry milk (NFDM), mix 3 tablespoons NFOM with 1 cup water.

5.4.1 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

5.4.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this document.
b. When a first article is required (see 3.1, 4.3, and 6.4).
c. Provisions for approved preproduction samples (see 3.4.3 and 6.4).
d. Levels of preservation and packing required (see 5.1 and 5.2).
e. When type III exterior coating of can is required (see 5.1.1).
f. Type and class of unit load required (see 5.2.1 and 5.2.3).

6.2 Appropriate level of pack. Based on conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 Commercial packing. Packing specified in 5.2.3 is intended for direct shipment from the supply source to the first consuming activity within CONUS for immediate consumption.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of DAR 7-104.55. The first article should be a preproduction sample. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.5 Supersession data. This document supersedes LP/P. DES 7-76, Cabbage, Dehydrated, Compressed, dated 7 April 1976.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Preparing activity:

Army - GL

Project No. 8915-0775

Review activities:

Army - MD, TS
Navy - MC, MS
DP - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1 DOCUMENT NUMBER	2 DOCUMENT TITLE
MIL-C-44122	Cabbage, Dehydrated, Compressed

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5 PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation

6 REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:02Z
Check the source to verify that this is the current version before use.