INCH-POUND

MIL-D-44144A(GL)
AMENDMENT 1
25 May 1993

MILITARY SPECIFICATION

DRYING TUMBLER, LAUNDRY

This amendment forms a part of MIL-D-44144A(GL), dated 22 December 1986, and is approved for use by the Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1, under "SPECIFICATIONS FEDERAL": Add "A-A-54337 - Sheet, Bed (Cotton-Polyester, White, Fitted)".

Delete title of "QQ-S-571" and substitute: "Solder, Electronic (96 to 485 Deg. C)".

PAGE 2

2.1.1, under "SPECIFICATIONS MILITARY": Delete title of "MIL-L-3153" and substitute: "Laundry and Dry Cleaning Machinery and Equipment, Packaging Of".

Delete "MIL-S-36868" and it's title.

Under "DRAWINGS"; Delete "6-1-8774 - Dryer, Diesel Fired, M-85 Laundry Drawing List".

PAGE 3

2.2, in source paragraph for "American Welding Society (AWS)": Delete address and substitute: "P.O. Box 351040, Miami, FL 33135".

PAGE 4

Paragraph 3.5, line 14, before "MIL-T-152"; add "type II of".

PAGE 5

3.6.2, line 2: Delete "(MIL-S-36868)" and substitute "(A-A-54337)".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

PAGE 7

Add the following new paragraph:

"3.6.10 Fuel pump. The fuel pump shall be adjusted to operate at a pressure of 120 ± 2 pounds per square inch gage (psig) for elevations up to 3,000 feet above sea level; 110 ± 2 psig for elevations 3,000 to 5,000 feet above sea level; or 100 ± 2 psig for elevations over 5,000 feet above sea level. Testing shall be as specified in 4.6.12."

PAGE 8

4.3, line 3: Delete "4.6.11" and substitute "4.6.12".

PAGE 11

4.4.4, TABLE II.: After last test, add the following:

"Fuel pump	3.6.10	4.6.12"

PAGE 12

4.6.1, TABLE III. Endurance test data: In the fourth column, delete "Number of drying cycles" and "80 (13 minutes each)" and substitute the following:

	"Number of drying cycles (13 minutes each)
First article	80
End item	10"

PAGE 13

4.6.10: Delete and substitute:

"4.6.10 Flame, signal test. An ac/dc multimeter with a 20,000 ohm/volt dc rating shall be connected to the output jacks, terminals 2 and 3, of the flame safeguard control. When the flame is detected a nominal reading of 115 volts ac shall be obtained. The dryer shall be started and operated for more than 2 minutes. The manual fuel valve shall then be closed. The time from when the flame is extinguished until the reading is 0 volts shall not be more than 4 seconds. When the flame is extinguished and the ignition spark is on for ignition retrial the reading shall be 0 volts. Any nonconformance with the control requirements of 3.6.8 shall constitute failure of this test."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.

PAGE 14

Add the following new paragraph:

"4.6.12 Fuel pump test. The fuel pump gage shall read a pressure in accordance with 3.6.10 without deviating more than 2 psig anytime during burner operation. Any nonconformance with the requirements of 3.6.10 shall constitute failure of this test."

Custodian:

Army - GL

Review activity:

Army - AV

Preparing activity:

Army - GL

(Project 3510-A332)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:11Z
Check the source to verify that this is the current version before use.