INCH-POUND

MIL-K-44156C(GL)
15 April 1994
SUPERSEDING
MIL-K-44156B(GL)
31 December 1991

# MILITARY SPECIFICATION

# KITCHEN, COMPANY LEVEL, FIELD FEEDING

## 1. SCOPE

*1.1 Scope. This document covers the components of two types of company level, field feeding kitchens.

*1.2 Classification. Field feeding kitchens covered by this specification shall be of the following types as specified (see 6.2):

Type I - Standard (T-ration preparation)
Type II - Enhanced (T-ration and limited A/B ration preparation)

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

*2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development and Engineering Center, Natick, MA 01760-5018 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 7360

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

| | | |
|---|---|---|
| A-A-391 | - | Boards, Food Slicing |
| A-A-1082 | - | Spoon, Food Service (Basting, Straining, and Mixing) |
| A-A-1106 | - | Extinguisher, Fire, Carbon Dioxide |
| A-A-1751 | - | Measure, Liquid (Aluminum) |
| A-A-2344 | - | Wrenches, Adjustable |
| *A-A-52078 | - | Lantern, Gasoline, Leaded or Nonleaded, with Case |
| H-B-178 | - | Brushes, Wire and Platers General Specification for |
| H-B-178/3 | - | Brushes, Wire and Platers, Shoe Handle Brushes |
| L-H-520 | - | Hose and Hose Assemblies, Non-Metallic (Rubber, Plastic) |
| XX-P-746 | - | Pump, Inflating, Manual (for Rubber Tires) |
| GGG-C-746 | - | Cutlery, Gallery and Kitchen (Cleaver, Forks, Knives, Spatulas, Steel and Server) |
| GGG-S-121 | - | Screwdriver and Screw Starter, Hand |
| *PPP-B-601 | - | Boxes, Wood, Cleated - Plywood |
| PPP-B-1364 | - | Boxes, Shipping, Corrugated Fiberboard, High Strength, Weather-Resistant, Double Wall |
| PPP-C-96 | - | Cans, Metal, 28 Gage and Lighter |
| PPP-T-45 | - | Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing |
| PPP-T-60 | - | Tape, Packaging, Waterproof |
| PPP-T-76 | - | Tape, Pressure Sensitive Adhesive, Packaging/Paper (For Carton Sealing) |

MILITARY

| | | |
|---|---|---|
| MIL-P-116 | - | Preservation, Methods of |
| MIL-B-121 | - | Barrier Material, Greaseproofed, Waterproofed, Flexible |
| MIL-B-273 | - | Bag, Drinking Water Storage, Dispensing, Cloth, Cotton Duck, Porous |
| MIL-T-704 | - | Treatment and Painting of Materiel |
| *MIL-A-8625 | - | Anodic Coatings For Aluminum and Aluminum Alloys |
| MIL-C-1283 | - | Can, Gasoline, Military, 5-Gallon |
| MIL-S-1285 | - | Spout, Can, Flexible |
| MIL-C-1429 | - | Cleaner, Burner Slot, for Range, Field, M-1937 |
| MIL-C-1700 | - | Chest: Tool, Gasoline Field Range Accessory Outfit |
| MIL-P-1735 | - | Pots, Cooking: With Covers & Splash Plate |
| MIL-W-6858 | - | Welding, Resistance: Spot and Seam |
| MIL-W-10698 | - | Wrench, Open End, and Wrench Assembly, Stamped Steel |
| MIL-U-10815 | - | Utensil, Cooking, Corrosion-Resisting Steel |
| MIL-F-10870 | - | Food Container, Insulated, with Inserts |
| MIL-P-14105 | - | Paint, Heat-Resisting (For Steel Surfaces) |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| *MIL-R-14601 | - | Range and Accessory Outfits, Field Gasoline |
| MIL-B-40098 | - | Burner Unit, Gasoline, Field Range Outfit, M2A |
| MIL-C-43613 | - | Can, Water, Military: Plastic, 5-Gallon Capacity |
| MIL-D-43916 | - | Dispenser, Liquid, Insulated |
| MIL-G-44013 | - | Gloves, Heat Protective |
| MIL-O-44368 | - | Opener, Can, Hand, for Tray Packs and Round Cans |
| MIL-C-46168 | - | Coating, Aliphatic Polyurethane, Chemical Agent Resistant |
| *MIL-C-52950 | | Crates, Wood, Open and Covered |
| MIL-P-53022 | - | Primer, Epoxy Coating, Corrosion Inhibiting, Lead and Chromate Free |
| *MIL-C-53109 | | Can, Fuel, Military: Plastic, 5- Gallon Capacity |
| MIL-T-83483 | - | Thread Compound, Antiseize, Molybdenum Disulfide-Petrolatum |

STANDARDS

MILITARY

| | | |
|---|---|---|
| MIL-STD-105 | - | Sampling Procedures and Tables for Inspection by Attributes |
| MIL-STD-129 | - | Marking for Shipment and Storage |
| MIL-STD-130 | - | Identification Marking of U.S. Military Property |
| MIL-STD-147 | - | Palletized Unit Loads |
| MIL-STD-2219 | - | Fusion Welding for Aerospace Applications |

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

| | | |
|---|---|---|
| *5-13-2544 | - | Ice Chest Assembly and Details |
| *5-13-2545 | - | Ice Chest Lid and Divider Assemblies |
| 5-13-3721 | - | Tray Pack Heater Tank Assembly |
| 5-13-3722 | - | Heater Tank, Frame Assembly |
| *5-13-3723 | - | Tank Assembly |
| 5-13-3727 | - | Support, Angle, L. H., Heater Frame |
| 5-13-3728 | - | Heating Unit Guide Rail Assembly |
| 5-13-3734 | - | Stiffener, Table Top |
| 5-13-3735 | - | Leg Support Mounting Bracket Assembly |
| 5-13-3736 | - | Leg Mounting Bracket Assembly |
| 5-13-3737 | - | Can Opener - Table Top Holder Assembly |
| 5-13-3739 | - | Table Top Assembly |
| 5-13-3751 | - | Table Assembly, Field |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| 5-13-3757 | - | Table Top |
| 5-13-3759 | - | Channel |
| 5-13-3765 | - | Support, Angle, R. H., Heater Frame |
| 5-13-3771 | - | Decal, Operating Instructions |
| 5-13-3773 | - | Decal, "Warning May Be Hot" |
| 5-13-3859 | - | Lifter Assembly, Tray Pack, Serving |
| 5-13-3860 | - | Handle, Inner |
| 5-13-3861 | - | Handle, Outer |
| 5-13-3862 | - | Plate, Lifting |
| 5-13-3866 | - | Outer Lifting Plate Assembly |
| 5-13-3867 | - | Inner Lifting Plate Assembly |
| 5-13-3868 | - | Base Rack Assembly |
| 5-13-3875 | - | Burner Rack Assembly |
| 5-13-3886 | - | Cook Pot Cradle |
| 5-13-3889 | - | Ring |
| 5-13-3961 | - | Tray Pack Lifter |
| 5-13-3963 | - | Table Leg Pad Assembly |
| 5-13-3969 | - | Can Opener, Mounted, Heavy-Duty |
| 5-13-3991 | - | Cook Pot Cradle Assembly |
| *5-13-3992 | - | Kitchen, Company Level Field Feeding (KCLFF) and Drawing List |
| 5-13-4265 | - | Lifter, Serving, Number Ten Can |
| 5-13-4266 | - | Outer Lifting Plate Assembly |
| 5-13-4267 | - | Inner Lifting Plate Assembly |
| 5-13-4268 | - | Plate, Lifting |
| 5-13-4269 | - | Handle, Outer |
| 5-13-4270 | - | Handle, Inner |
| *5-13-5625 | - | Griddle Assembly, Company Level, Kitchen, Field Feeding, Enhanced |
| *5-13-5626 | - | Griddle, Company Level, Kitchen, Field Feeding, Enhanced |
| *5-13-5627 | - | Base, Griddle, Company Level, Kitchen, Field Feeding, Enhanced |

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-WEE, Natick, MA 01760-5018.)

*2.2 Non-Government publications. Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Initial production inspection sample. When specified (see 6.2), the contractor shall furnish a sample for initial production inspection and approval (see 4.4 and 6.4).

3.3 Comparison inspection sample. When specified (see 6.2), the contractor shall furnish a sample for comparison inspection and approval (see 4.5 and 6.5).

*3.4 Alternate components. Components offered as equivalent to components specified hereinafter and on the referenced drawings as a specific manufacturer's part or model number or equal, shall be functionally equal to the manufacturer's model number identified, and of equal or better quality. The incorporation and inclusion of such a component in the design of the specified end product shall not require modification or change to any other specified component, and shall not reduce ease of maintenance to it or any other components, unless such modification or change is specifically approved by the contracting officer. Prior to manufacture of the first article, or if none is required, prior to commencing production, the contractor shall submit for the contracting officer's approval, a list identifying each proposed alternate component, together with proof that each listed component complies with requirements specified above. The contracting officer, at his option, may require a physical sample of the proposed substitution. Approval of the submitted listing, together with the necessary supporting data, authorizes use of the proposed component during fabrication but does not relieve the contractor of responsibility that these components perform in accordance with specified requirements when incorporated into the end product. Changes to any component after approval of First Article or initial production must be approved by the contracting officer.

3.5 Materials and components. The materials and components used shall conform to the applicable referenced specifications, standards, drawings, and requirements specified herein. Where materials are not definitely specified, they shall be of the quality normally used for the purpose in commercial practice provided the completed items comply with all provisions of this document. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

*3.6 Design and construction. The kitchens are designed for field preparation of T-Rations (type I) and T-Rations plus limited A/B rations (type II) in support of all divisional units. The design and construction for the company level field feeding kitchens shall be as specified herein and as shown on the drawings listed in 2.1.

*3.6.1 Welders. Prior to assigning any welder to structural welding on all of the kitchen components to be furnished under this document, the contractor shall provide the contracting officer or his authorized representative with the names of welders to be employed in the work, together with certification



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

that each of these welders has passed qualification tests as prescribed by either of the following listed codes for the type of welding operation to be performed:

a. Standard Qualification Procedure of the American Welding Society

b. Welding Qualification of the American Society of Mechanical Engineers

*3.7 Components, Type I - Standard KCLFF. The components of the type I company level field feeding kitchens shall be as specified in 3.7.1. through 3.7.8.

3.7.1 Heater cabinet. One heater cabinet shall be provided with each kitchen. The heater cabinet shall conform to Drawings 5-13-3721, 5-13-3722, and 5-13-3723 and all subsidiary drawings. When tested as specified in 4.7.1 the heater cabinet shall show no leakage of water.

3.7.2 Cook pot cradle assembly. One cook pot cradle assembly (Drawing 5-13-3991) shall be provided with each kitchen. The cook pot cradle assembly shall consist of the cook pot cradle, Drawing 5-13-3886; burner rack assembly, Drawing 5-13-3875; and base rack assembly, Drawing 5-13-3868. All subsidiary drawings to the above mentioned drawings are also applicable.

3.7.3 Cook tables. Two work tables shall be provided with each kitchen. The work table assembly shall conform to Drawings 5-13-3751, 5-13-3739, 5-13-3736, 5-13-3735, 5-13-3737, and 5-13-3963, and all subsidiary drawings.

3.7.4 Tray pack lifter. One tray pack lifter shall be furnished for extracting hot tray packs from the heater cabinet. The tray pack lifter shall conform to Drawing 5-13-3961.

3.7.5 Tray pack, serving lifter. One tray pack serving lifter shall be furnished for lifting hot tray packets from the opening table to the serving table. The serving lifter shall conform to Drawing 5-13-3859 and all subsidiary drawings.

3.7.6 Number ten can, serving lifter. One number ten can serving lifter shall be furnished for lifting hot number ten cans from the opening table to the serving table. The lifting server, number ten can, shall conform to Drawing 5-13-4265 and all subsidiary drawings.

3.7.7 Can opener, table mounted. One can opener, for use with work tables, shall be provided with each kitchen. The can opener shall conform to Drawing 5-13-3969.

3.7.8 Can and slip cover top. One can with slip cover top, conforming to type IV, round class 3 of PPP-C-96, shall be provided. The can shall have a lacquered finish and the dimensions shall be 1.75 ± .75 inches in height and 3.75 ± .75 inches in diameter.

*3.8 Components, Type II - Enhanced. The type II components shall consist of all the components and quantities specified in type I (3.7.1 through 3.7.8) in addition to the following components and quantities specified.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

*3.8.1 Griddle. One griddle shall be provided with each enhanced kitchen. The griddle shall conform to Drawings 5-13-5625 and 5-13-5626.

*3.8.2 Griddle Base. One griddle base, for use with the griddle, shall be provided with each enhanced kitchen. The griddle base shall conform to Drawings 5-13-5625 and 5-13-5627.

3.9 Government furnished property (GFP). The following property in the quantities specified shall be furnished by the Government with each kitchen (see 6.2 and 6.6).

*3.9.1 Type I - Standard.

| Item No. | Description | Identification National Stock No. | Quantity |
|---|---|---|---|
| 1 | Thread compound, antiseize, conforming to MIL-T-83483 | 8030-00-087-8630 | 1 |
| 2 | Bag, drinking water storage, conforming to MIL-B-273 | 4610-00-268-9890 | 1 |
| 3 | Board, food slicing/chopping, conforming to size 1 of A-A-391 | 7330-00-078-5706 | 1 |
| *4 | Brush, wire, conforming to H-B-178/3 of H-B-178/GEN | 7920-00-291-5815 | 1 |
| *5 | Burner unit, M2A, conforming to MIL-B-40098 (see 6.2) | 7310-01-113-9172 | 2 |
| *6 | Can, Fuel, Military: Plastic, 5 gallon, conforming to MIL-C-53109 | 7240-01-337-5269 | 2 |
| *7 | Can, water, plastic, 5-gallon, conforming to MIL-C-43613 | 7240-00-089-3827 | 8 |
| 8 | Cleaner, burner slot, conforming to MIL-C-1429 | 5120-00-379-2490 | 1 |
| *9 | Cover, Cooking Pot, conforming to MIL-P-1735 | 7330-00-250-6300 | 2 |
| *10 | Dispenser, liquid, insulated conforming to class 2 of MIL-D-43916 | 7310-01-245-6937 | 4 |
| *11 | Fire extinguisher, conforming to size 5 of A-A-1106 | 4210-00-270-4512 | 1 |
| *12 | First aid kit | 6545-00-919-6650 | 1 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

| Item No. | Description | Identification National Stock No. | Quantity |
|---|---|---|---|
| *13 | Food Container, conforming to MIL-F-10870 | 7330-00-238-2411 | 4 |
| *14 | Generator, preheater, conforming to MIL-B-40098 | 7310-00-999-2552 | 4 |
| *15 | Gloves, heat protective, conforming to type II of MIL-G-44013 | 8415-01-092-3910 | 1 pr |
| *16 | Hose, conforming to type II, grade A size 5/8 of L-H-520 | 4720-00-729-5334 | 1 |
| *17 | Hose, pump, inflating | 4720-00-379-2518 | 1 |
| *18 | Knife, boning, conforming to type III, grade D of GGG-C-746 | 7340-00-197-1271 | 1 |
| *19 | Knife, bread, conforming to type IV, size 1, grade A of GGG-C-746 | 7340-00-406-6531 | 1 |
| *20 | Lantern, gasoline, conforming to A-A-5208 | 6260-00-837-0996 | 1 |
| *21 | Measure, liquid, 2-quart, conforming to type IV, style A, size 3 of A-A-1751 | 7330-00-205-3096 | 1 |
| *22 | Opener, can, hand for tray packs and round cans conforming to MIL-O-44368 | 7330-01-245-0201 | 2 |
| *23 | Spout, can, gasoline, conforming to MIL-S-1285 | 7240-00-177-6154 | 1 |
| *24 | Pot, cooking, without cover, 10-gallon conforming to size 1 of MIL-P-1735 | 7330-00-292-2306 | 1 |
| *25 | Pot, cooking, with cover, 15-gallon conforming to size 2 of MIL-P-1735 | 7330-00-292-2307 | 1 |
| *26 | Pump, inflating, conforming to XX-P-746 | 4320-00-852-9036 | 1 |
| *27 | Screwdriver, flat, conforming to type I, class 5, design A, 4 inches long of GGG-S-121 | 5120-00-222-8852 | 1 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

| Item No. | Description | Identification National Stock No. | Quantity |
|---|---|---|---|
| *28 | Screwdriver, crosstip, Phillips conforming to type VI, class 1 of GGG-S-121 | 5120-00-234-8913 | 1 |
| *29 | Spoon, food service, basting conforming to type II of MIL-U-10815 | 7340-00-223-7800 | 4 |
| *30 | Spoon, serving, slotted, conforming to type II of A-A-1082 | 7340-00-205-1421 | 4 |
| *31 | Tool chest, conforming to MIL-C-1700 | 7310-00-310-8544 | 1 |
| *32 | Wrench, adjustable, conforming to size 8 of A-A-2344 | 5120-00-240-5328 | 1 |
| *33 | Wrench combination, conforming to type III of MIL-W-10698 | 5120-00-303-7737 | 1 |

*3.9.2 Type II - Enhanced. The type II GFP shall consist of all the property and quantities specified in type I in addition to the following property and quantities specified:

| Item No. | Description | Identification National Stock No. | Quantity |
|---|---|---|---|
| 1 | Chest, ice storage, conforming to drawings 5-13-2544 and 5-13-2545 | 4110-01-044-2487 | 1 |
| 2 | Food containers, insulated, with inserts, conforming to MIL-F-10870 | 7330-00-238-2411 | 12 |
| 3 | Range outfit, conforming to item 1 of MIL-R-14601 | 7360-00-082-2153 | 1 |
| 4 | Accessory outfit conforming to item 2 of MIL-R-14601 | 7360-00-187-4757 | 1 |

3.10 Instruction plate. An instruction plate on the heater cabinet shall be as shown on Drawing 5-13-3771.

3.10.1 Warning plates. Two warning plates indicating surfaces of heater cabinet "May Be Hot" shall be as shown on Drawing 5-13-3773. Two warning plates for the cook pot cradle shall be placed as shown on Drawing 5-13-3886.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

3.11 Finish.

*3.11.1 Surface preparation. The exterior surfaces of the table, heating cabinet, shroud, base rack, burner rack, and griddle base shall be cleaned and conditioned. Rough or sharp edges and corners, burrs, and slivers shall be removed. Ferrous surfaces on any components to be painted shall first be thoroughly cleaned and conditioned in accordance with type F of MIL-T-704. Aluminum and aluminum alloy surfaces shall be cleaned and conditioned in accordance with type G of MIL-T-704.

3.11.2 Primer paint treatment (For surfaces required to be painted). After surfaces are thoroughly dried from cleaning and conditioning, a coat of primer in accordance with MIL-P-53022 shall be applied in accordance with MIL-T-704, type G. The tables and shroud will not require a primer coat.

*3.11.3 Finish coat. After primer has thoroughly dried, the heating cabinet, base rack and burner rack shall be given a finish coat, color green 383 in accordance with MIL-T-704, Type F or G. The word "CARC" with the month and year of coating application, shall be stenciled in 1-inch high block letters using lusterless black paint 37030 conforming to MIL-C-46168 or MIL-C-53039 and shall be located near the instruction plate. The tables and shroud shall have a finished coat of MIL-C-14105 paint in color to match green 383 of MIL-C-46168. This paint shall contain no lead or chromate. The paint shall be applied so that there will be no streaks, crops, pinholes, cheeks, or cracks.

*3.11.4 Anodic coatings. Griddle surface shall be anodized in accordance with type III, class 1 coatings of MIL-A-8625 with a minimim thickness of 2.0 mils, unsealed using the Sanford process or equal.

3.12 Workmanship. The major components of the kitchen shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the acceptable quality level (AQL).

3.12.1 Welding. The surfaces of parts to be welded shall be free from oxide, scale, paint, grease, or other foreign matter. Welds shall have a smooth, regular bead, shall be uniform in cross section, and shall be free of pits, cracks, holes, undercuts, or incomplete fusion. All scale, weld flack, flux, splatter, rough surface, and projecting modules shall be removed.

*3.12.2 Fastening devices. Threaded fastener and rivet holes shall have burrs removed. Threaded fasteners shall not be broken, cracked, or stripped, and shall be securely torqued to prevent loosening during normal operation. Rivets shall fill the holes completely and the heads shall be in full contact with the surface of the riveted members.

*3.12.3 Finish. All components and assemblies of the kitchen shall be free from dirt, rust, or other extraneous material, burrs, slivers, rough die, tool or grind marks, dents and cracks. External surfaces shall be free from sharp edges and corners. Painted surfaces shall be smooth, uniformly coated, free of runs, wrinkles, peeling, and areas of no film. Any painted coating damaged during assembly or examination shall be touched-up by priming (see 3.11.2) and finished coat (see 3.11.3).



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

*3.12.4 Manuals. Unless otherwise specified (see 6.2), technical manuals shall be provided with each kitchen.

*3.12.5 Identification Markings. Marking shall be as specified on component drawings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein.

Except as otherwise specified in the contract or purchase order, the contractor may use his own or other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Initial production inspection (see 4.4).
c. Comparison sample inspection (see 4.5).
d. Quality conformance inspection (see 4.6).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.6.3 and 4.6.4, and shall be tested for the characteristic specified in 4.6.5. The presence of any defect or failure to pass any test shall be cause for rejection of the first article.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

4.4 Initial production sample inspection. When an initial production sample is required (see 3.2 and 6.2), the kitchen(s) shall be inspected as specified in 4.6.3, and 4.6.4 and tested for the characteristics specified in 4.6.5. The presence of any defect or failure of any test shall be cause for rejection of the initial production sample.

4.5 Comparison sample inspection. When a comparison sample is required (see 3.3 and 6.2), the kitchen(s) shall be inspected as specified in 4.6.3 and 4.6.4 and shall be tested for the characteristics specified in 4.6.5. The presence of any defect or failure of any test shall be cause for rejection of the comparison sample.

4.6 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.6.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.6.2 In-process inspection. Inspection shall be made at any point or during any phase of the manufacturing process to determine whether construction details which cannot be examined in the finished product are in accordance with specified requirements. Whenever nonconformance is noted, correction shall be made to the items affected, the lot in progress, and to the operation. Parts which cannot be corrected shall be removed from production.

4.5.2.1 Component dimensional examination. Prior to welding, each of the first completed components for the welded assemblies listed below shall be examined for conformance with all of the specified dimensions applicable to that item.

a. Heater tank assembly.
b. Cook pot cradle assembly.
c. Rack base assembly.
d. Burner rack assembly.
e. Work table assembly.
f. Lifter assembly-tray pack (handle support and lifter).
g. Safety lifter assembly-tray pack (lifting plate, inner handle and outer handle).
h. Safety lifter assembly-number ten can (lifting plate, inner handle and outer handles).
*i. Griddle assembly.

Any dimensional measurement exceeding the specified tolerance shall be cause for rejection of that component, correction of the manufacturing process as required, and examination of the next produced component until conformance to all specified dimensions is demonstrated.

4.6.2.2 In-process inspection of welding. In lieu of inspecting welding in accordance with the following procedures, the contractor may propose to the Procuring Contracting Officer (PCO) alternative procedures for operator and equipment certification. When necessary or when requested by the



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

Government, the contractor shall submit representative samples supporting these alternative procedures. The Government will reply to the contractor within ten working days after receipt of the proposal.

4.6.2.2.1 Spot welding. Spot welding shall be in accordance with MIL-W-6858 (metal arc and gas welding) except that pull tests shall be performed in lieu of magnetic penetrant and radiographic tests. The pull tests shall be performed at the daily start of each production run on each machine or whenever there is a break in production, adjustment on welding machine, or a change in operation. The pull tests shall verify minimum nugget size and complete bonding of the two metals. At least two sample welds shall be tested using material identical to the applicable components.

4.6.2.2.2 Metal arc welding. Unless otherwise specified on the drawing, all metal arc welding shall be according to MIL-STD-2219, Class C.

*4.6.3 End item visual examination. The completed kitchen, including all manufactured components shall be examined for the defects listed in table I. The lot size shall be expressed in units of manufactured kitchen components. The sample unit shall be one of each of the manufactured kitchen components. The inspection level shall be II. The finding of any major or minor defect shall be cause for rejection of the lot.

TABLE I. End item visual defects

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Material | Extraneous hole, tear, or crack in any component | 101 | |
| | Dent, bend, or other malformation in any component | 102 | |
| Finish | Extraneous material such as rust, dirt, oil, or grease | | 201 |
| | Rough tool, die, or grind marks | | 202 |
| | Dents, scratches, or cracks not affecting serviceability | | 203 |
| | Dents, scratches, or cracks affecting serviceability | 103 | |
| | Burrs or slivers which may inflict injury | 104 | |
| | Sharp edges or sharp corners | 105 | |
| | Extraneous holes | 106 | |
| | Burr on inside of holder of can opener | 107 | |
| | Finish on top of table or can opener holder not as specified | 108 | |
| Painted surfaces | Color not as specified | 109 | |
| | Film not smooth or not uniform | | 204 |
| | Area of no paint or film | | 205 |
| | Painted surface contains runs, streaks, wrinkles, drops, or grit | | 206 |
| | Paint is peeling | | 207 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Welding | Missing, incomplete or incorrectly located square groove or fillet weld | 110 | |
| | Flush, melt-thru, square groove, bend groove, fillet, and spot weld not of the specified type or size | | 208 |
| | Irregular or non-uniform cross section of fillet weld bead | | 209 |
| | Crack, burnhole, undercutting or overlapping of weld | | 210 |
| | Weld scale, flux or spatter not removed | | 211 |
| | Missing spot weld (15 per shroud), applicable to cook pot cradle | | 212 |
| | No bonding of spot weld, applicable to cook pot cradle and table assembly | 111 | |
| | Large and small shrouds are not spot welded on inside of supports and base, applicable to cook pot cradle | 112 | |
| | On lifter assembly, fillet weld not completely around support | 113 | |
| | Can opener holder is not fillet welded to table top all around holder on top side | 114 | |
| | Short mounting bracket is not assembled to table using five spot welds per side | 115 | |
| | Long mounting bracket or stiffener is not assembled to table using 13 spot welds per side | 116 | |
| | Cover hinge brackets on heater cabinet are not fillet welded all around to front and back panels | 117 | |
| | Outside corners of panels on heater cabinet are not convex fillet welded with proper size and spacing of weld | | 213 |
| | Top edge of panels on heater cabinet is not convex fillet welded all around | | 214 |
| | Bottom edge of side and rear panels on heater cabinet are not smooth square groove welded with the proper size and spacing of weld | | 215 |
| | Bottom edge of front panel on heater cabinet is not smooth square groove welded across front | | 216 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

| Examine | Defect | Classification Major | Classification Minor |
|---|---|---|---|
| Heater cabinet | Hinge pivot screw assembly not tight | 118 | |
| | Nut on hinge pivot screw not secured with locking component (DO NOT loosen nut to examine) | 119 | |
| | Top of drain pipe is above the bottom inside surface of tank | 120 | |
| | Drain pipe is not perpendicular to bottom of tank | | 217 |
| | Shut-off valve cannot fully open or close | 121 | |
| | Shut-off valve does not face the right side | 122 | |
| | Shut-off valve does not contain hose adapter | 123 | |
| | Covers are not free from binding when opening and closing | | 218 |
| | Covers are not flat against top of tank | | 219 |
| | Covers do not clear each other when closed | | 220 |
| | Catches bind when functioned | | 221 |
| | With catch closed, cover is not secured | 124 | |
| | Catch rivets are not secured or free from splits or cracks | | 222 |
| | Handles are not free from binding | | 223 |
| | Handle mounting screws are missing, loose, or stripped | 125 | |
| | Heater guide rails do not have retaining tabs (there are four) | | 224 |
| | Rivets on both ends of heat reflectors are not secure or free from splits or cracks | | 225 |
| | Rivets on the "Warning" and "Instruction" plates are not secure or free from splits or cracks | | 226 |
| | When tank is fabricated by welding, inside corners are not ground to match finish on metal | 126 | |
| Cook pot cradle assembly | Area of shroud or any other component protruding into 17-5/16 inch ring diameter opening | 127 | |
| | 1/2 inch side of front corner angles on burner rack assembly are not in the 19-3/4 front opening | 128 | |
| | Short carrier on burner rack assembly does not have a machined surface facing up and flush with the long carrier | 129 | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Work table | Legs do not travel to, and lock in fully opened position, and close under not more than moderate hand pressure | 130 | |
| | Legs fold without releasing lock arm | 131 | |
| | Nut with washer is not tight securing leg to table | | 227 |
| | Lower edge of table is not fully rolled back | 132 | |
| | Can opening does not angle to front when table is positioned with holder on right side | 133 | |
| Tray pack lifter assembly | Lifter cracked | 134 | |
| | Lifter not properly oriented on support | 135 | |
| | Lifter not centered on support | 136 | |
| Components and assemblies | Any component missing, or not as specified, or not furnished in the quantity specified | 137 | |
| Any item provided by the Government as a GFP item | Any item missing, or not as specified or not furnished in the quantity specified | 138 | |
| Instruction manual | Missing, incomplete, not legible | 139 | |
| *Griddle | Does not fit on griddle base | 140 | |
| | Not anodized as specified | 141 | |
| | Surfaces rough or pitted | 142 | |
| | Surface not one piece | 143 | |
| *Griddle Base | Does not accomodate griddle | 144 | |

*4.6.4 End item dimensional examination. The complete kitchen, including all manufactured components, but excluding all GFP items, shall be examined for all dimensions specified on the drawings or in the paragraph listed in table II. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of complete kitchen. The sample unit shall be one of each of all the components listed in table II. The inspection level shall be S-4 and the finding of any defect shall be cause for the ejection of the lot.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

TABLE II. End item dimensional defects

| Component | Examine |
|---|---|
| Tray pack heater tank assembly (Dwg. 5-13-3721) | All dimensions specified, and those dimensions on the following sub-assemblies:<br>a. Heater tank frame assembly (Dwg. 5-13-3722)<br>b. Width of angle supports (Dwgs. 5-13-3727/3765)<br>c. Tank assembly (Dwg. 5-13-3723) |
| Cook pot cradle (Dwg. 5-13-3886) | All dimensions specified, and those dimensions on the following sub-assembly:<br>a. Inside ring diameter at top (Dwg. 5-13-3889) |
| Burner rack assembly (Dwg. 5-13-3875) | All dimensions specified |
| Base rack assembly (Dwg. 5-13-3868) | All dimensions specified |
| Table assembly, field (Dwg. 5-13-3751) | All dimensions specified and those dimensions on the following sub-assemblies:<br>a. Table top assembly (Dwg. 5-13-3739)<br>b. Stiffener and leg mounting bracket (Dwgs. 5-13-3734/3736)<br>c. Channel holder (Dwg. 5-23-3759) |
| Tray pack lifter (Dwg. 5-13-3961) | All dimensions specified |
| Lifter assembly, tray pack, serving (Dwg. 5-13-3859) | All dimensions specified and those dimensions on the following sub-assemblies:<br>a. Boss location (Dwgs. 5-13-3866/3867)<br>b. Lifting plate location (Dwgs. 5-13-3866/3867)<br>c. Lifting plate (Dwg. 5-13-3862)<br>d. Inner handle (Dwg. 5-13-3860)<br>e. Outer handle (Dwg. 5-13-3861) |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

TABLE II. End item dimensional defects (cont'd)

| Component | Examine |
|---|---|
| Lifter assembly, number ten can, serving (Dwg. 5-13-4265) | All dimensions specified, and those dimensions on the following sub-assemblies:<br>a. Outer lifting plate assembly<br>b. Inner lifting plate assembly (Dwg. 5-13-4267)<br>c. Lifting plate (Dwg. 5-13-4268)<br>d. Inner handle (Dwg. 5-13-4270)<br>e. Outer handle (Dwg. 5-13-4269) |
| Griddle (Dwg. 5-13-5626) | All dimensions specified |
| Griddle Base (Dwg. 5-13-5627) | All dimensions specified |

4.6.5 End item testing. One representative heater cabinet shall be selected from the lot and tested as specified in 4.7.1. Any test failure shall be cause for rejection of the lot.

4.6.6 Packaging examination. An examination shall be made to determine that preservation and unit packing requirements are performed in accordance with MIL-P-116 and other documents, as applicable, cited in section 5 of this document. Examination shall also be made to determine that packing and marking requirements are in compliance with section 5 of the document. Defects shall be as indicated below. The lot size shall be the number of two box units offered for inspection at one time. The sample unit shall be one two box unit fully packaged. The inspection level shall be S-2. The finding of any defect shall be cause for rejection of the lot.

| Examine | Defect |
|---|---|
| *Preservation | Not in accordance with 5.1.1.1, 5.1.1.2, and table III |
| Components | Missing, damaged, or not as specified |
| Contents | Not as specified |
| Shipping container | Construction or dimensions not as specified |
| Palletization and bonding | Not as specified |
| Marking | Not as specified |
| Workmanship | Inadequate application of components, such as incomplete wrapping and securing of cushioning materials and tape to non-handle end of opener (applicable to hand can opener) |



Source: https://assist.dla.mil - Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

4.7 Methods of inspection.

4.7.1 Leakage test. Fill the heater cabinet tank with tap water to within 2 inches of the top. Let stand for 5 minutes. At that time observe the cabinet tank for leakage. Inability of the cabinet tank to comply with the requirement in 3.7.1 shall constitute failure of this test.

5. PACKAGING

5.1 Preservation. Preservation shall be level A.

*5.1.1 Level A.

*5.1.1.1 Type I - Standard. The component parts of each complete field type I kitchen (see 3.7 and 3.8), shall be cleaned and preserved in accordance with table III. Apply preservative to unpainted or uncoated metal surfaces only. Grease-proof barrier material shall conform to MIL-B-121. Secure barrier material with paper tape conforming to type III, grade A of PPP-T-45, or PPP-T-76. Seal openings with tape conforming to PPP-T-60.

*5.1.1.2 Type II - Enhanced. In addition to the preservation requirements specified in 5.1.1.1 the following requirements apply to the type II kitchens.

*5.1.1.2.1 Food containers, insulated, with inserts. The complete food containers with inserts shall be preserved in accordance with the applicable level A preservation requirements of MIL-F-10870.

*5.1.1.2.2 Chest, ice storage. Each ice chest shall be preserved in accordance with method III of MIL-P-116.

*5.1.1.2.3 Range outfit, field, item 1. Each complete range outfit shall be preserved in accordance with the applicable level A preservation requirements of MIL-R-14601.

*5.1.1.2.4 Accessory outfit, item 2. Each complete accessory outfit shall be preserved in accordance with the applicable level A preservation requirements of MIL-R-14601.

*5.1.1.2.5 Griddle and griddle base. The griddle shall be nested in the griddle base and preserved in accordance with MIL-P-116.

5.2 Packing. Packing shall be level B.

5.2.1 Level B packing.

*5.2.1.1 Type I - Standard. Each complete Type I field kitchen, preserved as specified in 5.1.1.1, shall be packed in a two-box unit. Each box shall be constructed in accordance with style DBLCC of PPP-B-1364. The approximate outside dimensions shall be 48 inches in length, 40 inches in width, and 43 inches in depth. Each box shall be mounted on a type I (4-way entry), type



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

IV or type V pallet in accordance with MIL-STD-147. Box 1 of 2 shall contain: heater cabinet, pot cradle, four food containers, water bag, cutting board, fire extinguisher, lantern, tool chest, and two M2A burners (see 6.2). Box 2 of 2 shall contain all remaining components. The contents of each box shall be cushioned, anchored, braced, and blocked as necessary to prevent movement and damage while in transit. When filled, the box shall be bonded with straps in accordance with bonding means K of MIL-STD-147.

*5.2.1.2 Type II - Enhanced. In addition to the packing requirements specified in 5.2.1.1 the following requirements apply to the type II kitchens.

*5.2.1.2.1 Food containers, insulated, with inserts. Two food containers with inserts, preserved as specified in 5.1.1.2.1, shall be packed in accordance with the applicable level B packing requirements of MIL-F-10870. Twelve food containers (six packs) with inserts shall be overpacked in a snug-fitting cleated plywood box conforming to domestic type of PPP-B-601.

*5.2.1.2.2 Chest, ice storage, accessory outfit, item 2, griddle and griddle base. The accessory outfit and griddle and griddle base shall be placed in the ice storage chest and properly cushioned in such a manner as to prevent movement and damage during transit. The ice storage chest, preserved as specified in 5.1.1.2.2, shall then be packed in a snug-fitting wood crate conforming to type I, style B of MIL-C-52950.

*5.2.1.2.3 Range outfit, field, item 1. Each complete range outfit, preserved as specified in 5.1.1.2.3, shall be packed in accordance with the applicable level B packing requirements of MIL-R-14601.

5.3 Marking. Marking of unit packs and shipping containers shall be in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory unless cited in the contract.)

*6.1 Intended use. The type I - standard company level field feeding kitchen is an assemblage of equipment that provides the capacity of heating and serving tray pack rations (T rations) in basic, hot, and cold climatic conditions with or without shelter from the environment. The type II - enhanced company level field feeding kitchen is the additional assemblage of equipment that provides the capability of heating and serving tray pack rations plus the limited capability of serving A (semi-perishable and non-perishable) and B (semi-perishable) rations.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

TABLE III. Preservation of company level field feeding kitchen components

| Quantity per unit | Component | Method of cleaning (MIL-P-116) | Type of preservation and application (MIL-P-116) | Type of grease proof barrier (MIL-B-121) | Method of preservation (MIL-P-116) | Special requirements |
|---|---|---|---|---|---|---|
| 1 | Heater cabinet | C-1 | P-1 | None | I | Apply to ferrous surfaces |
| 1 | Pot cradle assembly, complete | C-1 | P-14 Brush | None | III | |
| 2 | Work table, serving | None | None | None | III | |
| *4 | Food container, insulated | None | None | None | III | |
| 1 | Tray pack lifter | None | None | None | III | |
| 1 | Number ten can, serving lifter | None | None | None | III | |
| 1 | Tray pack, serving lifter | None | None | None | III | |
| 1 | Thread compound, antiseize | None | None | None | III | |
| 1 | Bag, drinking water storage | None | None | None | III | |
| 1 | Board, food slicing/chopping | None | None | None | III | |
| 1 | Brush, wire | C-1 | P-14 Dip | Type I or II, Grade A | I | |
| 2 | Burner unit, M2A | C-1 | P-14 Burner only | Type I or II, Grade A | I | |
| 1 | Can, slip cover top | None | None | None | III | |
| 2 | Can, gasoline, 5-gal. | None | None | None | III | |
| 2 | Can, opener, hand | C-1 | P-14 Burner | None | I | |

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

TABLE III. Preservation of company level field feeding kitchen components (cont'd)

| Quantity per unit | Component | Method of cleaning (MIL-P-116) | Type of preservation and application (MIL-P-116) | Type of grease proof barrier (MIL-B-121) | Method of preservation (MIL-P-116) | Special requirements |
|---|---|---|---|---|---|---|
| 1 | Can, opener, table mounted | C-1 | P-14 Brush | Type I or II, Grade A | I | |
| 8 | Can, water, plastic, 5-gal. | None | None | None | III | |
| 1 | Cleaner, burner slot | None | None | None | III | |
| 4 | Dispenser, liquid | None | None | None | None | |
| 1 | Fire extinguisher | None | None | None | III | |
| 1 | First aid kit | None | None | None | III | |
| 4 | Generator, preheater | C-1 | None | Type I or II, Grade A | III | |
| 1 pr | Gloves, heat protective | None | None | None | III | |
| 1 | Hose, garden, drain | None | None | None | III | |
| 1 | Hose, pump, inflating | None | None | None | III | |
| 1 | Knife, bonding | C-1 | P-14, Blade only | Type I or II, Grade A | I | |
| 1 | Knife, bread | C-1 | P-14, Blade only | Type I or II, Grade A | I | |
| 1 | Lantern, gasoline | None | None | None | III | |

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

TABLE III. Preservation of company level field feeding kitchen components (cont'd)

| Quantity per unit | Component | Method of cleaning (MIL-P-116) | Type of preservation and application (MIL-P-116) | Type of grease proof barrier (MIL-B-121) | Method of preservation (MIL-P-116) | Special requirements |
|---|---|---|---|---|---|---|
| 1 | Measure, liquid, 2-qt. | None | None | None | III | |
| 1 | Spout, can, gasoline | None | None | None | III | |
| 1 | Pot, cooking, 10-gal. with 2 covers | None | None | None | III | |
| 1 | Pot, cooking, 15-gal. with cover | None | None | None | III | |
| 1 | Pump, inflating | None | None | None | III | |
| 1 | Screwdriver, flat | C-1 | P-14 Dip | Type I or II, Grade A | I | |
| 1 | Screwdriver, cross tip, Phillips | C-1 | P-14 Dip | Type I or II, Grade A | I | |
| 4 | Spoon, food service, basting | None | None | None | III | |
| 4 | Spoon, serving, slotted | None | None | None | III | |
| 1 | Tool chest | C-1 | None | None | III | |
| 1 | Wrench, adjustable, crescent | C-1 | P-14 Dip | Type I or II, Grade A | I | |
| 1 | Wrench combination | C-1 | P-14 Dip | Type I or II, Grade A | I | |

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

*6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Type of kitchen required (see 1.2).
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When a first article is required (see 3.1, 4.3, and 6.3).
e. When initial production inspection sample is required (see 3.2, 4.4 and 6.4).
f. When comparison inspection sample is required (see 3.3, 4.5, and 6.5).
g. Source and delivery of Government furnished property (see 3.8).
*h. When the M2A burner units are not required (see 3.9, Item No. 5 and 5.2.1).
*i. When technical manuals are not required (see 3.12.4 and 6.7).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Initial production inspection. When an initial production inspection sample is required, the contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the initial production inspection sample.

6.5 Comparison inspection. When a comparison inspection sample is required, the contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the comparison inspection sample.

*6.6 Delivery of Government furnished property. The contracting officer shall insure that all components of the Kitchen, Company Level, Field Feeding and/or Kitchen, Company Level, Field Feeding- Enhanced are included as specified in 3.9.1 and 3.9.2 respectively, prior to supplying them to the contractor.

6.7 Manuals. Any requirements for equipment and instruction manuals for the kitchen covered by this document, should be included in DD Form 1423, Contract Data Requirements List and cited in the contract. Unless otherwise specified, no end item shall be shipped minus operator manuals without approval of the contracting officer.

*6.8 Subject term (key word) listing.

Food heating and serving equipment
Tray pack and A/B rations
Field Feeding



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.

*6.9 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodian:

Army - GL

Review activities:

Army - MD, TS, ME

Preparing activity:

Army - GL

Project 7360-A172



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:16Z
Check the source to verify that this is the current version before use.